

標題

MEPC 74 の審議結果の紹介

ClassNK

テクニカル インフォメーション

No. TEC-1192
発行日 2019年10月9日

各位

2019年5月13日から17日にIMO(英国・ロンドン)において第74回海洋環境保護委員会(MEPC 74)が開催されました。今般、IMOよりMEPC 74の議事録及び決議並びにサーキュラが発行されたことから、次の通り同会合の情報及び審議結果をお知らせ致します。

1. 温室効果ガス(GHG)関連

国際海運からの温室効果ガス(GHG)排出の抑制対策はIMOにて検討が進められており、現在までにエネルギー効率設計指標(EEDI)、エネルギー効率管理計画(SEEMP)による規制、及び燃料消費実績報告制度(DCS)が導入されています。

また、2018年4月に開催されたMEPC 72では、GHG削減目標とGHG排出削減策の候補を盛り込んだIMO GHG削減戦略が採択され、脱炭素化に向けたGHG削減手法についての検討が行われています。

(1) EEDI規制に関する技術開発状況レビュー

MARPOL条約 附属書VI 第21.6規則では、EEDIの改善に寄与する技術の開発動向を定期的にレビューし、要すればフェーズの開始時期、及び削減率を見直すことが規定されています。MEPC 71では、フェーズ3の早期実施やフェーズ4導入の必要性を検討するために、日本をコーディネータとする通信部会が設置されました。

今回の会合では、前回MEPC 73の合意事項と通信部会からの報告書を基に審議が行われました。

i) EEDIフェーズ3規制の見直し

フェーズ3の早期実施や削減率について、下記の合意事項を反映したMARPOL条約 附属書VIの改正案が承認されました。2020年春に開催されるMEPC 75で採択される予定です。

(次頁に続く)

NOTES:

- ClassNK テクニカル・インフォメーションは、あくまで最新情報の提供のみを目的として発行しています。
- ClassNK 及びその役員、職員、代理もしくは委託事業者のいずれも、掲載情報の正確性及びその情報の利用あるいは依存により発生する、いかなる損失及び費用についても責任は負いかねます。
- バックナンバーは ClassNK インターネット・ホームページ(URL: www.classnk.or.jp)においてご覧いただけます。

- コンテナ船の規制適用開始は 2025 年から 2022 年に前倒し、削減率は次の通り船のサイズにより定める。

DWT	削減率
10,000 以上 15,000 未満	15-30% (DWT に応じて線形補間)
15,000 以上 40,000 未満	30%
40,000 以上 80,000 未満	35%
80,000 以上 120,000 未満	40%
120,000 以上 200,000 未満	45%
200,000 以上	50%

- 一般貨物船、LNG 運搬船、クルーズ旅客船は適用開始を 2025 年から 2022 年に前倒し、削減率は 30%を維持する。
 - 15,000DWT 未満のガス運搬船(LPG 運搬船)は 2025 年の適用開始を維持するが、15,000DWT 以上の大型ガス運搬船(LPG 運搬船)は適用開始を 2025 年から 2022 年に前倒しする。削減率はサイズによらず 30%を維持する。
 - その他の船種は、現行の規定通り 2025 年の適用開始を維持し、削減率も 30%を維持する。
- ii) 超大型ばら積み貨物船のリファレンスライン
超大型ばら積み貨物船に対する規制値が極端に厳しくなることが認識されたことから、279,000DWT を超える超大型ばら積み貨物船に対するリファレンスラインを修正する MARPOL 条約 附属書 VI の改正案が承認されました。同改正案は、次回の MEPC 75 で採択される予定です。
- iii) 耐氷構造船に対する規制
IA Super 及び IA 適用の耐氷構造船に対し、その構造等を考慮した補正係数を EEDI 計算式に追加する EEDI 計算ガイドライン(決議 MEPC .308(73))の改正が採択されました。(添付 10 : MEPC.322(74) 参照)
- iv) EEDI フェーズ 4 規制の検討
EEDI フェーズ 4 規制導入の検討を継続するために、通信部会を継続することが合意されました。この通信部会では、燃費改善技術の開発・採用実績や船舶の安全性の観点から規制導入の可能性を検討し、2020 年春の MEPC 75 に中間報告、2020 年秋の MEPC 76 に最終報告を行う予定です。

(次頁に続く)

(2) EEDI 規制と最低推進出力規制

EEDI 規制への適合が要求される船舶の荒天下における操船性を維持するため、MEPC 65 において暫定の最低推進出力ガイドラインが策定されました。さらに MEPC 71 では、ガイドラインが改正されるまでの措置として、暫定ガイドラインの適用期間をフェーズ 2 まで延長することが合意されています。その一方、この最低推進出力規制に従い一定の出力を確保する必要がある反面、フェーズ 3 への対応がさらに困難になることが懸念されています。MEPC 73 では、EEDI 規制と最低推進出力規制の両方を満足するために、通常航海時には機関出力を制限し、非常時(荒天時)は出力制限を解除することを認める EEDI 計算ガイドラインの改正案が提案され、MEPC 74 にて継続審議を行うことになりました。

今回の会合では、この出力制限を EEDI 認証に導入するために、関連するガイドラインの策定や IEE 証書書式の改正が提案されました。審議の結果、出力制限の概念に多くの支持が集まり、より具体的な枠組みを規定するべく継続して審議していくことが合意されました。さらに、並行して最低推進出力ガイドラインを最終化するための検討作業を進めることも合意されました。

(3) IMO GHG 排出削減戦略

2015 年に採択されたパリ協定では、世界の平均気温上昇を産業革命以前から 2℃以内に抑えるという GHG の排出削減目標が世界的に共有されました。これを受け、MEPC 72 では、2030 年までの短期削減目標(2008 年比で IMO 全体での平均炭素密度を最低 40%改善)、2050 年までの中期削減目標(2008 年比で IMO 全体での GHG 排出量を最低 50%削減)及び長期削減目標(IMO 全体での GHG 排出量を今世紀中に中立化)、さらに各目標達成のための削減策の候補を盛り込んだ IMO GHG 削減戦略が採択されました。

今回の会合では、5 月 7 日から 10 日に開催された中間会合に引き続き、短期的削減策の検討を行い、2023 年までの合意を目標として今後も検討を継続することになりました。短期的削減策として提案されている主な対策は以下の通りです。

- 既存船の燃費性能による規制(Energy Efficiency Existing Ship Index、EEXI)
- 運航時の平均燃費実績による規制
- 運航時の平均速度による規制
- SEEMP を定期検査化し、自主的な燃費改善目標設定を義務化

また、GHG 排出量の削減を促進するための港湾開発を奨励する MEPC 決議を採択した他、GHG 排出削減策の検討を加速させるために、2019 年 11 月及び 2020 年 3 月に中間会合を開催することも合意されています。

2. 大気汚染関連

(1) 燃料油の硫黄分濃度規制

MARPOL 条約 附属書 VI の第 14 規則では、硫黄酸化物(SO_x)及び粒子状物質(PM)の排出を抑制するために、船舶で使用する燃料油中の硫黄分濃度を段階的に規制しており、一般海域で使用する燃料油中の硫黄分濃度の規制値が 2020 年から 3.50%から 0.50%へ強化されます。

今回の会合では、硫黄分濃度の 0.50%規制に対する統一の実施のためのガイドラインが採択されました。このガイドラインでは、適合燃料油の入手、及び使用に関して次の項目が記載されています。(添付 9 : MEPC.320(74) 参照)

(次頁に続く)

- 留意すべき燃料油の性状
- 旗国検査、及び寄港国検査(PSC)での確認項目
- 適合燃料油を調達できない場合に、旗国及び寄港国主管庁に提出する FONAR (Fuel Oil Non-Availability Report) の作成要領

また、適合燃料油が調達できないなどのやむを得ない事情により非適合燃料油を搭載してしまった場合について、船舶、旗国、及び沿岸国がとるべき対応を示すガイダンスが承認されました。このガイダンスでは、非適合油を補油して航行した船舶の次港の寄港国主管庁に対し、環境、安全、運航上の影響を考慮した上で、残留非適合燃料油を陸揚げする、もしくはそのまま船上に保持することを検討することが要請されています。また、旗国、寄港国主管庁及び船舶に対し、協力して最も適切な対応策を取ることが要請されています。

(添付 12 : MEPC.1/Circ.881 参照)

(2) 船上で使用する燃料油のサンプリング分析

SO_x 排出規制海域(ECA)における 2015 年からの硫黄分規制強化を受け、寄港国検査(PSC)等にて船上で燃料油のサンプリングを実施する必要があるため、MEPC 70 では燃料油の船上サンプリングに関するガイドラインを作成しました。

今回の会合では、既存船を含む全船を対象に、使用中の燃料油のサンプル採取位置の指定を義務付ける MARPOL 条約 附属書 VI 第 14 規則の改正案が承認されました。さらに、燃料油サンプル検証手順を規定する同条約 付録 VI について、使用している燃料油中の硫黄分を確認する手順を加えるための改正案も承認されました。これらは、次回の MEPC 75 で採択される予定となっていますが、改正案の早期適用を推奨するサーキュラが発行されています。(添付 13 : MEPC.1/Circ.882 参照)

また、燃料油の船上サンプリングに関するガイドラインについても、サンプリング位置の指定に関する改正が承認されています。(添付 11 : MEPC.1/Circ.864/Rev.1 参照)

(3) 排ガス浄化装置(EGCS)からの排水

MARPOL 条約 附属書 VI の第 14 規則に規定する燃料油中の硫黄分濃度規制については、第 4 規則により、同等の実効性を持つ排ガス浄化装置(EGCS)等の使用に替えることが認められています。

EGCS の搭載により硫黄分濃度の規制値を満足しない燃料油を使用する場合には、EGCS ガイドライン(決議 MEPC.259.(68))の要件に基づき、主管庁の承認を受ける必要があります。EGCS で用いた洗浄水の排水については、EGCS ガイドラインに規定される排出基準を満たすことで船外排出が可能となりますが、EGCS からの排水による海洋環境への悪影響を懸念する港湾では、EGCS ガイドラインへの適合に係わらず EGCS の使用を制限する動きが出てきています。

今回の会合では、EGCS からの排水による海洋環境への影響調査を行うべきとの新規作業が提案され、統一的規制の制定を見据えた影響調査の作業計画が承認されました。この作業は 2020 年 2 月に開催される汚染防止・対応小委員会(PPR 小委員会)から審議が開始されます。

(次頁に続く)

(4) 排ガス浄化装置 (EGCS) 故障時の取扱い

2020年のSOx規制強化に向けて排ガス浄化装置(EGCS)の普及が進んでおり、装置が故障した場合のガイダンスの作成が急務となっていました。

今回の会合では、単一の監視装置の故障時、及びEGCSの故障時に取るべき行動等を纏めたガイダンスが採択されました。本ガイダンスではシステムの応答性に起因する排出規制値の一時的な超過は違反とは見做さないとしたうえで、システムの誤作動が1時間以内に復旧できない場合は故障と判断し、旗国及び寄港国主管庁に報告するよう勧告しています。また、単一の監視装置の故障時には、その他の関連データの記録が正常な値であることを以て適合を示す際の取扱いが示されています。(添付14:MEPC.1/Circ.883参照)

3. バラスト水管理条約関連 - バラスト水処理装置搭載時の性能確認

前回MEPC 73までの審議では、バラスト水処理装置の搭載について、搭載試験時に処理済みのバラスト水の分析を行うことで装置の動作確認を行うべきとの方針が合意されています。その一方で、搭載試験時にバラスト水の分析を実施する根拠となる条約要件が存在しておらず、分析実施の要否について取扱いが不明確となっていました。

今回の会合では、バラスト水処理装置の搭載試験時にバラスト水の分析を行うことを義務付けるためのバラスト水管理条約の改正案が承認されました。本改正案は次回のMEPC 75で採択される予定です。

4. その他の議題

(1) 電子記録簿の利用

MARPOL条約では、同条約 附属書 I に規定される油記録簿等、船舶にて使用・発生する汚染物質等を管理するために、各種の記録簿を備えることを要求しています。昨今、管理維持の利便性の観点から記録簿の電子化が進んでおり、電子記録簿の利用基準の検討が進められていました。

今回の会合では、電子記録簿の利用に関するガイドライン、並びに電子記録簿の利用を可能にするためのMAPPOL条約附属書 I, II, V, VI 及びNOxテクニカルコードの改正が採択されました。条約改正が発効する2020年10月1日以降、紙媒体による記録簿の代わりに電子記録簿を使用する場合、電子記録簿は同ガイドラインに従って承認を受ける必要があります。

(添付1、3、5及び6:

MEPC.312(74)、MEPC.314(74)、MEPC.316(74)、MEPC.317(74) 参照)

(2) 海洋プラスチック廃棄物

近年問題となっているプラスチックごみの海洋投棄については、2013年に発効したMARPOL条約 附属書 V の改正により、全ての船舶からのプラスチックごみの排出が禁止されています。しかしながら、国連の調査によれば、未だ船舶に由来するプラスチックごみの排出が継続していることが報告されています。この問題に対し、船舶から排出される海洋プラスチックごみの発生原因や発生状況を把握するために、海洋プラスチックゴミに関する調査を実施することが合意されています。

今回の会合では、調査対象・調査方法等に関する作業計画を作成すると共に、漁具の偶発流出時の報告要件、コンテナ流出時の報告義務化等について、関連の小委員会で審議を行うことが合意されました。

(次頁に続く)

(3) AFS 条約の改正

2008年に発効した船舶の有害な防汚方法の規制に関する国際条約(AFS条約)では、船底塗料として有機スズ化合物を使用することが禁止されています。近年、新たに有害性が確認されたシブトリンを禁止物質に加えるよう欧州諸国からの提案がありました。

今回の会合では、シブトリンを禁止物質に加える同条約の改正案を審議しましたが、既存船に塗布されているシブトリンを含む船底塗料の除去の必要性について検討を行うべきとの意見が有り、2020年2月に開催される汚染防止・対応小委員会(PPR小委員会)で継続して審議を行うことになりました。

(4) 汚水処理装置に関するガイドライン

汚水による汚染防止を規定するMARPOL条約 附属書IVでは、船舶に汚水処理装置を搭載することが規定されており、汚水処理装置は排水基準及び性能試験等に関するガイドライン(決議MEPC.227(64))に従って承認を受けたものを使用する必要があります。しかしながら、適切な処理がされずに船舶から汚水が排出されているとの調査報告を鑑み、要件を強化すべきとの提案がありました。

今回の会合では、汚水処理装置に対する技術要件、及び検査要件を見直すための新規作業計画が合意されました。2020年2月に開催される汚染防止・対応小委員会(PPR小委員会)から審議が開始されます。

5. 採択された強制要件

今回の会合で採択された主な強制要件は以下の通りです。

(1) 耐氷構造船に対するEEDI規制適用

Polar CodeのA類に該当する(いわゆるIA Superを超える)耐氷構造船をEEDI規制から適用除外するためのMARPOL条約 附属書VIの改正が採択されました。

(添付5:MEPC.316(74)参照)

発効日:2020年10月1日

(2) MARPOL条約 附属書II及びIBC/BCH Codeの改正

残留性浮遊物質の排出/予備洗浄に関する規定が、MARPOL条約 附属書IIに追加されました。また硫化水素検知器の設置要求や、最低要件一覧の改正を含む、IBC Code、及びBCH Codeの改正が採択されました。

本改正に関する情報は、別途弊会テクニカルインフォメーションを発行してお知らせする予定です。

(添付4、7、8及び15:MEPC.315(74)、MEPC.318(74)、MEPC.319(74)、MEPC.1/Circ.886参照)

発効日:2021年1月1日

(次頁に続く)

(3) 電子記録簿 (4. (1)項参照)

電子記録簿の利用に関するガイドラインを適用するため、MAPPOL 条約附属書 I、 II、 V、 VI及び NO_x テクニカルコードの改正が採択されました。

発効日:2020年10月1日

(4) SCR を備えるディーゼル機関の NO_x 認証スキーム

SCR を備えるディーゼル機関に対する NO_x 認証は、SCR とディーゼル機関を組み合わせた状態で NO_x 計測試験を実施するスキーム A、またはディーゼル機関単独での NO_x 計測試験と SCR の脱硝率計測試験を別個に実施するスキーム B のいずれかの手順に基づき実施されます。現行の NO_x テクニカルコードでは、組み合わせた状態での試験(スキーム A)が適切でないと主管庁が認める場合にスキーム B が適用可能と規定されています。今回の会合では、スキーム B 適用に対する主管庁承認を不要とし、スキーム A とスキーム B を同等に適用可能とするための NO_x テクニカルコードの改正が採択されました。この改正により、申請者が認証スキームを任意に選択できるようになります。これに加え、同改正を反映するための SCR 認証ガイドライン(決議 MEPC.291(71))の改正も採択されています。

(添付 2 及び 6 : MEPC.313(74)、MEPC.317(74) 参照)

発効日:2020年10月1日

MEPC 74 の審議概要につきましては IMO ホームページにも掲載されていますのでご参照下さい。
<http://www.imo.org/MediaCentre/MeetingSummaries/MEPC/Pages/Default.aspx>

(次頁に続く)

なお、本件に関してご不明な点は、以下の部署にお問い合わせください。

一般財団法人 日本海事協会 (ClassNK)

本部 管理センター別館 国際部

住所: 東京都千代田区紀尾井町 3-3 (郵便番号 102-0094)

Tel.: 03-5226-2038

Fax: 03-5226-2734

E-mail: xad@classnk.or.jp

添付:

1. Res. MEPC.312(74)
2. Res. MEPC.313(74)
3. Res. MEPC.314(74)
4. Res. MEPC.315(74)
5. Res. MEPC.316(74)
6. Res. MEPC.317(74)
7. Res. MEPC.318(74)
8. Res. MEPC.319(74)
9. Res. MEPC.320(74)
10. Res. MEPC.322(74)
11. MEPC.1/Circ.864/Rev.1
12. MEPC.1/Circ.881
13. MEPC.1/Circ.882
14. MEPC.1/Circ.883
15. MEPC.1/Circ.886

ANNEX 1

RESOLUTION MEPC.312(74) (adopted on 17 May 2019)

GUIDELINES FOR THE USE OF ELECTRONIC RECORD BOOKS UNDER MARPOL

THE MARINE ENVIRONMENT PROTECTION COMMITTEE,

RECALLING Article 38(a) of the Convention on the International Maritime Organization concerning the functions of the Marine Environment Protection Committee conferred upon it by international conventions for the prevention and control of marine pollution from ships,

NOTING resolutions MEPC.314(74), MEPC.316(74) and MEPC.317(74), by which it adopted amendments to MARPOL Annexes I, II, V and VI and the Technical Code on Control of Emission of Nitrogen Oxides from Marine Diesel Engines (NO_x Technical Code 2008), respectively, to enable the use of electronic record books,

RECOGNIZING the need to develop guidance for the use of electronic record books,

HAVING CONSIDERED, at its seventy-fourth session, the draft Guidelines for the use of electronic record books under MARPOL, prepared by the Sub-Committee on Pollution Prevention and Response, at its fifth session,

- 1 ADOPTS the *Guidelines for the use of electronic record books under MARPOL*, the text of which is set out in the annex to this resolution;
- 2 INVITES Governments to apply the Guidelines as soon as possible, or when the above-mentioned amendments to MARPOL Annexes I, II, V and VI and the NO_x Technical Code 2008 enter into force;
- 3 AGREES to keep the Guidelines under review in light of experience gained.

ANNEX

GUIDELINES FOR THE USE OF ELECTRONIC RECORD BOOKS UNDER MARPOL

1 INTRODUCTION

1.1 A key element of the International Convention for the Prevention of Pollution from Ships (MARPOL) regulations is the recording of discharges associated with the prevention of pollution from ships. A number of MARPOL Annexes require the recording of particular discharges.

1.2 The format for the recording of discharges under MARPOL is provided in the appendixes to the relevant MARPOL Annexes. Traditionally, the format of these record books has been provided in hard copy by the Administration. However, as companies and shipowners increasingly focus on ways to operate in an environmentally responsible manner and aim to reduce the heavy burden associated with paperwork through electronic means, the concept of operational logs in an electronic format has become a popular consideration.

1.3 It is considered that this approach to recording and reporting should be encouraged as it may have many benefits for the retention of records by companies, crew and officers.

1.4 It is expected that as companies and shipowners increasingly explore electronic record keeping, flag State Administrations will be requested to approve electronic recording systems (henceforth referred to as an electronic record book). This guidance aims to provide standardized information on approving an electronic record book to ensure the obligations of MARPOL are met and that there is a consistent approach to approving such systems.

2 APPLICATION

2.1 These Guidelines are only applicable to the use of electronic record books on board to meet the requirements of the following record books and recording requirements under the MARPOL Annexes and the Technical Code on Control of Emission of Nitrogen Oxides from Marine Diesel Engines (NO_x Technical Code):

- .1 Oil Record Book, parts I and II (MARPOL Annex I, regulations 17.1 and 36.1);
- .2 Cargo Record Book (MARPOL Annex II, regulation 15.1);
- .3 Garbage Record Book, parts I and II (MARPOL Annex V, regulation 10.3);
- .4 Ozone-depleting Substances Record Book (MARPOL Annex VI, regulation 12.6);
- .5 recording of the tier and on/off status of marine diesel engines (MARPOL Annex VI, regulation 13.5.3);
- .6 Record of Fuel Oil Changeover (MARPOL Annex VI, regulation 14.6); and
- .7 Record Book of Engine Parameters (NO_x Technical Code, paragraph 6.2.2.7).

2.2 The use of an electronic record book to record operational logs is an alternative method to a hard copy record book. The electronic record book may allow ships to utilize their technology to reduce administrative burdens and contribute to on board environmental initiatives, e.g. reduction of paper use.

2.3 These Guidelines do not provide information on the management of electronic access to, or electronic versions of, certificates and other documents that do not log continuous operations of a ship.

2.4 These Guidelines do not address the exchange of information from a ship to a company headquarters or other body, as this exchange is not a requirement of record books under MARPOL.

2.5 If a shipowner decides to use an electronic record book to record operational logs, instead of a hard copy record book, the following guidance should be taken into consideration by the Administration when approving the electronic record book for use.

3 DEFINITIONS

For the purposes of these Guidelines, the following definitions apply to the extent consistent with MARPOL:

- .1 **Administration:** means the Government of the State under whose authority the ship is operating. With respect to a ship entitled to fly a flag of any State, the Administration is the Government of that State. With respect to fixed or floating platforms engaged in exploration and exploitation of the seabed and subsoil thereof adjacent to the coast over which the coastal State exercises sovereign rights for the purposes of exploration and exploitation of their natural resources, the Administration is the Government of the coastal State concerned.
- .2 **Audit Logging:** means logs recording user activities, exceptions and information security events, where logs are kept for an agreed period to assist in future investigations and access control monitoring (ISO/IEC 27001:2006). The time and date for the log should be Universal Co-ordinated Time (UTC) derived from ship's time.
- .3 **Backup:** means to make a duplicate copy of a file, program, etc. as a safeguard against loss or corruption of the original. The specific properties of the backup such as its format, frequency, storage location, retention period, are unique to each business organization and should be defined in accordance with a Business Continuity Plan.
- .4 **Business Continuity Plan:** means a collection of procedures and information that is developed, compiled and maintained in readiness for use in the event of an emergency or disaster.
- .5 **Company:** means the Owner of the ship or any other organization or person such as the Manager or the Bareboat Charterer, who has assumed the responsibility for the operation of the ship from the shipowner and who on assuming such responsibility has agreed to take over all the duties and responsibility imposed.
- .6 **Credentials:** means data that is transferred to establish the claimed identity of an entity. (ISO 7498-2). Examples of credentials include a unique code/password, electronic key, digital certificate, hardware key, biometric data (e.g. fingerprint).

- .7 **Cryptography:** means the discipline which embodies principles, means and methods for the transformation of data in order to hide its information content, prevent its undetected modification and/or prevent its unauthorized use (ISO 7498-2).
- .8 **Data:** means a re-interpretable representation of information in a formalized manner suitable for communication, interpretation or processing (ISO/IEC 2382-1).
- .9 **Digital certificate:** means a cryptographic transformation (see "cryptography") of a data unit in an asymmetric (public key) cryptosystem, using a Digital Signature to unite an identity with a public key.
- .10 **Digital signature:** means data appended to, or a cryptographic transformation (see "cryptography") of, a data unit that allows a recipient of the data unit to prove the source and integrity of the data unit and protect against forgery e.g. by the recipient (ISO 7498-2).
- .11 **Document:** means books, manuals, plans, instructions and similar media that are not certificates and are used to convey a ship's information.
- .12 **Electronic record book:** means a device or system used to electronically record the entries for discharges, transfers and other operations as required under MARPOL Annexes and the NO_x Technical Code.
- .13 **Functional Unit:** means an entity of hardware, software, or both, capable of accomplishing a specified purpose ISO/IEC 2382-1:1993 Information technology-Vocabulary- Part 1: Fundamental terms, definition 10.01.40.
- .14 **Graphic character:** means a character, other than a *control character*, that has a visual representation and is normally produced by writing, printing or displaying (ISO 2382-4).
- .15 **IEC 60092 (series):** means standards published by the International Electrotechnical Commission (IEC) on Electrical Installations on Ships.
- .16 **IEC 60533:** means standard published by the International Electrotechnical Commission (IEC) on Electrical and Electronic Installations on Ships – Electromagnetic Compatibility.
- .17 **Offline:** means usage #1. Pertaining to the operation of a functional unit when not under the direct control of the system with which it is associated. Offline units are not available for immediate use on demand by the system. Offline units may be independently operated. Usage #2. Pertaining to equipment that is disconnected from a system, is not in operation, and usually has its main power source disconnected or turned off.
- .18 **Portable Document Format (PDF):** means a digital form for representing documents that enables users to exchange and view electronic documents easily and reliably, independent of the environment in which they were created and the environment in which they are viewed or printed (ISO 32000).

- .19 **Port:** means any port, terminal, offshore terminal, ship and repair yard or roadstead which is normally used for the loading, unloading, repair and anchoring of ships, or any other place at which a ship can call.
- .20 **Key:** means a sequence of symbols that controls the operation of encipherment and decipherment (see "cryptography").
- .21 **Private key:** means (in a public key cryptosystem) that key of a user's key pair which is known only by that user (ISO/IEC 9594-8).
- .22 **Public key:** means (in a public key cryptosystem) that key of a user's key pair which is publicly known (ISO/IEC 9594-8).
- .23 **Role Based Access Control (RBAC):** means a control mechanism that provides different access levels to guarantee that individuals and devices can only gain access to and perform operations on network elements, stored information, and information flows for which they are authorized (ISO/IEC 27033-2:2012).
- .24 **Shipowner:** means one who owns or operates a ship, whether a person, a corporation or other legal entity, and any person acting on behalf of the owner or operator.
- .25 **Signature:** means the handwritten means of identifying the signer of a document or an electronic equivalent which is uniquely and securely linked to an individual.
- .26 **Standardized:** means the prescription of an authoritative rule, principle, means of judgement or estimation, criterion, measure of correctness, measure of perfection or some definite degree of any quality that determines what is adequate for a purpose.
- .27 **Storage (device):** means a functional unit into which data can be placed, in which they can be retained, and from which they can be retrieved (ISO/IEC 2382-1:1993 Information technology – Vocabulary – Part 1: #;Fundamental terms).

4 SYSTEM SPECIFICATIONS

4.1 Ability of the electronic record book to meet regulations under MARPOL

4.1.1 The use and output presentation of any electronic record book approved by an Administration should satisfy the requirements of all relevant regulations under MARPOL.

4.1.2 As MARPOL specifies the recording of a range of information for specific circumstances, an approved system should only allow a complete entry to be saved for verification by the master. For example, for a MARPOL Annex V discharge at sea, the entry should not be able to be saved without the entry of the latitude and longitude of the discharge. It is suggested that where possible, technology which can automatically input required data be installed to ensure accuracy. In the case of equipment failure, manual input should be allowed and the change of the source of data recorded. The automatic data value inputs should be protected by measures aimed at preventing attempts at manipulation or falsification. The system should automatically record any attempts to manipulate or falsify any data.

4.1.3 To assist with consistent recording of data such as dates and positions, the system should be developed to display entry fields and request data formats that are as consistent as possible with other electronic reporting required by IMO and other shipboard systems. Electronic record books should be presented in the form as specified in relevant MARPOL Annexes in order to assist the smooth transition from hard copy record books to electronic ones.

4.1.4 In order to comply with MARPOL requirements, an electronic record book should have the capability to retain all records made for the minimum period as specified in each Annex of MARPOL. The capability to produce a hard copy of verified records for the master to certify as a true copy, upon request from relevant authorities, should also be provided.

4.2 Updates to the electronic record book

As MARPOL and its Annexes continue to evolve, it is essential that all approved electronic record books are reviewed and appropriately updated to ensure relevant MARPOL amendments are incorporated in the electronic record book. Any updates should not cause loss of existing records, nor make them unreadable, and the system should continue to present all records in the form specified by MARPOL. Updates to the system should be completed prior to the entry into force of the relevant MARPOL amendments.

4.3 Security and accountability of the electronic record book

4.3.1 To ensure the security of an electronic record book, it is critical that the system implements Role Based Access Control. At a minimum, all access to the application should use a unique personal login identifier and password for each user. This level of security ensures that the user making entries into the application is accountable for any false entries or omissions.

4.3.2 MARPOL requires the signature of the relevant officer entering a record. As such, the electronic record book should implement Audit Logging. Audit Logging should record a user code, identifying symbol, such as a graphic character, or an equivalent identifier against each entry to uniquely identify the user and whether the user provided accessed or amended an entry.

4.3.3 Electronic signatures applied to an electronic record book should meet authentication standards, as adopted by the Administration.

4.3.4 Records and entries should be protected by measures aimed at preventing and detecting attempts at unauthorized deletion, destruction or amendment. After an entry is saved by the user, the system should secure the information against unauthorized or untraceable changes. Any change(s) to the entry by the same user or a different user should be automatically recorded and made visible both in the system and in any output presentation or printed versions of the electronic record book. The entry should appear in the list of entries in a format that makes it clear that the entry has been amended. To create transparency of changes to saved or verified entries, it is essential that the system is designed to retain both the original entry and the amendment(s).

4.3.5 If an entry requires amendment, it is recommended that the reason and user identifier, for the officer making the amendment, be recorded for verification by the master. The original entries and all amendments should be retained and visible.

4.3.6 MARPOL also requires that information in the record book be verified (e.g. regulation 17 of MARPOL Annex I requires that each page of the Oil Record Book be signed by the master of the ship). For verification of a single or series of saved entries by the master, the electronic record book should have an additional authentication factor to allow verification. This additional authentication factor should be in the form of additional credentials supplied by the master at the time of verification.

4.3.7 The electronic record book should also be able to log and identify the entries made, amended or verified by time. This will assist in identifying those situations where actions requiring an entry are undertaken over days or weeks and all entered at one time, where such an approach to making entries is consistent with MARPOL (e.g. regulation 10 of MARPOL Annex V requires entries to be "promptly recorded" and "signed for on the date of discharge or incineration" by the officer in charge).

4.3.8 To provide for different stages of the data entry and approval process, the electronic record book should provide a status field for each entry that clearly determines the verification stage of the entry. For example, when an entry has been saved in the system by the user, the entry should reflect a term such as "pending" or "awaiting verification". Once the master has verified an entry, a term such as "verified" should be automatically reflected.

4.3.9 If an entry is amended after the master has verified it, the electronic record book should automatically return the entry to "pending" or "re-verification" notifying the master that the entry requires re-verification.

4.3.10 To ensure that entries are verified in a timely manner, the system should provide a reminder that verification by the master is required. It is recommended that where possible, verifications occur prior to arrival in port. Entries not verified should be accompanied by comments advising of the reason for non-verification.

4.3.11 If a recorded entry correlates with a receipt for services (such as a receipt received when waste is discharged to a reception facility), or the endorsement provided during regulatory surveys or inspections (such as endorsement of the Cargo Record Book), the electronic record book should allow this receipt or endorsement to be identified or attached to the relevant entry in the system. This receipt can be referenced in the system with a hard copy receipt or endorsement made available upon request. Alternatively, the receipt or endorsement can be attached to the entry in any form deemed acceptable by the Administration (such as a scanned copy of the original in PDF), and the original retained.

4.4 Storage of data recorded in the electronic record book

4.4.1 To create the same level of confidence as a hard copy record book, any electronic record book should form part of the Information Technology Business Continuity Plan. This includes having an appropriate method for backing up data and data recovery if the system were to fail or not be available from the ships' network. Consideration should also be given to alternate power supplies to ensure consistent access to the system. Both data recovery and power sources are essential to allow ongoing entries to be made and facilitate port State control (PSC) inspections.

4.4.2 The electronic record book should have the capability to allow automatic backup of data in the system to offline storage. Backups should ensure the offline record is updated automatically every time changes are made to entries to ensure the backing up process is not forgotten by the user.

4.4.3 The recorded data stored in the offline space should be:

- .1 developed using cryptography so that unauthorized access to the information is not possible, and so that once the data has been saved it is in a read-only format with no amendments able to be made to the record (unless done so through the application or by a user with the appropriate level of authorization);
- .2 in a format that can be transferred from the point of record to another storage location. Examples include a local (removable) storage peripheral device, local and remote network storage;
- .3 maintained in a format that ensures the longevity and integrity of the record; and
- .4 in a format that allows output presentation and printing of the record.

4.4.4 This offline record may be provided in any format deemed appropriate by the Administration and should be digitally signed by the master. The properties of the digital signature need to appear on the offline record, including the title; full name of the signer; and date and time of signing. It is recommended that the document be presented in PDF; however, an alternative format may be used. Alternative formats should allow the exchange and view of electronic documents independent of the environment in which they were created and the environment in which they are viewed or printed, in a simple way and with fidelity.

4.4.5 An electronic record book and infrastructure related to the system including computers and peripherals, should be installed in compliance with IEC 60092 and IEC 60533, where applicable.

5 DECLARATION

5.1 Any electronic system deemed to meet the above criteria should be provided with written confirmation by the Administration and carried on board the ship for the purpose of regulatory surveys or inspections. An example of a declaration can be seen in the appendix.

5.2 Delegating the assessment of the electronic record book against these Guidelines and the issuing of a declaration on behalf of the Administration by recognized organizations (ROs) is at the discretion of the Administration.

6 MARPOL INSPECTION AND ENFORCEMENT

6.1 Inspection

6.1.1 An electronic record book should have the ability to meet the company verification/audit requirements (such as integration with the ships Safety Management System (International Safety Management Code)). The record book should also have the ability to meet all flag State and survey requirements. In addition, an electronic record book should meet all control provisions as set out in the relevant Annexes of MARPOL. Such a system should also meet any general requirements set out in the *Procedures for port State control, 2017* (resolution A.1119(30)), as amended, as well as support the detection of violations and enforcement of the Convention as outlined in Article 6 of MARPOL.

6.1.2 The use of and reliance upon electronic record books in no way relieves shipowners of their existing duty to accurately maintain and produce records during an inspection, as required by MARPOL. It is recommended that if a ship cannot produce the electronic record book or a declaration provided by the Administration during the PSC inspection, the PSC officer should request to view an alternative verified copy of the records or a hard copy record book for verification.

6.2 Equipment requirements during an inspection

As the electronic record book will be presented using the ships' onboard equipment, it should not be necessary for officers to carry additional equipment (e.g. electronic devices to view the records) during inspections. Officers may choose to carry additional equipment on board to aid in the verification process if the ships' onboard equipment is unavailable.

6.3 Prosecution

To accommodate current procedures when investigating illegal discharges under MARPOL, the electronic record book should allow for the specific entry, relevant page, pages or the entirety of the electronic record book to be printed at the time of an investigation and each printed page physically signed by the master to certify it as a "true copy". All printed pages should provide the following details in addition to those required under MARPOL for record books:

- .1 the title and full name of the person that entered the record (in addition to the person's unique username and/or ID in the electronic record book);
- .2 any changes that were made to the entries;
- .3 the date and time of printing;
- .4 the name and version number of the electronic record book from which the true copy was produced; and
- .5 page numbering and number of pages to ensure the report is complete.

APPENDIX

EXAMPLE DECLARATION

DECLARATION OF MARPOL ELECTRONIC RECORD BOOK

Issued under the authority of the Government of:

.....

(full designation of the country)

*In reference to the requirements set out in the
International Convention for the Prevention of Pollution from Ships (MARPOL)*

Name of ship.....

IMO number

Flag State of ship.....

Gross tonnage.....

This is to declare that the electronic system designed to record entries in accordance with MARPOL Annex(es) installed on board the ship listed above has been assessed by this Administration to meet the relevant requirements as set out in MARPOL and is consistent with the Guidelines developed by the International Maritime Organization (IMO).

Electronic Record Book Manufacturer

Electronic Record Book Supplier

Electronic Record Book Installer

Electronic Record Book Software
Name/Version

Electronic Record Book is in accordance with
MEPC Resolution/s

Date of installation
(dd/mm/yy)

A copy of this declaration should be carried on board a ship fitted with this Electronic Record Book at all times.

.....
NAME SIGNATURE DATE
(dd/mm/yy)

Seal or stamp of the Authority, as appropriate

ANNEX 2

RESOLUTION MEPC.313(74)
(adopted on 17 May 2019)

**AMENDMENTS TO THE 2017 GUIDELINES ADDRESSING ADDITIONAL ASPECTS OF
THE NO_x TECHNICAL CODE 2008 WITH REGARD TO PARTICULAR REQUIREMENTS
RELATED TO MARINE DIESEL ENGINES FITTED WITH SELECTIVE CATALYTIC
REDUCTION (SCR) SYSTEMS (RESOLUTION MEPC.291(71))**

THE MARINE ENVIRONMENT PROTECTION COMMITTEE,

RECALLING Article 38(a) of the Convention on the International Maritime Organization concerning the functions of the Marine Environment Protection Committee (the Committee) conferred upon it by international conventions for the prevention and control of marine pollution from ships,

RECALLING ALSO that, at its fifty-eighth session, it adopted, by resolution MEPC.176(58), a revised MARPOL Annex VI (hereinafter "MARPOL Annex VI") and, by resolution MEPC.177(58), a revised Technical Code on Control of Emission of Nitrogen Oxides from Marine Diesel Engines (hereinafter "NO_x Technical Code 2008"),

NOTING regulation 13 of MARPOL Annex VI which makes the NO_x Technical Code 2008 mandatory under that Annex,

NOTING ALSO that the use of NO_x-reducing devices is envisaged in the NO_x Technical Code 2008 and that selective catalytic reduction systems (hereinafter referred to as "SCR systems") are such NO_x-reducing devices for compliance with the Tier III NO_x limit,

NOTING FURTHER that, at its sixty-second session, it adopted, by resolution MEPC.198(62), the *2011 Guidelines addressing additional aspects to the NO_x Technical Code 2008 with regard to particular requirements related to marine diesel engines fitted with Selective Catalytic Reduction (SCR) Systems*, and, at its sixty-eighth session, by resolution MEPC.260(68), amendments thereto,

NOTING FURTHER that, at its seventy-first session, it adopted, by resolution MEPC.291(71), the *2017 Guidelines addressing additional aspects to the NO_x Technical Code 2008 with regard to particular requirements related to marine diesel engines fitted with Selective Catalytic Reduction (SCR) Systems* (hereinafter "the 2017 Guidelines"),

RECOGNIZING the need to update the 2017 Guidelines in line with the amendments to the NO_x Technical Code 2008, adopted by the Committee, at its seventy-fourth session, by resolution MEPC.317(74),

HAVING CONSIDERED, at its seventy-fourth session, draft amendments to the 2017 Guidelines, prepared by the Sub-Committee on Pollution Prevention and Response, at its fifth session,

1 ADOPTS amendments to the *2017 Guidelines addressing additional aspects to the NO_x Technical Code 2008 with regard to particular requirements related to marine diesel engines fitted with Selective Catalytic Reduction (SCR) Systems*, as set out in the annex to the present resolution;

2 INVITES Administrations to take the aforementioned amendments into account when certifying engines fitted with SCR systems;

3 REQUESTS Parties to MARPOL Annex VI and other Member Governments to bring the amendments to the attention of shipowners, ship operators, shipbuilders, marine diesel engine manufacturers and any other interested parties;

4 AGREES to keep these Guidelines, as amended, under review, in light of experience gained with their application.

ANNEX

AMENDMENTS TO THE 2017 GUIDELINES ADDRESSING ADDITIONAL ASPECTS OF THE NO_x TECHNICAL CODE 2008 WITH REGARD TO PARTICULAR REQUIREMENTS RELATED TO MARINE DIESEL ENGINES FITTED WITH SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEMS (RESOLUTION MEPC.291(71))

- 1 Paragraph 1.3 is replaced with the following:

"1.3 According to paragraph 2.2.5.1 of the NTC 2008, where a NO_x-reducing device is to be included within the EIAPP certification, it must be recognized as a component of the engine, and its presence shall be recorded in the engine's Technical File."

- 2 Paragraph 3.1.1 is replaced with the following:

"3.1.1 Engine systems fitted with SCR should be certified in accordance with chapter 2 of the NTC 2008. The procedures provided by Scheme A or Scheme B of these Guidelines should be applied."

ANNEX 3

RESOLUTION MEPC.314(74)
(adopted on 17 May 2019)

**AMENDMENTS TO THE ANNEX OF THE INTERNATIONAL CONVENTION FOR THE
PREVENTION OF POLLUTION FROM SHIPS, 1973, AS MODIFIED BY THE
PROTOCOL OF 1978 RELATING THERETO**

Amendments to MARPOL Annexes I, II and V

(Electronic Record Books)

THE MARINE ENVIRONMENT PROTECTION COMMITTEE,

RECALLING Article 38(a) of the Convention on the International Maritime Organization concerning the functions of the Marine Environment Protection Committee conferred upon it by international conventions for the prevention and control of marine pollution from ships,

RECALLING ALSO article 16 of the International Convention for the Prevention of Pollution from Ships, 1973, as modified by the Protocol of 1978 relating thereto (MARPOL), which specifies the amendment procedure and confers upon the appropriate body of the Organization the function of considering and adopting amendments thereto,

HAVING CONSIDERED, at its seventy-fourth session, proposed amendments to MARPOL Annexes I, II and V concerning Electronic Record Books, which were circulated in accordance with article 16(2)(a) of MARPOL,

1 ADOPTS, in accordance with article 16(2)(d) of MARPOL, amendments to MARPOL Annexes I, II and V, the text of which is set out in the annex to the present resolution;

2 DETERMINES, in accordance with article 16(2)(f)(iii) of MARPOL, that the amendments shall be deemed to have been accepted on 1 April 2020 unless prior to that date, not less than one third of the Parties or Parties the combined merchant fleets of which constitute not less than 50% of the gross tonnage of the world's merchant fleet, have communicated to the Organization their objection to the amendments;

3 INVITES the Parties to note that, in accordance with article 16(2)(g)(ii) of MARPOL, the said amendments shall enter into force on 1 October 2020 upon their acceptance in accordance with paragraph 2 above;

4 REQUESTS the Secretary-General, for the purposes of article 16(2)(e) of MARPOL, to transmit certified copies of the present resolution and the text of the amendments contained in the annex to all Parties to MARPOL;

5 REQUESTS ALSO the Secretary-General to transmit copies of the present resolution and its annex to Members of the Organization which are not Parties to MARPOL.

ANNEX

AMENDMENTS TO MARPOL ANNEXES I, II AND V

(Electronic Record Books)

MARPOL ANNEX I

REGULATIONS FOR THE PREVENTION OF POLLUTION BY OIL

Regulation 1 – Definitions

1 A new paragraph 39 is added as follows:

"39 *Electronic Record Book* means a device or system, approved by the Administration, used to electronically record the required entries for discharges, transfers and other operations as required under this Annex in lieu of a hard copy record book."

Regulation 17 – Oil Record Book Part I – Machinery space operations

2 The second sentence of paragraph 1 is replaced by the following:

"The Oil Record Book, whether as a part of the ship's official logbook, as an electronic record book which shall be approved by the Administration taking into account the Guidelines developed by the Organization*, or otherwise, shall be in the form specified in appendix III to this Annex."

3 In the second sentence of paragraph 4, the words "or group of electronic entries" are inserted after the words "each completed page".

Regulation 36 – Oil Record Book Part II – Cargo/ballast operations

4 The second sentence of paragraph 1 is replaced by the following:

"The Oil Record Book Part II, whether as a part of the ship's official logbook, as an electronic record book which shall be approved by the Administration taking into account the Guidelines developed by the Organization*, or otherwise, shall be in the Form specified in appendix III to this Annex."

5 In the second sentence of paragraph 5, the words "or group of electronic entries" are inserted after the words "each completed page".

* Refer to the *Guidelines for the use of electronic record books under MARPOL*, adopted by resolution MEPC.312(74)"

MARPOL ANNEX II

REGULATIONS FOR THE CONTROL OF POLLUTION OF NOXIOUS LIQUID SUBSTANCES IN BULK

Regulation 1 – Definitions

6 A new paragraph 22 is added as follows:

"22 *Electronic Record Book* means a device or system, approved by the Administration, used to electronically record the required entries for discharges, transfers and other operations as required under this Annex in lieu of a hard copy record book."

Regulation 15 – Cargo Record Book

7 The existing paragraph 1 is replaced by the following:

"Every ship to which this Annex applies shall be provided with a Cargo Record Book, whether as a part of the ship's official logbook, as an electronic record book which shall be approved by the Administration taking into account Guidelines developed by the Organization*, or otherwise, in the form specified in appendix II to this Annex."

8 In the first sentence of paragraph 4, the words "or group of electronic entries" are inserted after the words "each page".

MARPOL ANNEX V

REGULATIONS FOR THE PREVENTION OF POLLUTION BY GARBAGE FROM SHIPS

Regulation 1 – Definitions

9 A new paragraph 19 is added as follows:

"19 *Electronic Record Book* means a device or system, approved by the Administration, used to electronically record the required entries for discharges, transfers and other operations as required under this Annex in lieu of a hard copy record book."

Regulation 10 – Placards, garbage management plans and garbage record-keeping

10 The second sentence of the chapeau of paragraph 3 is replaced by the following:

"The Garbage Record Book, whether as a part of the ship's official logbook, or as an electronic record book which shall be approved by the Administration taking into account the Guidelines developed by the Organization*, or otherwise, shall be in the form specified in appendix II to this Annex:"

11 In the second sentence of paragraph 3.1, the words "or group of electronic entries" are inserted after the words "each completed page".

* Refer to the *Guidelines for the use of electronic record books under MARPOL*, adopted by resolution MEPC.312(74)"

ANNEX 4

**RESOLUTION MEPC.315(74)
(adopted on 17 May 2019)**

**AMENDMENTS TO THE ANNEX OF THE INTERNATIONAL CONVENTION FOR THE
PREVENTION OF POLLUTION FROM SHIPS, 1973, AS MODIFIED BY THE
PROTOCOL OF 1978 RELATING THERETO**

Amendments to MARPOL Annex II

(Cargo residues and tank washings of persistent floating products)

THE MARINE ENVIRONMENT PROTECTION COMMITTEE,

RECALLING Article 38(a) of the Convention on the International Maritime Organization concerning the functions of the Marine Environment Protection Committee conferred upon it by international conventions for the prevention and control of marine pollution from ships,

RECALLING ALSO article 16 of the International Convention for the Prevention of Pollution from Ships, 1973, as modified by the Protocol of 1978 relating thereto (MARPOL), which specifies the amendment procedure and confers upon the appropriate body of the Organization the function of considering and adopting amendments thereto,

HAVING CONSIDERED, at its seventy-fourth session, proposed amendments to MARPOL Annex II concerning cargo residues and tank washings of persistent floating products, which were circulated in accordance with article 16(2)(a) of MARPOL,

1 ADOPTS, in accordance with article 16(2)(d) of MARPOL, amendments to MARPOL Annex II, the text of which is set out in the annex to the present resolution;

2 DETERMINES, in accordance with article 16(2)(f)(iii) of MARPOL, that the amendments shall be deemed to have been accepted on 1 July 2020 unless prior to that date, not less than one third of the Parties or Parties the combined merchant fleets of which constitute not less than 50% of the gross tonnage of the world's merchant fleet, have communicated to the Organization their objection to the amendments;

3 INVITES the Parties to note that, in accordance with article 16(2)(g)(ii) of MARPOL, the said amendments shall enter into force on 1 January 2021 upon their acceptance in accordance with paragraph 2 above;

4 REQUESTS the Secretary-General, for the purposes of article 16(2)(e) of MARPOL, to transmit certified copies of the present resolution and the text of the amendments contained in the annex to all Parties to MARPOL;

5 REQUESTS ALSO the Secretary-General to transmit copies of the present resolution and its annex to Members of the Organization which are not Parties to MARPOL.

ANNEX

AMENDMENTS TO MARPOL ANNEX II

(Cargo residues and tank washings of persistent floating products)

CHAPTER 1 – GENERAL

Regulation 1 – Definitions

1 A new paragraph 23 is added as follows:

"23 *Persistent floater* means a slick forming substance with the following properties:

- Density: \leq sea water (1025 kg/m^3 at 20°C);
- Vapour pressure: $\leq 0.3 \text{ kPa}$;
- Solubility: $\leq 0.1\%$ (for liquids) $\leq 10\%$ (for solids); and
- Kinematic viscosity: $> 10 \text{ cSt}$ at 20°C ."

**CHAPTER 5 – OPERATIONAL DISCHARGES OF RESIDUES
OF NOXIOUS LIQUID SUBSTANCES**

Regulation 13 – Control of discharges of residues of noxious liquid substances

2 A new paragraph 7.1.4 is inserted after existing paragraph 7.1.3 as follows:

"7.1.4 For substances assigned to category Y that are persistent floaters with a viscosity equal to or greater than $50 \text{ mPa}\cdot\text{s}$ at 20°C and/or with a melting point equal to or greater than 0°C , as identified by '16.2.7' in column 'o' of chapter 17 of the IBC Code, the following shall apply in the areas in paragraph 9:

- .1 a prewash procedure as specified in appendix VI to this annex shall be applied;
- .2 the residue/water mixture generated during the prewash shall be discharged to a reception facility at the port of unloading until the tank is empty; and
- .3 any water subsequently introduced into the tank may be discharged into the sea in accordance with the discharge standards in regulation 13.2."

3 A new paragraph 9 is inserted after existing paragraph 8.2 as follows:

"9 Areas to which regulation 13.7.1.4 applies

9.1 the *North West European waters* include the North Sea and its approaches, the Irish Sea and its approaches, the Celtic Sea, the English Channel and its approaches and part of the North East Atlantic immediately to the west of Ireland. The area is bounded by lines joining the following points:

48°27' N on the French coast
48°27' N; 006°25' W
49°52' N; 007°44' W
50°30' N; 012° W
56°30' N; 012° W
62° N; 003° W
62° N on the Norwegian coast
57°44.8' N on the Danish and Swedish coasts

9.2 the *Baltic Sea area* means the Baltic Sea proper with the Gulf of Bothnia, the Gulf of Finland and the entrance to the Baltic Sea bounded by the parallel of the Skaw in the Skagerrak at 57°44.8' N;

9.3 the *Western European waters* is an area that covers the United Kingdom, Ireland, Belgium, France, Spain and Portugal, from the Shetland Islands in the North to Cape S. Vicente in the South, and the English Channel and its approaches. The area is bounded by lines joining the following points:

58°30' N on the UK coast
58°30' N; 000° W
62° N; 000° W
62° N; 003° W
56°30' N; 012° W
54°40'40.9" N; 015° W
50°56'45.3" N; 015° W
48°27' N; 006°25' W
48°27' N; 008° W
44°52' N; 003°10' W
44°52' N; 010° W
44°14' N; 011°34' W
42°55' N; 012°18' W
41°50' N; 011°34' W
37°00' N; 009°49' W
36°20' N; 009°00' W
36°20' N; 007°47' W
37°10' N; 007°25' W
51°22'25" N; 003°21'52.5" E
52°12' N; on the UK east coast
52°10.3' N; 006°21.8' W
52°01.52' N; 005°04.18' W
54°51.43' N; 005°08.47' W
54°40.39' N; 005°34.34' W

9.4 the *Norwegian Sea* is bounded by lines joining the following points:"

69°47.6904' N; 030°49.059' E
69°58.758' N; 031°6.2598' E
70°8.625' N; 031°35.1354' E
70°16.4826' N; 032°4.3836' E
73°23.0652' N; 036°28.5732' E
73°35.6586' N; 035°27.3378' E
74°2.9748' N; 033°17.8596' E
74°20.7084' N; 030°33.5052' E
74°29.7972' N; 026°28.1808' E
74°24.2448' N; 022°55.0272' E
74°13.7226' N; 020°15.9762' E
73°35.439' N; 016°36.4974' E
73°14.8254' N; 014°9.4266' E
72°42.54' N; 011°42.1392' E
71°58.2' N; 009°54.96' E
71°37.5612' N; 008°43.8222' E
70°43.161' N; 006°36.0672' E
69°36.624' N; 004°47.322' E
68°58.3164' N; 003°51.2154' E
68°14.9892' N; 003°17.0322' E
67°25.7982' N; 003°10.2078' E
66°49.7292' N; 003°25.1304' E
66°25.9344' N; 003°17.1102' E
65°22.7214' N; 001°24.5928' E
64°25.9692' N; 000°29.3214' W
63°53.2242' N; 000°29.442' W
62°53.4654' N; 000°38.355' E
62° N; 001°22.2498' E
62° N; 004°52.3464' E

APPENDIX IV – STANDARD FORMAT FOR THE PROCEDURES AND ARRANGEMENTS MANUAL

Section 4 – Procedures relating to the cleaning of cargo tanks, the discharge of residues, ballasting and deballasting

4 Paragraph 4.4.5 is replaced by the following:

".5 Persistent floaters with a viscosity equal to or greater than 50 mPa·s at 20°C and/or a melting point equal to or greater than 0°C

This section should contain instructions on how to deal with tank washings of substances identified by the presence of '16.2.7' in column 'o' of chapter 17 of the IBC Code and the latest version of the MEPC.2/Circular, when operating in the areas specified in regulation 13.9 of Annex II."

Addendum A – Flow diagrams – Cleaning of cargo tanks and disposal of tank washings/ballast containing residues of category X, Y and Z substances

5 A new Note 4 is inserted after existing Note 3 as follows:

"Note 4: Within the areas specified in regulation 13.9 of Annex II, regulation 13.7.1.4 applies to substances that are identified by '16.2.7' in column 'o' of chapter 17 of the IBC Code."

APPENDIX VI – PREWASH PROCEDURES

6 A new section C is added after existing paragraph 21 as follows:

"C For all ships

Prewash procedures for persistent floaters to which regulation 13.7.1.4 of Annex II of MARPOL applies

Persistent floaters with a viscosity equal to or greater than 50 mPa·s at 20°C and/or a melting point equal to or greater than 0°C, shall be treated as solidifying or high-viscosity substances for the purposes of the prewash.

Where it is determined that the use of small amounts of cleaning additives would improve and maximize the removal of cargo residues during a prewash, then this should be done in consultation and with prior agreement from the reception facility."

ANNEX 5

**RESOLUTION MEPC.316(74)
(adopted on 17 May 2019)**

**AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1997 TO AMEND THE
INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS,
1973, AS MODIFIED BY THE PROTOCOL OF 1978 RELATING THERETO**

Amendments to MARPOL Annex VI

(Electronic Record Books and EEDI regulations for ice-strengthened ships)

THE MARINE ENVIRONMENT PROTECTION COMMITTEE,

RECALLING Article 38(a) of the Convention on the International Maritime Organization concerning the functions of the Marine Environment Protection Committee conferred upon it by international conventions for the prevention and control of marine pollution from ships,

RECALLING ALSO article 16 of the International Convention for the Prevention of Pollution from Ships, 1973, as modified by the Protocols of 1978 and 1997 relating thereto (MARPOL), which specifies the amendment procedure and confers upon the appropriate body of the Organization the function of considering amendments thereto for adoption by the Parties,

HAVING CONSIDERED, at its seventy-fourth session, proposed amendments to MARPOL Annex VI concerning Electronic Record Books and EEDI regulations for ice-strengthened ships, which were circulated in accordance with article 16(2)(a) of MARPOL,

1 ADOPTS, in accordance with article 16(2)(d) of MARPOL, amendments to MARPOL Annex VI, the text of which is set out in the annex to the present resolution;

2 DETERMINES, in accordance with article 16(2)(f)(iii) of MARPOL, that the amendments shall be deemed to have been accepted on 1 April 2020 unless prior to that date, not less than one third of the Parties or Parties the combined merchant fleets of which constitute not less than 50% of the gross tonnage of the world's merchant fleet, have communicated to the Organization their objection to the amendments;

3 INVITES the Parties to note that, in accordance with article 16(2)(g)(ii) of MARPOL, the said amendments shall enter into force on 1 October 2020 upon their acceptance in accordance with paragraph 2 above;

4 REQUESTS the Secretary-General, for the purposes of article 16(2)(e) of MARPOL, to transmit certified copies of the present resolution and the text of the amendments contained in the annex to all Parties to MARPOL;

5 REQUESTS ALSO the Secretary-General to transmit copies of the present resolution and its annex to Members of the Organization which are not Parties to MARPOL.

ANNEX

AMENDMENTS TO MARPOL ANNEX VI

(Electronic Record Books and EEDI regulations for ice-strengthened ships)

Regulation 2 – Definitions

1 Paragraph 42 is replaced by the following:

"42 *Polar Code* means the International Code for Ships Operating in Polar Waters, consisting of an introduction, parts I-A and II-A and parts I-B and II-B, adopted by resolutions MSC.385(94) and MEPC.264(68), as may be amended, provided that:

- .1 amendments to the environment-related provisions of the introduction and chapter 1 of part II-A of the Polar Code are adopted, brought into force and take effect in accordance with the provisions of article 16 of the present Convention concerning the amendment procedures applicable to an appendix to an annex; and
- .2 amendments to part II-B of the Polar Code are adopted by the Marine Environment Protection Committee in accordance with its Rules of Procedure."

2 A new paragraph 51 is added as follows:

"51 *Electronic Record Book* means a device or system, approved by the Administration, used to electronically record the required entries for discharges, transfers and other operations as required under this Annex in lieu of a hard copy record book."

Regulation 12 – Ozone-depleting substances

3 In the second sentence of paragraph 6, the words "recording system" are replaced by "record book**".

4 A new sentence is inserted at the end of paragraph 6 as follows:

"An electronic recording system referred to in regulation 12.6, as adopted by resolution MEPC.176(58), shall be considered an electronic record book, provided the electronic recording system is approved by the Administration on or before the first International Air Pollution Prevention (IAPP) Certificate renewal survey carried out on or after 1 October 2020, but not later than 1 October 2025, taking into account the Guidelines developed by the Organization**"

Regulation 13 – Nitrogen oxides (NO_x)

5 In paragraph 5.3, the words "or electronic record book*", " are inserted after the words "shall be recorded in such logbook".

** Refer to the *Guidelines for the use of electronic record books under MARPOL*, adopted by resolution MEPC.312(74)."

Regulation 14 – Sulphur oxides (SO_x) and particulate matter

6 In the last sentence of paragraph 6, the words "or electronic record book*," are inserted after the words "shall be recorded in such logbook".

Regulation 19 – Application

7 In the last sentence of paragraph 3, the words "cargo ships having ice-breaking capability" are replaced by the words "category A ships as defined in the Polar Code".

Appendix I

Form of International Air Pollution Prevention (IAPP) Certificate (Regulation 8)

8 In the introductory paragraph of Appendix I, the words "by resolution MEPC.176(58) in 2008" are deleted.

Appendix VIII

Form of International Energy Efficiency (IEE) Certificate

9 In the introductory paragraph, the words "by resolution MEPC.203(62)" are deleted.

Appendix X

Form of Statement of Compliance – Fuel Oil Consumption Reporting

10 In the introductory paragraph, the word "by" between "Pollution" and "Ships" in the first sentence is replaced by the word "from".

* Refer to the *Guidelines for the use of electronic record books under MARPOL*, adopted by resolution MEPC.312(74)."

ANNEX 6

RESOLUTION MEPC.317(74)
(adopted on 17 May 2019)

AMENDMENTS TO THE NO_x TECHNICAL CODE 2008

(Electronic Record Books and Certification requirements for SCR systems)

THE MARINE ENVIRONMENT PROTECTION COMMITTEE,

RECALLING Article 38(a) of the Convention on the International Maritime Organization concerning the functions of the Marine Environment Protection Committee conferred upon it by international conventions for the prevention and control of marine pollution from ships,

RECALLING ALSO article 16 of the International Convention for the Prevention of Pollution from Ships, 1973, as modified by the Protocols of 1978 and 1997 relating thereto (MARPOL), which specifies the amendment procedure and confers upon the appropriate body of the Organization the function of considering and adopting amendments thereto,

RECALLING FURTHER regulation 13 of MARPOL Annex VI which makes the Technical Code on Control of Emission of Nitrogen Oxides from Marine Diesel Engines ("the NO_x Technical Code 2008") mandatory under that Annex,

HAVING CONSIDERED, at its seventy-fourth session, draft amendments to the NO_x Technical Code 2008 related to Electronic Record Books and certification requirements for SCR systems, which were circulated in accordance with article 16(2)(a) of MARPOL,

1 ADOPTS, in accordance with article 16(2)(d) of MARPOL, amendments to the NO_x Technical Code 2008, as set out in the annex to the present resolution;

2 DETERMINES, in accordance with article 16(2)(f)(iii) of MARPOL, that the amendments shall be deemed to have been accepted on 1 April 2020, unless prior to that date not less than one third of the Parties or Parties, the combined merchant fleets of which constitute not less than 50% of the gross tonnage of the world's merchant fleet, have communicated to the Organization their objection to the amendments;

3 INVITES the Parties to note that, in accordance with article 16(2)(g)(ii) of MARPOL, the said amendments shall enter into force on 1 October 2020 upon their acceptance in accordance with paragraph 2 above;

4 REQUESTS the Secretary-General, for the purposes of article 16(2)(e) of MARPOL, to transmit certified copies of the present resolution and the text of the amendments contained in the annex to all Parties to MARPOL;

5 REQUESTS ALSO the Secretary-General to transmit copies of the present resolution and its annex to the Members of the Organization which are not Parties to MARPOL.

ANNEX

AMENDMENTS TO THE NO_x TECHNICAL CODE 2008

(Electronic Record Books and Certification requirements for SCR systems)

Chapter 1 – General

1.3 Definitions

1 A new paragraph 1.3.20 is added as follows:

"1.3.20 *Electronic Record Book* means a device or system, approved by the Administration, used to electronically record the entries required under this Code in lieu of a hard copy record book."

Chapter 2 – Surveys and certification

2.2 Procedures for pre-certification of an engine

2 Paragraph 2.2.5.1 is replaced by the following:

".1 Where a NO_x-reducing device is to be included within the EIAPP certification, it must be recognized as a component of the engine, and its presence shall be recorded in the engine's Technical File. The applicable test procedure shall be performed and the combined engine/NO_x-reducing device shall be approved and pre-certified by the Administration taking into account Guidelines developed by the Organization*. However, the pre-certification in accordance with the procedure not involving the testing for the combined engine/NO_x-reducing device on a test bed as given by the Guidelines developed by the Organization is subject to the limitations given in paragraph 2.2.4.2."

Chapter 6 – Procedures for demonstrating compliance with NO_x emission limits on board

6.2.2 Documentation for an engine parameter check method

3 In paragraph 6.2.2.7.1, after the words "a record book", the words "or electronic record book**" are inserted.

Appendix I Form of EIAPP Certificate

4 In the introductory paragraph, the words "by resolution MEPC.176(58) in 2008" are deleted.

* Refer to the 2017 Guidelines addressing additional aspects to the NO_x Technical Code 2008 with regard to particular requirements related to marine diesel engines fitted with selective catalytic reduction (SCR) systems, adopted by resolution MEPC.291(71), as amended (resolution MEPC.313(74)).

** Refer to the Guidelines for the use of electronic record books under MARPOL, adopted by resolution MEPC.312(74)."

ANNEX 7

**RESOLUTION MEPC.318(74)
(adopted on 17 May 2019)**

**AMENDMENTS TO THE INTERNATIONAL CODE FOR THE CONSTRUCTION AND
EQUIPMENT OF SHIPS CARRYING DANGEROUS
CHEMICALS IN BULK (IBC CODE)**

(Amendments to Chapters 1, 15, 16, 17, 18, 19 and 21)

THE MARINE ENVIRONMENT PROTECTION COMMITTEE,

RECALLING Article 38(a) of the Convention on the International Maritime Organization concerning the functions of the Marine Environment Protection Committee conferred upon it by international conventions for the prevention and control of marine pollution from ships,

RECALLING ALSO resolution MEPC.19(22) by which it adopted the *International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk* ("the IBC Code"), and resolution MEPC.16(22) by which the IBC Code has become mandatory under Annex II of the International Convention for the Prevention of Pollution from Ships, 1973, as modified by the Protocol of 1978 relating thereto (MARPOL),

RECALLING FURTHER article 16 of MARPOL and regulation 1.4 of MARPOL Annex II concerning the procedure for amending the IBC Code,

HAVING CONSIDERED, at its seventy-fourth session, proposed amendments to the IBC Code, which were circulated in accordance with article 16(2)(a) of MARPOL,

1 ADOPTS, in accordance with article 16(2)(d) of MARPOL, amendments to the IBC Code, the text of which is set out in the annex to the present resolution;

2 DETERMINES, in accordance with article 16(2)(f)(iii) of MARPOL, that the amendments to the IBC Code shall be deemed to have been accepted on 1 July 2020 unless, prior to that date, not less than one third of the Parties or Parties, the combined merchant fleets of which constitute not less than 50% of the gross tonnage of the world's merchant fleet, have communicated to the Organization their objection to the amendments;

3 INVITES the Parties to note that, in accordance with article 16(2)(g)(ii) of MARPOL, the amendments to the IBC Code shall enter into force on 1 January 2021 upon their acceptance in accordance with paragraph 2 above;

4 REQUESTS the Secretary-General, for the purposes of article 16(2)(e) of MARPOL, to transmit certified copies of the present resolution and the text of the amendments to the IBC Code contained in the annex, to all Parties to MARPOL;

5 REQUESTS ALSO the Secretary-General to transmit copies of the present resolution and its annex to the Members of the Organization which are not Parties to MARPOL.

ANNEX

AMENDMENTS TO THE INTERNATIONAL CODE FOR THE CONSTRUCTION AND EQUIPMENT OF SHIPS CARRYING DANGEROUS CHEMICALS IN BULK (IBC CODE)

Chapter 1

General

- 1 The existing section 1.3 is replaced by the following:

"1.3 Definitions

The following definitions apply unless expressly provided otherwise. (Additional definitions are given in individual chapters).

- 1.3.1 *Accommodation spaces* are those spaces used for public spaces, corridors, lavatories, cabins, offices, hospitals, cinemas, games and hobbies rooms, barber shops, pantries containing no cooking appliances and similar spaces. *Public spaces* are those portions of the accommodation spaces which are used for halls, dining rooms, lounges and similar permanently enclosed spaces.
- 1.3.2 *Administration* means the Government of the State whose flag the ship is entitled to fly. For *Administration (Port)* see *Port Administration*.
- 1.3.3 *Anniversary date* means the day and the month of each year which will correspond to the date of expiry of the International Certificate of Fitness for the Carriage of Dangerous Chemicals in Bulk.
- 1.3.4 *Boiling point* is the temperature at which a product exhibits a vapour pressure equal to the atmospheric pressure.
- 1.3.5 *Breadth (B)* means the maximum breadth of the ship, measured amidships to the moulded line of the frame in a ship with a metal shell and to the outer surface of the hull in a ship with a shell of any other material. The breadth (*B*) shall be measured in metres.
- 1.3.6 *Cargo area* is that part of the ship that contains cargo tanks, slop tanks, cargo pump-rooms including pump-rooms, cofferdams, ballast or void spaces adjacent to cargo tanks or slop tanks and also deck areas throughout the entire length and breadth of the part of the ship over the above-mentioned spaces. Where independent tanks are installed in hold spaces, cofferdams, ballast or void spaces at the after end of the aftermost hold space or at the forward end of the forward-most hold space are excluded from the cargo area.
- 1.3.7 *Cargo pump-room* is a space containing pumps and their accessories for the handling of the products covered by the Code.

- 1.3.8 *Cargo service spaces* are spaces within the cargo area used for workshops, lockers and storerooms of more than 2 m² in area, used for cargo-handling equipment.
- 1.3.9 *Cargo tank* is the envelope designed to contain the cargo.
- 1.3.10 *Chemical tanker* is a cargo ship constructed or adapted and used for the carriage in bulk of any liquid product listed in chapter 17.
- 1.3.11 *Cofferdam* is the isolating space between two adjacent steel bulkheads or decks. This space may be a void space or a ballast space.
- 1.3.12 *Control stations* are those spaces in which ship's radio or main navigating equipment or the emergency source of power is located or where the fire-recording or fire-control equipment is centralized. This does not include special fire-control equipment which can be most practically located in the cargo area.
- 1.3.13 *Dangerous chemicals* means any liquid chemicals designated as presenting a safety hazard, based on the safety criteria for assigning products to chapter 17.
- 1.3.14 *Density* is the ratio of the mass to the volume of a product, expressed in terms of kilograms per cubic metre. This applies to liquids, gases and vapours.
- 1.3.15 *Explosive/flammability limits/range* are the conditions defining the state of fuel-oxidant mixture at which application of an adequately strong external ignition source is only just capable of producing flammability in a given test apparatus.
- 1.3.16 *Flashpoint* is the temperature in degrees Celsius at which a product will give off enough flammable vapour to be ignited. Values given in the Code are those for a "closed-cup test" determined by an approved flashpoint apparatus.
- 1.3.17 *Gas-freeing* means the process where a portable or fixed ventilation system is used to introduce fresh air into a tank in order to reduce the concentration of hazardous gases or vapours to a level safe for tank entry.
- 1.3.18 *Hold space* is the space enclosed by the ship's structure in which an independent cargo tank is situated.
- 1.3.19 *Independent* means that a piping or venting system, for example, is in no way connected to another system and that there are no provisions available for the potential connection to other systems.
- 1.3.20 *Length (L)* means 96% of the total length on a waterline at 85% of the least moulded depth measured from the top of the keel, or the length from the foreside of the stem to the axis of the rudder stock on that waterline, if that be greater. In ships designed with a rake of keel, the waterline on which this length is measured shall be parallel to the designed waterline. The length (L) shall be measured in metres.

- 1.3.21 *Machinery spaces of category A* are those spaces and trunks to such spaces which contain:
- .1 internal-combustion machinery used for main propulsion; or
 - .2 internal-combustion machinery used for purposes other than main propulsion where such machinery has in the aggregate a total power output of not less than 375 kW; or
 - .3 any oil-fired boiler or oil fuel unit or any oil-fired equipment other than boilers, such as inert gas generators, incinerators, etc.
- 1.3.22 *Machinery spaces* are all machinery spaces of category A and all other spaces containing propelling machinery, boilers, oil fuel units, steam and internal-combustion engines, generators and major electrical machinery, oil filling station, refrigerating, stabilizing, ventilation and air-conditioning machinery, and similar spaces, and trunks to such spaces.
- 1.3.23 *MARPOL* means the International Convention for the Prevention of Pollution from Ships, 1973, as modified by the Protocol of 1978 relating thereto and by the Protocol of 1997, as amended.
- 1.3.24 *Noxious Liquid Substance* means any substance indicated in the Pollution Category column of chapters 17 or 18 of the International Bulk Chemical Code, or the current MEPC.2/Circular or provisionally assessed under the provisions of regulation 6.3 of MARPOL Annex II as falling into categories X, Y or Z.
- 1.3.25 *Oil fuel unit* is the equipment used for the preparation of oil fuel for delivery to an oil-fired boiler, or equipment used for the preparation for delivery of heated oil to an internal-combustion engine, and includes any oil pressure pumps, filters and heaters dealing with oil at a gauge pressure of more than 0.18 MPa.
- 1.3.26 *Organization* is the International Maritime Organization (IMO).
- 1.3.27 *Permeability* of a space means the ratio of the volume within that space which is assumed to be occupied by water to the total volume of that space.
- 1.3.28 *Port Administration* means the appropriate authority of the country in the port of which the ship is loading or unloading.
- 1.3.29 *Products* is the collective term used to cover both Noxious Liquid Substances and Dangerous Chemicals.
- 1.3.30 *Pump-room* is a space, located in the cargo area, containing pumps and their accessories for the handling of ballast and oil fuel.
- 1.3.31 *Purging* means the introduction of inert gas into a tank which is already in an inert condition with the object of further reducing the oxygen content; and/or reducing the existing hydrocarbon or other flammable vapours content to a level below which combustion cannot be supported if air is subsequently introduced into the tank.

- 1.3.32 *Recognized organization* is an organization authorized by an Administration in accordance with MARPOL Annex II regulation 8.2.2 and SOLAS regulation XI-1/1.
- 1.3.33 *Recognized standards* are applicable international or national standards acceptable to the Administration or standards laid down and maintained by an organization which complies with the standards adopted by the Organization and which is recognized by the Administration.
- 1.3.34 *Reference temperature* is the temperature at which the vapour pressure of the cargo corresponds to the set pressure of the pressure-relief valve.
- 1.3.35 *Separate* means that a cargo piping system or cargo vent system, for example, is not connected to another cargo piping or cargo vent system.
- 1.3.36 *Service spaces* are those spaces used for galleys, pantries containing cooking appliances, lockers, mail and specie rooms, storerooms, workshops other than those forming part of the machinery spaces and similar spaces and trunks to such spaces.
- 1.3.37 *SOLAS* means the International Convention for the Safety of Life at Sea, 1974, as amended.
- 1.3.38 *Vapour pressure* is the equilibrium pressure of the saturated vapour above a liquid expressed in Pascals (Pa) at a specified temperature.
- 1.3.39 *Void space* is an enclosed space in the cargo area external to a cargo tank, other than a hold space, ballast space, oil fuel tank, cargo pump-room, pump-room, or any space in normal use by personnel."

2 Paragraph 1.5.1.2 is replaced by the following:

"1.5.1.2 The recognized organization referred to in 1.3.32 shall comply with the provisions of SOLAS and MARPOL and with Parts 1 and 2 of the Code for Recognized Organizations (RO Code), as adopted by resolutions MSC.349(92) and MEPC.237(65), as may be amended."

Chapter 15

Special requirements

3 In paragraph 15.8.25.1, the reference to paragraph "1.3.18" in the second set of brackets is replaced by "1.3.19".

4 Section 15.15 is replaced by the following:

"15.15 Hydrogen sulphide (H₂S) detection equipment for bulk liquids

Hydrogen sulphide (H₂S) detection equipment shall be provided on board ships carrying bulk liquids prone to H₂S formation. It should be noted that scavengers and biocides, when used, may not be 100% effective in controlling the formation of H₂S. Toxic vapour detection instruments complying with the requirement in 13.2.1 of the Code for testing for H₂S may be used to satisfy this requirement."

Chapter 16

Operational requirements

5 Paragraph 16.2.7 is replaced by the following:

"16.2.7 Where *column o* in the table of chapter 17 refers to this paragraph, the cargo is subject to the prewash requirements in regulation 13.7.1.4 of Annex II of MARPOL."

6 The complete text of chapters 17, 18 and 19 is replaced by the following:

"Chapter 17

Summary of minimum requirements

17.1 Mixtures of noxious liquid substances presenting pollution hazards only, and which are assessed or provisionally assessed under regulation 6.3 of MARPOL Annex II, may be carried under the requirements of the Code applicable to the appropriate position of the entry in this chapter for Noxious Liquid Substances, not otherwise specified (n.o.s.).

17.2 EXPLANATORY NOTES

Product name (<i>column a</i>)	The product name shall be used in the shipping document for any cargo offered for bulk shipments. Any additional name may be included in brackets after the product name. In some cases, the product names are not identical with the names given in previous issues of the Code.
UN Number (<i>column b</i>)	Deleted
Pollution Category (<i>column c</i>)	The letter X, Y, Z means the Pollution Category assigned to each product under MARPOL Annex II.
Hazards (<i>column d</i>)	"S" means that the product is included in the Code because of its safety hazards; "P" means that the product is included in the Code because of its pollution hazards; and "S/P" means that the product is included in the Code because of both its safety and pollution hazards.
Ship Type (<i>column e</i>)	1: Ship Type 1 (2.1.2.1) 2: Ship Type 2 (2.1.2.2) 3: Ship Type 3 (2.1.2.3)
Tank type (<i>column f</i>)	1: independent tank (4.1.1) 2: integral tank (4.1.2) G: gravity tank (4.1.3) P: pressure tank (4.1.4)
Tank vents (<i>column g</i>)	Cont.: controlled venting Open: open venting

Tank environmental control (column h)	Inert: inerting (9.1.2.1) Pad: liquid or gas padding (9.1.2.2) Dry: drying (9.1.2.3) Vent: natural or forced ventilation (9.1.2.4) No: no special requirements under this Code (inerting may be required under SOLAS)
Electrical equipment (column i)	Temperature classes (i') T1 to T6 - indicates no requirements blank no information Apparatus group (i'') IIA, IIB or IIC: - indicates no requirements blank no information Flash point (i''') Yes: flashpoint exceeding 60°C (10.1.6) No: flashpoint not exceeding 60°C (10.1.6) NF: non-flammable product (10.1.6)
Gauging (column j)	O: open gauging (13.1.1.1) R: restricted gauging (13.1.1.2) C: closed gauging (13.1.1.3)
Vapour detection (column k)	F: flammable vapours T: toxic vapours No: indicates no special requirements under this Code
Fire protection (column l)	A: alcohol-resistant foam or multi-purpose foam B: regular foam; encompasses all foams that are not of an alcohol-resistant type, including fluoro-protein and aqueous-film-forming foam (AFFF) C: water-spray D: dry chemical No: no special requirements under this Code
Materials of construction (column m)	Deleted
Emergency equipment (column n)	Yes: see 14.3.1 No: no special requirements under this Code
Specific and operational requirements (column o)	When specific reference is made to chapters 15 and/or 16, these requirements shall be additional to the requirements in any other column.

a	c	d	e	f	g	h	i'	ii''	iii'''	j	k	l	n	o
Acetic acid	Z	S/P	3	2G	Cont	No	T1	IIA	No	C	F	AC	Yes	15.11.2, 15.11.3, 15.11.4, 15.11.6, 15.11.7, 15.11.8, 15.17, 15.19, 16.2.9
Acetic anhydride	Z	S/P	2	2G	Cont	No	T2	IIA	No	R	FT	AC	Yes	15.11.2, 15.11.3, 15.11.4, 15.11.6, 15.11.7, 15.11.8, 15.12.3, 15.12.4, 15.19.6
Acetochlor	X	S/P	2	2G	Open	No			Yes	O	No	AC	No	15.19.6, 16.2.6, 16.2.9
Acetone cyanohydrin	Y	S/P	1	1G	Cont	No	-	-	Yes	C	T	AC	Yes	15.12, 15.13, 15.17, 15.19, 16.6.1, 16.6.2, 16.6.3
Acetonitrile	Z	S/P	3	2G	Cont	No	T2	IIA	No	R	FT	AC	No	15.12.3, 15.12.4, 15.19.6
Acetonitrile (Low purity grade)	Y	S/P	3	2G	Cont	No	T1	IIA	No	R	FT	AC	No	15.12.3, 15.12.4, 15.19.6
Acid oil mixture from soya bean, corn (maize) and sunflower oil refining	Y	S/P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Acrylamide solution (50% or less)	Y	S/P	3	2G	Cont	No			NF	C	T	No	No	15.12, 15.13, 15.17, 15.19, 16.2.9, 16.6.1
Acrylic acid	Y	S/P	2	2G	Cont	No	T2	IIA	No	C	FT	AC	Yes	15.11.2, 15.11.3, 15.11.4, 15.11.6, 15.11.7, 15.11.8, 15.12.3, 15.12.4, 15.13, 15.17, 15.19, 16.2.9, 16.6.1
Acrylic acid/ethenesulphonic acid copolymer with phosphonate groups, sodium salt solution	Z	P	3	2G	Open	No			Yes	O	No	ABC	No	
Acrylonitrile	Y	S/P	2	2G	Cont	No	T1	IIB	No	C	FT	AC	Yes	15.12, 15.13, 15.17, 15.19
Acrylonitrile-Styrene copolymer dispersion in polyether polyol	Y	P	3	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6
Adiponitrile	Z	S/P	2	2G	Cont	No	-	-	Yes	C	T	AC	Yes	15.12, 15.17, 15.19, 16.2.9

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Alachlor technical (90% or more)	X	S/P	2	2G	Cont	No			Yes	C	T	AC	No	15.12, 15.17, 15.19.6, 16.2.9
Alcohol (C9-C11) poly (2.5-9) ethoxylate	Y	S/P	3	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.9
Alcohol (C6-C17) (secondary) poly(3-6) ethoxylates	Y	S/P	2	2G	Cont	No			Yes	C	T	AC	Yes	15.12, 15.17, 15.19, 16.2.9
Alcohol (C6-C17) (secondary) poly(7-12) ethoxylates	Y	S/P	2	2G	Cont	No			Yes	C	T	AC	Yes	15.12, 15.17, 15.19, 16.2.6, 16.2.9
Alcohol (C10-C18) poly(7) ethoxylate	Y	S/P	3	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6, 16.2.9
Alcohol (C12-C16) poly(1-6) ethoxylates	Y	S/P	2	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.9
Alcohol (C12-C16) poly(20+) ethoxylates	Y	S/P	3	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.9
Alcohol (C12-C16) poly(7-19) ethoxylates	Y	S/P	2	2G	Cont	No			Yes	C	T	AC	Yes	15.12, 15.17, 15.19, 16.2.9
Alcohols (C13+)	Y	P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.9
Alcohols (C12+), primary, linear	Y	S/P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Alcohols (C8-C11), primary, linear and essentially linear	Y	S/P	2	2G	Cont	No	-	-	Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6, 16.2.9
Alcohols (C12-C13), primary, linear and essentially linear	Y	S/P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Alcohols (C14-C18), primary, linear and essentially linear	Y	S/P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6
Alkanes (C6-C9)	X	S/P	2	2G	Cont	No	T3	IIA	No	C	FT	AC	No	15.12, 15.17, 15.19.6
Iso- and cyclo-alkanes (C10-C11)	Y	S/P	3	2G	Cont	No	T3	IIA	No	R	F	AC	No	15.19.6
Iso- and cyclo-alkanes (C12+)	Y	S/P	3	2G	Cont	No	T3	IIA	No	R	F	AC	No	15.19.6
n-Alkanes (C9-C11)	Y	S/P	3	2G	Cont	No	T3	IIA	No	R	F	ABC	No	15.19.6
n-Alkanes (C10 – C20)	Y	P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Alkaryl polyethers (C9-C20)	Y	S/P	2	2G	Cont	No			Yes	C	T	ABC	Yes	15.12, 15.17, 15.19, 16.2.6
Alkenoic acid, polyhydroxy ester borated	Y	S/P	2	2G	Cont	No	-	-	Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6
Alkenyl (C11+) amide	X	S/P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Alkenyl (C16-C20) succinic anhydride	Z	S/P	3	2G	Cont	No			Yes	C	T	ABC	Yes	15.12, 15.17, 15.19
Alkyl acrylate/vinylpyridine copolymer in toluene	Y	S/P	2	2G	Cont	No	T1	IIB	No	C	FT	ABC	No	15.12, 15.17, 15.19.6, 16.2.9
Alkylaryl phosphate mixtures (more than 40% Diphenyl tolyl phosphate, less than 0.02% ortho-isomers)	X	S/P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6
Alkylated (C4-C9) hindered phenols	Y	S/P	2	2G	Cont	No	-	-	Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6, 16.2.9
Alkylbenzene, alkylindane, alkylindene mixture (each C12-C17)	Z	P	3	2G	Open	No			Yes	O	No	AC	No	
Alkyl benzene distillation bottoms	Y	S/P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6
Alkylbenzene mixtures (containing at least 50% of toluene)	Y	S/P	3	2G	Cont	No	T1	IIA	No	C	FT	ABC	No	15.12, 15.17, 15.19.6
Alkylbenzenes mixtures (containing naphthalene)	X	S/P	2	2G	Cont	No			Yes	C	T	ABC	No	15.12, 15.17, 15.19.6
Alkyl (C3-C4) benzenes	Y	S/P	2	2G	Cont	No	T1	IIA	No	R	FT	ABC	No	15.12.3, 15.12.4, 15.19.6
Alkyl (C5-C8) benzenes	X	S/P	2	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6
Alkyl (C9+)benzenes	Y	S/P	3	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6
Alkyl (C11-C17) benzene sulphonic acid	Y	S/P	2	2G	Cont	No	-	-	Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Alkylbenzene sulphonic acid, sodium salt solution	Y	S/P	2	2G	Cont	No	-	-	NF	C	T	No	Yes	15.12, 15.17, 15.19, 16.2.6, 16.2.9
Alkyl/cyclo (C4-C5) alcohols	Y	S/P	3	2G	Cont	No	T2	IIB	No	R	FT	AC	No	15.12.3, 15.12.4, 15.19.6
Alkyl (C10-C15, C12 rich) phenol poly (4-12) ethoxylate	Y	S/P	2	2G	Cont	No			Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6
Alkyl (C12+) dimethylamine	X	S/P	1	2G	Cont	No	-	-	Yes	C	T	ABC	Yes	15.12, 15.17, 15.19
Alkyl dithiocarbamate (C19-C35)	Y	P	3	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Alkyldithiothiadiazole (C6-C24)	Y	P	3	2G	Open	No	-	-	Yes	O	No	AC	No	15.19.6, 16.2.6
Alkyl ester copolymer (C4-C20)	Y	P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Alkyl (C7-C9) nitrates	Y	S/P	2	2G	Cont	No			Yes	C	T	ABC	Yes	15.12, 15.17, 15.19, 15.20, 16.6.1, 16.6.2, 16.6.3
Alkyl (C8-C10)/(C12-C14):(40% or less/60% or more) polyglucoside solution (55% or less)	Y	S/P	3	2G	Cont	No			Yes	C	T	AC	Yes	15.12, 15.17, 15.19, 16.2.6, 16.2.9
Alkyl (C8-C10)/(C12-C14):(60% or more/40% or less) polyglucoside solution(55% or less)	Y	S/P	3	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6, 16.2.9
Alkyl (C7-C11)phenol poly(4-12) ethoxylate	Y	S/P	2	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6
Alkyl (C8-C40) phenol sulphide	Z	S/P	3	2G	Open	No			Yes	O	No	ABC	No	
Alkyl (C8-C9) phenylamine in aromatic solvents	Y	S/P	2	2G	Cont	No	T1	IIB	No	R	FT	ABC	No	15.12.3, 15.12.4, 15.19.6
Alkyl (C9-C15) phenyl propoxylate	Z	S/P	3	2G	Cont	No			Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6
Alkyl (C8-C10) polyglucoside solution (65% or less)	Y	S/P	3	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Alkyl (C8-C10)/(C12-C14):(50%/50%) polyglucoside solution (55% or less)	Y	S/P	3	2G	Cont	No			Yes	C	T	AC	Yes	15.12, 15.17, 15.19, 16.2.6, 16.2.9
Alkyl (C12-C14) polyglucoside solution (55% or less)	Y	S/P	3	2G	Cont	No			Yes	C	T	AC	Yes	15.12, 15.17, 15.19, 16.2.9
Alkyl (C12-C16) propoxyamine ethoxylate	X	S/P	2	2G	Cont	No	-	-	Yes	C	T	AC	Yes	15.12, 15.17, 15.19, 16.2.6
Alkyl (C10-C20, saturated and unsaturated) phosphite	Y	P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.9
Alkyl sulphonic acid ester of phenol	Y	P	3	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6
Alkyl (C18+) toluenes	Y	S/P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.9
Alkyl (C18-C28) toluenesulphonic acid	Y	S/P	2	2G	Cont	No	-	-	Yes	C	T	ABC	Yes	15.11.2, 15.11.3, 15.11.4, 15.11.6, 15.11.7, 15.11.8, 15.12, 15.17, 15.19, 16.2.6, 16.2.9
Alkyl (C18-C28) toluenesulphonic acid, calcium salts, borated	Y	S/P	3	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6
Alkyl (C18-C28) toluenesulphonic acid, calcium salts, low overbase	Y	S/P	2	2G	Cont	No	-	-	Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6
Alkyl (C18-C28) toluenesulphonic acid, calcium salts, high overbase	Y	S/P	3	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6
Allyl alcohol	Y	S/P	2	2G	Cont	No	T2	IIB	No	C	FT	AC	Yes	15.12, 15.17, 15.19
Allyl chloride	Y	S/P	2	2G	Cont	No	T2	IIA	No	C	FT	AC	No	15.12, 15.17, 15.19
Aluminium chloride/Hydrogen chloride solution	Y	S/P	2	2G	Cont	No	-	-	NF	C	T	No	Yes	15.11, 15.12, 15.17, 15.19
Aluminium hydroxide, sodium hydroxide, sodium carbonate solution (40% or less)	Y	S/P	2	2G	Cont	No			NF	C	T	No	Yes	15.12, 15.17, 15.19
Aluminium sulphate solution	Y	S/P	2	2G	Cont	No			NF	C	T	No	Yes	15.12, 15.17, 15.19
2-(2-Aminoethoxy) ethanol	Z	S/P	3	2G	Cont	No			Yes	C	T	AD	Yes	15.12, 15.17, 15.19

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Aminoethyldiethanolamine/Aminoethylethanolamine solution	Z	S/P	3	2G	Cont	No	-	-	Yes	C	T	AC	Yes	15.12, 15.17, 15.19, 16.2.9
Aminoethyl ethanolamine	Z	S/P	3	2G	Cont	No	-	-	Yes	C	T	AC	Yes	15.12, 15.17, 15.19
N-Aminoethylpiperazine	Z	S/P	3	2G	Cont	No			Yes	C	T	AC	Yes	15.12, 15.17, 15.19
2-Amino-2-methyl-1-propanol	Z	S/P	3	2G	Cont	No			Yes	C	T	AC	Yes	15.12, 15.17, 15.19
Ammonia aqueous (28% or less)	Y	S/P	2	2G	Cont	No			NF	C	T	No	Yes	15.12, 15.17, 15.19
Ammonium chloride solution (less than 25%) (*)	Z	S/P	3	2G	Open	No	-	-	NF	O	No	No	No	
Ammonium hydrogen phosphate solution	Z	P	3	2G	Open	No			Yes	O	No	AC	No	
Ammonium lignosulphonate solutions	Z	P	3	2G	Open	No	-	-	Yes	O	No	AC	No	16.2.9
Ammonium nitrate solution (93% or less) (*)	Z	S/P	2	1G	Cont	No			NF	R	T	No	No	15.2, 15.11.4, 15.11.6, 15.12.3, 15.12.4, 15.18, 15.19.6, 16.2.9
Ammonium polyphosphate solution	Z	P	3	2G	Open	No	-	-	Yes	O	No	AC	No	
Ammonium sulphate solution	Z	P	3	2G	Open	No			NF	O	No	No	No	
Ammonium sulphide solution (45% or less) (*)	Y	S/P	2	2G	Cont	Inert	T4	IIB	No	C	FT	AC	No	15.12, 15.17, 15.19, 16.6.1, 16.6.2, 16.6.3
Ammonium thiosulphate solution (60% or less)	Z	S/P	3	2G	Open	No			NF	O	No	No	No	

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Amyl acetate (all isomers)	Y	S/P	3	2G	Cont	No	T2	IIA	No	R	F	ABC	No	15.19.6
n-Amyl alcohol	Z	S/P	2	2G	Cont	No	T2	IIA	No	C	FT	ABC	Yes	15.12, 15.17, 15.19
Amyl alcohol, primary	Z	S/P	3	2G	Cont	No	T2	IIA	No	R	FT	ABC	No	15.12.3, 15.12.4, 15.19.6
sec-Amyl alcohol	Z	S/P	3	2G	Cont	No	T2	IIA	No	R	FT	ABC	No	15.12.3, 15.12.4, 15.19.6
tert-Amyl alcohol	Z	S/P	3	2G	Cont	No	T2	IIA	No	R	F	AC	No	15.19.6
tert-Amyl ethyl ether	Z	P	3	2G	Cont	No	T3	IIA	No	R	F	ABC	No	15.19.6
tert-Amyl methyl ether	X	S/P	2	2G	Cont	No	T2	IIB	No	R	FT	AC	No	15.12.3, 15.12.4, 15.19.6
Aniline	Y	S/P	2	2G	Cont	No	T1	IIA	Yes	C	T	AC	Yes	15.12, 15.17, 15.19
Aryl polyolefins (C11-C50)	Y	P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Aviation alkylates (C8 paraffins and iso-paraffins BPT 95 - 120°C)	X	S/P	2	2G	Cont	No	T3	IIA	No	R	F	ABC	No	15.19.6
Barium long chain (C11-C50) alkaryl sulphonate	Y	S/P	2	2G	Cont	No			Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19, 16.2.6, 16.2.9
Benzene and mixtures having 10% benzene or more (i)	Y	S/P	3	2G	Cont	No	T1	IIA	No	C	FT	ABC	No	15.12, 15.17, 15.19.6, 16.2.9
Benzene sulphonyl chloride	Y	S/P	3	2G	Cont	No			Yes	C	T	ABC	Yes	15.12, 15.17, 15.19, 16.2.9
Benzenetricarboxylic acid, trioctyl ester	Y	S/P	2	2G	Cont	No			Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6
Benzyl acetate	Y	S/P	2	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6
Benzyl alcohol	Y	S/P	3	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Benzyl chloride	Y	S/P	2	2G	Cont	No	T1	IIA	No	C	FT	ABC	Yes	15.12, 15.13, 15.17, 15.19
Bio-fuel blends of Diesel/gas oil and FAME (>25% but <99% by volume)	X	S/P	2	2G	Cont	No	-	-	Yes	C	T	ABC	No	15.12, 15.17, 15.19.6
Bio-fuel blends of Diesel/gas oil and vegetable oil (>25% but <99% by volume)	X	S/P	2	2G	Cont	No	-	-	Yes	C	T	ABC	No	15.12, 15.17, 15.19.6
Bio-fuel blends of Gasoline and Ethyl alcohol (>25% but <99% by volume)	X	S/P	2	2G	Cont	No	T3	IIA	No	R	FT	AC	No	15.12, 15.17, 15.19.6
Bis (2-ethylhexyl) terephthalate	Y	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6
Brake fluid base mix: Poly(2-8)alkylene (C2-C3) glycols/Polyalkylene (C2-C10) glycols monoalkyl (C1-C4) ethers and their borate esters	Z	P	3	2G	Open	No	-	-	Yes	O	No	AC	No	
Bromochloromethane	Z	P	3	2G	Open	No			NF	O	No	No	No	
Butene oligomer	X	P	2	2G	Cont	No	T4	IIB	No	R	F	ABC	No	15.19.6
2-Butoxyethanol (58%)/Hyperbranched polyesteramide (42%) (mixture)	Y	S/P	2	2G	Cont	No			Yes	C	T	AC	No	15.12.3, 15.12.4, 15.19
Butyl acetate (all isomers)	Y	P	3	2G	Cont	No	T2	IIA	No	R	F	AC	No	15.19.6
Butyl acrylate (all isomers)	Y	S/P	3	2G	Cont	No	T2	IIB	No	R	F	ABC	No	15.13, 15.19.6, 16.6.1, 16.6.2
tert-Butyl alcohol	Z	P	3	2G	Cont	No	T1	IIA	No	R	F	AC	No	15.19.6
Butylamine (all isomers)	Y	S/P	2	2G	Cont	No	T2	IIA	No	C	FT	AC	Yes	15.12, 15.17, 15.19
Butylbenzene (all isomers)	X	S/P	2	2G	Cont	No	T2	IIA	No	R	FT	ABC	No	15.12.3, 15.12.4, 15.19.6
Butyl benzyl phthalate	X	S/P	2	2G	Cont	No			Yes	C	T	AC	No	15.12, 15.17, 15.19.6

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Butyl butyrate (all isomers)	Y	S/P	3	2G	Cont	No	T1	IIA	No	R	F	ABC	No	15.19.6
Butyl/Decyl/Cetyl/Eicosyl methacrylate mixture	Y	S/P	2	2G	Open	No	T3	IIA	No	R	F	ABC	No	15.13, 15.19.6, 16.6.1, 16.6.2
Butylene glycol	Z	S/P	3	2G	Open	No			Yes	O	No	AC	No	
1,2-Butylene oxide	Y	S/P	3	2G	Cont	Inert	T2	IIB	No	C	FT	AC	No	15.8.1 to 15.8.7, 15.8.12, 15.8.13, 15.8.16, 15.8.17, 15.8.18, 15.8.19, 15.8.21, 15.8.25, 15.8.27, 15.8.29, 15.12, 15.17, 15.19.6
n-Butyl ether	Y	S/P	3	2G	Cont	Inert	T4	IIB	No	R	F	AC	No	15.4.6, 15.19
Butyl methacrylate	Z	S/P	3	2G	Cont	No	T3	IIA	No	R	F	ABC	No	15.13, 15.19.6, 16.6.1, 16.6.2
n-Butyl propionate	Y	P	3	2G	Cont	No	T2	IIA	No	R	F	ABC	No	15.19.6
Butyraldehyde (all isomers)	Y	S/P	3	2G	Cont	No	T3	IIA	No	R	F	AC	No	15.19.6
Butyric acid	Y	S/P	3	2G	Cont	No			Yes	O	No	AC	No	15.11.2, 15.11.3, 15.11.4, 15.11.6, 15.11.7, 15.11.8, 15.19.6
gamma-Butyrolactone	Y	S/P	3	2G	Cont	No			Yes	C	T	ABC	No	15.12, 15.17, 15.19.6
Calcium alkaryl sulphonate (C11-C50)	Z	S/P	3	2G	Open	No	-	-	Yes	O	No	ABC	No	
Calcium alkyl (C10-C28) salicylate	Y	S/P	2	2G	Cont	No	-	-	Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.9
Calcium hydroxide slurry	Y	S/P	2	2G	Cont	No	-	-	Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.9

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Calcium hypochlorite solution (15% or less)	Y	S/P	2	2G	Cont	No			NF	R	T	No	No	15.12.3, 15.12.4, 15.19.6
Calcium hypochlorite solution (more than 15%)	X	S/P	1	2G	Cont	No			NF	R	T	No	No	15.12.3, 15.12.4, 15.19
Calcium lignosulphonate solutions	Z	P	3	2G	Open	No	-	-	NF	O	No	No	No	16.2.9
Calcium long-chain alkyl (C5-C10) phenate	Y	P	3	2G	Open	No			Yes	O	No	AC	No	15.19.6
Calcium long-chain alkyl (C11-C40) phenate	Y	S/P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6
Calcium long-chain alkyl phenate sulphide (C8-C40)	Y	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6
Calcium long-chain alkyl salicylate (C13+)	Y	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Calcium long-chain alkyl (C18-C28) salicylate	Y	S/P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Calcium nitrate/Magnesium nitrate/Potassium chloride solution	Z	S/P	3	2G	Open	No	-	-	NF	O	No	No	No	16.2.9
Calcium nitrate solution (50% or less)	Z	S	3	2G	Open	No	-	-	NF	O	No	No	No	16.2.9
Camelina oil	Y	S/P	2(k)	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7
epsilon-Caprolactam (molten or aqueous solutions)	Z	S/P	3	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6
Carbolic oil	Y	S/P	2	2G	Cont	No			Yes	C	FT	ABC	Yes	15.12, 15.17, 15.19, 16.2.9
Carbon disulphide	Y	S/P	1	1G	Cont	Pad+inert	T6	IIC	No	C	FT	C	Yes	15.3, 15.12, 15.17, 15.18, 15.19
Carbon tetrachloride	Y	S/P	2	2G	Cont	No			NF	C	T	No	No	15.12, 15.17, 15.19.6

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Cashew nut shell oil (untreated)	Y	S/P	2	2G	Cont	No			Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6, 16.2.7, 16.2.9
Castor oil	Y	S/P	2(k)	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Cesium formate solution (*)	Y	S/P	3	2G	Open	No	-	-	NF	O	No	No	No	15.19.6
Cetyl/Eicosyl methacrylate mixture	Y	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.13, 15.19.6, 16.2.9, 16.6.1, 16.6.2
Chlorinated paraffins (C10-C13)	X	S/P	1	2G	Cont	No			NF	C	T	No	No	15.12, 15.17, 15.19, 16.2.6
Chlorinated paraffins (C14-C17) (with 50% chlorine or more, and less than 1% C13 or shorter chains)	X	S/P	1	2G	Cont	No	-	-	Yes	C	T	AC	No	15.12, 15.17, 15.19
Chloroacetic acid (80% or less)	Y	S/P	2	2G	Cont	No			NF	C	T	No	Yes	15.11.2, 15.11.3, 15.11.4, 15.11.6, 15.11.7, 15.11.8, 15.12, 15.17, 15.18, 15.19, 16.2.9
Chlorobenzene	Y	S/P	2	2G	Cont	No	T1	IIA	No	R	FT	ABC	No	15.12.3, 15.12.4, 15.19.6
Chloroform	Y	S/P	3	2G	Cont	No			NF	C	T	No	No	15.12, 15.17, 15.19.6
Chlorohydrins (crude)	Y	S/P	2	2G	Cont	No	T3	IIA	No	C	FT	AC	Yes	15.12, 15.17, 15.19
4-Chloro-2-methylphenoxyacetic acid, dimethylamine salt solution	Y	S/P	2	2G	Cont	No			NF	R	T	No	No	15.12.3, 15.12.4, 15.19.6, 16.2.9
o-Chloronitrobenzene	Y	S/P	2	2G	Cont	No			Yes	C	T	ABC	No	15.12.3, 15.12.4, 15.19, 16.2.6, 16.2.9
1-(4-Chlorophenyl)-4,4- dimethyl-pentan-3-one	Y	S/P	2	2G	Open	No			Yes	O	No	ABD	No	15.19.6, 16.2.6, 16.2.9
2- or 3-Chloropropionic acid	Z	S/P	2	2G	Cont	No			Yes	C	T	AC	No	15.11.2, 15.11.3, 15.11.4, 15.11.6, 15.11.7, 15.11.8, 15.12.3, 15.12.4, 15.19, 16.2.9

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Chlorosulphonic acid	Y	S/P	1	2G	Cont	No			NF	C	T	No	Yes	15.11.2, 15.11.3, 15.11.4, 15.11.5, 15.11.6, 15.11.7, 15.11.8, 15.12, 15.16.2, 15.17, 15.18, 15.19
m-Chlorotoluene	Y	S/P	2	2G	Cont	No	T4	IIA	No	R	FT	ABC	No	15.12.3, 15.12.4, 15.19
o-Chlorotoluene	Y	P	2	2G	Cont	No	T1	IIA	No	R	F	ABC	No	15.19.6
p-Chlorotoluene	Y	P	2	2G	Cont	No	T1	IIA	No	R	F	ABC	No	15.19.6, 16.2.9
Chlorotoluenes (mixed isomers)	Y	P	2	2G	Cont	No	T4	IIA	No	R	F	ABC	No	15.19.6
Choline chloride solutions	Z	P	3	2G	Open	No			Yes	O	No	AC	No	
Citric acid (70% or less)	Z	S/P	3	2G	Cont	No			Yes	C	T	AC	Yes	15.12, 15.17, 15.19
Coal tar	X	S/P	2	2G	Cont	No	T2	IIA	Yes	C	T	BD	No	15.12, 15.17, 15.19.6, 16.2.6, 16.2.9
Coal tar naphtha solvent	Y	S/P	2	2G	Cont	No	T3	IIA	No	C	FT	ABC	No	15.12, 15.17, 15.19.6, 16.2.9
Coal tar pitch (molten) (*)	X	S/P	2	1G	Cont	No	T2	IIA	Yes	C	T	ABCD	No	15.12, 15.17, 15.19.6, 16.2.6, 16.2.9
Cocoa butter	Y	S/P	2(k)	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Coconut oil	Y	S/P	2(k)	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Coconut oil fatty acid	Y	S/P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Coconut oil fatty acid methyl ester	Y	P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6
Copper salt of long chain (C17+) alkanolic acid	Y	P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Corn Oil	Y	S/P	2(k)	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Cotton seed oil	Y	S/P	2(k)	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Creosote (coal tar)	X	S/P	1	2G	Cont	No	T2	IIA	Yes	C	T	AD	No	15.12, 15.17, 15.19.6, 16.2.6, 16.2.9
Cresols (all isomers)	Y	S/P	1	2G	Cont	No	T1	IIA	Yes	C	T	ABC	Yes	15.12, 15.18, 15.19, 16.2.9
Cresol/Phenol/Xylenol mixture	Y	S/P	2	2G	Cont	No			Yes	C	T	AC	Yes	15.12, 15.17, 15.19
Cresylic acid, dephenolized	Y	S/P	2	2G	Cont	No			Yes	C	T	ABC	Yes	15.12, 15.17, 15.19
Cresylic acid, sodium salt solution	Y	S/P	2	2G	Cont	No	T4	IIB	No	C	FT	AC	Yes	15.12, 15.17, 15.19, 16.2.9
Crotonaldehyde	X	S/P	1	1G	Cont	No	T3	IIB	No	C	FT	AC	Yes	15.12, 15.17, 15.18, 15.19
1,5,9-Cyclododecatriene	X	S/P	2	2G	Open	No			Yes	O	No	AC	No	15.13, 15.19.6, 16.6.1, 16.6.2
Cycloheptane	X	S/P	2	2G	Cont	No	T4	IIA	No	R	F	AC	No	15.19.6
Cyclohexane	Y	S/P	2	2G	Cont	No	T3	IIA	No	R	F	AC	No	15.19.6, 16.2.9
Cyclohexane-1,2-dicarboxylic acid, diisononyl ester	Y	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6
Cyclohexane oxidation products, sodium salts solution	Z	P	3	2G	Open	No			NF	O	No	No	No	
Cyclohexanol	Y	P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.9
Cyclohexanone	Z	S/P	3	2G	Cont	No	T2	IIA	No	R	F	AC	No	15.19.6
Cyclohexanone, Cyclohexanol mixture	Y	S/P	3	2G	Cont	No			Yes	R	F	AC	No	15.19.6
Cyclohexyl acetate	Y	S/P	3	2G	Cont	No	T2	IIA	No	R	FT	AC	No	15.12.3, 15.12.4, 15.19.6
Cyclohexylamine	Y	S/P	3	2G	Cont	No	T3	IIA	No	C	FT	AC	Yes	15.12, 15.17, 15.19

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
1,3-Cyclopentadiene dimer (molten)	Y	S/P	2	2G	Cont	No	T1	IIB	No	R	FT	AC	No	15.12.3, 15.12.4, 15.19, 16.2.6, 16.2.9
Cyclopentane	Y	P	2	2G	Cont	No	T2	IIA	No	R	F	AC	No	15.19.6
Cyclopentene	Y	S/P	3	2G	Cont	No	T2	IIA	No	R	F	AC	No	15.19.6
p-Cymene	Y	S/P	2	2G	Cont	No	T2	IIA	No	R	F	AC	No	15.19.6
Decahydronaphthalene	Y	S/P	2	2G	Cont	No	T3	IIA	No	R	FT	ABC	No	15.12.3, 15.12.4, 15.19.6
Decanoic acid	X	S/P	2	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.9
Decene	X	P	2	2G	Cont	No	T3	IIA	No	R	F	AC	No	15.19.6
Decyl acrylate	X	S/P	1	2G	Cont	No	-	-	Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.13, 15.19, 16.6.1, 16.6.2
Decyl alcohol (all isomers)	Y	P	2	2G	Open	No			Yes	O	No	AC	No	15.19.6, 16.2.9(e)
Decyl/Dodecyl/Tetradecyl alcohol mixture	Y	S/P	2	2G	Cont	No	-	-	Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.9
Decyloxytetrahydrothiophene dioxide	X	S/P	2	2G	Open	No			Yes	O	No	AC	No	15.19.6, 16.2.9
Diacetone alcohol	Z	S/P	3	2G	Cont	No	T1	IIA	No	R	FT	AC	No	15.12.3, 15.12.4, 15.19.6
Dialkyl (C8-C9) diphenylamines	Z	P	3	2G	Open	No			Yes	O	No	ABC	No	
Dialkyl (C7-C13) phthalates	X	S/P	2	2G	Cont	No			Yes	C	T	ABC	No	15.12, 15.17, 15.19.6, 16.2.6
Dialkyl (C9-C10) phthalates	Y	S/P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6
Dialkyl thiophosphates sodium salts solution	Y	S/P	2	2G	Cont	No	-	-	Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.9

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
2,6-Diaminohexanoic acid phosphonate mixed salts solution	Z	S/P	3	2G	Cont	No			NF	R	No	No	No	15.11, 15.17, 15.19.6
Dibromomethane	Y	S/P	2	2G	Open	No			NF	O	No	No	No	15.19.6
Dibutylamine	Y	S/P	2	2G	Cont	No	T2	IIA	No	C	FT	ABC	Yes	15.12, 15.17, 15.19
Dibutyl hydrogen phosphonate	Y	S/P	2	2G	Cont	No			Yes	C	T	AC	Yes	15.12, 15.17, 15.19, 16.2.9
2,6-Di-tert-butylphenol	X	S/P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.9
Dibutyl phthalate	X	S/P	2	2G	Cont	No			Yes	C	T	AC	No	15.12, 15.17, 15.19.6
Dibutyl terephthalate	Y	P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.9
Dichlorobenzene (all isomers)	X	S/P	2	2G	Cont	No	T1	IIA	Yes	C	T	ABD	No	15.12, 15.17, 15.19.6
3,4-Dichloro-1-butene	Y	S/P	2	2G	Cont	No	T1	IIA	No	R	FT	ABC	No	15.12.3, 15.12.4, 15.19.6
1,1-Dichloroethane	Z	S/P	3	2G	Cont	No	T2	IIA	No	R	F	AC	No	15.19.6
Dichloroethyl ether	Y	S/P	2	2G	Cont	No	T2	IIA	No	C	FT	AC	Yes	15.12, 15.17, 15.18, 15.19
1,6-Dichlorohexane	Y	P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6
2,2'-Dichloroisopropyl ether	Y	S/P	2	2G	Cont	No			Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19
Dichloromethane	Y	S/P	3	2G	Cont	No	T1	IIA	No	C	FT	ABC	No	15.12, 15.17, 15.19.6
2,4-Dichlorophenol	Y	S/P	2	2G	Cont	Dry			Yes	C	T	AD	Yes	15.12, 15.16.2, 15.17, 15.19, 16.2.6, 16.2.9
2,4-Dichlorophenoxyacetic acid, diethanolamine salt solution	Y	S/P	3	2G	Cont	No			NF	C	T	No	Yes	15.12, 15.17, 15.19, 16.2.9
2,4-Dichlorophenoxyacetic acid, dimethylamine salt solution (70% or less)	Y	S/P	3	2G	Cont	No			NF	C	T	No	Yes	15.12, 15.17, 15.19, 16.2.9

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
2,4-Dichlorophenoxyacetic acid, triisopropanolamine salt solution	Y	S/P	3	2G	Cont	No			NF	C	T	No	Yes	15.12, 15.17, 15.19, 16.2.6, 16.2.9
1,1-Dichloropropane	Y	S/P	2	2G	Cont	No	T1	IIA	No	R	F	ABC	No	15.19.6
1,2-Dichloropropane	Y	S/P	3	2G	Cont	No	T1	IIA	No	R	FT	ABC	No	15.12.3, 15.12.4, 15.19.6
1,3-Dichloropropene	X	S/P	2	2G	Cont	No	T2	IIA	No	C	FT	ABC	Yes	15.12, 15.17, 15.19
Dichloropropene/Dichloropropane mixtures	X	S/P	2	2G	Cont	No	T2	IIA	No	C	FT	ABD	No	15.12, 15.17, 15.19
2,2-Dichloropropionic acid	Y	S/P	2	2G	Cont	Dry			Yes	C	T	AD	Yes	15.11.2, 15.11.4, 15.11.6, 15.11.7, 15.11.8, 15.12, 15.16.2, 15.17, 15.19, 16.2.9
Dicyclopentadiene, Resin Grade, 81-89%	Y	S/P	2	2G	Cont	Inert	T2	IIB	No	C	FT	ABC	Yes	15.12, 15.13, 15.17, 15.19
Diethanolamine	Y	S/P	3	2G	Cont	No	T1	IIA	Yes	C	T	AC	No	15.12, 15.17, 15.19.6, 16.2.6, 16.2.9
Diethylamine	Y	S/P	3	2G	Cont	No	T2	IIA	No	C	FT	AC	Yes	15.12, 15.17, 15.19
Diethylaminoethanol	Y	S/P	2	2G	Cont	No	T2	IIA	No	R	FT	AC	No	15.12.3, 15.12.4, 15.19.6
2,6-Diethylaniline	Y	S/P	2	2G	Cont	No			Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.9
Diethylbenzene	Y	S/P	2	2G	Cont	No	T2	IIA	No	R	FT	AC	No	15.12.3, 15.12.4, 15.19.6
Diethylene glycol	Z	S/P	3	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6
Diethylene glycol dibutyl ether	Z	S/P	3	2G	Open	No	-	-	Yes	O	No	AC	No	
Diethylene glycol diethyl ether	Z	S/P	3	2G	Cont	No	-	-	Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Diethylene glycol phthalate	Y	S/P	3	2G	Cont	No	-	-	Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6
Diethylenetriamine	Y	S/P	3	2G	Cont	No	-	-	Yes	C	T	ABC	No	15.12, 15.17, 15.19
Diethylenetriaminepentaacetic acid, pentasodium salt solution	Z	P	3	2G	Open	No	-	-	Yes	O	No	AC	No	
Diethyl ether (*)	Z	S/P	2	1G	Cont	Inert	T4	IIB	No	R	F	AC	No	15.4, 15.14, 15.19
Di-(2-ethylhexyl) adipate	Y	S/P	2	2G	Cont	No			Yes	C	T	ABC	No	15.12, 15.17, 15.19.6
Di-(2-ethylhexyl) phosphoric acid	Y	S/P	2	2G	Cont	No			Yes	R	T	AD	No	15.12.3, 15.12.4, 15.19.6
Diethyl phthalate	Y	S/P	2	2G	Open	No			Yes	O	No	AC	No	15.19.6
Diethyl sulphate	Y	S/P	2	2G	Cont	No			Yes	C	T	AC	Yes	15.12, 15.17, 15.19
Diglycidyl ether of bisphenol A	X	S/P	2	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6, 16.2.9
Diglycidyl ether of bisphenol F	Y	S/P	2	2G	Cont	No			Yes	C	T	AC	No	15.12, 15.17, 15.19.6, 16.2.6
Diheptyl phthalate	Y	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6
Di-n-hexyl adipate	X	S/P	1	2G	Open	No			Yes	O	No	AC	No	15.19
Dihexyl phthalate	Y	S/P	2	2G	Cont	No			Yes	C	T	ABC	No	15.12, 15.17, 15.19.6
Diisobutylamine	Y	S/P	2	2G	Cont	No	T4	IIB	No	C	FT	ABC	No	15.12.3, 15.12.4, 15.19
Diisobutylene	Y	P	2	2G	Cont	No	T2	IIA	No	R	F	AC	No	15.19.6
Diisobutyl ketone	Y	S/P	3	2G	Cont	No	T2	IIA	No	R	FT	AC	No	15.12.3, 15.12.4, 15.19.6
Diisobutyl phthalate	X	S/P	2	2G	Cont	No			Yes	C	T	AC	No	15.12, 15.17, 15.19.6
Diisononyl adipate	Y	S/P	2	2G	Open	No	-	-	Yes	O	No	AC	No	15.19.6
Diisooctyl phthalate	Y	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6
Diisopropanolamine	Z	P	3	2G	Open	No	-	-	Yes	O	No	AC	No	16.2.9
Diisopropylamine	Y	S/P	3	2G	Cont	No	T2	IIA	No	R	FT	AC	No	15.12.3, 15.12.4, 15.17, 15.19.6

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Diisopropylbenzene (all isomers)	X	S/P	2	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6
Diisopropylnaphthalene	Y	S/P	2	2G	Open	No	-	-	Yes	O	No	AC	No	15.19.6
N,N-Dimethylacetamide	Z	S/P	3	2G	Cont	No	-	-	Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6
N,N-Dimethylacetamide solution (40% or less)	Z	S/P	3	2G	Cont	No			NF	R	T	No	No	15.12.3, 15.12.4, 15.19.6
Dimethyl adipate	Y	P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.9
Dimethylamine solution (45% or less)	Y	S/P	3	2G	Cont	No	T2	IIA	No	R	FT	AC	No	15.12.3, 15.12.4, 15.19
Dimethylamine solution (greater than 45% but not greater than 55%)	Y	S/P	3	2G	Cont	No	T2	IIB	No	R	FT	AC	No	15.12.3, 15.12.4, 15.19
Dimethylamine solution (greater than 55% but not greater than 65%)	Y	S/P	3	2G	Cont	No	T2	IIB	No	R	FT	AC	No	15.12.3, 15.12.4, 15.14, 15.19
N,N-Dimethylcyclohexylamine	Y	S/P	2	2G	Cont	No	T3	IIB	No	C	FT	AC	Yes	15.12, 15.17, 15.19
Dimethyl disulphide	Y	S/P	2	2G	Cont	No	T3	IIA	No	R	FT	ABC	No	15.12.3, 15.12.4, 15.19.6
N,N-Dimethyldodecylamine	Y	S/P	2	2G	Cont	No			Yes	C	T	ABC	Yes	15.12, 15.17, 15.19
Dimethylethanolamine	Y	S/P	3	2G	Cont	No	T3	IIA	No	R	FT	AC	No	15.12.3, 15.12.4, 15.19.6
Dimethylformamide	Y	S/P	3	2G	Cont	No	T2	IIA	No	C	FT	AC	No	15.12, 15.17, 15.19.6
Dimethyl glutarate	Y	S/P	3	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Dimethyl hydrogen phosphite	Y	S/P	3	2G	Cont	No	T4	IIB	No	R	F	AC	No	15.19.6
Dimethyl octanoic acid	Y	S/P	2	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6, 16.2.9
Dimethyl phthalate	Y	S/P	3	2G	Open	No			Yes	O	No	AC	No	15.19.6, 16.2.9
Dimethylpolysiloxane	Y	P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6
2,2-Dimethylpropane-1,3-diol (molten or solution)	Z	P	3	2G	Open	No	-	-	Yes	O	No	ABC	No	16.2.9
Dimethyl succinate	Y	P	2	2G	Open	No			Yes	O	No	AC	No	15.19.6, 16.2.9
Dinitrotoluene (molten)	X	S/P	2	2G	Cont	No			Yes	C	T	AC	No	15.12, 15.17, 15.19, 15.21, 16.2.6, 16.2.9, 16.6.4
Dinonyl phthalate	Y	S/P	2	2G	Open	No	-	-	Yes	O	No	AC	No	15.19.6
Diocetyl phthalate	Y	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6
1,4-Dioxane	Y	S/P	3	2G	Cont	No	T2	IIB	No	C	FT	AC	No	15.12, 15.17, 15.19.6, 16.2.9
Dipentene	Y	S/P	2	2G	Cont	No	T3	IIA	No	C	FT	AC	No	15.12.3, 15.12.4, 15.19.6
Diphenyl	X	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Diphenylamine (molten)	Y	S/P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Diphenylamine, reaction product with 2,2,4-Trimethylpentene	Y	S/P	2	2G	Open	No			Yes	O	No	AC	No	15.19, 16.2.6
Diphenylamines, alkylated	Y	S/P	2	2G	Open	No			Yes	O	No	AC	No	15.19, 16.2.6, 16.2.9
Diphenyl/Diphenyl ether mixtures	X	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.9
Diphenyl ether	X	P	2	2G	Open	No			Yes	O	No	AC	No	15.19.6, 16.2.9
Diphenyl ether/Diphenyl phenyl ether mixture	X	P	2	2G	Open	No			Yes	O	No	AC	No	15.19.6, 16.2.9

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Diphenylmethane diisocyanate	Y	S/P	2	2G	Cont	Dry	-	-	Yes(a)	C	T(a)	AB(b)D	Yes	15.12, 15.16.2, 15.17, 15.19, 16.2.6, 16.2.9
Diphenylol propane-epichlorohydrin resins	X	S/P	2	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6, 16.2.9
Di-n-propylamine	Y	S/P	2	2G	Cont	No	T3	IIB	No	C	FT	AC	Yes	15.12.3, 15.12.4, 15.17, 15.19.6
Dipropylene glycol	Z	P	3	2G	Open	No			Yes	O	No	AC	No	
Dithiocarbamate ester (C7-C35)	X	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6
Ditridecyl adipate	Y	S/P	2	2G	Cont	No	-	-	Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6
Ditridecyl phthalate	Y	S/P	2	2G	Open	No	-	-	Yes	O	No	AC	No	15.19.6
Diundecyl phthalate	Y	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Dodecane (all isomers)	Y	S/P	2	2G	Cont	No	T3	IIA	No	R	F	ABC	No	15.19.6
tert-Dodecanethiol	Y	S/P	3	2G	Cont	No			Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6
1-Dodecene	Y	S/P	3	2G	Open	No			Yes	O	No	ABC	No	15.19.6
Dodecene (all isomers)	X	S/P	2	2G	Cont	No			Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6
Dodecyl alcohol	Y	S/P	2	2G	Open	No			Yes	O	No	AC	No	15.19.6, 16.2.9
n-Dodecyl mercaptan	X	S/P	1	2G	Cont	No			Yes	C	T	ABC	Yes	15.12, 15.17, 15.19
Dodecylamine/Tetradecylamine mixture	Y	S/P	2	2G	Cont	No			Yes	C	T	ABC	Yes	15.12, 15.17, 15.19, 16.2.9
Dodecylbenzene	Y	S/P	2	2G	Cont	No	-	-	Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6
Dodecyl diphenyl ether disulphonate solution	X	S/P	2	2G	Cont	No			NF	C	T	No	Yes	15.12, 15.17, 15.19, 16.2.6

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Dodecyl hydroxypropyl sulphide	X	P	2	2G	Open	No			Yes	O	No	AC	No	15.19.6
Dodecyl methacrylate	Y	S/P	3	2G	Open	No			Yes	O	No	AC	No	15.13, 15.19.6
Dodecyl/Octadecyl methacrylate mixture	Y	S/P	2	2G	Open	No	-	-	Yes	O	No	AC	No	15.13, 15.19.6, 16.2.6, 16.6.1, 16.6.2
Dodecyl/Pentadecyl methacrylate mixture	Y	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.13, 15.19.6, 16.6.1, 16.6.2
Dodecyl phenol	X	S/P	2	2G	Cont	No			Yes	C	T	AC	Yes	15.12, 15.17, 15.19, 16.2.6
Dodecyl Xylene	Y	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6
Drilling brines (containing zinc chloride)	X	S/P	2	2G	Open	No			NF	O	No	No	Yes	15.19.6
Drilling brines (containing calcium bromide)	Z	S/P	3	2G	Open	No			NF	O	No	No	No	15.19.6
Epichlorohydrin	Y	S/P	2	2G	Cont	No	T2	IIB	No	C	FT	AC	Yes	15.12, 15.17, 15.19
Ethanolamine	Y	S/P	3	2G	Cont	No	T2	IIA	Yes	C	FT	AC	Yes	15.12, 15.17, 15.19, 16.2.9
2-Ethoxyethyl acetate	Y	S/P	3	2G	Cont	No	T2	IIA	No	C	FT	AC	No	15.12, 15.17, 15.19.6
Ethoxylated long chain (C16+) alkyloxyalkylamine	Y	S/P	2	2G	Cont	No	-	-	Yes	C	T	ABC	Yes	15.12, 15.17, 15.19, 16.2.9
Ethoxylated tallow amine (>95%)	X	S/P	2	2G	Cont	Inert	-	-	Yes	C	T	ABC	Yes	15.12, 15.17, 15.19, 16.2.6, 16.2.9
Ethyl acetate	Z	S/P	3	2G	Cont	No	T2	IIA	No	R	F	ABC	No	15.19.6
Ethyl acetoacetate	Z	S/P	3	2G	Open	No			Yes	O	No	AC	No	
Ethyl acrylate	Y	S/P	2	2G	Cont	No	T2	IIB	No	C	FT	AC	No	15.12, 15.13, 15.17, 15.19, 16.6.1, 16.6.2
Ethylamine (*)	Y	S/P	2	1G	Cont	No	T2	IIA	No	C	F	AC	No	15.12.3.2, 15.14, 15.19
Ethylamine solutions (72% or less)	Y	S/P	3	2G	Cont	No	T2	IIA	No	C	F	AC	No	15.12.3.2, 15.14, 15.19

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Ethyl amyl ketone	Y	S/P	2	2G	Cont	No	T2	IIA	No	R	FT	AC	No	15.12.3, 15.12.4, 15.19.6
Ethylbenzene	Y	S/P	2	2G	Cont	No	T2	IIA	No	C	FT	AC	No	15.12, 15.17, 15.19.6
Ethyl tert-butyl ether	Y	S/P	2	2G	Cont	No	T2	IIB	No	R	FT	AC	No	15.12.3, 15.12.4, 15.19.6
Ethyl butyrate	Y	S/P	2	2G	Cont	No	T2	IIA	No	R	FT	AC	No	15.12.3, 15.12.4, 15.19.6
Ethylcyclohexane	Y	S/P	2	2G	Cont	No	T3	IIA	No	R	F	AC	No	15.19.6
N-Ethylcyclohexylamine	Y	S/P	2	2G	Cont	No	T3	IIB	No	C	FT	AC	No	15.12.3, 15.12.4, 15.19
S-Ethyl dipropylthiocarbamate	Y	S/P	2	2G	Cont	No			Yes	C	T	AC	No	15.12, 15.17, 15.19.6, 16.2.9
Ethylene carbonate	Z	S/P	3	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.9
Ethylene chlorohydrin	Y	S/P	1	2G	Cont	No	T2	IIA	No	C	FT	AC	Yes	15.12, 15.17, 15.18, 15.19
Ethylene cyanohydrin	Y	S/P	2	2G	Cont	No		IIB	Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6
Ethylenediamine	Y	S/P	2	2G	Cont	No	T2	IIA	No	C	FT	AC	Yes	15.12, 15.17, 15.19, 16.2.9
Ethylenediaminetetraacetic acid, tetrasodium salt solution	Y	S/P	3	2G	Cont	No	-	-	Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6
Ethylene dibromide	Y	S/P	2	2G	Cont	No			NF	C	T	No	No	15.12, 15.17, 15.19, 16.2.9
Ethylene dichloride	Y	S/P	3	2G	Cont	No	T2	IIA	No	C	FT	ABC	No	15.12, 15.17, 15.19
Ethylene glycol	Z	S/P	3	2G	Open	No			Yes	O	No	AC	No	15.19.6
Ethylene glycol acetate	Y	S/P	3	2G	Cont	No	-	-	Yes	C	T	AC	Yes	15.12, 15.17, 15.19
Ethylene glycol butyl ether acetate	Y	S/P	3	2G	Open	No			Yes	O	No	AC	No	15.19.6
Ethylene glycol diacetate	Y	S/P	2	2G	Open	No			Yes	O	No	AC	No	15.19.6

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Ethylene glycol methyl ether acetate	Y	S/P	3	2G	Cont	No			Yes	C	T	AC	No	15.12, 15.17, 15.19.6
Ethylene glycol monoalkyl ethers	Y	S/P	3	2G	Cont	No	T2	IIB	No	C	FT	AC	No	15.12.3, 15.12.4, 15.19, 16.2.9
Ethylene glycol phenyl ether	Z	S/P	3	2G	Open	No	-	-	Yes	O	No	AC	No	16.2.9,
Ethylene glycol phenyl ether/Diethylene glycol phenyl ether mixture	Z	S/P	3	2G	Cont	No	-	-	Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.9
Ethylene glycol (>75%)/sodium alkyl carboxylates/borax mixture	Y	S/P	3	2G	Cont	No			Yes	C	T	AC	No	15.12, 15.17, 15.19.6
Ethylene glycol (>85%)/sodium alkyl carboxylates mixture	Z	S/P	3	2G	Open	No	-	-	Yes	O	No	AC	No	15.19.6
Ethylene oxide/Propylene oxide mixture with an ethylene oxide content of not more than 30% by mass	Y	S/P	2	1G	Cont	Inert	T2	IIB	No	C	FT	AC	Yes	15.8, 15.12, 15.14, 15.17, 15.19
Ethylene-vinyl acetate copolymer (emulsion)	Y	S/P	3	2G	Cont	No	-	-	Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6, 16.2.9
Ethyl-3-ethoxypropionate	Y	P	2	2G	Cont	No	T2	IIA	No	R	F	AC	No	15.19.6
2-Ethylhexanoic acid	Y	S/P	3	2G	Cont	No			Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6
2-Ethylhexyl acrylate	Y	S/P	3	2G	Cont	No	-	-	Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.13, 15.19.6, 16.6.1, 16.6.2
2-Ethylhexylamine	Y	S/P	2	2G	Cont	No	T3	IIA	No	C	FT	AC	Yes	15.12, 15.17, 15.19.6
2-Ethyl-2-(hydroxymethyl) propane-1,3-diol (C8-C10) ester	Y	P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Ethylidene norbornene	Y	S/P	2	2G	Cont	No	T3	IIB	No	R	FT	ABC	No	15.12.3, 15.12.4, 15.19.6

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Ethyl methacrylate	Y	S/P	3	2G	Cont	No	T2	IIA	No	R	F	ABC	No	15.13, 15.19.6, 16.6.1, 16.6.2
N-Ethylmethylallylamine	Y	S/P	2	2G	Cont	No	T2	IIB	No	C	FT	AC	No	15.12.3, 15.12.4, 15.19
Ethyl propionate	Y	S/P	3	2G	Cont	No	T1	IIA	No	R	FT	AC	No	15.12.3, 15.12.4, 15.19.6
2-Ethyl-3-propylacrolein	Y	S/P	3	2G	Cont	No	T3	IIA	No	R	F	AC	No	15.19.6, 16.2.9
Ethyl toluene	Y	P	2	2G	Cont	No	T1	IIA	No	R	F	ABC	No	15.19.6
Fatty acid (saturated C13+)	Y	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.9
Fatty acid methyl esters (m)	Y	S/P	2	2G	Cont	No	-	-	Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6, 16.2.9
Fatty acids, (C8-C10)	Y	S/P	2	2G	Cont	No	-	-	Yes	C	T	ABC	Yes	15.12, 15.17, 15.19, 16.2.6, 16.2.9
Fatty acids, (C12+)	Y	S/P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Fatty acids, (C16+)	Y	P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6
Fatty acids, essentially linear (C6-C18) 2-ethylhexyl ester	Y	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6
Ferric chloride solutions	Y	S/P	3	2G	Cont	No			NF	C	T	No	Yes	15.11, 15.12, 15.17, 15.19, 16.2.9
Ferric nitrate/Nitric acid solution	Y	S/P	2	2G	Cont	No			NF	C	T	No	Yes	15.11, 15.12, 15.17, 15.19
Fish oil	Y	S/P	2(k)	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Fish silage protein concentrate (containing 4% or less formic acid)	Y	P	2	2G	Open	No			NF	O	No	No	No	15.19.6, 16.2.6
Fish protein concentrate (containing 4% or less formic acid)	Z	P	3	2G	Open	No	-	-	NF	O	No	No	No	
Fluorosilicic acid solution (20-30%)	Y	S/P	3	2G	Cont	No			NF	C	T	No	Yes	15.11, 15.12, 15.17, 15.19

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Formaldehyde solutions (45% or less)	Y	S/P	3	2G	Cont	No	T2	IIB	No	C	FT	AC	Yes	15.12, 15.17, 15.19, 16.2.9
Formamide	Y	S/P	3	2G	Cont	No			Yes	C	T	AC	No	15.12, 15.17, 15.19.6, 16.2.9
Formic acid (85% or less acid)	Y	S/P	3	2G	Cont	No	-	-	Yes	C	T(g)	AC	Yes	15.11.2, 15.11.3, 15.11.4, 15.11.6, 15.11.7, 15.11.8, 15.12.3, 15.12.4, 15.17, 15.19, 16.2.9
Formic acid (over 85%)	Y	S/P	3	2G	Cont	No	T1	IIA	No	C	FT(g)	AC	Yes	15.11.2, 15.11.3, 15.11.4, 15.11.6, 15.11.7, 15.11.8, 15.12.3, 15.12.4, 15.17, 15.19, 16.2.9
Formic acid mixture (containing up to 18% propionic acid and up to 25% sodium formate)	Z	S/P	3	2G	Cont	No	-	-	Yes	R	T(g)	AC	No	15.11.2, 15.11.3, 15.11.4, 15.11.6, 15.11.7, 15.11.8, 15.12.3, 15.12.4, 15.19.6
Furfural	Y	S/P	3	2G	Cont	No	T2	IIB	No	C	FT	AC	Yes	15.12, 15.17, 15.19
Furfuryl alcohol	Y	S/P	3	2G	Cont	No	-	-	Yes	C	T	AC	Yes	15.12, 15.17, 15.19
Glucitol/glycerol blend propoxylated (containing less than 10% amines)	Z	S/P	3	2G	Cont	No	-	-	Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6
Glucitol/glycerol blend propoxylated (containing 10% or more amines)	Y	S/P	2	2G	Cont	No			Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6
Glutaraldehyde solutions (50% or less)	Y	S/P	3	2G	Cont	No			NF	C	T	No	Yes	15.12, 15.17, 15.19
Glycerine	Z	S	3	2G	Open	No			Yes	O	No	AC	No	16.2.9
Glycerol monooleate	Y	S/P	2	2G	Open	No	-	-	Yes	O	No	AC	No	15.19.6, 16.2.6, 16.2.9
Glycerol propoxylated	Z	S/P	3	2G	Cont	No	-	-	Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6
Glycerol, propoxylated and ethoxylated	Z	P	3	2G	Open	No	-	-	Yes	O	No	ABC	No	

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Glycerol/sucrose blend propoxylated and ethoxylated	Z	P	3	2G	Open	No	-	-	Yes	O	No	ABC	No	
Glyceryl triacetate	Z	S/P	3	2G	Open	No			Yes	O	No	ABC	No	15.19.6
Glycidyl ester of C10 trialkylacetic acid	Y	S/P	2	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6
Glycine, sodium salt solution	Z	S/P	3	2G	Open	No			NF	O	No	No	No	
Glycolic acid solution (70% or less)	Z	S/P	3	2G	Cont	No	-	-	NF	C	T	No	Yes	15.12.3, 15.12.4, 15.17, 15.19, 16.2.9
Glyoxal solution (40% or less)	Y	S/P	3	2G	Cont	No			Yes	C	T	AC	Yes	15.12, 15.17, 15.19, 16.2.9
Glyoxylic acid solution (50% or less)	Y	S/P	3	2G	Cont	No	-	-	Yes	C	T	ACD	Yes	15.11.2, 15.11.3, 15.11.4, 15.11.6, 15.11.7, 15.11.8, 15.12, 15.17, 15.19, 16.2.9, 16.6.1, 16.6.2, 16.6.3
Glyphosate solution (not containing surfactant)	Y	S/P	2	2G	Cont	No			Yes	C	T	AC	Yes	15.12, 15.17, 15.19, 16.2.9
Grape Seed Oil	Y	S/P	2(k)	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7
Groundnut oil	Y	P	2(k)	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Heptane (all isomers)	X	P	2	2G	Cont	No	T3	IIA	No	R	F	AC	No	15.19.6
n-Heptanoic acid	Z	S/P	3	2G	Cont	No			Yes	R	No	ABC	No	15.19.6, 15.17
Heptanol (all isomers) (d)	Y	S/P	3	2G	Cont	No	T3	IIA	No	R	FT	ABC	No	15.12.3, 15.12.4, 15.19.6
Heptene (all isomers)	Y	P	2	2G	Cont	No	T3	IIA	No	R	F	ABC	No	15.19.6
Heptyl acetate	Y	S/P	2	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6
1-Hexadecylnaphthalene / 1,4-bis(hexadecyl)naphthalene mixture	Y	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6
Hexamethylenediamine (molten)	Y	S/P	3	2G	Cont	No	-	-	Yes	C	T	AC	Yes	15.12, 15.17, 15.19, 16.2.9

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Hexamethylenediamine adipate (50% in water)	Z	P	3	2G	Open	No			Yes	O	No	AC	No	
Hexamethylenediamine solution	Y	S/P	3	2G	Cont	No			Yes	C	T	AC	Yes	15.12, 15.17, 15.19
Hexamethylene diisocyanate	Y	S/P	2	2G	Cont	Dry	T1	IIB	Yes	C	T	AC(b)D	Yes	15.12, 15.16.2, 15.17, 15.18, 15.19
Hexamethylene glycol	Z	S/P	3	2G	Open	No			Yes	O	No	AC	No	
Hexamethyleneimine	Y	S/P	2	2G	Cont	No	T2	IIB	No	R	FT	AC	No	15.12.3, 15.12.4, 15.19
Hexamethylenetetramine solutions	Z	S	3	2G	Open	No			Yes	O	No	AC	No	15.19.6
Hexane (all isomers)	Y	S/P	2	2G	Cont	No	T3	IIA	No	C	FT	AC	No	15.12, 15.17, 15.19.6
1,6-Hexanediol, distillation overheads	Y	S/P	3	2G	Cont	No	-	-	Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.9
Hexanoic acid	Y	S/P	3	2G	Cont	No			Yes	C	T	ABC	Yes	15.12, 15.17, 15.19
Hexanol	Y	S/P	2	2G	Cont	No			Yes	C	T	ABC	Yes	15.12, 15.17, 15.19
Hexene (all isomers)	Y	S/P	3	2G	Cont	No	T3	IIA	No	R	F	AC	No	15.19.6
Hexyl acetate	Y	S/P	2	2G	Cont	No	T2	IIA	No	R	F	AC	No	15.19.6
Hexylene glycol	Z	S	3	2G	Cont	No			Yes	C	T	AC	Yes	15.12, 15.17, 15.19
Hydrocarbon wax	X	S/P	2	2G	Cont	No	-	-	Yes	C	T	ABC	No	15.12, 15.17, 15.19.6, 16.2.6, 16.2.9
Hydrochloric acid (*)	Z	S/P	3	1G	Cont	No			NF	C	T	No	Yes	15.11, 15.12, 15.17, 15.19
Hydrogen peroxide solutions (over 60% but not over 70% by mass)	Y	S/P	2	2G	Cont	No			NF	R	T	No	No	15.5.1, 15.12.3, 15.12.4, 15.19.6
Hydrogen peroxide solutions (over 8% but not over 60% by mass)	Y	S/P	3	2G	Cont	No			NF	R	T	No	No	15.5.2, 15.18, 15.12.3, 15.12.4, 15.19.6
2-Hydroxyethyl acrylate	Y	S/P	2	2G	Cont	No			Yes	C	T	AC	Yes	15.12, 15.13, 15.17, 15.19, 16.6.1, 16.6.2
N-(Hydroxyethyl)ethylenediaminetriacetic acid, trisodium salt solution	Y	S/P	3	2G	Cont	No			Yes	C	T	AC	No	15.12, 15.17, 15.19.6

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
2-Hydroxy-4-(methylthio)butanoic acid	Z	S/P	3	2G	Cont	No			Yes	C	T	AC	Yes	15.12, 15.17, 15.19
Illipe oil	Y	P	2(k)	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Isoamyl alcohol	Z	S/P	3	2G	Cont	No	T2	IIA	No	R	FT	ABC	No	15.12.3, 15.12.4, 15.19.6
Isobutyl alcohol	Z	S/P	3	2G	Cont	No	T2	IIA	No	R	F	ABC	No	15.19.6
Isobutyl formate	Z	P	3	2G	Cont	No	T2	IIA	No	R	F	ABC	No	15.19.6
Isobutyl methacrylate	Z	S/P	3	2G	Cont	No	T1	IIA	No	R	F	ABC	No	15.13, 15.19.6, 16.6.1, 16.6.2
Isophorone	Y	S/P	3	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6
Isophoronediamine	Y	S/P	3	2G	Cont	No			Yes	C	T	AC	Yes	15.12, 15.17, 15.19, 16.2.9
Isophorone diisocyanate	Y	S/P	2	2G	Cont	Dry			Yes	C	T	ABD	Yes	15.12, 15.16.2, 15.17, 15.19
Isoprene	Y	S/P	2	2G	Cont	No	T3	IIB	No	C	FT	ABC	No	15.12, 15.13, 15.14, 15.17, 15.19.6, 16.6.1, 16.6.2
Isopropanolamine	Y	S/P	3	2G	Cont	No	T2	IIA	Yes	R	No	AC	No	15.19.6, 16.2.6, 16.2.9
Isopropyl acetate	Z	P	3	2G	Cont	No	T1	IIA	No	R	F	ABC	No	15.19.6
Isopropylamine	Y	S/P	3	2G	Cont	No	T2	IIA	No	C	FT	AC	No	15.12.3.2, 15.14, 15.19
Isopropylamine (70% or less) solution	Y	S/P	3	2G	Cont	No	T2	IIA	No	C	FT	AC	No	15.12.3.2, 15.19
Isopropylcyclohexane	Y	S/P	2	2G	Cont	No	T3	IIA	No	R	F	AC	No	15.19.6, 16.2.9
Isopropyl ether	Y	S/P	3	2G	Cont	Inert	T2	IIA	No	R	F	AC	No	15.4.6, 15.13, 15.19.6, 16.6.1, 16.6.2
Jatropha oil	Y	P	2(k)	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7
Lactic acid	Z	S/P	3	2G	Cont	No			Yes	C	T	AC	Yes	15.12, 15.17, 15.19

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Lactonitrile solution (80% or less)	Y	S/P	1	1G	Cont	No			NF	C	T	No	Yes	15.12, 15.13, 15.17, 15.18, 15.19, 16.6.1, 16.6.2, 16.6.3
Lard	Y	S/P	2(k)	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Latex, ammonia (1% or less)- inhibited	Y	S/P	2	2G	Open	No	-	-	Yes	O	No	AC	No	15.19.6, 16.2.6, 16.2.9
Latex: Carboxylated styrene-Butadiene copolymer; Styrene-Butadiene rubber	Z	S/P	3	2G	Open	No	-	-	Yes	O	No	AC	No	16.2.9
Lauric acid	X	S/P	2	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6, 16.2.9
Ligninsulphonic acid, magnesium salt solution	Z	P	3	2G	Open	No	-	-	Yes	O	No	AC	No	
Ligninsulphonic acid, sodium salt solution	Z	P	3	2G	Open	No	-	-	Yes	O	No	AC	No	16.2.9
Linseed oil	Y	S/P	2(k)	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Liquid chemical wastes	X	S/P	2	2G	Cont	No			No	C	FT	AC	No	15.12, 15.17, 15.19, 20.5.1, 20.7
Long-chain alkaryl polyether (C11-C20)	Y	S/P	2	2G	Cont	No			Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6, 16.2.9
Long-chain alkaryl sulphonic acid (C16-C60)	Y	S/P	2	2G	Cont	No	-	-	Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.9
Long-chain alkylphenate/Phenol sulphide mixture	Y	S/P	2	2G	Cont	No	-	-	Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6, 16.2.9
Long-chain alkylphenol (C14-C18)	Y	S/P	2	2G	Cont	No			Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6
Long-chain alkylphenol (C18-C30)	Y	S/P	2	2G	Cont	No			Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
L-Lysine solution (60% or less)	Z	P	3	2G	Open	No			Yes	O	No	AC	No	
Magnesium chloride solution	Z	P	3	2G	Open	No			Yes	O	No	AC	No	
Magnesium hydroxide slurry	Z	S	3	2G	Open	No	-	-	NF	O	No	No	No	16.2.9
Magnesium long-chain alkaryl sulphonate (C11-C50)	Y	S/P	2	2G	Cont	No	-	-	Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6, 16.2.9
Magnesium long-chain alkyl salicylate (C11+)	Y	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Maleic anhydride	Y	S/P	3	2G	Cont	No			Yes	C	T	AC(f)	Yes	15.12, 15.17, 15.19, 16.2.9
Maleic anhydride-sodium allylsulphonate copolymer solution	Z	P	3	2G	Open	No			Yes	O	No	ABC	No	
Mango kernel oil	Y	P	2(k)	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Mercaptobenzothiazol, sodium salt solution	X	S/P	2	2G	Open	No			NF	O	No	No	No	15.19.6, 16.2.9
Mesityl oxide	Z	S/P	3	2G	Cont	No	T2	IIB	No	R	FT	AC	No	15.12.3, 15.12.4, 15.19.6
Metam sodium solution	X	S/P	2	2G	Cont	No	-	-	NF	C	T	No	No	15.12.3, 15.12.4, 15.19
Methacrylic acid	Y	S/P	3	2G	Cont	No			Yes	C	T	AC	No	15.13, 15.12.3, 15.12.4, 15.19, 16.2.9, 16.6.1
Methacrylic acid - alkoxy poly (alkylene oxide) methacrylate copolymer, sodium salt aqueous solution (45% or less)	Z	S/P	3	2G	Open	No	-	-	NF	O	No	No	No	16.2.9
Methacrylic resin in ethylene dichloride	Y	S/P	3	2G	Cont	No	T2	IIA	No	C	FT	ABC	No	15.12, 15.17, 15.19, 16.2.9
Methacrylonitrile	Y	S/P	2	2G	Cont	No	T1	IIA	No	C	FT	AC	Yes	15.12, 15.13, 15.17, 15.19

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
3-Methoxy-1-butanol	Z	S/P	3	2G	Cont	No	T2	IIA	No	R	F	AC	No	15.19.6
3-Methoxybutyl acetate	Y	S/P	3	2G	Open	No			Yes	O	No	ABC	No	15.19.6
N-(2-Methoxy-1-methyl ethyl)-2-ethyl-6-methyl chloroacetanilide	X	S/P	1	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19, 16.2.6
Methyl acetate	Z	P	3	2G	Cont	No	T1	IIA	No	R	F	AC	No	15.19.6
Methyl acetoacetate	Z	S/P	3	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6
Methyl acrylate	Y	S/P	3	2G	Cont	No	T1	IIB	No	C	FT	AC	No	15.12, 15.17, 15.13, 15.19
Methyl alcohol (*)	Y	S/P	3	2G	Cont	No	T1	IIA	No	C	FT	AC	No	15.12.1, 15.12.2, 15.12.3.2, 15.12.3.3, 15.12.4, 15.17, 15.19
Methylamine solutions (42% or less)	Y	S/P	2	2G	Cont	No	T2	IIA	No	C	FT	AC	Yes	15.12, 15.17, 15.19
Methylamyl acetate	Y	P	2	2G	Cont	No	T2	IIA	No	R	F	ABC	No	15.19.6
Methylamyl alcohol	Z	S/P	3	2G	Cont	No	T2	IIA	No	R	FT	ABC	No	15.12.3, 15.12.4, 15.19.6
Methyl amyl ketone	Z	S/P	3	2G	Cont	No	T2	IIA	No	R	F	ABC	No	15.19.6
N-Methylaniline	Y	S/P	2	2G	Cont	No	-	-	Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6
alpha-Methylbenzyl alcohol with acetophenone (15% or less)	Y	S/P	2	2G	Cont	No	-	-	Yes	C	T	ABC	Yes	15.12, 15.17, 15.19, 16.2.6, 16.2.9
Methylbutenol	Y	S/P	3	2G	Cont	No	T4	IIA	No	R	FT	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.9
Methyl tert-butyl ether	Z	P	3	2G	Cont	No	T1	IIA	No	R	F	ABC	No	15.19.6
Methyl butyl ketone	Y	S/P	3	2G	Cont	No	T2	IIA	No	C	FT	ABC	No	15.12, 15.17, 15.19.6
Methylbutynol	Z	S/P	3	2G	Cont	No	T4	IIB	No	R	F	AC	No	15.19.6

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Methyl butyrate	Y	S/P	3	2G	Cont	No	T4	IIA	No	R	FT	AC	No	15.12.3, 15.12.4, 15.19.6
Methylcyclohexane	Y	S/P	2	2G	Cont	No	T3	IIA	No	R	F	AC	No	15.19.6
Methylcyclopentadiene dimer	Y	S/P	2	2G	Cont	No	T4	IIB	No	R	FT	ABC	No	15.12.3, 15.12.4, 15.19.6
Methylcyclopentadienyl manganese tricarbonyl	X	S/P	2	2G	Cont	No	-	-	Yes	C	T	ABC	Yes	15.12, 15.17, 15.18, 15.19, 16.2.9
Methyl diethanolamine	Y	S/P	3	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6
2-Methyl-6-ethyl aniline	Y	S/P	3	2G	Cont	No			Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6
Methyl ethyl ketone	Z	S/P	3	2G	Cont	No	T1	IIA	No	R	F	AC	No	15.19.6
2-Methyl-5-ethyl pyridine	Y	S/P	2	2G	Cont	No	-	-	Yes	C	T	ABC	Yes	15.12, 15.17, 15.19
Methyl formate	Z	S/P	2	2G	Cont	No	T1	IIA	No	R	FT	AC	No	15.12.3, 15.12.4, 15.14, 15.19.6
2-Methylglutaronitrile with 2-Ethylsuccinonitrile (12% or less)	Z	S/P	3	2G	Cont	No	-	-	Yes	C	T	ABC	Yes	15.12, 15.17, 15.19
2-Methyl-2-hydroxy-3-butyne	Z	S/P	3	2G	Cont	No	T3	IIA	No	R	F	AC	No	15.19.6, 16.2.9
Methyl isobutyl ketone	Z	S/P	3	2G	Cont	No	T1	IIA	No	R	FT	ABC	No	15.12.3, 15.12.4, 15.19.6
Methyl methacrylate	Y	S/P	3	2G	Cont	No	T2	IIA	No	R	F	AC	No	15.13, 15.19.6
3-Methyl-3-methoxybutanol	Z	S/P	3	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6
Methyl naphthalene (molten)	X	S/P	2	2G	Cont	No			Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6
N-Methylglucamine solution (70% or less)	Z	S	3	2G	Cont	No			Yes	C	T	AC	Yes	15.12, 15.17, 15.19, 16.2.9
2-Methyl-1,3-propanediol	Z	P	3	2G	Open	No	-	-	Yes	O	No	AC	No	

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
2-Methylpyridine	Z	S/P	3	2G	Cont	No	T1	IIA	No	C	F	AC	No	15.12.3.2, 15.19
3-Methylpyridine	Z	S/P	3	2G	Cont	No	T1	IIA	No	C	FT	AC	No	15.12.3, 15.12.4, 15.19
4-Methylpyridine	Z	S/P	3	2G	Cont	No	T1	IIA	No	C	FT	AC	No	15.12.3, 15.12.4, 15.19, 16.2.9
N-Methyl-2-pyrrolidone	Y	S/P	3	2G	Cont	No			Yes	C	T	AC	No	15.12, 15.17, 15.19.6
Methyl propyl ketone	Z	S	3	2G	Cont	No	T1	IIA	No	R	FT	ABC	No	15.12.3, 15.12.4, 15.19.6
Methyl salicylate	Y	S/P	3	2G	Cont	No			Yes	C	T	AC	No	15.12, 15.17, 15.19.6
alpha-Methylstyrene	Y	S/P	2	2G	Cont	No	T1	IIB	No	C	FT	AD(j)	No	15.12, 15.13, 15.17, 15.19.6, 16.6.1, 16.6.2
3-(methylthio)propionaldehyde	Y	S/P	2	2G	Cont	No	T3	IIA	No	R	FT	ABC	No	15.12, 15.17, 15.19.6
Molybdenum polysulphide long chain alkyl dithiocarbamide complex	Y	S/P	2	2G	Cont	No	-	-	Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6, 16.2.9
Morpholine	Y	S/P	3	2G	Cont	No	T2	IIA	No	C	FT	AC	No	15.12.3, 15.12.4, 15.19
Motor fuel anti-knock compound (containing lead alkyls)	X	S/P	1	1G	Cont	Inert	T4	IIA	No	C	FT	AC	Yes	15.6, 15.12, 15.17, 15.18, 15.19
Myrcene	X	S/P	2	2G	Cont	No	T3	IIA	No	R	FT	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.9
Naphthalene (molten)	X	S/P	2	2G	Cont	No	T1	IIA	Yes	C	T	ABC	No	15.12, 15.17, 15.19.6, 16.2.9
Naphthalene crude (molten)	Y	S/P	2	2G	Cont	No			Yes	C	T	ABC	No	15.12, 15.17, 15.19.6, 16.2.6, 16.2.9
Naphthalenesulphonic acid-Formaldehyde copolymer, sodium salt solution	Z	S/P	3	2G	Open	No	-	-	Yes	O	No	AC	No	16.2.9
Neodecanoic acid	Y	S/P	2	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6
Nitrating acid (mixture of sulphuric and nitric acids)	Y	S/P	1	1G	Cont	No			NF	C	T	No	Yes	15.11, 15.12, 15.16.2, 15.17, 15.18, 15.19

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Nitric acid (70% and over)	Y	S/P	2	2G	Cont	No			NF	C	T	No	Yes	15.11, 15.12, 15.16.2, 15.17, 15.19
Nitric acid (less than 70%)	Y	S/P	2	2G	Cont	No			NF	C	T	No	Yes	15.11, 15.12, 15.17, 15.19
Nitrilotriacetic acid, trisodium salt solution	Y	S/P	3	2G	Cont	No			Yes	C	T	AC	No	15.12, 15.17, 15.19.6
Nitrobenzene	Y	S/P	2	2G	Cont	No	-	-	Yes	C	T	ABC	No	15.12, 15.17, 15.19, 16.2.9
Nitroethane	Y	S/P	3	2G	Cont	No	T2	IIB	No	R	FT	ABC(f)	No	15.12.3, 15.12.4, 15.19.6, 16.6.1, 16.6.2, 16.6.4
Nitroethane (80%)/ Nitropropane(20%)	Y	S/P	3	2G	Cont	No	T2	IIB	No	R	FT	ABC(f)	No	15.12.3, 15.12.4, 15.19.6, 16.6.1, 16.6.2, 16.6.3
Nitroethane, 1-Nitropropane (each 15% or more) mixture	Y	S/P	3	2G	Cont	No	T2	IIB	No	R	FT	ABC(f)	No	15.12.3, 15.12.4, 15.19.6, 16.2.6, 16.6.1, 16.6.2, 16.6.3
o-Nitrophenol (molten)	Y	S/P	2	2G	Cont	No	T4	IIB	No	R	F	ABC	No	15.19.6, 16.2.6, 16.2.9
1- or 2-Nitropropane	Y	S/P	3	2G	Cont	No	T2	IIB	No	C	FT	AC	No	15.12, 15.17, 15.19
Nitropropane (60%)/Nitroethane (40%) mixture	Y	S/P	2	2G	Cont	No	T2	IIB	No	C	FT	ABC(f)	No	15.12, 15.17, 15.19.6
o- or p-Nitrotoluenes	Y	S/P	2	2G	Cont	No		IIB	Yes	C	T	ABC	No	15.12, 15.17, 15.19.6
Nonane (all isomers)	X	S/P	2	2G	Cont	No	T3	IIA	No	R	F	ABC	No	15.19.6
Nonanoic acid (all isomers)	Y	S/P	2	2G	Cont	No			Yes	C	T	ABC	Yes	15.12, 15.17, 15.19, 16.2.9
Non-edible industrial grade palm oil	Y	S/P	2	2G	Cont	No	-	-	Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6, 16.2.7, 16.2.9
Nonene (all isomers)	Y	P	2	2G	Cont	No	T3	IIA	No	R	F	AC	No	15.19.6
Nonyl alcohol (all isomers)	Y	S/P	2	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Nonyl methacrylate monomer	Y	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.9
Nonylphenol	X	S/P	1	2G	Cont	No			Yes	C	T	AC	Yes	15.12, 15.17, 15.19, 16.2.6, 16.2.9
Nonylphenol poly(4+)ethoxylate	Y	S/P	2	2G	Cont	No	-	-	Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6
Noxious liquid, NF, (1) n.o.s. (trade name, contains) ST1, Cat. X	X	P	1	2G	Open	No	-	-	Yes	O	No	AC	No	15.19, 16.2.6
Noxious liquid, F, (2) n.o.s. (trade name, contains) ST1, Cat. X	X	P	1	2G	Cont	No	T3	IIA	No	R	F	AC	No	15.19, 16.2.6
Noxious liquid, NF, (3) n.o.s. (trade name, contains) ST2, Cat. X	X	P	2	2G	Open	No	-		Yes	O	No	AC	No	15.19, 16.2.6
Noxious liquid, F, (4) n.o.s. (trade name, contains) ST2, Cat. X	X	P	2	2G	Cont	No	T3	IIA	No	R	F	AC	No	15.19, 16.2.6
Noxious liquid, NF, (5) n.o.s. (trade name, contains) ST2, Cat. Y	Y	P	2	2G	Open	No	-		Yes	O	No	AC	No	15.19, 16.2.6, 16.2.9(l)
Noxious liquid, F, (6) n.o.s. (trade name, contains) ST2, Cat. Y	Y	P	2	2G	Cont	No	T3	IIA	No	R	F	AC	No	15.19, 16.2.6, 16.2.9(l)
Noxious liquid, NF, (7) n.o.s. (trade name, contains) ST3, Cat. Y	Y	P	3	2G	Open	No	-	-	Yes	O	No	AC	No	15.19, 16.2.6, 16.2.9(l)

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Noxious liquid, F, (8) n.o.s. (trade name, contains) ST3, Cat. Y	Y	P	3	2G	Cont	No	T3	IIA	No	R	F	AC	No	15.19, 16.2.6, 16.2.9(l)
Noxious liquid, NF, (9) n.o.s. (trade name, contains) ST3, Cat. Z	Z	P	3	2G	Open	No	-		Yes	O	No	AC	No	
Noxious liquid, F, (10) n.o.s. (trade name, contains) ST3, Cat. Z	Z	P	3	2G	Cont	No	T3	IIA	No	R	F	AC	No	15.19.6
Octamethylcyclotetrasiloxane	Y	P	2	2G	Cont	No	T2	IIA	No	R	F	AC	No	15.19.6, 16.2.9
Octane (all isomers)	X	P	2	2G	Cont	No	T3	IIA	No	R	F	AC	No	15.19.6
Octanoic acid (all isomers)	Y	S/P	2	2G	Cont	No	-	-	Yes	C	T	ABC	Yes	15.12, 15.17, 15.19
Octanol (all isomers)	Y	S/P	2	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6
Octene (all isomers)	Y	P	2	2G	Cont	No	T3	IIA	No	R	F	AC	No	15.19.6
n-Octyl acetate	Y	S/P	3	2G	Open	No			Yes	O	No	AC	No	15.19.6, 16.2.9
Octyl aldehydes	Y	S/P	2	2G	Cont	No	T4	IIB	No	R	F	AC	No	15.19.6, 16.2.9
Octyl decyl adipate	Y	S/P	2	2G	Open	No	-	-	Yes	O	No	AC	No	15.19.6, 16.2.9
n-Octyl mercaptan	X	S/P	1	2G	Open	No			Yes	O	No	ABC	No	15.19
Offshore contaminated bulk liquid P (o)	X	P	2	2G	Open	No	-	-	Yes	O	No	AC	No	15.19.6
Offshore contaminated bulk liquid S (o)	X	S/P	2	2G	Cont	No	T3	IIA	No	C	FT	AC	Yes	15.12, 15.15, 15.17, 15.19
Olefin-Alkyl ester copolymer (molecular weight 2000+)	Y	P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Olefin Mixture (C7-C9) C8 rich, stabilised	X	P	2	2G	Cont	No	T3	IIB	No	R	F	ABC	No	15.13, 15.19.6
Olefin mixtures (C5-C7)	Y	S/P	3	2G	Cont	No	T3	IIA	No	R	F	AC	No	15.19.6
Olefin mixtures (C5-C15)	X	S/P	2	2G	Cont	No	T3	IIA	No	R	FT	AC	No	15.12.3, 15.12.4, 15.19.6

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Olefins (C13+, all isomers)	Y	P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.9
alpha-Olefins (C6-C18) mixtures	X	S/P	2	2G	Cont	No	T4	IIA	No	R	FT	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.9
Oleic acid	Y	S/P	2	2G	Cont	No			Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.9
Oleum	Y	S/P	2	2G	Cont	Dry	-	-	NF	C	T	No	Yes	15.11.2 to 15.11.8, 15.12, 15.16.2, 15.17, 15.19, 16.2.6
Oleylamine	X	S/P	2	2G	Cont	No			Yes	C	T	AC	Yes	15.12, 15.17, 15.19, 16.2.9
Olive oil	Y	S/P	2(k)	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Oxygenated aliphatic hydrocarbon mixture	Z	S/P	3	2G	Open	No	-	-	Yes	O	No	ABC	No	
Palm acid oil	Y	S/P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Palm fatty acid distillate	Y	S/P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Palm kernel acid oil	Y	S/P	2	2G	Cont	No			Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6, 16.2.7, 16.2.9
Palm kernel fatty acid distillate	Y	S/P	2	2G	Cont	No	-	-	Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6, 16.2.7, 16.2.9
Palm kernel oil	Y	S/P	2(k)	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Palm kernel olein	Y	P	2(k)	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Palm kernel stearin	Y	P	2(k)	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Palm mid-fraction	Y	P	2(k)	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Palm oil	Y	P	2(k)	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Palm oil fatty acid methyl ester	Y	P	2	2G	Open	No	-	-	Yes	O	No	AC	No	15.19.6, 16.2.9
Palm olein	Y	P	2(k)	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Palm stearin	Y	P	2(k)	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Paraffin wax, highly-refined	Y	P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Paraffin wax, semi-refined	X	S/P	2	2G	Cont	No	-	-	Yes	C	T	ABC	No	15.12, 15.17, 15.19.6, 16.2.6, 16.2.9
Paraldehyde	Z	S/P	3	2G	Cont	No	T3	IIB	No	R	F	AC	No	15.19.6, 16.2.9
Paraldehyde-ammonia reaction product	Y	S/P	2	2G	Cont	No	T1	IIB	No	C	FT	ABC	Yes	15.12, 15.17, 15.19
Pentachloroethane	Y	S/P	2	2G	Cont	No			NF	C	T	No	No	15.12, 15.17, 15.19.6
1,3-Pentadiene	Y	P	3	2G	Cont	No	T1	IIA	No	R	F	ABC	No	15.13, 15.19.6, 16.6.1, 16.6.2, 16.6.3
1,3-Pentadiene (greater than 50%), cyclopentene and isomers, mixtures	Y	S/P	2	2G	Cont	Inert	T3	IIB	No	C	FT	ABC	Yes	15.12, 15.13, 15.17, 15.19
Pentaethylenhexamine	X	S/P	2	2G	Cont	No			Yes	C	T	ABC	Yes	15.12, 15.17, 15.19
Pentane (all isomers)	Y	P	3	2G	Cont	No	T2	IIA	No	R	F	AC	No	15.14, 15.19.6
Pentanoic acid	Y	S/P	2	2G	Cont	No			Yes	C	T	ABC	Yes	15.12, 15.17, 15.19
n-Pentanoic acid (64%)/2-Methyl butyric acid (36%) mixture	Y	S/P	2	2G	Cont	No			Yes	C	T	ABC	Yes	15.11.2, 15.11.3, 15.11.4, 15.11.6, 15.11.7, 15.11.8, 15.12, 15.17, 15.19
Pentene (all isomers)	Y	P	2	2G	Cont	No	T3	IIA	No	R	F	AC	No	15.14, 15.19.6
n-Pentyl propionate	Y	S/P	3	2G	Cont	No	T2	IIA	No	R	FT	ABC	No	15.12.3, 15.12.4, 15.19.6
Perchloroethylene	Y	S/P	2	2G	Cont	No			NF	C	T	No	No	15.12, 15.17, 15.19.6

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Phenol	Y	S/P	2	2G	Cont	No	T1	IIA	Yes	C	T	AC	Yes	15.12, 15.17, 15.19, 16.2.9
1-Phenyl-1-xylyl ethane	Y	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6
Phosphate esters, alkyl (C12-C14) amine	Y	S/P	2	2G	Cont	No	T4	IIB	No	R	FT	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6, 16.2.9
Phosphoric acid	Z	S/P	3	2G	Cont	No			NF	C	T	No	Yes	15.11.1, 15.11.2, 15.11.3, 15.11.4, 15.11.6, 15.11.7, 15.11.8, 15.12, 15.17, 15.19, 16.2.9
Phosphorus, yellow or white (*)	X	S/P	1	1G	Cont	Pad+(vent or inert)			No(c)	C	No	ABC	No	15.7, 15.19, 16.2.9
Phthalic anhydride (molten)	Y	S/P	2	2G	Cont	No	T1	IIA	Yes	C	T	ABC	Yes	15.12, 15.17, 15.19, 16.2.6, 16.2.9
alpha-Pinene	X	S/P	2	2G	Cont	No	T3	IIA	No	R	F	ABC	No	15.19.6
beta-Pinene	X	S/P	2	2G	Cont	No	T1	IIB	No	R	F	ABC	No	15.19.6
Pine oil	X	S/P	2	2G	Open	No			Yes	O		ABC	No	15.19.6, 16.2.6, 16.2.9
Piperazine, 68% solution	Y	S/P	2	2G	Cont	No			Yes	C	T	AC	Yes	15.12, 15.17, 15.19, 16.2.6, 16.2.9
Polyacrylic acid solution (40% or less)	Z	S/P	3	2G	Open	No	-	-	Yes	O	No	AC	No	
Polyalkyl (C18-C22) acrylate in xylene	Y	S/P	2	2G	Cont	No	T1	IIB	No	R	FT	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6, 16.2.9
Polyalkylalkenaminesuccinimide, molybdenum oxysulphide	Y	P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6
Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether	Z	P	3	2G	Open	No	-	-	Yes	O	No	AC	No	
Poly(2-8)alkylene glycol monoalkyl (C1-C6) ether acetate	Y	P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6
Polyalkyl (C10-C20) methacrylate	Y	P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Polyalkyl (C10-C18) methacrylate/ethylene-propylene copolymer mixture	Y	P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Polyaluminium chloride solution	Z	S	3	2G	Open	No			NF	O	No	No	No	
Polybutene	Y	P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6
Polybutenyl succinimide	Y	P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Poly(2+)cyclic aromatics	X	S/P	1	2G	Cont	No			Yes	C	T	ABC	No	15.12, 15.17, 15.19, 16.2.6, 16.2.9
Polyether (molecular weight 1350+)	Y	P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6
Polyethylene glycol	Z	P	3	2G	Open	No			Yes	O	No	AC	No	
Polyethylene glycol dimethyl ether	Z	S/P	3	2G	Open	No			Yes	O	No	AC	No	
Poly(ethylene glycol) methylbutenyl ether (MW>1000)	Z	P	3	2G	Open	No	-	-	Yes	O	No	AC	No	16.2.9
Polyethylene polyamines	Y	S/P	2	2G	Cont	No	-	-	Yes	C	T	AC	Yes	15.12, 15.17, 15.19, 16.2.6, 16.2.9
Polyethylene polyamines (more than 50% C5 -C20 paraffin oil)	Y	S/P	2	2G	Cont	No			Yes	C	T	AC	Yes	15.12, 15.17, 15.19, 16.2.9
Polyferric sulphate solution	Y	S/P	3	2G	Cont	No			NF	C	T	No	Yes	15.12, 15.17, 15.19
Poly(iminoethylene)-graft-N-poly(ethyleneoxy) solution (90% or less)	Z	S/P	3	2G	Open	No	-	-	NF	O	No	No	No	16.2.9
Polyisobutenamine in aliphatic (C10-C14) solvent	Y	S/P	2	2G	Cont	No	-	-	Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6
(Polyisobutene) amino products in aliphatic hydrocarbons	Y	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Polyisobutenyl anhydride adduct	Z	S/P	3	2G	Open	No			Yes	O	No	ABC	No	
Poly(4+)isobutylene (MW>224)	X	P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Polyisobutylene (MW≤224)	Y	P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.9
Polyglycerin, sodium salt solution (containing less than 3% sodium hydroxide)	Z	S	2	2G	Cont	No			Yes	C	T	AC	Yes	15.12, 15.17, 15.19. 16.2.9
Polymethylene polyphenyl isocyanate	Y	S/P	3	2G	Cont	Dry			Yes(a)	C	T(a)	AD	Yes	15.12, 15.16.2, 15.17, 15.19.6, 16.2.9
Polyolefin (molecular weight 300+)	Y	P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Polyolefin amide alkeneamine (C17+)	Y	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6
Polyolefin amide alkeneamine borate (C28-C250)	Y	P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Polyolefin amide alkeneamine polyol	Y	P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Polyolefinamine (C28-C250)	Y	S/P	2	2G	Cont	No			Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.9
Polyolefinamine in alkyl (C2-C4) benzenes	Y	S/P	2	2G	Cont	No	T2	IIB	No	R	FT	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6, 16.2.9
Polyolefinamine in aromatic solvent	Y	S/P	2	2G	Cont	No	T2	IIB	No	R	FT	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6, 16.2.9
Polyolefin aminoester salts (molecular weight 2000+)	Y	S/P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Polyolefin anhydride	Y	S/P	2	2G	Cont	No			Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6, 16.2.9
Polyolefin ester (C28-C250)	Y	P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Polyolefin phenolic amine (C28-C250)	Y	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Polyolefin phosphorusulphide, barium derivative (C28-C250)	Y	P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Poly(20)oxyethylene sorbitan monooleate	Y	P	3	2G	Open	No			Yes	O	No	AC	No	15.19.6, 16.2.6, 16.2.9
Poly(5+)propylene	Y	P	3	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.9
Polypropylene glycol	Z	S/P	3	2G	Open	No			Yes	O	No	AC	No	15.19.6
Polysiloxane	Y	P	2	2G	Cont	No	T2	IIB	No	R	F	ABC	No	15.19.6, 16.2.9
Potassium chloride solution	Z	P	3	2G	Open	No	-	-	NF	O	No	No	No	16.2.9
Potassium hydroxide solution (*)	Y	S/P	3	2G	Open	No			NF	C	No	No	No	15.12.3.2, 15.19
Potassium formate solutions (*)	Z	S	3	2G	Open	No			NF	R	No	No	No	15.19.6
Potassium oleate	Y	S/P	2	2G	Open	No			Yes	O	No	AC	No	15.19.6, 16.2.6, 16.2.9
Potassium thiosulphate (50% or less)	Y	S/P	3	2G	Cont	No			NF	R	T	No	No	15.12.3, 15.12.4, 15.19.6, 16.2.9
n-Propanolamine	Y	S/P	3	2G	Cont	No			Yes	C	T	ABC	Yes	15.12, 15.17, 15.19, 16.2.9
2-Propene-1-aminiium, N,N-dimethyl-N-2-propenyl-, chloride, homopolymer solution	Y	P	3	2G	Open	No	-	-	NF	O	No	No	No	15.19.6
beta-Propiolactone	Y	S/P	1	2G	Cont	No		IIA	Yes	C	T	AC	Yes	15.12, 15.17, 15.18, 15.19
Propionaldehyde	Y	S/P	3	2G	Cont	Inert	T4	IIB	No	R	F	AC	No	15.19.6
Propionic acid	Y	S/P	3	2G	Cont	No	T1	IIA	No	C	FT	AC	Yes	15.11.2, 15.11.3, 15.11.4, 15.11.6, 15.11.7, 15.11.8, 15.12, 15.17, 15.19

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Propionic anhydride	Y	S/P	2	2G	Cont	No	T2	IIA	Yes	C	T	AC	Yes	15.12, 15.17, 15.19
Propionitrile	Y	S/P	1	1G	Cont	No	T1	IIB	No	C	FT	AC	Yes	15.12, 15.17, 15.18, 15.19
n-Propyl acetate	Y	P	3	2G	Cont	No	T1	IIA	No	R	F	ABC	No	15.19.6
n-Propyl alcohol	Y	S/P	3	2G	Cont	No	T2	IIA	No	C	FT	AC	No	15.12, 15.17, 15.19.6
n-Propylamine	Z	S/P	2	2G	Cont	Inert	T2	IIA	No	C	FT	AC	Yes	15.12, 15.17, 15.19
Propylbenzene (all isomers)	Y	P	3	2G	Cont	No	T2	IIA	No	R	F	ABC	No	15.19.6
Propylene carbonate	Z	S	3	2G	Cont	No			Yes	C	T	ABC	Yes	15.12, 15.17, 15.19
Propylene glycol methyl ether acetate	Z	P	3	2G	Cont	No	T2	IIA	No	R	F	AC	No	
Propylene glycol monoalkyl ether	Z	S/P	3	2G	Cont	No	T3	IIA	No	R	F	AC	No	15.19.6
Propylene glycol phenyl ether	Z	S/P	3	2G	Open	No			Yes	O	No	ABC	No	
Propylene oxide	Y	S/P	2	2G	Cont	Inert	T2	IIB	No	C	FT	AC	No	15.8, 15.12, 15.14, 15.17, 15.19
Propylene tetramer	X	S/P	2	2G	Cont	No	T3	IIA	No	R	F	ABC	No	15.19.6
Propylene trimer	Y	S/P	2	2G	Cont	No	T3	IIA	No	R	F	ABC	No	15.19.6
Pyridine	Y	S/P	3	2G	Cont	No	T1	IIA	No	R	FT	AC	No	15.12.3, 15.12.4, 15.19.6
Pyrolysis gasoline (containing benzene)	Y	S/P	2	2G	Cont	No	T3	IIA	No	C	FT	ABC	No	15.12, 15.17, 15.19.6
Rapeseed oil	Y	P	2(k)	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Rapeseed oil (low erucic acid containing less than 4% free fatty acids)	Y	P	2(k)	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Rape seed oil fatty acid methyl esters	Y	S/P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6
Resin oil, distilled	Y	S/P	2	2G	Cont	No	T1	IIA	No	C	FT	ABC	No	15.12, 15.17, 15.19.6
Rice bran oil	Y	S/P	2(k)	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Rosin	Y	S/P	2	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6, 16.2.9
Safflower oil	Y	S/P	2(k)	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Shea butter	Y	S/P	2(k)	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Sodium alkyl (C14-C17) sulphonates (60-65% solution)	Y	S/P	2	2G	Cont	No			NF	R	T	No	No	15.12.3, 15.12.4, 15.19.6, 16.2.6, 16.2.9
Sodium aluminosilicate slurry	Z	P	3	2G	Open	No			NF	O	No	No	No	16.2.9
Sodium benzoate	Z	S/P	3	2G	Open	No			Yes	O	No	AC	No	16.2.9
Sodium borohydride (15% or less)/Sodium hydroxide solution (*)	Y	S/P	3	2G	Open	No			NF	C	No	No	No	15.19, 16.2.6, 16.2.9
Sodium bromide solution (less than 50%) (*)	Y	S/P	3	2G	Open	No	-	-	NF	R	No	No	No	15.19.6
Sodium carbonate solution (*)	Z	S/P	3	2G	Open	No			NF	R	No	No	No	15.19.6
Sodium chlorate solution (50% or less) (*)	Z	S/P	3	2G	Open	No			NF	R	No	No	No	15.9, 15.12, 15.19, 16.2.9
Sodium dichromate solution (70% or less)	Y	S/P	1	1G	Cont	No			NF	C	T	No	Yes	15.12, 15.17, 15.18, 15.19
Sodium hydrogen sulphide (6% or less)/Sodium carbonate (3% or less) solution	Z	S/P	3	2G	Open	No			NF	O	No	No	No	15.19.6, 16.2.9
Sodium hydrogen sulphite solution (45% or less)	Z	P	3	2G	Open	No			NF	O	No	No	No	16.2.9
Sodium hydrosulphide/Ammonium sulphide solution (*)	Y	S/P	2	2G	Cont	No	T4	IIB	No	C	FT	AC	Yes	15.12, 15.15, 15.17, 15.19, 16.6.1, 16.6.2, 16.6.3
Sodium hydrosulphide solution (45% or less) (*)	Z	S/P	3	2G	Cont	Vent or pad (gas)			NF	R	T	No	Yes	15.12, 15.15, 15.19.6, 16.2.9
Sodium hydroxide solution (*)	Y	S/P	3	2G	Open	No			NF	C	No	No	No	15.19, 16.2.6, 16.2.9

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Sodium hypochlorite solution (15% or less)	Y	S/P	2	2G	Cont	No	-	-	NF	R	No	No	No	15.17, 15.19.6
Sodium methylate 21-30% in methyl alcohol	Y	S/P	2	2G	Cont	No	T1	IIA	No	C	FT	AC	Yes	15.12, 15.17, 15.19, 16.2.6 (only if >28%), 16.2.9
Sodium nitrite solution	Y	S/P	3	2G	Cont	No			NF	C	T	No	No	15.12.3, 15.12.4, 15.19, 16.2.6, 16.2.9
Sodium petroleum sulphonate	Y	S/P	2	2G	Cont	No			Yes	R	T	ABC	Yes	15.12.3, 15.12.4, 15.19.6, 16.2.6
Sodium poly(4+)acrylate solutions	Z	S/P	3	2G	Open	No	-	-	Yes	O	No	AC	No	16.2.9
Sodium silicate solution	Y	S/P	3	2G	Cont	No			NF	C	T	No	Yes	15.12, 15.17, 15.19, 16.2.9
Sodium sulphate solutions	Z	S	3	2G	Open	No			NF	O	No	No	No	16.2.9,
Sodium sulphide solution (15% or less)	Y	S/P	3	2G	Cont	No			NF	C	T	No	Yes	15.12, 15.17, 15.19, 16.2.9
Sodium sulphite solution (25% or less)	Y	S/P	3	2G	Open	No			NF	O	No	No	No	15.19.6, 16.2.9
Sodium thiocyanate solution (56% or less)	Y	S/P	3	2G	Open	No			NF	O	No	No	No	15.19.6, 16.2.9
Soyabean oil	Y	S/P	2(k)	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Soybean Oil Fatty Acid Methyl Ester	Y	P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.9
Styrene monomer	Y	S/P	3	2G	Cont	No	T1	IIA	No	C	FT	ABC	No	15.12, 15.13, 15.17, 15.19.6, 16.6.1, 16.6.2
Sulphohydrocarbon (C3-C88)	Y	P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Sulpholane	Y	S/P	3	2G	Open	No			Yes	O	No	AC	No	15.19.6, 16.2.9
Sulphur (molten) (*)	Z	S	3	1G	Open	Vent or pad (gas)	T3		Yes	O	FT	No	No	15.10, 16.2.9

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Sulphuric acid	Y	S/P	2	2G	Cont	No			NF	C	T	No	Yes	15.11, 15.12, 15.16.2, 15.17, 15.19, 16.2.9
Sulphuric acid, spent	Y	S/P	2	2G	Cont	No			NF	C	T	No	Yes	15.11, 15.12, 15.16.2, 15.17, 15.19
Sulphurized fat (C14-C20)	Z	S/P	3	2G	Open	No			Yes	O	No	ABC	No	
Sulphurized polyolefinamide alkene (C28-C250) amine	Z	P	3	2G	Open	No	-	-	Yes	O	No	AC	No	
Sunflower seed oil	Y	S/P	2(k)	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Tall oil, crude	Y	S/P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6
Tall oil, distilled	Y	P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6
Tall oil fatty acid (resin acids less than 20%)	Y	S/P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6
Tall oil pitch	Y	P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Tall oil soap, crude	Y	S/P	2	2G	Cont	No			Yes	C	T	ABC	Yes	15.12, 15.17, 15.19, 16.2.6
Tallow	Y	P	2(k)	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Tallow fatty acid	Y	P	2	2G	Open	No	-	-	Yes	O	No	AC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Tetrachloroethane	Y	S/P	2	2G	Cont	No			NF	R	T	No	No	15.12.3, 15.12.4, 15.19
Tetraethylene glycol	Z	P	3	2G	Open	No			Yes	O	No	AC	No	
Tetraethylene pentamine	Y	S/P	2	2G	Cont	No			Yes	C	T	AC	Yes	15.12, 15.17, 15.19
Tetrahydrofuran	Z	S	3	2G	Cont	No	T3	IIB	No	R	F	AC	No	15.19.6
Tetrahydronaphthalene	Y	S/P	2	2G	Cont	No			Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6
Tetramethylbenzene (all isomers)	X	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.9
Titanium dioxide slurry	Z	P	3	2G	Open	No			NF	O	No	No	No	

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Toluene	Y	S/P	3	2G	Cont	No	T1	IIA	No	C	FT	AC	No	15.12, 15.17, 15.19.6
Toluenediamine	Y	S/P	2	2G	Cont	No			Yes	C	T	ABC	Yes	15.12, 15.17, 15.18, 15.19, 16.2.6, 16.2.9
Toluene diisocyanate	Y	S/P	2	2G	Cont	Dry	-	-	Yes	C	T	ABC(b)D	Yes	15.12, 15.16.2, 15.17, 15.18, 15.19, 16.2.9
o-Toluidine	Y	S/P	2	2G	Cont	No			Yes	C	T	ABC	No	15.12, 15.17, 15.19
Tributyl phosphate	Y	S/P	3	2G	Cont	No			Yes	C	T	ABC	No	15.12.3, 15.12.4, 15.19.6
1,2,3-Trichlorobenzene (molten)	X	S/P	2	2G	Cont	No			Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6, 16.2.9
1,2,4-Trichlorobenzene	X	S/P	1	2G	Cont	No			Yes	C	T	ABC	No	15.12, 15.17, 15.19, 16.2.9
1,1,1-Trichloroethane	Y	P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6
1,1,2-Trichloroethane	Y	S/P	3	2G	Open	No			NF	O	No	No	No	15.19.6
Trichloroethylene	Y	S/P	2	2G	Cont	No	-	-	NF	C	T	No	No	15.12, 15.17, 15.19.6
1,2,3-Trichloropropane	Y	S/P	3	2G	Cont	No			Yes	C	T	ABC	No	15.12, 15.17, 15.19
1,1,2-Trichloro-1,2,2-Trifluoroethane	Y	P	2	2G	Open	No			NF	O	No	No	No	15.19.6
Tricresyl phosphate (containing 1% or more ortho-isomer)	Y	S/P	2	2G	Cont	No	-	-	Yes	C	T	ABC	No	15.12, 15.17, 15.19, 16.2.6
Tricresyl phosphate (containing less than 1% ortho-isomer)	Y	S/P	2	2G	Cont	No			Yes	C	T	ABC	No	15.12, 15.17, 15.19.6, 16.2.6
Tridecane	Y	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6
Tridecanoic acid	Y	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Tridecyl acetate	Y	S/P	3	2G	Cont	No	-	-	Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6
Triethanolamine	Z	S/P	3	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6, 16.2.9
Triethylamine	Y	S/P	3	2G	Cont	No	T2	IIA	No	C	FT	ABC	No	15.12.3, 15.12.4, 15.19

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Triethylbenzene	X	S/P	2	2G	Cont	No			Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6
Triethylenetetramine	Y	S/P	2	2G	Cont	No	-	-	Yes	C	T	AC	Yes	15.12, 15.17, 15.19, 16.2.9
Triethyl phosphate	Z	S/P	3	2G	Open	No			Yes	O	No	AC	No	15.19.6
Triethyl phosphite	Z	S/P	3	2G	Cont	No	T3	IIA	No	R	FT	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.9
Triisopropanolamine	Z	S/P	3	2G	Open	No			Yes	O	No	AC	No	15.19.6, 16.2.9
Triisopropylated phenyl phosphates	X	P	2	2G	Open	No			Yes	O	No	AC	No	15.19.6, 16.2.6
Trimethylacetic acid	Y	S/P	2	2G	Cont	No			Yes	R	T	AC	No	15.11, 15.12.3, 15.12.4, 15.19.6, 16.2.6, 16.2.9
Trimethylamine solution (30% or less)	Z	S/P	2	2G	Cont	No	T3	IIB	No	R	FT	AC	No	15.12.3, 15.12.4, 15.14, 15.19.6
Trimethylbenzene (all isomers)	X	S/P	2	2G	Cont	No	T1	IIA	No	R	F	ABC	No	15.19.6
Trimethylol propane propoxylated	Z	S/P	3	2G	Open	No	-	-	Yes	O	No	ABC	No	
2,2,4-Trimethyl-1,3-pentanediol diisobutyrate	Y	S/P	3	2G	Open	No			Yes	O	No	ABC	No	15.19.6
2,2,4-Trimethyl-1,3-pentanediol-1-isobutyrate	Y	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6
1,3,5-Trioxane	Y	S/P	3	2G	Cont	No	T2	IIB	No	C	FT	AC	No	15.12, 15.17, 15.19.6, 16.2.9
Tripropylene glycol	Z	P	3	2G	Open	No			Yes	O	No	AC	No	
Trixylyl phosphate	X	S/P	1	2G	Cont	No			Yes	C	T	ABC	No	15.12, 15.17, 15.19.6, 16.2.6

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Tung oil	Y	S/P	2(k)	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Turpentine	X	S/P	2	2G	Cont	No	T3	IIA	No	R	FT	AC	No	15.19.6
Undecanoic acid	Y	S/P	2	2G	Cont	No			Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.6, 16.2.9
1-Undecene	X	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6
Undecyl alcohol	X	S/P	2	2G	Cont	No			Yes	R	T	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.9
Urea/Ammonium nitrate solution	Y	S/P	3	2G	Open	No	-	-	NF	O	No	No	No	15.19.6
Urea/Ammonium phosphate solution	Y	S/P	2	2G	Cont	No			Yes	R	T	AC	No	15.12.3, 15.12.4, 15.19.6
Urea solution	Z	S/P	3	2G	Open	No			Yes	O	No	AC	No	16.2.9,
Used cooking oil (m)	X	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Used cooking oil (Triglycerides, C16-C18 and C18 unsaturated) (m) (n)	Y	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Valeraldehyde (all isomers)	Y	S/P	3	2G	Cont	Inert	T3	IIB	No	R	F	ABC	No	15.4.6, 15.13, 15.19.6, 16.6.1, 16.6.2
Vegetable acid oils (m)	Y	S/P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Vegetable fatty acid distillates (m)	Y	P	2	2G	Open	No	-	-	Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Vegetable oil mixtures, containing less than 15% free fatty acid (m)	Y	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.7, 16.2.9
Vinyl acetate	Y	S/P	3	2G	Cont	No	T2	IIA	No	C	FT	ABC	No	15.12, 15.13, 15.17, 15.19.6, 16.6.1, 16.6.2
Vinyl ethyl ether	Z	S/P	2	2G	Cont	Inert	T3	IIB	No	R	F	ABC	No	15.4, 15.13, 15.14, 15.19.6, 16.6.1, 16.6.2

a	c	d	e	f	g	h	i'	i''	i'''	j	k	l	n	o
Vinylidene chloride	Y	S/P	2	2G	Cont	Inert	T2	IIA	No	C	FT	ABC	No	15.12, 15.13, 15.14, 15.17, 15.19, 16.6.1, 16.6.2
Vinyl neodecanoate	Y	S/P	2	2G	Cont	No			Yes	C	T	ABC	Yes	15.12, 15.13, 15.17, 15.19, 16.6.1, 16.6.2
Vinyltoluene	Y	S/P	2	2G	Cont	No	T1	IIA	No	C	FT	ABC	No	15.12, 15.13, 15.17, 15.19.6, 16.6.1, 16.6.2
White spirit, low (15-20%) aromatic	Y	S/P	2	2G	Cont	No	T3	IIA	No	R	FT	ABC	No	15.12.3, 15.12.4, 15.19.6, 16.2.9
Wood lignin with sodium acetate/oxalate	Z	S/P	3	2G	Open	No	-	-	NF	O	No	No	No	
Xylenes	Y	P	2	2G	Cont	No	T1	IIA	No	R	F	ABC	No	15.19.6, 16.2.9 (h)
Xylenes/ethylbenzene (10% or more) mixture	Y	S/P	2	2G	Cont	No	T2	IIA	No	R	FT	ABC	No	15.12.3, 15.12.4, 15.19.6
Xylenol	Y	S/P	2	2G	Cont	No	-	IIA	Yes	C	T	ABC	Yes	15.12, 15.17, 15.19, 16.2.9
Zinc alkaryl dithiophosphate (C7-C16)	Y	P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6, 16.2.9
Zinc alkenyl carboxamide	Y	S/P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6
Zinc alkyl dithiophosphate (C3-C14)	Y	P	2	2G	Open	No			Yes	O	No	ABC	No	15.19.6, 16.2.6

Footnotes to products in chapter 17

Some entries in chapter 17 contain footnotes, as either letters or symbols in parentheses following the name of the product, in *column a* of the tables. These provide additional information about the carriage requirements for the product. The definitions of these footnotes are included below.

- a If the product to be carried contains flammable solvents such that the flashpoint does not exceed 60°C, then special electrical systems and a flammable-vapour detector shall be provided.
- b Although water is suitable for extinguishing open-air fires involving chemicals to which this footnote applies, water shall not be allowed to contaminate closed tanks containing these chemicals because of the risk of hazardous gas generation.
- c Phosphorus, yellow or white, is carried above its autoignition temperature and therefore flashpoint is not appropriate. Electrical equipment requirements may be similar to those for substances with a flashpoint above 60°C.
- d Requirements are based on those isomers having a flashpoint of 60°C or less; some isomers have a flashpoint greater than 60°C and therefore the requirements based on flammability would not apply to such isomers.
- e Applies to n-decyl alcohol only.
- f Dry chemical shall not be used as fire-extinguishing media.
- g Confined spaces shall be tested for both formic acid vapours and carbon monoxide gas, a decomposition product.
- h Applies to p-xylene only.
- i For mixtures containing no other components with safety hazards and where the pollution category is Y or less.
- j Only certain alcohol-resistant foams are effective.
- k Requirements for Ship Type identified in *column e* might be subject to regulation 4.1.3 of Annex II of MARPOL.
- l Applicable when the melting point is equal to or greater than 0°C.
- m From vegetable oils, animal fats and fish oils specified in the IBC Code.
- n Confirmation that the product is composed of Triglycerides, C16-C18 and C18 unsaturated shall be required in order for the entry to be used. Otherwise, the more generic entry "Used cooking oil (m)" must be used.
- o Indicates that the entries are to be used solely for backloading of contaminated bulk liquids from offshore installations used in the search and exploitation of seabed mineral resources.
- * Indicates that with reference to chapter 21 of the IBC Code (paragraph 21.1.3), deviations from the normal assignment criteria used for some carriage requirements have been implemented.

Chapter 18

List of products to which the Code does not apply

18.1 The following are products which have been reviewed for their safety and pollution hazards and determined not to present hazards to such an extent as to warrant application of the Code.

18.2 Although the products listed in this chapter fall outside the scope of the Code, the attention of Administrations is drawn to the fact that some safety precautions may be needed for their safe transportation. Accordingly, Administrations shall prescribe appropriate safety requirements.

18.3 Some liquid substances are identified as falling into Pollution Category Z and, therefore, subject to certain requirements of MARPOL Annex II.

18.4 Liquid mixtures which are assessed or provisionally assessed under regulation 6.3 of MARPOL Annex II as falling into Pollution Category Z or OS, and which do not present safety hazards, may be carried under the appropriate entry in this chapter for "Noxious or Non-Noxious Liquid Substances, not otherwise specified (n.o.s.)".

EXPLANATORY NOTES

Product name	The product name shall be used in the shipping document for any cargo offered for bulk shipments. Any additional name may be included in brackets after the product name. In some cases, the product names are not identical with the names given in previous issues of the Code.
Pollution Category	The letter Z means the Pollution Category assigned to each product under Annex II of MARPOL. OS means the product was evaluated and found to fall outside Categories X, Y, or Z.

Product Name	Pollution Category
Acetone	Z
Alcoholic beverages, n.o.s.	Z
Apple juice	OS
n-Butyl alcohol	Z
sec-Butyl alcohol	Z
Calcium carbonate slurry	OS
Clay slurry	OS
Coal slurry	OS
Ethyl alcohol	Z
Glucose solution	OS
Glycerol ethoxylated	OS
Hydrogenated starch hydrolysate	OS
Isopropyl alcohol	Z
Kaolin slurry	OS
Lecithin	OS
Maltitol solution	OS

Product Name	Pollution Category
Microsilica slurry	OS
Molasses	OS
Noxious liquid, (11) n.o.s. (trade name, contains) Cat. Z	Z
Non noxious liquid, (12) n.o.s. (trade name, contains) Cat. OS	OS
Orange juice (concentrated)	OS
Orange juice (not concentrated)	OS
Potassium chloride solution (less than 26%)	OS
Propylene glycol	OS
Sodium acetate solutions	Z
Sodium bicarbonate solution (less than 10%)	OS
Sorbitol solution	OS
Sulphonated polyacrylate solution	Z
Tetraethyl silicate monomer/oligomer (20% in ethanol)	Z
Triethylene glycol	OS
Vegetable protein solution (hydrolysed)	OS
Water	OS

Chapter 19

Index of Products Carried in Bulk

19.1 The first column of the Index of Products Carried in Bulk (hereafter referred to as "the Index") provides the so-called Index Name. Where the Index Name is in capitals and in bold, the Index Name is identical to the Product Name in either chapter 17 or chapter 18. The second column listing the relevant Product Name is therefore empty. Where the Index Name is non-bold lower case it reflects a synonym for which the Product Name in either chapter 17 or chapter 18 is given in the second column. The relevant chapter of the IBC Code is reflected in the third column.

19.2 Following a review of chapter 19, a column listing UN numbers which was previously included had been removed from the Index. Since UN numbers are only available for a limited number of Index Names and there are inconsistencies between some of the names used in chapter 19 and those linked to UN numbers, it was decided to remove UN number references in order to avoid any confusion.

19.3 The Index has been developed for information purposes only. None of the Index Names indicated in non-bold lower case in the first column shall be used as the Product Name on the shipping document.

19.4 Prefixes forming an integral part of the name are shown in ordinary (roman) type and are taken into account in determining the alphabetical order of entries. These include such prefixes as:

Mono Di Tri Tetra Penta Iso Bis Neo Ortho Cyclo

19.5 Prefixes that are disregarded for purposes of alphabetical order are the following:

n-	(normal-)
sec-	(secondary-)
tert-	(tertiary-)
o-	(ortho-)
m-	(meta-)
p-	(para-)
N-	
O-	
S-	
sym-	(symmetrical)
uns-	(unsymmetrical)
dl-	
D-	
L-	
cis-	
trans-	
(E)-	
(Z)-	
alpha-	(α -)
beta-	(β -)
gamma-	(γ -)
epsilon-	(ϵ -)
omega-	(ω -)

19.6 The Index utilizes a note after the Index Name for some entries (shown as (a) or (b)) which indicates that the following qualifications apply:

- (a) this Index Name represents a subset of the corresponding Product Name.
- (b) The Product Name corresponding to this Index Name contains a carbon chain length qualification. Since the Index Name should always represent a subset or be an exact synonym of the corresponding Product Name, the carbon chain length characteristics should be checked for any product identified by this Index Name.

Index Name	Product Name	Chapter
Abietic anhydride	ROSIN	17
acedimethylamide	N,N-DIMETHYLACETAMIDE	17
Acetaldehyde cyanohydrin solution (80% or less)	LACTONITRILE SOLUTION (80% OR LESS)	17
Acetaldehyde trimer	PARALDEHYDE	17
ACETIC ACID		17
Acetic acid anhydride	ACETIC ANHYDRIDE	17
Acetic acid, ethenyl ester	VINYL ACETATE	17
Acetic acid, methyl ester	METHYL ACETATE	17
Acetic acid, vinyl ester	VINYL ACETATE	17
ACETIC ANHYDRIDE		17
Acetic ester	ETHYL ACETATE	17
Acetic ether	ETHYL ACETATE	17
Acetic oxide	ACETIC ANHYDRIDE	17
Acetoacetic acid, methyl ester	METHYL ACETOACETATE	17
Acetoacetic ester	ETHYL ACETOACETATE	17
ACETOCHLOR		17
ACETONE		18
ACETONE CYANOHYDRIN		17
ACETONITRILE		17
ACETONITRILE (LOW PURITY GRADE)		17
Acetyl anhydride	ACETIC ANHYDRIDE	17
Acetylene tetrachloride	TETRACHLOROETHANE	17
Acetyl ether	ACETIC ANHYDRIDE	17
Acetyl oxide	ACETIC ANHYDRIDE	17
ACID OIL MIXTURE FROM SOYABEAN, CORN (MAIZE) AND SUNFLOWER OIL REFINING		17
Acroleic acid	ACRYLIC ACID	17
ACRYLAMIDE SOLUTION (50% OR LESS)		17
ACRYLIC ACID		17
ACRYLIC ACID/ETHENESULPHONIC ACID COPOLYMER WITH PHOSPHONATE GROUPS, SODIUM SALT SOLUTION		17
Acrylic acid, 2-hydroxyethyl ester	2-HYDROXYETHYL ACRYLATE	17
Acrylic amide solution, 50% or less	ACRYLAMIDE SOLUTION (50% OR LESS)	17
Acrylic resin monomer	METHYL METHACRYLATE	17
ACRYLONITRILE		17
ACRYLONITRILE-STYRENE COPOLYMER DISPERSION IN POLYETHER POLYOL		17
Adipic acid, bis(2-ethylhexyl) ester	DI-(2-ETHYLHEXYL) ADIPATE	17
ADIPONITRILE		17
ALACHLOR TECHNICAL (90% OR MORE)		17
Alcohol	ETHYL ALCOHOL	18
Alcohol, C10	DECYL ALCOHOL (ALL ISOMERS)	17
Alcohol, C11	UNDECYL ALCOHOL	17
Alcohol, C12	DODECYL ALCOHOL	17
Alcohol, C7 (a)	HEPTANOL (ALL ISOMERS) (D)	17
Alcohol, C8	OCTANOL (ALL ISOMERS)	17
Alcohol, C9	NONYL ALCOHOL (ALL ISOMERS)	17

Index Name	Product Name	Chapter
ALCOHOLIC BEVERAGES, N.O.S.		18
ALCOHOL (C9-C11) POLY(2.5-9)ETHOXYLATE		17
ALCOHOL (C10-C18) POLY (7) ETHOXYLATE		17
ALCOHOL (C6-C17) (SECONDARY) POLY(3-6)ETHOXYLATES		17
ALCOHOL (C6-C17) (SECONDARY) POLY(7-12)ETHOXYLATES		17
ALCOHOL (C12-C16) POLY(1-6) ETHOXYLATES		17
ALCOHOL (C12-C16) POLY(20+)ETHOXYLATES		17
ALCOHOL (C12-C16) POLY(7-19)ETHOXYLATES		17
ALCOHOLS (C13+)		17
Alcohols, C13 - C15	ALCOHOLS (C13+)	17
ALCOHOLS (C12+), PRIMARY, LINEAR		17
ALCOHOLS (C8-C11), PRIMARY, LINEAR AND ESSENTIALLY LINEAR		17
ALCOHOLS (C12-C13), PRIMARY, LINEAR AND ESSENTIALLY LINEAR		17
ALCOHOLS (C14-C18), PRIMARY, LINEAR AND ESSENTIALLY LINEAR		17
Aldehyde collidine	2-METHYL-5-ETHYL PYRIDINE	17
Aldehydine	2-METHYL-5-ETHYL PYRIDINE	17
ALKANES (C6-C9)		17
ISO- AND CYCLO-ALKANES (C10-C11)		17
ISO- AND CYCLO-ALKANES (C12+)		17
N-ALKANES (C9-C11)		17
N-ALKANES (C10-C20)		17
Alkane(C10-C18)sulfonic acid, phenyl ester (a)	ALKYL SULPHONIC ACID ESTER OF PHENOL	17
ALKARYL POLYETHERS (C9-C20)		17
ALKENOIC ACID, POLYHYDROXY ESTER BORATED		17
ALKENYL (C11+) AMIDE		17
ALKENYL (C16-C20) SUCCINIC ANHYDRIDE		17
ALKYL ACRYLATE/VINYLPYRIDINE COPOLYMER IN TOLUENE		17
ALKYL/CYCLO (C4-C5) ALCOHOLS		17
ALKYLARYL PHOSPHATE MIXTURES (MORE THAN 40% DIPHENYL TOLYL PHOSPHATE, LESS THAN 0.02% ORTHO-ISOMERS)		17
ALKYLATED (C4-C9) HINDERED PHENOLS		17
ALKYLBENZENE, ALKYLINDANE, ALKYLINDENE MIXTURE (EACH C12-C17)		17
ALKYLBENZENE DISTILLATION BOTTOMS		17
ALKYLBENZENE MIXTURES (CONTAINING AT LEAST 50% OF TOLUENE)		17
ALKYL (C3-C4) BENZENES		17
ALKYL (C5-C8) BENZENES		17
ALKYL(C9+)BENZENES		17
ALKYLBENZENES MIXTURES (CONTAINING NAPHTHALENE)		17

Index Name	Product Name	Chapter
ALKYL (C11-C17) BENZENE SULPHONIC ACID		17
ALKYLBENZENE SULPHONIC ACID, SODIUM SALT SOLUTION		17
ALKYL (C12+) DIMETHYLAMINE		17
ALKYL DITHIOCARBAMATE (C19-C35)		17
ALKYL DITHIOTHIA DIAZOLE (C6-C24)		17
ALKYL ESTER COPOLYMER (C4-C20)		17
ALKYL (C8-C10)/(C12-C14):(40% OR LESS/60% OR MORE) POLYGLUCOSIDE SOLUTION (55% OR LESS)		17
ALKYL (C8-C10)/(C12-C14):(60% OR MORE/40% OR LESS) POLYGLUCOSIDE SOLUTION(55% OR LESS)		17
ALKYL (C7-C9) NITRATES		17
2,2'- [3-(Alkyl(C16-C18)oxy)propylimino]diethanol (a)	ETHOXYLATED LONG CHAIN (C16+) ALKYOXYALKYLAMINE	17
Alkylphenol, long-chain (C14-C18)	LONG-CHAIN ALKYLPHENOL (C14-C18)	17
Alkylphenol, long-chain (C18-C30)	LONG-CHAIN ALKYLPHENOL (C18-C30)	17
ALKYL(C7-C11)PHENOL POLY(4-12) ETHOXYLATE		17
ALKYL (C8-C40) PHENOL SULPHIDE		17
ALKYL (C8-C9) PHENYLAMINE IN AROMATIC SOLVENTS		17
ALKYL (C9-C15) PHENYL PROPOXYLATE		17
ALKYL (C8-C10) POLYGLUCOSIDE SOLUTION (65% OR LESS)		17
ALKYL (C8-C10)/(C12-C14):(50%/50%) POLYGLUCOSIDE SOLUTION (55% OR LESS)		17
ALKYL (C12-C14) POLYGLUCOSIDE SOLUTION (55% OR LESS)		17
ALKYL(C12-C16) PROPOXYAMINE ETHOXYLATE		17
ALKYL (C10-C15, C12 RICH) PHENOL POLY(4-12)ETHOXYLATE		17
ALKYL (C10-C20, SATURATED AND UNSATURATED) PHOSPHITE		17
ALKYL SULPHONIC ACID ESTER OF PHENOL		17
ALKYL (C18+) TOLUENES		17
Alkyltoluenesulfonic acid, calcium salts, high overbase (up to 70% in mineral oil)	ALKYL (C18-C28) TOLUENESULPHONIC ACID, CALCIUM SALTS, HIGH OVERBASE	17
Alkyl(C18-C28)toluenesulfonic acid,calcium salts, low overbase (up to 60% in mineral oil)	ALKYL (C18-C28) TOLUENESULPHONIC ACID, CALCIUM SALTS, LOW OVERBASE	17
ALKYL(C18-C28)TOLUENESULPHONIC ACID		17
ALKYL(C18-C28)TOLUENESULPHONIC ACID, CALCIUM SALTS, BORATED		17
ALKYL (C18-C28) TOLUENESULPHONIC ACID, CALCIUM SALTS, HIGH OVERBASE		17
ALKYL (C18-C28) TOLUENESULPHONIC ACID, CALCIUM SALTS, LOW OVERBASE		17
3-Alky(C16-C18)oxy-N,N'-bis(2-hydroxyethyl)propan-1-amine (a)	ETHOXYLATED LONG CHAIN (C16+) ALKYOXYALKYLAMINE	17
ALLYL ALCOHOL		17
ALLYL CHLORIDE		17
ALUMINIUM CHLORIDE/HYDROGEN CHLORIDE SOLUTION		17
ALUMINIUM HYDROXIDE, SODIUM HYDROXIDE, SODIUM CARBONATE SOLUTION (40% OR LESS)		17

Index Name	Product Name	Chapter
Aluminium silicate hydroxide	KAOLIN SLURRY	18
ALUMINIUM SULPHATE SOLUTION		17
Aminoacetic acid, sodium salt solution	GLYCINE, SODIUM SALT SOLUTION	17
1-Amino-3-aminomethyl-3,5,5-trimethylcyclohexane	ISOPHORONEDIAMINE	17
Aminobenzene	ANILINE	17
1-Aminobutane (a)	BUTYLAMINE (ALL ISOMERS)	17
2-Aminobutane	BUTYLAMINE (ALL ISOMERS)	17
Aminocyclohexane	CYCLOHEXYLAMINE	17
Aminoethane	ETHYLAMINE	17
Aminoethane solutions, 72% or less	ETHYLAMINE SOLUTIONS (72% OR LESS)	17
2-Aminoethanol	ETHANOLAMINE	17
2-(2-AMINOETHOXY) ETHANOL		17
2-(2-Aminoethylamino)ethanol	AMINOETHYL ETHANOLAMINE	17
AMINOETHYLDIETHANOLAMINE/AMINOETHYLETHANOLAMINE SOLUTION		17
AMINOETHYL ETHANOLAMINE		17
N-(2-aminoethyl)ethylenediamine	DIETHYLENETRIAMINE	17
1-(2-Aminoethyl)piperazine	N-AMINOETHYLPIPERAZINE	17
N-AMINOETHYLPIPERAZINE		17
2-Aminoisobutane (a)	BUTYLAMINE (ALL ISOMERS)	17
Aminomethane solutions, 42% or less	METHYLAMINE SOLUTIONS (42% OR LESS)	17
1-Amino-2-methylbenzene	O-TOLUIDINE	17
2-Amino-1-methylbenzene	O-TOLUIDINE	17
2-AMINO-2-METHYL-1-PROPANOL		17
3-Aminomethyl-3,5,5-trimethylcyclohexylamine	ISOPHORONEDIAMINE	17
Aminophen	ANILINE	17
1-Aminopropane	N-PROPYLAMINE	17
2-Aminopropane	ISOPROPYLAMINE	17
2-Aminopropane (70% or less) solution	ISOPROPYLAMINE (70% OR LESS) SOLUTION	17
1-Amino-2-propanol	ISOPROPANOLAMINE	17
1-Aminopropan-2-ol	ISOPROPANOLAMINE	17
3-Aminopropan-1-ol	N-PROPANOLAMINE	17
2-Aminotoluene	O-TOLUIDINE	17
o-Aminotoluene	O-TOLUIDINE	17
5-Amino-1,3,3-trimethylcyclohexylmethylamine	ISOPHORONEDIAMINE	17
AMMONIA AQUEOUS (28% OR LESS)		17
Ammonia water, 28% or less	AMMONIA AQUEOUS (28% OR LESS)	17
AMMONIUM CHLORIDE SOLUTION (LESS THAN 25%) (*)		17
AMMONIUM HYDROGEN PHOSPHATE SOLUTION		17
Ammonium hydroxide, 28% or less	AMMONIA AQUEOUS (28% OR LESS)	17
AMMONIUM LIGNOSULPHONATE SOLUTIONS		17
AMMONIUM NITRATE SOLUTION (93% OR LESS) (*)		17
AMMONIUM POLYPHOSPHATE SOLUTION		17
AMMONIUM SULPHATE SOLUTION		17
AMMONIUM SULPHIDE SOLUTION (45% OR LESS) (*)		17

Index Name	Product Name	Chapter
AMMONIUM THIOSULPHATE SOLUTION (60% OR LESS)		17
AMYL ACETATE (ALL ISOMERS)		17
Amyl acetate, commercial (a)	AMYL ACETATE (ALL ISOMERS)	17
n-Amyl acetate (a)	AMYL ACETATE (ALL ISOMERS)	17
sec-Amyl acetate (a)	AMYL ACETATE (ALL ISOMERS)	17
Amylacetic ester (a)	AMYL ACETATE (ALL ISOMERS)	17
Amyl alcohol	N-AMYL ALCOHOL	17
N-AMYL ALCOHOL		17
AMYL ALCOHOL, PRIMARY		17
SEC-AMYL ALCOHOL		17
TERT-AMYL ALCOHOL		17
Amyl aldehyde	VALERALDEHYDE (ALL ISOMERS)	17
Amylcarbinol	HEXANOL	17
Amylene hydrate	TERT-AMYL ALCOHOL	17
TERT-AMYL ETHYL ETHER		17
Amyl ethyl ketone	ETHYL AMYL KETONE	17
TERT-AMYL METHYL ETHER		17
n-Amyl methyl ketone	METHYL AMYL KETONE	17
n-Amyl propionate	N-PENTYL PROPIONATE	17
Anaesthetic ether	DIETHYL ETHER (*)	17
ANILINE		17
Aniline oil	ANILINE	17
Anilinobenzene	DIPHENYLAMINE (MOLTEN)	17
Anthracene oil (coal tar fraction) (a)	COAL TAR	17
Ant oil, artificial	FURFURAL	17
APPLE JUICE		18
Aqua fortis	NITRIC ACID (70% AND OVER)	17
Argilla	KAOLIN SLURRY	18
ARYL POLYOLEFINS (C11-C50)		17
AVIATION ALKYLATES (C8 PARAFFINS AND ISO-PARAFFINS BPT 95 - 120°C)		17
Azacycloheptane	HEXAMETHYLENEIMINE	17
3-Azapentane-1,5-diamine	DIETHYLENTRIAMINE	17
Azepane	HEXAMETHYLENEIMINE	17
Azotic acid	NITRIC ACID (70% AND OVER)	17
BARIUM LONG CHAIN (C11-C50) ALKARYL SULPHONATE		17
Basic calcium alkyl salicylate in approximately 30% mineral oil (b)	CALCIUM LONG-CHAIN ALKYL SALICYLATE (C13+)	17
Battery acid	SULPHURIC ACID	17
Behenyl alcohol (a)	ALCOHOLS (C13+)	17
Benzenamine	ANILINE	17
1,4-Benzenedicarboxylic acid, bis(2-ethylhexyl) ester	BIS(2-ETHYLHEXYL) TEREPHTHALATE	17
1,4-Benzenedicarboxylic acid, butyl ester	DIBUTYL TEREPHTHALATE	17
1,2-Benzenedicarboxylic acid, diethyl ester	DIETHYL PHTHALATE	17
1,2-Benzenedicarboxylic acid, diundecyl ester	DIUNDECYL PHTHALATE	17
BENZENE AND MIXTURES HAVING 10% BENZENE OR MORE (I)		17

Index Name	Product Name	Chapter
BENZENE SULPHONYL CHLORIDE		17
BENZENESULPHONYL CHLORIDE	BENZENE SULPHONYL CHLORIDE	17
BENZENETRICARBOXYLIC ACID, TRIOCTYL ESTER		17
Benzenol	PHENOL	17
Benzol	BENZENE AND MIXTURES HAVING 10% BENZENE OR MORE (I)	17
Benzole	BENZENE AND MIXTURES HAVING 10% BENZENE OR MORE (I)	17
Benzophenol	PHENOL	17
2-Benzothiazolethiol, sodium salt solution	MERCAPTOBENZOTHIAZOL, SODIUM SALT SOLUTION	17
Benzothiazole-2-thiol, sodium salt solution	MERCAPTOBENZOTHIAZOL, SODIUM SALT SOLUTION	17
(2-Benzothiazolylthio) sodium solution	MERCAPTOBENZOTHIAZOL, SODIUM SALT SOLUTION	17
BENZYL ACETATE		17
BENZYL ALCOHOL		17
Benzyl butyl phthalate	BUTYL BENZYL PHTHALATE	17
BENZYL CHLORIDE		17
Betaprone	BETA-PROPIOLACTONE	17
Betula oil	METHYL SALICYLATE	17
Biformyl	GLYOXAL SOLUTION (40% OR LESS)	17
BIO-FUEL BLENDS OF DIESEL/GAS OIL AND FAME (>25% BUT <99% BY VOLUME)		17
BIO-FUEL BLENDS OF DIESEL/GAS OIL AND VEGETABLE OIL (>25% BUT <99% BY VOLUME)		17
BIO-FUEL BLENDS OF GASOLINE AND ETHYL ALCOHOL (>25% BUT <99% BY VOLUME)		17
Biphenyl	DIPHENYL	17
Bis(methylcyclopentadiene)	METHYLCYCLOPENTADIENE DIMER	17
2,5-Bis(alkyl(C7+)thio)-1,3,4-thiadiazole	ALKYL DITHIOTHIAZOLE (C6-C24)	17
Bis(2-aminoethyl)amine	DIETHYLENETRIAMINE	17
N,N'-Bis(2-aminoethyl)ethane-1,2-diamine	TRIETHYLENETETRAMINE	17
N,N'-Bis(2-aminoethyl)ethylenediamine	TRIETHYLENETETRAMINE	17
N,N-Bis(2-(bis(carboxymethyl)amino)ethyl)glycine, pentasodium salt solution	DIETHYLENETRIAMINEPENTAACETIC ACID, PENTASODIUM SALT SOLUTION	17
Bis(2-butoxyethyl) ether	DIETHYLENE GLYCOL DIBUTYL ETHER	17
N,N- Bis(carboxymethyl)glycine trisodium salt solution	NITRILOTRIACETIC ACID, TRISODIUM SALT SOLUTION	17
Bis(chloroethyl) ether	DICHLOROETHYL ETHER	17
Bis(2-chloroethyl) ether	DICHLOROETHYL ETHER	17
Bis (2-chloroisopropyl) ether	2,2'-DICHLOROISOPROPYL ETHER	17
Bis(2-chloro-1-methylethyl) ether	2,2'-DICHLOROISOPROPYL ETHER	17
Bis[2-(2,3-epoxypropoxy)phenyl]methane	DIGLYCIDYL ETHER OF BISPHENOL F	17
2,2-Bis[4-(2,3-epoxypropoxy)phenyl]propane	DIGLYCIDYL ETHER OF BISPHENOL A	17
Bis(2-ethoxyethyl) ether	DIETHYLENE GLYCOL DIETHYL ETHER	17
Bis(2-ethylhexyl) adipate	DI-(2-ETHYLHEXYL) ADIPATE	17
Bis (2-ethylhexyl)-1-4-benzenedicarboxylate	BIS(2-ETHYLHEXYL) TEREPHTHALATE	17
Bis(2-ethylhexyl) hydrogen phosphate	DI-(2-ETHYLHEXYL) PHOSPHORIC ACID	17
Bis(2-ethylhexyl) phthalate	DIOCTYL PHTHALATE	17

Index Name	Product Name	Chapter
BIS(2-ETHYLHEXYL) TEREPHTHALATE		17
Bis(2-hydroxyethyl)amine	DIETHANOLAMINE	17
Bis(2-hydroxyethyl)ammonium 2,4-dichlorophenoxyacetate solution	2,4-DICHLOROPHENOXYACETIC ACID, DIETHANOLAMINE SALT SOLUTION	17
Bis(2-hydroxyethyl) ether	DIETHYLENE GLYCOL	17
Bis(2-hydroxypropyl)amine	DIISOPROPANOLAMINE	17
Bis(6-methylheptyl) phthalate	DIOCTYL PHTHALATE	17
Blackstrap molasses (a)	MOLASSES	18
Blend of propoxylated polyether polyols with >10% additives	GLUCITOL/GLYCEROL BLEND PROPOXYLATED (CONTAINING 10% OR MORE AMINES)	17
Bolus alba	KAOLIN SLURRY	18
BRAKE FLUID BASE MIX: POLY(2-8)ALKYLENE (C2-C3) GLYCOLS/POLYALKYLENE (C2-C10) GLYCOLS MONOALKYL (C1-C4) ETHERS AND THEIR BORATE ESTERS		17
Bran oil	FURFURAL	17
BROMOCHLOROMETHANE		17
Butaldehyde (a)	BUTYRALDEHYDE (ALL ISOMERS)	17
Butanal (a)	BUTYRALDEHYDE (ALL ISOMERS)	17
n-Butanal (a)	BUTYRALDEHYDE (ALL ISOMERS)	17
1,3-Butanediol (a)	BUTYLENE GLYCOL	17
Butane-1,3-diol (a)	BUTYLENE GLYCOL	17
1,4-Butanediol (a)	BUTYLENE GLYCOL	17
Butane -1,4-diol (a)	BUTYLENE GLYCOL	17
2,3-Butanediol (a)	BUTYLENE GLYCOL	17
Butane-2,3-diol (a)	BUTYLENE GLYCOL	17
Butane, 2-ethoxy-2-methyl-ether	TERT-AMYL ETHYL ETHER	17
Butanoic acid	BUTYRIC ACID	17
Butanol	N-BUTYL ALCOHOL	18
1-Butanol	N-BUTYL ALCOHOL	18
Butanol-1	N-BUTYL ALCOHOL	18
Butan-1-ol	N-BUTYL ALCOHOL	18
2-Butanol	SEC-BUTYL ALCOHOL	18
Butan-2-ol	SEC-BUTYL ALCOHOL	18
Butanol acetate (a)	BUTYL ACETATE (ALL ISOMERS)	17
2-Butanol acetate (a)	BUTYL ACETATE (ALL ISOMERS)	17
1,4-Butanolide	GAMMA-BUTYROLACTONE	17
Butan-4-olide	GAMMA-BUTYROLACTONE	17
n-Butanol	N-BUTYL ALCOHOL	18
sec-Butanol	SEC-BUTYL ALCOHOL	18
tert-Butanol	TERT-BUTYL ALCOHOL	17
2-Butanone	METHYL ETHYL KETONE	17
Butan-2-one	METHYL ETHYL KETONE	17
2-Butenal	CROTONALDEHYDE	17
Butene dimer	OCTENE (ALL ISOMERS)	17
BUTENE OLIGOMER		17
1-Butoxybutane	N-BUTYL ETHER	17
2-Butoxyethanol (a)	ETHYLENE GLYCOL MONOALKYL ETHERS	17

Index Name	Product Name	Chapter
2-tert-butoxyethanol (a)	ETHYLENE GLYCOL MONOALKYL ETHERS	17
2-BUTOXYETHANOL (58%)/HYPERBRANCHED POLYESTERAMIDE (42%) (MIXTURE)		17
2-(2-Butoxyethoxy)ethanol (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL(C1-C6) ETHER	17
2-(2-Butoxyethoxy)ethyl acetate (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL (C1-C6) ETHER ACETATE	17
2-Butoxyethyl acetate	ETHYLENE GLYCOL BUTYL ETHER ACETATE	17
1-Butoxypropan-2-ol (a)	PROPYLENE GLYCOL MONOALKYL ETHER	17
Butyl acetate (a)	BUTYL ACETATE (ALL ISOMERS)	17
BUTYL ACETATE (ALL ISOMERS)		17
n-Butyl acetate (a)	BUTYL ACETATE (ALL ISOMERS)	17
sec-Butyl acetate (a)	BUTYL ACETATE (ALL ISOMERS)	17
tert-Butyl acetate (a)	BUTYL ACETATE (ALL ISOMERS)	17
BUTYL ACRYLATE (ALL ISOMERS)		17
n-Butyl acrylate (a)	BUTYL ACRYLATE (ALL ISOMERS)	17
Butyl alcohol	N-BUTYL ALCOHOL	18
N-BUTYL ALCOHOL		18
SEC-BUTYL ALCOHOL		18
TERT-BUTYL ALCOHOL		17
n-Butyl aldehyde (a)	BUTYRALDEHYDE (ALL ISOMERS)	17
BUTYLAMINE (ALL ISOMERS)		17
n-Butylamine (a)	BUTYLAMINE (ALL ISOMERS)	17
sec-Butylamine (a)	BUTYLAMINE (ALL ISOMERS)	17
tert-Butylamine (a)	BUTYLAMINE (ALL ISOMERS)	17
BUTYLBENZENE (ALL ISOMERS)		17
tert-Butylbenzene (a)	BUTYLBENZENE (ALL ISOMERS)	17
BUTYL BENZYL PHTHALATE		17
Butyl butanoate (a)	BUTYL BUTYRATE (ALL ISOMERS)	17
BUTYL BUTYRATE (ALL ISOMERS)		17
n-Butyl butyrate (a)	BUTYL BUTYRATE (ALL ISOMERS)	17
n-Butylcarbinol	N-AMYL ALCOHOL	17
Butyl carbitol (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL(C1-C6) ETHER	17
Butyl carbitol acetate (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL (C1-C6) ETHER ACETATE	17
Butyl cellosolve acetate	ETHYLENE GLYCOL BUTYL ETHER ACETATE	17
BUTYL/DECYL/CETYL/EICOSYL METHACRYLATE MIXTURE		17
Butyl/decyl/hexadecyl/icosyl methacrylate mixture (a)	BUTYL/DECYL/CETYL/EICOSYL METHACRYLATE MIXTURE	17
Butyl diglycol acetate (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL (C1-C6) ETHER ACETATE	17
BUTYLENE GLYCOL		17
alpha-Butylene glycol (a)	BUTYLENE GLYCOL	17
beta-Butylene glycol (a)	BUTYLENE GLYCOL	17
1,3-Butylene glycol, 3-methyl ether	3-METHOXY-1-BUTANOL	17
1,3-Butylene glycol, 3-methyl ether, 1-acetate	3-METHOXYBUTYL ACETATE	17

Index Name	Product Name	Chapter
Butylene oxide	TETRAHYDROFURAN	17
1,2-BUTYLENE OXIDE		17
Butyl ethanoate	BUTYL ACETATE (ALL ISOMERS)	17
Butyl ether	N-BUTYL ETHER	17
N-BUTYL ETHER		17
Butylethylacetic acid (a)	OCTANOIC ACID (ALL ISOMERS)	17
Butylethylene	HEXENE (ALL ISOMERS)	17
tert-Butyl ethyl ether	ETHYL TERT-BUTYL ETHER	17
iso-Butyl ketone	DIISOBUTYL KETONE	17
BUTYL METHACRYLATE		17
tert-Butyl methyl ether	METHYL TERT-BUTYL ETHER	17
Butyl methyl ketone	METHYL BUTYL KETONE	17
Butyl phthalate	DIBUTYL PHTHALATE	17
N-BUTYL PROPIONATE		17
BUTYRALDEHYDE (ALL ISOMERS)		17
n-Butyraldehyde	BUTYRALDEHYDE (ALL ISOMERS)	17
BUTYRIC ACID		17
n-Butyric acid	BUTYRIC ACID	17
Butyric alcohol	N-BUTYL ALCOHOL	18
Butyric aldehyde (a)	BUTYRALDEHYDE (ALL ISOMERS)	17
GAMMA-BUTYROLACTONE		17
Cajeputene	DIPENTENE	17
CALCIUM ALKARYL SULPHONATE (C11-C50)		17
Calcium alkyl(longchain) salicylate (overbased) in mineral oil (LOA) (b)	CALCIUM LONG-CHAIN ALKYL SALICYLATE (C13+)	17
CALCIUM ALKYL (C10-C28) SALICYLATE		17
Calcium bis(O-alkylsalicylate) (b)	CALCIUM LONG-CHAIN ALKYL SALICYLATE (C13+)	17
Calcium bromide / zinc bromide solution	DRILLING BRINES (CONTAINING ZINC CHLORIDE)	17
CALCIUM CARBONATE SLURRY		18
CALCIUM HYDROXIDE SLURRY		17
CALCIUM HYPOCHLORITE SOLUTION (15% OR LESS)		17
CALCIUM HYPOCHLORITE SOLUTION (MORE THAN 15%)		17
CALCIUM LIGNOSULPHONATE SOLUTIONS		17
CALCIUM LONG-CHAIN ALKYL (C5-C10) PHENATE		17
CALCIUM LONG-CHAIN ALKYL (C11-C40) PHENATE		17
CALCIUM LONG-CHAIN ALKYL PHENATE SULPHIDE (C8-C40)		17
CALCIUM LONG-CHAIN ALKYL SALICYLATE (C13+)		17
CALCIUM LONG-CHAIN ALKYL (C18-C28) SALICYLATE		17
CALCIUM NITRATE/MAGNESIUM NITRATE/POTASSIUM CHLORIDE SOLUTION		17
CALCIUM NITRATE SOLUTIONS (50% OR LESS)		17
CAMELINA OIL		17
Camelina Sativa Oil	CAMELINA OIL	17

Index Name	Product Name	Chapter
Camelina Sativa Seed Oil	CAMELINA OIL	17
Cane molasses (a)	MOLASSES	18
Canola oil	RAPESEED OIL (LOW ERUCIC ACID CONTAINING LESS THAN 4% FREE FATTY ACIDS)	17
Capric acid	DECANOIC ACID	17
Caproic acid	HEXANOIC ACID	17
Caprolactam	EPSILON-CAPROLACTAM (MOLTEN OR AQUEOUS SOLUTIONS)	17
EPSILON-CAPROLACTAM (MOLTEN OR AQUEOUS SOLUTIONS)		17
Caproyl alcohol	HEXANOL	17
Capryl alcohol (a)	OCTANOL (ALL ISOMERS)	17
Caprylic acid (a)	OCTANOIC ACID (ALL ISOMERS)	17
Caprylyl acetate	N-OCTYL ACETATE	17
Carbamide solution	UREA SOLUTION	17
Carbinol	METHYL ALCOHOL (*)	17
Carbitol acetate (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL (C1-C6) ETHER ACETATE	17
Carbitol solvent (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL(C1-C6) ETHER	17
Carbolic acid	PHENOL	17
CARBOLIC OIL		17
Carbon bisulphide	CARBON DISULPHIDE	17
CARBON DISULPHIDE		17
CARBON TETRACHLORIDE		17
Carbonyldiamide solution	UREA SOLUTION	17
Carbonyldiamine solution	UREA SOLUTION	17
Carboxyethyliminobis(ethylenenitrilo)tetraacetic acid, pentasodium salt solution	DIETHYLENETRIAMINEPENTAACETIC ACID, PENTASODIUM SALT SOLUTION	17
CASHEW NUT SHELL OIL (UNTREATED)		17
CASTOR OIL		17
Caustic potash solution	POTASSIUM HYDROXIDE SOLUTION (*)	17
Caustic soda	SODIUM HYDROXIDE SOLUTION (*)	17
Caustic soda solution	SODIUM HYDROXIDE SOLUTION (*)	17
Cellosolve acetate	2-ETHOXYETHYL ACETATE	17
Cesium formate solution	CESIUM FORMATE SOLUTION (*)	17
CESIUM FORMATE SOLUTION (*)		17
CETYL/EICOSYL METHACRYLATE MIXTURE		17
Cetyl / stearyl alcohol (a)	ALCOHOLS (C13+)	17
China clay	KAOLIN SLURRY	18
CHLORINATED PARAFFINS (C10-C13)		17
CHLORINATED PARAFFINS (C14-C17) (WITH 50% CHLORINE OR MORE, AND LESS THAN 1% C13 OR SHORTER CHAINS)		17
CHLOROACETIC ACID (80% OR LESS)		17
alpha-Chloroallyl chloride	1,3-DICHLOROPROPENE	17
Chloroallylene	ALLYL CHLORIDE	17
CHLOROBENZENE		17

Index Name	Product Name	Chapter
Chlorobenzol	CHLOROBENZENE	17
Chlorobromomethane	BROMOCHLOROMETHANE	17
1-Chloro-2-(beta-chloroethoxy)ethane	DICHLOROETHYL ETHER	17
1-Chloro-2,3-epoxypropane	EPICHLOROHYDRIN	17
2-Chloroethanol	ETHYLENE CHLOROXYDRIN	17
2-Chloro-N-ethoxymethyl-6'-ethylacet-o-toluidide	ACETOCHLOR	17
2-Chloro-N-(ethoxymethyl)-N-(2-ethyl-6-methylphenyl)acetamide	ACETOCHLOR	17
2-Chloroethyl alcohol	ETHYLENE CHLOROXYDRIN	17
beta-Chloroethyl alcohol	ETHYLENE CHLOROXYDRIN	17
Chloroethyl ether	DICHLOROETHYL ETHER	17
2-Chloro-6'-ethyl-N-(2-methoxy-1-methylethyl)acet-o-toluidide	N-(2-METHOXY-1-METHYL ETHYL)-2-ETHYL-6-METHYL CHLOROACETANILIDE	17
2-Chloro-N-(2-ethyl-6-methylphenyl)-N-(2-methoxy-1-methylethyl)acetamide	N-(2-METHOXY-1-METHYL ETHYL)-2-ETHYL-6-METHYL CHLOROACETANILIDE	17
CHLOROFORM		17
CHLOROXYDRINS (CRUDE)		17
m-Chloromethylbenzene	M-CHLOROTOLUENE	17
o-Chloromethylbenzene	O-CHLOROTOLUENE	17
p-Chloromethylbenzene	P-CHLOROTOLUENE	17
(Chloromethyl)ethylene oxide	EPICHLOROXYDRIN	17
(2-Chloro-1-methylethyl) ether	2,2'-DICHLOROISOPROPYL ETHER	17
2-Chloro-1-methylethyl ether	2,2'-DICHLOROISOPROPYL ETHER	17
Chloromethyloxirane	EPICHLOROXYDRIN	17
4-CHLORO-2-METHYLPHENOXYACETIC ACID, DIMETHYLAMINE SALT SOLUTION		17
1-Chloro-2-nitrobenzene	O-CHLORONITROBENZENE	17
O-CHLORONITROBENZENE		17
1-(4-CHLOROPHENYL)-4,4- DIMETHYL-PENTAN-3-ONE		17
2- or 3- Chloropropanoic acid	2- OR 3-CHLOROPROPIONIC ACID	17
3-Chloropropene	ALLYL CHLORIDE	17
2- OR 3-CHLOROPROPIONIC ACID		17
alpha- or beta- Chloropropionic acid	2- OR 3-CHLOROPROPIONIC ACID	17
3-Chloropropylene	ALLYL CHLORIDE	17
alpha-Chloropropylene	ALLYL CHLORIDE	17
Chloropropylene oxide	EPICHLOROXYDRIN	17
CHLOROSULPHONIC ACID		17
Chlorosulphuric acid	CHLOROSULPHONIC ACID	17
3-Chlorotoluene	M-CHLOROTOLUENE	17
4-Chlorotoluene	P-CHLOROTOLUENE	17
alpha-Chlorotoluene	BENZYL CHLORIDE	17
M-CHLOROTOLUENE		17
O-CHLOROTOLUENE		17
P-CHLOROTOLUENE		17
CHLOROTOLUENES (MIXED ISOMERS)		17
CHOLINE CHLORIDE SOLUTIONS		17
Cinene	DIPENTENE	17
Cinnamene	STYRENE MONOMER	17

Index Name	Product Name	Chapter
Cinnamol	STYRENE MONOMER	17
cis-Butenedioic anhydride	MALEIC ANHYDRIDE	17
cis-9-Octadecenoic acid	OLEIC ACID	17
CITRIC ACID (70% OR LESS)		17
CLAY SLURRY		18
COAL SLURRY		18
COAL TAR		17
Coal tar distillate	COAL TAR NAPHTHA SOLVENT	17
COAL TAR NAPHTHA SOLVENT		17
COAL TAR PITCH (MOLTEN) (*)		17
COCOA BUTTER		17
COCONUT OIL		17
COCONUT OIL FATTY ACID		17
COCONUT OIL FATTY ACID METHYL ESTER		17
Colamine	ETHANOLAMINE	17
Cold pressed grape seed oil	GRAPE SEED OIL	17
Cologne spirits	ETHYL ALCOHOL	18
Colonial spirit	METHYL ALCOHOL (*)	17
Colophony	ROSIN	17
Columbian spirit	METHYL ALCOHOL (*)	17
Columbian spirits	METHYL ALCOHOL (*)	17
COPPER SALT OF LONG CHAIN (C17+) ALKANOIC ACID		17
CORN OIL		17
COTTON SEED OIL		17
CREOSOTE (COAL TAR)		17
CRESOL/PHENOL/XYLENOL MIXTURE		17
CRESOLS (ALL ISOMERS)		17
CRESYLIC ACID, DEPHENOLIZED		17
Cresylic acids	CRESOLS (ALL ISOMERS)	17
CRESYLIC ACID, SODIUM SALT SOLUTION		17
Cresylols	CRESOLS (ALL ISOMERS)	17
CROTONALDEHYDE		17
Crotonic aldehyde	CROTONALDEHYDE	17
Crude grape seed oil	GRAPE SEED OIL	17
CTMP (Chemi Thermo Mechanical Pulp) concentrate	WOOD LIGNIN WITH SODIUM ACETATE/OXALATE	17
Cumene (a)	PROPYLBENZENE (ALL ISOMERS)	17
Cumol (a)	PROPYLBENZENE (ALL ISOMERS)	17
Cyanoethylene	ACRYLONITRILE	17
2-Cyanopropan-2-ol	ACETONE CYANOHYDRIN	17
2-Cyano-2-propanol	ACETONE CYANOHYDRIN	17
2-cyanopropene-1	METHACRYLONITRILE	17
Cyclic propylene carbonate	PROPYLENE CARBONATE	17
1,5,9-CYCLODODECATRIENE		17

Index Name	Product Name	Chapter
CYCLOHEPTANE		17
Cyclohexamethylenimine	HEXAMETHYLENEIMINE	17
CYCLOHEXANE		17
CYCLOHEXANE-1,2-DICARBOXYLIC ACID, DIISONONYL ESTER		17
Cyclohexane1,2-Di-Isononyldicarboxylate	CYCLOHEXANE-1,2-DICARBOXYLIC ACID, DIISONONYL ESTER	17
CYCLOHEXANE OXIDATION PRODUCTS, SODIUM SALTS SOLUTION		17
Cyclohexane, oxidized, aqueous extraction, sodium salt	CYCLOHEXANE OXIDATION PRODUCTS, SODIUM SALTS SOLUTION	17
CYCLOHEXANOL		17
CYCLOHEXANONE		17
CYCLOHEXANONE, CYCLOHEXANOL MIXTURE		17
Cyclohexatriene	BENZENE AND MIXTURES HAVING 10% BENZENE OR MORE (I)	17
CYCLOHEXYL ACETATE		17
CYCLOHEXYLAMINE		17
Cyclohexyldimethylamine	N,N-DIMETHYLCYCLOHEXYLAMINE	17
Cyclohexyl(ethyl)amine	N-ETHYLCYCLOHEXYLAMINE	17
Cyclohexyl(ethyl)amine	N-ETHYLCYCLOHEXYLAMINE	17
Cyclohexyl ketone	CYCLOHEXANONE	17
Cyclohexylmethane	METHYLCYCLOHEXANE	17
1,3-CYCLOPENTADIENE DIMER (MOLTEN)		17
CYCLOPENTANE		17
CYCLOPENTENE		17
Cyclotetramethylene oxide	TETRAHYDROFURAN	17
P-CYMENE		17
Cymol	P-CYMENE	17
Dalapon (ISO)	2,2-DICHLOROPROPIONIC ACID	17
DCDP	DICYCLOPENTADIENE, RESIN GRADE, 81-89%	17
Deanol	DIMETHYLETHANOLAMINE	17
DECAHYDRONAPHTHALENE		17
DECANOIC ACID		17
Decan-1-ol	DECYL ALCOHOL (ALL ISOMERS)	17
n-Decanol	DECYL ALCOHOL (ALL ISOMERS)	17
Decatoic acid	DECANOIC ACID	17
DECENE		17
Decoic acid	DECANOIC ACID	17
DECYL ACRYLATE		17
Decyl alcohol	DECYL ALCOHOL (ALL ISOMERS)	17
DECYL ALCOHOL (ALL ISOMERS)		17
Decylbenzene (a)	ALKYL(C9+)BENZENES	17
DECYL/DODECYL/TETRADECYL ALCOHOL MIXTURE		17
Decylic acid	DECANOIC ACID	17
Decyl octyl adipate	OCTYL DECYL ADIPATE	17

Index Name	Product Name	Chapter
DECYLOXYTETRAHYDROTHIOPHENE DIOXIDE		17
Degummed grape seed oil	GRAPE SEED OIL	17
1-Deoxy-1-methylamino-D-glucitol solution (70% or less)	N-METHYLGLUCAMINE SOLUTION (70% OR LESS)	17
Detergent alkylate	ALKYL(C9+)BENZENES	17
Diacetic ester	ETHYL ACETOACETATE	17
Diacetone	DIACETONE ALCOHOL	17
DIACETONE ALCOHOL		17
Di[alkyl/alkenyl(C10-C20)] hydrogen phosphite (a)	ALKYL (C10-C20, SATURATED AND UNSATURATED) PHOSPHITE	17
DIALKYL (C8-C9) DIPHENYLAMINES		17
DIALKYL (C7-C13) PHTHALATES		17
DIALKYL (C9 - C10) PHTHALATES		17
DIALKYL THIOPHOSPHATES SODIUM SALTS SOLUTION		17
1,2-Diaminoethane	ETHYLENEDIAMINE	17
1,6-Diaminohexane	HEXAMETHYLENEDIAMINE (MOLTEN)	17
1,6-Diaminohexane solutions	HEXAMETHYLENEDIAMINE SOLUTION	17
2,6-Diaminohexanoic acid	L-LYSINE SOLUTION (60% OR LESS)	17
2,6-DIAMINOHEXANOIC ACID PHOSPHONATE MIXED SALTS SOLUTION		17
Diaminotoluene (a)	TOLUENEDIAMINE	17
2,4-Diaminotoluene (a)	TOLUENEDIAMINE	17
2,6-Diaminotoluene (a)	TOLUENEDIAMINE	17
3,6-Diazaoctane-1,8-diamine	TRIETHYLENETETRAMINE	17
1,2-Dibromoethane	ETHYLENE DIBROMIDE	17
DIBROMOMETHANE		17
2,2'-Dibutoxyethyl ether	DIETHYLENE GLYCOL DIBUTYL ETHER	17
DIBUTYLAMINE		17
Dibutylbenzene-1,2-dicarboxylate	DIBUTYL PHTHALATE	17
Dibutyl carbinol (a)	NONYL ALCOHOL (ALL ISOMERS)	17
Dibutyl ether	N-BUTYL ETHER	17
n-Dibutyl ether	N-BUTYL ETHER	17
Dibutyl hydrogen phosphite	DIBUTYL HYDROGEN PHOSPHONATE	17
DIBUTYL HYDROGEN PHOSPHONATE		17
2,6-DI-TERT-BUTYLPHENOL		17
Dibutyl phosphonate	DIBUTYL HYDROGEN PHOSPHONATE	17
DIBUTYL PHTHALATE		17
Dibutyl ortho-phthalate	DIBUTYL PHTHALATE	17
DIBUTYL TEREPHTHALATE		17
DICHLOROBENZENE (ALL ISOMERS)		17
1,2-Dichlorobenzene (a)	DICHLOROBENZENE (ALL ISOMERS)	17
m-Dichlorobenzene (a)	DICHLOROBENZENE (ALL ISOMERS)	17
o-Dichlorobenzene (a)	DICHLOROBENZENE (ALL ISOMERS)	17
3,4-Dichlorobut-1-ene	3,4-DICHLORO-1-BUTENE	17
3,4-DICHLORO-1-BUTENE		17
2,2'-Dichlorodiethyl ether	DICHLOROETHYL ETHER	17

Index Name	Product Name	Chapter
Dichlorodiisopropyl ether	2,2'-DICHLOROISOPROPYL ETHER	17
1,1-DICHLOROETHANE		17
1,2-Dichloroethane	ETHYLENE DICHLORIDE	17
1,1-Dichloroethene	VINYLDENE CHLORIDE	17
Dichloroether	DICHLOROETHYL ETHER	17
1,1-Dichloroethylene	VINYLDENE CHLORIDE	17
DICHLOROETHYL ETHER		17
2,2'-Dichloroethyl ether	DICHLOROETHYL ETHER	17
Dichloroethyl oxide	DICHLOROETHYL ETHER	17
1,6-DICHLOROHEXANE		17
2,2'-DICHLOROISOPROPYL ETHER		17
DICHLOROMETHANE		17
2,4-DICHLOROPHENOL		17
2,4-DICHLOROPHENOXYACETIC ACID, DIETHANOLAMINE SALT SOLUTION		17
2,4-DICHLOROPHENOXYACETIC ACID, DIMETHYLAMINE SALT SOLUTION (70% OR LESS)		17
2,4-DICHLOROPHENOXYACETIC ACID, TRIISOPROPANOLAMINE SALT SOLUTION		17
1,1-DICHLOROPROPANE		17
1,2-DICHLOROPROPANE		17
Dichloropropane / dichloropropene mixtures	DICHLOROPROPENE/DICHLOROPROPANE MIXTURES	17
2,2-Dichloropropanoic acid	2,2-DICHLOROPROPIONIC ACID	17
1,3-DICHLOROPROPENE		17
DICHLOROPROPENE/DICHLOROPROPANE MIXTURES		17
2,2-DICHLOROPROPIONIC ACID		17
Dichloropropylene	1,3-DICHLOROPROPENE	17
1,4-Dicyanobutane	ADIPONITRILE	17
Dicyclopentadiene	1,3-CYCLOPENTADIENE DIMER (MOLTEN)	17
DICYCLOPENTADIENE, RESIN GRADE, 81-89%		17
Didecyl phthalate (a)	DIALKYL (C7-C13) PHTHALATES	17
Didodecyl phthalate (a)	DIALKYL (C7-C13) PHTHALATES	17
DIETHANOLAMINE		17
DIETHYLAMINE		17
DIETHYLAMINOETHANOL		17
2-Diethylaminoethanol	DIETHYLAMINOETHANOL	17
2,6-DIETHYLANILINE		17
DIETHYLBENZENE		17
Diethyl 'carbitol'	DIETHYLENE GLYCOL DIETHYL ETHER	17
Diethylene dioxide	1,4-DIOXANE	17
1,4-Diethylene dioxide	1,4-DIOXANE	17
Diethylene ether	1,4-DIOXANE	17
DIETHYLENE GLYCOL		17
Diethylene glycol butyl ether (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL(C1-C6) ETHER	17

Index Name	Product Name	Chapter
Diethylene glycol butyl ether acetate (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL (C1-C6) ETHER ACETATE	17
DIETHYLENE GLYCOL DIBUTYL ETHER		17
DIETHYLENE GLYCOL DIETHYL ETHER		17
Diethylene glycol ethyl ether (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL(C1-C6) ETHER	17
Diethylene glycol ethyl ether acetate (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL (C1-C6) ETHER ACETATE	17
Diethylene glycol methyl ether (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL(C1-C6) ETHER	17
Diethylene glycol methyl ether acetate (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL (C1-C6) ETHER ACETATE	17
Diethylene glycol monobutyl ether (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL(C1-C6) ETHER	17
Diethylene glycol monobutyl ether acetate (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL (C1-C6) ETHER ACETATE	17
Diethylene glycol monoethyl ether (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL(C1-C6) ETHER	17
Diethylene glycol monoethyl ether acetate (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL (C1-C6) ETHER ACETATE	17
Diethylene glycol monomethyl ether (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL(C1-C6) ETHER	17
Diethylene glycol monomethyl ether acetate (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL (C1-C6) ETHER ACETATE	17
DIETHYLENE GLYCOL PHTHALATE		17
DIETHYLENETRIAMINE		17
DIETHYLENETRIAMINEPENTAACETIC ACID, PENTASODIUM SALT SOLUTION		17
N,N-Diethylethanamine	TRIETHYLAMINE	17
N,N-Diethylethanolamine	DIETHYLAMINOETHANOL	17
DIETHYL ETHER (*)		17
DI-(2-ETHYLHEXYL) ADIPATE		17
DI-(2-ETHYLHEXYL) PHOSPHORIC ACID		17
Di (2-ethylhexyl) Terephthalate	BIS(2-ETHYLHEXYL) TEREPHTHALATE	17
Diethyl oxide	DIETHYL ETHER (*)	17
DIETHYL PHTHALATE		17
DIETHYL SULPHATE		17
Diformyl	GLYOXAL SOLUTION (40% OR LESS)	17
DIGLYCIDYL ETHER OF BISPHENOL A		17
DIGLYCIDYL ETHER OF BISPHENOL F		17
Diglycol	DIETHYLENE GLYCOL	17
Diglycolamine	2-(2-AMINOETHOXY) ETHANOL	17
Diglycol phthalate	DIETHYLENE GLYCOL PHTHALATE	17
DIHEPTYL PHTHALATE		17
DI-N-HEXYL ADIPATE		17
DIHEXYL PHTHALATE		17
1,3-Dihydroisobenzofuran-1,3-dione (molten)	PHTHALIC ANHYDRIDE (MOLTEN)	17
2,3-Dihydroxybutane (a)	BUTYLENE GLYCOL	17
2,2'-Dihydroxydiethylamine	DIETHANOLAMINE	17
Di-(2-hydroxyethyl)amine	DIETHANOLAMINE	17

Index Name	Product Name	Chapter
Dihydroxyethyl ether	DIETHYLENE GLYCOL	17
1,6-Dihydroxyhexane	HEXAMETHYLENE GLYCOL	17
1,2-Dihydroxypropane	PROPYLENE GLYCOL	18
Diisobutene	DIISOBUTYLENE	17
DIISOBUTYLAMINE		17
Diisobutylcarbinol (a)	NONYL ALCOHOL (ALL ISOMERS)	17
DIISOBUTYLENE		17
alpha-Diisobutylene (a)	DIISOBUTYLENE	17
beta-Diisobutylene (a)	DIISOBUTYLENE	17
DIISOBUTYL KETONE		17
DIISOBUTYL PHTHALATE		17
2,4-diisocyanato-1-methylbenzene	TOLUENE DIISOCYANATE	17
2,4-Diisocyanatotoluene	TOLUENE DIISOCYANATE	17
Diisodecyl phthalate (a)	DIALKYL (C7-C13) PHTHALATES	17
DIISONONYL ADIPATE		17
Diisononyl phthalate (a)	DIALKYL (C7-C13) PHTHALATES	17
DIISOCTYL PHTHALATE		17
DIISOPROPANOLAMINE		17
DIISOPROPYLAMINE		17
DIISOPROPYLBENZENE (ALL ISOMERS)		17
Diisopropyl ether	ISOPROPYL ETHER	17
DIISOPROPYLNAPHTHALENE		17
Diisopropyl oxide	ISOPROPYL ETHER	17
N,N-DIMETHYLACETAMIDE		17
N,N-DIMETHYLACETAMIDE SOLUTION (40% OR LESS)		17
Dimethylacetylene carbinol	2-METHYL-2-HYDROXY-3-BUTYNE	17
DIMETHYL ADIPATE		17
DIMETHYLAMINE SOLUTION (45% OR LESS)		17
DIMETHYLAMINE SOLUTION (GREATER THAN 45% BUT NOT GREATER THAN 55%)		17
DIMETHYLAMINE SOLUTION (GREATER THAN 55% BUT NOT GREATER THAN 65%)		17
Dimethylaminoethanol	DIMETHYLETHANOLAMINE	17
2-(Dimethylamino)ethanol	DIMETHYLETHANOLAMINE	17
Dimethylbenzenes	XYLENES	17
1,3-Dimethylbutanol	METHYLAMYL ALCOHOL	17
1,3-Dimethylbutan-1-ol	METHYLAMYL ALCOHOL	17
1,3-Dimethylbutyl acetate (a)	METHYLAMYL ACETATE	17
Dimethylcarbinol	ISOPROPYL ALCOHOL	18
N,N-DIMETHYLCYCLOHEXYLAMINE		17
DIMETHYL DISULPHIDE		17
N,N-Dimethyldodecanamine	N,N-DIMETHYLDODECYLAMINE	17
N,N-Dimethyldodecan-1-amine	N,N-DIMETHYLDODECYLAMINE	17
N,N-DIMETHYLDODECYLAMINE		17
1,1-Dimethylethanol	TERT-BUTYL ALCOHOL	17

Index Name	Product Name	Chapter
DIMETHYLETHANOLAMINE		17
1,1-Dimethylethyl alcohol	TERT-BUTYL ALCOHOL	17
Dimethyl ethyl carbinol	TERT-AMYL ALCOHOL	17
1,1-dimethylethyl methyl ether	METHYL TERT-BUTYL ETHER	17
Dimethylformaldehyde	ACETONE	18
DIMETHYLFORMAMIDE		17
DIMETHYL GLUTARATE		17
2,6-Dimethyl-4-heptanone	DIISOBUTYL KETONE	17
2,6-Dimethylheptan-4-one	DIISOBUTYL KETONE	17
N,N-Dimethylhexanamine (a)	ALKYL (C12+) DIMETHYLAMINE	17
DIMETHYL HYDROGEN PHOSPHITE		17
Dimethylhydroxybenzenes (all isomers)	XYLENOL	17
1,1'-Dimethyl-2,2'-iminodiethanol	DIISOPROPANOLAMINE	17
Dimethyl ketal	ACETONE	18
Dimethyl ketone	ACETONE	18
N,N-dimethylaurylamine	N,N-DIMETHYLDODECYLAMINE	17
N,N-Dimethylmethanamine solution (30% or less)	TRIMETHYLAMINE SOLUTION (30% OR LESS)	17
6,6-Dimethyl-2-methylenebicyclo[3.1.1]heptane	BETA-PINENE	17
DIMETHYL OCTANOIC ACID		17
2,2-Dimethyloctanoic acid (a)	NEODECANOIC ACID	17
2,3-Dimethylphenol (a)	XYLENOL	17
2,4-Dimethylphenol (a)	XYLENOL	17
2,5-Dimethylphenol (a)	XYLENOL	17
2,6-Dimethylphenol (a)	XYLENOL	17
3,4-Dimethylphenol (a)	XYLENOL	17
3,5-Dimethylphenol (a)	XYLENOL	17
Dimethylphenols	XYLENOL	17
Dimethylphenyl phosphate (3:1) (all isomers)	TRIXYLYL PHOSPHATE	17
DIMETHYL PHTHALATE		17
DIMETHYLPOLYSILOXANE		17
2,2-Dimethylpropane (a)	PENTANE (ALL ISOMERS)	17
2,2-DIMETHYLPROPANE-1,3-DIOL (MOLTEN OR SOLUTION)		17
2,2-Dimethylpropanoic acid	TRIMETHYLACETIC ACID	17
1,1-Dimethylpropargyl alcohol	2-METHYL-2-HYDROXY-3-BUTYNE	17
2,2-Dimethylpropionic acid	TRIMETHYLACETIC ACID	17
1,1-Dimethylpropyl ethyl ether	TERT-AMYL ETHYL ETHER	17
1,1-Dimethylpropynol	2-METHYL-2-HYDROXY-3-BUTYNE	17
DIMETHYL SUCCINATE		17
N,N-Dimethyltetradecanamine (a)	ALKYL (C12+) DIMETHYLAMINE	17
Dimethyl(tetradecyl)amine (a)	ALKYL (C12+) DIMETHYLAMINE	17
3,9-Dimethyltricyclo[5.2.1.0 ^{2,6}]deca-3,9-diene	METHYLCYCLOPENTADIENE DIMER	17
Dimethyltrimethylene glycol	2,2-DIMETHYLPROPANE-1,3-DIOL (MOLTEN OR SOLUTION)	17
DINITROTOLUENE (MOLTEN)		17
DINONYL PHTHALATE		17
Dinonyl phthalate (a)	DIALKYL (C7-C13) PHTHALATES	17

Index Name	Product Name	Chapter
3,6-Dioxaoctane-1,8-diol	TRIETHYLENE GLYCOL	18
Diocetyl adipate	DI-(2-ETHYLHEXYL) ADIPATE	17
Diocetyl hydrogen phosphate	DI-(2-ETHYLHEXYL) PHOSPHORIC ACID	17
Diocetyl phosphoric acid	DI-(2-ETHYLHEXYL) PHOSPHORIC ACID	17
DIOCTYL PHTHALATE		17
Diocetyl terephthalate	BIS(2-ETHYLHEXYL) TEREPHTHALATE	17
2,4-D-diolamine	2,4-DICHLOROPHOXYACETIC ACID, DIETHANOLAMINE SALT SOLUTION	17
1,4-Dioxan	1,4-DIOXANE	17
1,4-DIOXANE		17
1,3-Dioxolan-2-one	ETHYLENE CARBONATE	17
Dioxolone-2	ETHYLENE CARBONATE	17
1,1-Dioxothiolan	SULPHOLANE	17
Dioxyethylene ether	1,4-DIOXANE	17
DIPENTENE		17
DIPHENYL		17
DIPHENYLAMINE (MOLTEN)		17
DIPHENYLAMINE, REACTION PRODUCT WITH 2,2,4-TRIMETHYLPENTENE		17
DIPHENYLAMINES, ALKYLATED		17
DIPHENYL/DIPHENYL ETHER MIXTURES		17
Diphenyl/diphenyl oxide mixtures	DIPHENYL/DIPHENYL ETHER MIXTURES	17
Diphenyl dodecyl ether disulphonate solution	DODECYL DIPHENYL ETHER DISULPHONATE SOLUTION	17
Diphenyl dodecyl oxide disulphonate solution	DODECYL DIPHENYL ETHER DISULPHONATE SOLUTION	17
DIPHENYL ETHER		17
DIPHENYL ETHER/DIPHENYL PHENYL ETHER MIXTURE		17
DIPHENYLMETHANE DIISOCYANATE		17
DIPHENYLOL PROPANE-EPICHLOROHYDRIN RESINS		17
Diphenyl oxide	DIPHENYL ETHER	17
Diphenyl oxide / diphenyl phenyl ether mixture	DIPHENYL ETHER/DIPHENYL PHENYL ETHER MIXTURE	17
Dipropylamine	DI-N-PROPYLAMINE	17
n-Dipropylamine	DI-N-PROPYLAMINE	17
DI-N-PROPYLAMINE		17
DIPROPYLENE GLYCOL		17
Dipropylene glycol methyl ether (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL(C1-C6) ETHER	17
Dipropylene glycol monomethyl ether (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL(C1-C6) ETHER	17
Disodium carbonate solution	SODIUM CARBONATE SOLUTION (*)	17
Distillates (Petroleum), Steam Cracked, C8 - C12 Fraction (a)	RESIN OIL, DISTILLED	17
DITHIOCARBAMATE ESTER (C7-C35)		17
DITRIDECYL ADIPATE		17
DITRIDECYL PHTHALATE		17
DIUNDECYL PHTHALATE		17

Index Name	Product Name	Chapter
dl-Lactic acid	LACTIC ACID	17
dl-p-Mentha-1,8-diene	DIPENTENE	17
1-Docosanol (a)	ALCOHOLS (C13+)	17
Docosan-1-ol (a)	ALCOHOLS (C13+)	17
DODECANE (ALL ISOMERS)		17
1-Dodecanethiol	N-DODECYL MERCAPTAN	17
TERT-DODECANETHIOL		17
Dodecanoic acid	LAURIC ACID	17
1-Dodecanol	DODECYL ALCOHOL	17
Dodecan-1-ol	DODECYL ALCOHOL	17
n-Dodecanol	DODECYL ALCOHOL	17
DODECENE (ALL ISOMERS)		17
1-DODECENE		17
Dodec-1-ene	1-DODECENE	17
DODECYL ALCOHOL		17
n-Dodecyl alcohol	DODECYL ALCOHOL	17
DODECYLAMINE/TETRADECYLAMINE MIXTURE		17
DODECYLBENZENE		17
Dodecylbenzenesulphonic acid (contains 1.5% sulphuric acid)	ALKYL (C11-C17) BENZENE SULPHONIC ACID	17
Dodecyl dimethylamine	N,N-DIMETHYLDODECYLAMINE	17
DODECYL DIPHENYL ETHER DISULPHONATE SOLUTION		17
Dodecyl diphenyl oxide disulphonate solution	DODECYL DIPHENYL ETHER DISULPHONATE SOLUTION	17
Dodecylene	DODECENE (ALL ISOMERS)	17
DODECYL HYDROXYPROPYL SULPHIDE		17
Dodecylic acid	LAURIC ACID	17
N-DODECYL MERCAPTAN		17
tert-Dodecyl mercaptan	TERT-DODECANETHIOL	17
DODECYL METHACRYLATE		17
Dodecyl 2-methylprop-2-enoate	DODECYL METHACRYLATE	17
Dodecyl-2-methyl-2-propenoate	DODECYL METHACRYLATE	17
DODECYL/OCTADECYL METHACRYLATE MIXTURE		17
DODECYL/PENTADECYL METHACRYLATE MIXTURE		17
DODECYL PHENOL		17
Dodecyl, Tetradecyl, hexadecyl-dimethylamine mixture	ALKYL (C12+) DIMETHYLAMINE	17
2-Dodecylthio-1-methylethanol	DODECYL HYDROXYPROPYL SULPHIDE	17
1-(Dodecylthio)propan-2-ol	DODECYL HYDROXYPROPYL SULPHIDE	17
DODECYL XYLENE		17
Drilling brine: potassium chloride solution	POTASSIUM CHLORIDE SOLUTION	17
DRILLING BRINES (CONTAINING CALCIUM BROMIDE)		17
DRILLING BRINES (CONTAINING ZINC CHLORIDE)		17
(E)-But-2-enal	CROTONALDEHYDE	17
Enanthic acid	N-HEPTANOIC ACID	17
Enanthylic acid	N-HEPTANOIC ACID	17

Index Name	Product Name	Chapter
Engravers' acid	NITRIC ACID (70% AND OVER)	17
EPOCHLOROHYDRIN		17
1,2-Epoxybutane	1,2-BUTYLENE OXIDE	17
1,4-epoxybutane	TETRAHYDROFURAN	17
1,2-Epoxypropane	PROPYLENE OXIDE	17
2,3-Epoxypropyl ester of mixed C10 trialkylacetic acids	GLYCIDYL ESTER OF C10 TRIALKYLACETIC ACID	17
2,3-Epoxypropyl neodecanoate	GLYCIDYL ESTER OF C10 TRIALKYLACETIC ACID	17
EPTC	S-ETHYL DIPROPYLTHIOCARBAMATE	17
Essence of Mirbane	NITROBENZENE	17
Essence of Myrbane	NITROBENZENE	17
Ethanamine solutions, 72% or less	ETHYLAMINE SOLUTIONS (72% OR LESS)	17
Ethancarbonitrile	PROPIONITRILE	17
Ethanedial	GLYOXAL SOLUTION (40% OR LESS)	17
1,2-Ethanediol	ETHYLENE GLYCOL	17
Ethanoic acid	ACETIC ACID	17
Ethanoic anhydride	ACETIC ANHYDRIDE	17
Ethanol	ETHYL ALCOHOL	18
ETHANOLAMINE		17
ethenyl acetate	VINYL ACETATE	17
ethenyl ethanoate	VINYL ACETATE	17
Ether	DIETHYL ETHER (*)	17
Ethynyl trichloride	TRICHLOROETHYLENE	17
2-Ethoxyethanol (a)	ETHYLENE GLYCOL MONOALKYL ETHERS	17
2-(2-Ethoxyethoxy)ethanol (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL(C1-C6) ETHER	17
2-(2-Ethoxyethoxy)ethyl acetate (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL(C1-C6) ETHER ACETATE	17
2-ETHOXYETHYL ACETATE		17
ETHOXYLATED LONG CHAIN (C16+) ALKYOXYALKYLAMINE		17
ETHOXYLATED TALLOW AMINE (> 95%)		17
2-Ethoxy-2-methylpropane	ETHYL TERT-BUTYL ETHER	17
1-Ethoxypropan-2-ol (a)	PROPYLENE GLYCOL MONOALKYL ETHER	17
ETHYL ACETATE		17
ETHYL ACETOACETATE		17
Ethyl acetone	METHYL PROPYL KETONE	17
ETHYL ACRYLATE		17
ETHYL ALCOHOL		18
ETHYLAMINE (*)		17
ETHYLAMINE SOLUTIONS (72% OR LESS)		17
Ethylaminocyclohexane	N-ETHYLCYCLOHEXYLAMINE	17
ETHYL AMYL KETONE		17
ETHYLBENZENE		17
Ethyl benzol	ETHYLBENZENE	17
Ethyl butanoate	ETHYL BUTYRATE	17

Index Name	Product Name	Chapter
ETHYL TERT-BUTYL ETHER		17
ETHYL BUTYRATE		17
2-Ethylcaproic acid	2-ETHYLHEXANOIC ACID	17
Ethyl carbinol	N-PROPYL ALCOHOL	17
Ethyl cyanide	PROPIONITRILE	17
ETHYLCYCLOHEXANE		17
N-ETHYLCYCLOHEXYLAMINE		17
Ethyldimethylmethane (a)	PENTANE (ALL ISOMERS)	17
S-Ethyl dipropylcarbamothioate	S-ETHYL DIPROPYLTHIOCARBAMATE	17
S-ETHYL DIPROPYLTHIOCARBAMATE		17
Ethylene alcohol	ETHYLENE GLYCOL	17
Ethylene bis(iminodiacetic acid) tetrasodium salt solution	ETHYLENEDIAMINETETRAACETIC ACID, TETRASODIUM SALT SOLUTION	17
Ethylene bromide	ETHYLENE DIBROMIDE	17
ETHYLENE CARBONATE		17
Ethylenecarboxylic acid	ACRYLIC ACID	17
Ethylene chloride	ETHYLENE DICHLORIDE	17
ETHYLENE CHLOROHYDRIN		17
ETHYLENE CYANOHYDRIN		17
Ethylene diacetate	ETHYLENE GLYCOL DIACETATE	17
ETHYLENEDIAMINE		17
ETHYLENEDIAMINETETRAACETIC ACID, TETRASODIUM SALT SOLUTION		17
ETHYLENE DIBROMIDE		17
ETHYLENE DICHLORIDE		17
Ethylenedinitrilotetraacetic acid tetrasodium salt solution	ETHYLENEDIAMINETETRAACETIC ACID, TETRASODIUM SALT SOLUTION	17
2,2'-Ethylenedioxydiethanol	TRIETHYLENE GLYCOL	18
ETHYLENE GLYCOL		17
ETHYLENE GLYCOL ACETATE		17
Ethylene glycol acrylate	2-HYDROXYETHYL ACRYLATE	17
Ethylene glycol butyl ether (a)	ETHYLENE GLYCOL MONOALKYL ETHERS	17
ETHYLENE GLYCOL BUTYL ETHER ACETATE		17
Ethylene glycol n-butyl ether (58%)/ Hyperbranched polyesteramide (42%)	2-BUTOXYETHANOL (58%)/HYPERBRANCHED POLYESTERAMIDE (42%) (MIXTURE)	17
Ethylene glycol tert-butyl ether (a)	ETHYLENE GLYCOL MONOALKYL ETHERS	17
ETHYLENE GLYCOL DIACETATE		17
Ethylene glycol ethyl ether (a)	ETHYLENE GLYCOL MONOALKYL ETHERS	17
Ethylene glycol ethyl ether acetate	2-ETHOXYETHYL ACETATE	17
Ethylene glycol isopropyl ether (a)	ETHYLENE GLYCOL MONOALKYL ETHERS	17
Ethylene glycol methyl ether (a)	ETHYLENE GLYCOL MONOALKYL ETHERS	17
ETHYLENE GLYCOL METHYL ETHER ACETATE		17
ETHYLENE GLYCOL MONOALKYL ETHERS		17
Ethylene glycol monoalkyl ethers (58%)/ Hyperbranched polyesteramide (42%)	2-BUTOXYETHANOL (58%)/HYPERBRANCHED POLYESTERAMIDE (42%) (MIXTURE)	17

Index Name	Product Name	Chapter
Ethylene glycol monobutyl ether (a)	ETHYLENE GLYCOL MONOALKYL ETHERS	17
Ethylene glycol monobutyl ether (58%)/ Hyperbranched polyesteramide (42%)	2-BUTOXYETHANOL (58%)/HYPERBRANCHED POLYESTERAMIDE (42%) (MIXTURE)	17
Ethylene glycol mono-tert-butyl ether (a)	ETHYLENE GLYCOL MONOALKYL ETHERS	17
Ethylene glycol monoethyl ether (a)	ETHYLENE GLYCOL MONOALKYL ETHERS	17
Ethylene glycol monoethyl ether acetate	2-ETHOXYETHYL ACETATE	17
Ethylene glycol monomethyl ether (a)	ETHYLENE GLYCOL MONOALKYL ETHERS	17
Ethylene glycol monomethyl ether acetate	ETHYLENE GLYCOL METHYL ETHER ACETATE	17
Ethylene glycol monophenyl ether	ETHYLENE GLYCOL PHENYL ETHER	17
ETHYLENE GLYCOL PHENYL ETHER		17
ETHYLENE GLYCOL PHENYL ETHER/DIETHYLENE GLYCOL PHENYL ETHER MIXTURE		17
ETHYLENE GLYCOL (>75%)/SODIUM ALKYL CARBOXYLATES/BORAX MIXTURE		17
ETHYLENE GLYCOL (>85%)/SODIUM ALKYL CARBOXYLATES MIXTURE		17
ETHYLENE OXIDE/PROPYLENE OXIDE MIXTURE WITH AN ETHYLENE OXIDE CONTENT OF NOT MORE THAN 30% BY MASS		17
Ethylene tetrachloride	PERCHLOROETHYLENE	17
Ethylene trichloride	TRICHLOROETHYLENE	17
ETHYLENE-VINYL ACETATE COPOLYMER (EMULSION)		17
Ethyl ethanoate	ETHYL ACETATE	17
Ethyl ether	DIETHYL ETHER (*)	17
ETHYL-3-ETHOXYPROPIONATE		17
Ethyl fluid (a)	MOTOR FUEL ANTI-KNOCK COMPOUND (CONTAINING LEAD ALKYL)	17
Ethylformic acid	PROPIONIC ACID	17
Ethyl glycol (a)	ETHYLENE GLYCOL MONOALKYL ETHERS	17
2-Ethylhexaldehyde (a)	OCTYL ALDEHYDES	17
2-Ethylhexanal (a)	OCTYL ALDEHYDES	17
2-ETHYLHEXANOIC ACID		17
2-Ethylhexanol (a)	OCTANOL (ALL ISOMERS)	17
2-Ethylhexenal	2-ETHYL-3-PROPYLACROLEIN	17
2-Ethylhex-2-enal	2-ETHYL-3-PROPYLACROLEIN	17
2-Ethylhexoic acid (a)	OCTANOIC ACID (ALL ISOMERS)	17
2-ETHYLHEXYL ACRYLATE		17
2-Ethylhexyl alcohol (a)	OCTANOL (ALL ISOMERS)	17
2-ETHYLHEXYLAMINE		17
2-ETHYL-2-(HYDROXYMETHYL) PROPANE-1,3-DIOL (C8-C10) ESTER		17
Ethyllic acid	ACETIC ACID	17
5-Ethylidenebicyclo(2.2.1)hept-2-ene	ETHYLIDENE NORBORNENE	17
Ethylidene chloride	1,1-DICHLOROETHANE	17
ETHYLIDENE NORBORNENE		17
ETHYL METHACRYLATE		17
N-ETHYLMETHYLALLYLAMINE		17
N-Ethyl-2-methylallylamine	N-ETHYLMETHYLALLYLAMINE	17

Index Name	Product Name	Chapter
2-Ethyl-6-methylaniline	2-METHYL-6-ETHYL ANILINE	17
2-Ethyl-6-methylbenzenamine	2-METHYL-6-ETHYL ANILINE	17
1-ethyl-4-methylbenzene	ETHYL TOLUENE	17
Ethyl methyl ketone	METHYL ETHYL KETONE	17
5-Ethyl-2-methylpyridine	2-METHYL-5-ETHYL PYRIDINE	17
Ethyl oxide	DIETHYL ETHER (*)	17
Ethyl phosphate	TRIETHYL PHOSPHATE	17
Ethyl phthalate	DIETHYL PHTHALATE	17
5-Ethyl-2-picoline	2-METHYL-5-ETHYL PYRIDINE	17
Ethyl propenoate	ETHYL ACRYLATE	17
ETHYL PROPIONATE		17
2-ETHYL-3-PROPYLACROLEIN		17
Ethyl sulphate	DIETHYL SULPHATE	17
ETHYL TOLUENE		17
6-Ethyl-2-toluidine	2-METHYL-6-ETHYL ANILINE	17
6-Ethyl-o-toluidine	2-METHYL-6-ETHYL ANILINE	17
Ethyl vinyl ether	VINYL ETHYL ETHER	17
Extra virgin grape seed oil	GRAPE SEED OIL	17
FATTY ACID (SATURATED C13+)		17
FATTY ACID METHYL ESTERS (M)		17
FATTY ACIDS, (C8-C10)		17
FATTY ACIDS, (C12+)		17
FATTY ACIDS, (C16+)		17
FATTY ACIDS, ESSENTIALLY LINEAR (C6-C18) 2-ETHYLHEXYL ESTER		17
Feeding corn molasses (a)	MOLASSES	18
Fermentation alcohol	ETHYL ALCOHOL	18
FERRIC CHLORIDE SOLUTIONS		17
FERRIC NITRATE/NITRIC ACID SOLUTION		17
FISH OIL		17
FISH PROTEIN CONCENTRATE (CONTAINING 4% OR LESS FORMIC ACID)		17
FISH SILAGE PROTEIN CONCENTRATE (CONTAINING 4% OR LESS FORMIC ACID)		17
FLUROSILICIC ACID SOLUTION (20-30%)		17
FORMALDEHYDE SOLUTIONS (45% OR LESS)		17
Formaldehyde trimer	1,3,5-TRIOXANE	17
Formalin	FORMALDEHYDE SOLUTIONS (45% OR LESS)	17
FORMAMIDE		17
Formdimethylamide	DIMETHYLFORMAMIDE	17
FORMIC ACID (85% OR LESS ACID)		17
FORMIC ACID (OVER 85%)		17
FORMIC ACID MIXTURE (CONTAINING UP TO 18% PROPIONIC ACID AND UP TO 25% SODIUM FORMATE)		17
Formic aldehyde	FORMALDEHYDE SOLUTIONS (45% OR LESS)	17

Index Name	Product Name	Chapter
Formylformic acid	GLYOXYLIC ACID SOLUTION (50 % OR LESS)	17
Fural	FURFURAL	17
2-Furaldehyde	FURFURAL	17
2,5-Furandione	MALEIC ANHYDRIDE	17
Furan-2,5-dione	MALEIC ANHYDRIDE	17
FURFURAL		17
2-Furfuraldehyde	FURFURAL	17
FURFURYL ALCOHOL		17
Furylcarbinol	FURFURYL ALCOHOL	17
Fused poly(2+)cyclic aromatic hydrocarbons (b)	POLY(2+)CYCLIC AROMATICS	17
Gaultheria oil	METHYL SALICYLATE	17
Glacial acetic acid	ACETIC ACID	17
GLUCITOL/GLYCEROL BLEND PROPOXYLATED (CONTAINING 10% OR MORE AMINES)		17
GLUCITOL/GLYCEROL BLEND PROPOXYLATED (CONTAINING LESS THAN 10% AMINES)		17
Glucitol solution	SORBITOL SOLUTION	18
D-Glucitol solution	SORBITOL SOLUTION	18
GLUCOSE SOLUTION		18
GLUTARALDEHYDE SOLUTIONS (50% OR LESS)		17
Glycerin	GLYCERINE	17
GLYCERINE		17
Glycerin triacetate	GLYCERYL TRIACETATE	17
Glyceritol	GLYCERINE	17
Glycerol	GLYCERINE	17
GLYCEROL ETHOXYLATED		18
GLYCEROL MONOOLEATE		17
Glycerol oleate	GLYCEROL MONOOLEATE	17
Glycerol 1-oleate	GLYCEROL MONOOLEATE	17
GLYCEROL PROPOXYLATED		17
GLYCEROL, PROPOXYLATED AND ETHOXYLATED		17
GLYCEROL/SUCROSE BLEND PROPOXYLATED AND ETHOXYLATED		17
Glycerol triacetate	GLYCERYL TRIACETATE	17
GLYCERYL TRIACETATE		17
GLYCIDYL ESTER OF C10 TRIALKYLACETIC ACID		17
Glycidyl neodecanoate	GLYCIDYL ESTER OF C10 TRIALKYLACETIC ACID	17
GLYCINE, SODIUM SALT SOLUTION		17
Glycol	ETHYLENE GLYCOL	17
Glycol carbonate	ETHYLENE CARBONATE	17
Glycol chlorohydrin	ETHYLENE CHLOROHYDRIN	17
Glycol dichloride	ETHYLENE DICHLORIDE	17
GLYCOLIC ACID SOLUTION (70% OR LESS)		17
Glycol monobutyl ether (a)	ETHYLENE GLYCOL MONOALKYL ETHERS	17
Glycols, polyethylene mono(p-nonylphenyl) ether (b)	ALKARYL POLYETHERS (C9-C20)	17

Index Name	Product Name	Chapter
Glycyl alcohol	GLYCERINE	17
Glyoxaldehyde	GLYOXAL SOLUTION (40% OR LESS)	17
Glyoxalic acid	GLYOXYLIC ACID SOLUTION (50 % OR LESS)	17
GLYOXAL SOLUTION (40% OR LESS)		17
GLYOXYLIC ACID SOLUTION (50 % OR LESS)		17
Glyphosate	GLYPHOSATE SOLUTION (NOT CONTAINING SURFACTANT)	17
Glyphosate-mono(isopropylammonium)	GLYPHOSATE SOLUTION (NOT CONTAINING SURFACTANT)	17
GLYPHOSATE SOLUTION (NOT CONTAINING SURFACTANT)		17
Grain alcohol	ETHYL ALCOHOL	18
GRAPE SEED OIL		17
GROUNDNUT OIL		17
Hemimellitene (a)	TRIMETHYLBENZENE (ALL ISOMERS)	17
Hendecanoic acid	UNDECANOIC ACID	17
1-Hendecanol	UNDECYL ALCOHOL	17
cyclo-Heptamethylene	CYCLOHEPTANE	17
HEPTANE (ALL ISOMERS)		17
1-Heptanecarboxylic acid (a)	OCTANOIC ACID (ALL ISOMERS)	17
3-Heptanecarboxylic acid (a)	OCTANOIC ACID (ALL ISOMERS)	17
Heptanoic acid	N-HEPTANOIC ACID	17
N-HEPTANOIC ACID		17
HEPTANOL (ALL ISOMERS) (D)		17
2-Heptanone	METHYL AMYL KETONE	17
Heptan-2-one	METHYL AMYL KETONE	17
HEPTENE (ALL ISOMERS)		17
Heptoic acid	N-HEPTANOIC ACID	17
HEPTYL ACETATE		17
Heptyl alcohol, all isomers (a)	HEPTANOL (ALL ISOMERS) (D)	17
Heptylcarbinol (a)	OCTANOL (ALL ISOMERS)	17
Heptylene, mixed isomers	HEPTENE (ALL ISOMERS)	17
Heptylic acid	N-HEPTANOIC ACID	17
n-Heptylic acid	N-HEPTANOIC ACID	17
1-Hexadecene	OLEFINS (C13+, ALL ISOMERS)	17
Hexadecyl and icosyl methacrylate mixture (a)	CETYL/EICOSYL METHACRYLATE MIXTURE	17
1-HEXADECYLNAPHTHALENE / 1,4-BIS(HEXADECYL)NAPHTHALENE MIXTURE		17
Hexadecylnaphthalene/dihexadecylnaphthalene mixture	1-HEXADECYLNAPHTHALENE / 1,4-BIS(HEXADECYL)NAPHTHALENE MIXTURE	17
Hexadecyl / octadecyl alcohol (a)	ALCOHOLS (C13+)	17
Hexaethylene glycol (a)	POLYETHYLENE GLYCOL	17
Hexafluorosilicate solution (20-30%)	FLUOROSILICIC ACID SOLUTION (20-30%)	17
Hexahydroaniline	CYCLOHEXYLAMINE	17
Hexahydro-1H-azepine	HEXAMETHYLENEIMINE	17
Hexahydrobenzene	CYCLOHEXANE	17
Hexahydro-l-H-azepine	HEXAMETHYLENEIMINE	17

Index Name	Product Name	Chapter
Hexahydrophenol	CYCLOHEXANOL	17
Hexahydrotoluene	METHYLCYCLOHEXANE	17
Hexamethylene	CYCLOHEXANE	17
HEXAMETHYLENEDIAMINE (MOLTEN)		17
HEXAMETHYLENEDIAMINE ADIPATE (50% IN WATER)		17
HEXAMETHYLENEDIAMINE SOLUTION		17
1,6-Hexamethylenediamine solution	HEXAMETHYLENEDIAMINE SOLUTION	17
Hexamethylenediammonium adipate solution (50% solution)	HEXAMETHYLENEDIAMINE ADIPATE (50% IN WATER)	17
HEXAMETHYLENE DIISOCYANATE		17
Hexamethylene-1,6-diisocyanate	HEXAMETHYLENE DIISOCYANATE	17
HEXAMETHYLENE GLYCOL		17
HEXAMETHYLENEIMINE		17
HEXAMETHYLENETETRAMINE SOLUTIONS		17
Hexamine	HEXAMETHYLENETETRAMINE SOLUTIONS	17
Hexanaphthene	CYCLOHEXANE	17
1,6-Hexandiamine hexanedioate (1:1)	HEXAMETHYLENEDIAMINE ADIPATE (50% IN WATER)	17
HEXANE (ALL ISOMERS)		17
1,6-Hexanediamine	HEXAMETHYLENEDIAMINE (MOLTEN)	17
1,6-Hexanediamine solutions	HEXAMETHYLENEDIAMINE SOLUTION	17
Hexane-1,6-diamine solutions	HEXAMETHYLENEDIAMINE SOLUTION	17
Hexanedioic acid, bis(2-ethylhexyl) ester	DI-(2-ETHYLHEXYL) ADIPATE	17
1,6-Hexanediol	HEXAMETHYLENE GLYCOL	17
Hexane-1,6-diol	HEXAMETHYLENE GLYCOL	17
1,6-HEXANEDIOL, DISTILLATION OVERHEADS		17
n-Hexane	HEXANE (ALL ISOMERS)	17
HEXANOIC ACID		17
HEXANOL		17
Hexan-1-ol	HEXANOL	17
2-Hexanone	METHYL BUTYL KETONE	17
Hexan-2-one	METHYL BUTYL KETONE	17
HEXENE (ALL ISOMERS)		17
1-Hexene (a)	HEXENE (ALL ISOMERS)	17
Hex-1-ene (a)	HEXENE (ALL ISOMERS)	17
2-Hexene (a)	HEXENE (ALL ISOMERS)	17
Hexone	METHYL ISOBUTYL KETONE	17
HEXYL ACETATE		17
sec-Hexyl acetate	METHYLAMYL ACETATE	17
Hexyl alcohol	HEXANOL	17
Hexylene (a)	HEXENE (ALL ISOMERS)	17
HEXYLENE GLYCOL		17
Hexyl ethanoate	HEXYL ACETATE	17
Highly-Reactive Polyisobutylene	POLY(4+)ISOBUTYLENE (MW>224)	17
Homopiperidine	HEXAMETHYLENEIMINE	17
HYDROCARBON WAX		17

Index Name	Product Name	Chapter
HYDROCHLORIC ACID (*)		17
Hydrofluorosilic acid solution (20-30%)	FLUOROSILICIC ACID SOLUTION (20-30%)	17
Hydrofuran	TETRAHYDROFURAN	17
Hydrogenated maltose syrup	MALTITOL SOLUTION	18
Hydrogenated oligosaccharide	HYDROGENATED STARCH HYDROLYSATE	18
HYDROGENATED STARCH HYDROLYSATE		18
Hydrogencarboxylic acid	FORMIC ACID (85% OR LESS ACID)	17
Hydrogen chloride, aqueous	HYDROCHLORIC ACID (*)	17
HYDROGEN PEROXIDE SOLUTIONS (OVER 60% BUT NOT OVER 70% BY MASS)		17
HYDROGEN PEROXIDE SOLUTIONS (OVER 8% BUT NOT OVER 60% BY MASS)		17
Hydrogen sulphate	SULPHURIC ACID	17
alpha-Hydro-omega-hydroxypoly[oxy(methyl-1,2-ethanediyl)]	POLYPROPYLENE GLYCOL	17
Hydroxyacetic acid	GLYCOLIC ACID SOLUTION (70% OR LESS)	17
Hydroxybenzene	PHENOL	17
4-Hydroxybutanoic acid lactone	GAMMA-BUTYROLACTONE	17
4-Hydroxybutyric acid lactone	GAMMA-BUTYROLACTONE	17
gamma-Hydroxybutyric acid lactone	GAMMA-BUTYROLACTONE	17
Hydroxydimethylbenzenes	XYLENOL	17
Hydroxyethanoic acid	GLYCOLIC ACID SOLUTION (70% OR LESS)	17
2-Hydroxyethyl acetate	ETHYLENE GLYCOL ACETATE	17
2-HYDROXYETHYL ACRYLATE		17
beta-Hydroxyethyl acrylate	2-HYDROXYETHYL ACRYLATE	17
2-Hydroxyethylamine	ETHANOLAMINE	17
N-beta-Hydroxyethylethylenediamine	AMINOETHYL ETHANOLAMINE	17
N-(HYDROXYETHYL)ETHYLENEDIAMINETRIACETIC ACID, TRISODIUM SALT SOLUTION		17
beta-Hydroxyethyl phenyl ether	ETHYLENE GLYCOL PHENYL ETHER	17
2-Hydroxyethyl propenoate	2-HYDROXYETHYL ACRYLATE	17
2-Hydroxyethyl 2-propenoate	2-HYDROXYETHYL ACRYLATE	17
alpha-Hydroxyisobutyronitrile	ACETONE CYANOHYDRIN	17
4-Hydroxy-2-keto-4-methylpentane	DIACETONE ALCOHOL	17
4-Hydroxy-4-methylpentanone-2	DIACETONE ALCOHOL	17
4-Hydroxy-4-methylpentan-2-one	DIACETONE ALCOHOL	17
2-Hydroxy-2-methylpropionitrile	ACETONE CYANOHYDRIN	17
2-HYDROXY-4-(METHYLTHIO)BUTANOIC ACID		17
2-Hydroxy-4-(methylthio)butyric acid	2-HYDROXY-4-(METHYLTHIO)BUTANOIC ACID	17
2-Hydroxynitrobenzene (molten)	O-NITROPHENOL (MOLTEN)	17
1-Hydroxy-2-phenoxyethane	ETHYLENE GLYCOL PHENYL ETHER	17
2-Hydroxypropanoic acid	LACTIC ACID	17
2-Hydroxypropionic acid	LACTIC ACID	17
alpha-Hydroxypropionic acid	LACTIC ACID	17
3-Hydroxypropionic acid, lactone.	BETA-PROPIOLACTONE	17
beta-Hydroxypropionitrile	ETHYLENE CYANOHYDRIN	17
2-Hydroxypropionitrile solution (80% or less)	LACTONITRILE SOLUTION (80% OR LESS)	17
alpha-Hydroxypropionitrile solution (80% or less)	LACTONITRILE SOLUTION (80% OR LESS)	17

Index Name	Product Name	Chapter
3-Hydroxypropionitrile	ETHYLENE CYANOHYDRIN	17
2-Hydroxypropionitrile solution (80% or less)	LACTONITRILE SOLUTION (80% OR LESS)	17
2-[2-(2-hydroxypropoxy)propoxy]propan-1-ol	TRIPROPYLENE GLYCOL	17
2-Hydroxypropylamine	ISOPROPANOLAMINE	17
3-Hydroxypropylamine	N-PROPANOLAMINE	17
alpha-Hydroxytoluene	BENZYL ALCOHOL	17
3-Hydroxy-2,2,4-trimethylpentyl isobutyrate	2,2,4-TRIMETHYL-1,3-PENTANEDIOL-1- ISOBUTYRATE	17
ILLIPE OIL		17
2,2'-Iminodi(ethylamine)	DIETHYLENETRIAMINE	17
2,2'-Iminodiethanol	DIETHANOLAMINE	17
1,1'-Iminodipropan-2-ol	DIISOPROPANOLAMINE	17
Iron (III) chloride solutions	FERRIC CHLORIDE SOLUTIONS	17
Iron (III) nitrate / nitric acid solution	FERRIC NITRATE/NITRIC ACID SOLUTION	17
Isoacetophenone	ISOPHORONE	17
Isoamyl acetate (a)	AMYL ACETATE (ALL ISOMERS)	17
ISOAMYL ALCOHOL		17
Isobutaldehyde (a)	BUTYRALDEHYDE (ALL ISOMERS)	17
Isobutanal (a)	BUTYRALDEHYDE (ALL ISOMERS)	17
Isobutanol	ISOBUTYL ALCOHOL	17
Isobutanolamine	2-AMINO-2-METHYL-1-PROPANOL	17
Isobutyl acetate	BUTYL ACETATE (ALL ISOMERS)	17
Isobutyl acrylate (a)	BUTYL ACRYLATE (ALL ISOMERS)	17
ISOBUTYL ALCOHOL		17
Isobutyl aldehyde (a)	BUTYRALDEHYDE (ALL ISOMERS)	17
Isobutylamine (a)	BUTYLAMINE (ALL ISOMERS)	17
Isobutylcarbinol	ISOAMYL ALCOHOL	17
ISOBUTYL FORMATE		17
Isobutyl ketone	DIISOBUTYL KETONE	17
ISOBUTYL METHACRYLATE		17
Isobutylmethylcarbinol	METHYLAMYL ALCOHOL	17
Isobutyl methyl ketone	METHYL ISOBUTYL KETONE	17
Isobutylmethylemethanol	METHYLAMYL ALCOHOL	17
Isobutyraldehyde (a)	BUTYRALDEHYDE (ALL ISOMERS)	17
Isobutyric aldehyde (a)	BUTYRALDEHYDE (ALL ISOMERS)	17
alpha-Isocyanatobenzyl-omega-isocyanatophenylpoly[(phenyl isocyanate)-alt-formaldehyde]	POLYMETHYLENE POLYPHENYL ISOCYANATE	17
3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	ISOPHORONE DIISOCYANATE	17
Isodecanol	DECYL ALCOHOL (ALL ISOMERS)	17
Isodecyl alcohol	DECYL ALCOHOL (ALL ISOMERS)	17
Isododecane (a)	DODECANE (ALL ISOMERS)	17
Isodurene (a)	TETRAMETHYLBENZENE (ALL ISOMERS)	17
Isononanoic acid	NONANOIC ACID (ALL ISOMERS)	17
Isononanol	NONYL ALCOHOL (ALL ISOMERS)	17
Isooctane (a)	OCTANE (ALL ISOMERS)	17
Isooctanol	OCTANOL (ALL ISOMERS)	17
Isopentane (a)	PENTANE (ALL ISOMERS)	17

Index Name	Product Name	Chapter
Isopentanol	AMYL ALCOHOL, PRIMARY	17
Isopentanol	ISOAMYL ALCOHOL	17
Isopentyl acetate (a)	AMYL ACETATE (ALL ISOMERS)	17
Isopentyl alcohol	ISOAMYL ALCOHOL	17
ISOPHORONE		17
ISOPHORONEDIAMINE		17
ISOPHORONE DIISOCYANATE		17
ISOPRENE		17
Isopropanol	ISOPROPYL ALCOHOL	18
ISOPROPANOLAMINE		17
Isopropenylbenzene	ALPHA-METHYLSTYRENE	17
2-Isopropoxyethanol (a)	ETHYLENE GLYCOL MONOALKYL ETHERS	17
2-Isopropoxypropane	ISOPROPYL ETHER	17
ISOPROPYL ACETATE		17
Isopropylacetone	METHYL ISOBUTYL KETONE	17
ISOPROPYL ALCOHOL		18
ISOPROPYLAMINE		17
ISOPROPYLAMINE (70% OR LESS) SOLUTION		17
Isopropylammonium N-(phosphonomethyl)glycine	GLYPHOSATE SOLUTION (NOT CONTAINING SURFACTANT)	17
Isopropylcarbinol	ISOBUTYL ALCOHOL	17
Isopropyl carbinol	ISOBUTYL ALCOHOL	17
ISOPROPYLCYCLOHEXANE		17
1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate	2,2,4-TRIMETHYL-1,3-PENTANEDIOL DIISOBUTYRATE	17
ISOPROPYL ETHER		17
Isopropylideneacetone	MESITYL OXIDE	17
Isopropyl oxide	ISOPROPYL ETHER	17
4-Isopropyltoluene	P-CYMENE	17
p-Isopropyltoluene	P-CYMENE	17
4-Isopropyltoluol	P-CYMENE	17
Isovaleral	VALERALDEHYDE (ALL ISOMERS)	17
Isovaleraldehyde	VALERALDEHYDE (ALL ISOMERS)	17
Isovaleric aldehyde	VALERALDEHYDE (ALL ISOMERS)	17
Isovalerone	DIISOBUTYL KETONE	17
JATROPHA OIL		17
Kaolin clay slurry	KAOLIN SLURRY	18
Kaolinite slurry	KAOLIN SLURRY	18
KAOLIN SLURRY		18
Ketohexamethylene	CYCLOHEXANONE	17
Ketone propane	ACETONE	18
Ketopropane	ACETONE	18
LACTIC ACID		17
LACTONITRILE SOLUTION (80% OR LESS)		17
LARD		17

Index Name	Product Name	Chapter
LATEX, AMMONIA (1% OR LESS)- INHIBITED		17
LATEX: CARBOXYLATED STYRENE-BUTADIENE COPOLYMER; STYRENE-BUTADIENE RUBBER		17
LAURIC ACID		17
Lauryl alcohol	DODECYL ALCOHOL	17
Lead alkyls, n.o.s. (a)	MOTOR FUEL ANTI-KNOCK COMPOUND (CONTAINING LEAD ALKYLs)	17
Lead tetraethyl (a)	MOTOR FUEL ANTI-KNOCK COMPOUND (CONTAINING LEAD ALKYLs)	17
Lead tetramethyl (a)	MOTOR FUEL ANTI-KNOCK COMPOUND (CONTAINING LEAD ALKYLs)	17
LECITHIN		18
LIGNINSULPHONIC ACID, MAGNESIUM SALT SOLUTION		17
LIGNINSULPHONIC ACID, SODIUM SALT SOLUTION		17
Limonene	DIPENTENE	17
Linear alkylbenzene (LAB) bottoms (a)	ALKYLBENZENE DISTILLATION BOTTOMS	17
Linear alkyl(C12-C16) propoxyamine ethoxylate	ALKYL(C12-C16) PROPOXYAMINE ETHOXYLATE	17
LINSEED OIL		17
LIQUID CHEMICAL WASTES		17
Liquid paraffin	N-ALKANES (C10-C20)	17
LONG-CHAIN ALKARYL POLYETHER (C11-C20)		17
LONG-CHAIN ALKARYL SULPHONIC ACID (C16-C60)		17
LONG-CHAIN ALKYLPHENATE/PHENOL SULPHIDE MIXTURE		17
LONG-CHAIN ALKYLPHENOL (C14-C18)		17
LONG-CHAIN ALKYLPHENOL (C18-C30)		17
Lye, soda solution	SODIUM HYDROXIDE SOLUTION (*)	17
L-LYSINE SOLUTION (60% OR LESS)		17
Magnesia hydrate	MAGNESIUM HYDROXIDE SLURRY	17
MAGNESIUM CHLORIDE SOLUTION		17
MAGNESIUM HYDROXIDE SLURRY		17
Magnesium Lignasulphonate solution	LIGNINSULPHONIC ACID, MAGNESIUM SALT SOLUTION	17
MAGNESIUM LONG-CHAIN ALKARYL SULPHONATE (C11-C50)		17
MAGNESIUM LONG-CHAIN ALKYL SALICYLATE (C11+)		17
MALEIC ANHYDRIDE		17
MALEIC ANHYDRIDE-SODIUM ALLYLSULPHONATE COPOLYMER SOLUTION		17
Maltitol	MALTITOL SOLUTION	18
MALTITOL SOLUTION		18
Maltitol syrup	MALTITOL SOLUTION	18
MANGO KERNEL OIL		17
Meglumine solution (70% or less)	N-METHYLGLUCAMINE SOLUTION (70% OR LESS)	17
MERCAPTOBENZOTHAZOL, SODIUM SALT SOLUTION		17
Mesitylene	TRIMETHYLBENZENE (ALL ISOMERS)	17

Index Name	Product Name	Chapter
MESITYL OXIDE		17
Metaformaldehyde	1,3,5-TRIOXANE	17
Metam-sodium	METAM SODIUM SOLUTION	17
METAM SODIUM SOLUTION		17
METHACRYLIC ACID		17
METHACRYLIC ACID - ALKOXPOLY (ALKYLENE OXIDE) METHACRYLATE COPOLYMER, SODIUM SALT AQUEOUS SOLUTION (45% OR LESS)		17
alpha-Methacrylic acid	METHACRYLIC ACID	17
Methacrylic acid, dodecyl ester	DODECYL METHACRYLATE	17
Methacrylic acid, lauryl ester	DODECYL METHACRYLATE	17
METHACRYLIC RESIN IN ETHYLENE DICHLORIDE		17
METHACRYLONITRILE		17
Methanal	FORMALDEHYDE SOLUTIONS (45% OR LESS)	17
Methanamide	FORMAMIDE	17
Methanamine	METHYLAMINE SOLUTIONS (42% OR LESS)	17
Methanecarboxylic acid	ACETIC ACID	17
Methanoic acid	FORMIC ACID (85% OR LESS ACID)	17
Methanol	METHYL ALCOHOL (*)	17
Methenamine	HEXAMETHYLENETETRAMINE SOLUTIONS	17
3-METHOXY-1-BUTANOL		17
3-Methoxybutan-1-ol	3-METHOXY-1-BUTANOL	17
3-METHOXYBUTYL ACETATE		17
2-Methoxyethanol (a)	ETHYLENE GLYCOL MONOALKYL ETHERS	17
2-(2-Methoxyethoxy)ethanol (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL(C1-C6) ETHER	17
2-[2-(2-Methoxyethoxy)ethoxy]ethanol (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL(C1-C6) ETHER	17
2-(2-Methoxyethoxy)ethyl acetate (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL (C1-C6) ETHER ACETATE	17
2-Methoxyethyl acetate	ETHYLENE GLYCOL METHYL ETHER ACETATE	17
2-Methoxy-2-methylbutane	TERT-AMYL METHYL ETHER	17
3-Methoxy-3-methylbutan-1-ol	3-METHYL-3-METHOXYBUTANOL	17
2-Methoxy-1-methylethyl acetate	PROPYLENE GLYCOL METHYL ETHER ACETATE	17
N-(2-METHOXY-1-METHYL ETHYL)-2-ETHYL-6-METHYL CHLOROACETANILIDE		17
2-methoxy-2-methylpropane	METHYL TERT-BUTYL ETHER	17
1-Methoxypropan-2-ol (a)	PROPYLENE GLYCOL MONOALKYL ETHER	17
1-Methoxy-2-propanol acetate	PROPYLENE GLYCOL METHYL ETHER ACETATE	17
1-(2-Methoxypropoxy)propan-2-ol (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL(C1-C6) ETHER	17
3-[3-(3-Methoxypropoxy)propoxy]propan-1-ol (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL(C1-C6) ETHER	17
Methoxytriglycol (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL(C1-C6) ETHER	17
Methylacetaldehyde	PROPIONALDEHYDE	17
METHYL ACETATE		17

Index Name	Product Name	Chapter
Methylacetic acid	PROPIONIC ACID	17
METHYL ACETOACETATE		17
Methyl acetylacetate	METHYL ACETOACETATE	17
beta-Methylacrolein	CROTONALDEHYDE	17
METHYL ACRYLATE		17
2-Methylacrylic acid	METHACRYLIC ACID	17
2-Methylacrylic acid, dodecyl ester	DODECYL METHACRYLATE	17
2-Methylacrylic acid, lauryl ester	DODECYL METHACRYLATE	17
METHYL ALCOHOL (*)		17
METHYLAMINE SOLUTIONS (42% OR LESS)		17
1-Methyl-2-aminobenzene	O-TOLUIDINE	17
2-Methyl-1-aminobenzene	O-TOLUIDINE	17
METHYLAMYL ACETATE		17
METHYLAMYL ALCOHOL		17
METHYL AMYL KETONE		17
Methyl n-amyl ketone	METHYL AMYL KETONE	17
2-Methylaniline	O-TOLUIDINE	17
N-METHYLANILINE		17
o-Methylaniline	O-TOLUIDINE	17
2-Methylbenzenamine	O-TOLUIDINE	17
o-Methylbenzenamine	O-TOLUIDINE	17
Methylbenzene	TOLUENE	17
Methylbenzol	TOLUENE	17
ALPHA-METHYLBENZYL ALCOHOL WITH ACETOPHENONE (15% OR LESS)		17
2-Methyl-1,3-butadiene	ISOPRENE	17
3-Methyl-1,3-butadiene	ISOPRENE	17
2-Methylbutanal	VALERALDEHYDE (ALL ISOMERS)	17
3-Methylbutanal	VALERALDEHYDE (ALL ISOMERS)	17
2-Methylbutane (a)	PENTANE (ALL ISOMERS)	17
Methyl butanoate	METHYL BUTYRATE	17
2-Methyl-2-butanol	TERT-AMYL ALCOHOL	17
2-Methylbutan-2-ol	TERT-AMYL ALCOHOL	17
2-Methyl-4-butanol	ISOAMYL ALCOHOL	17
3-Methyl-1-butanol	AMYL ALCOHOL, PRIMARY	17
3-Methylbutan-1-ol	AMYL ALCOHOL, PRIMARY	17
3-Methyl-1-butanol	ISOAMYL ALCOHOL	17
3-Methylbutan-1-ol	ISOAMYL ALCOHOL	17
3-Methylbutan-3-ol	TERT-AMYL ALCOHOL	17
3-Methylbut-1-ene (a)	PENTENE (ALL ISOMERS)	17
Methylbutenes (a)	PENTENE (ALL ISOMERS)	17
METHYLBUTENOL		17
1-Methylbutyl acetate (a)	AMYL ACETATE (ALL ISOMERS)	17
2-Methyl-2-butyl alcohol	TERT-AMYL ALCOHOL	17
3-Methyl-1-butyl alcohol	ISOAMYL ALCOHOL	17
3-Methyl-3-butyl alcohol	TERT-AMYL ALCOHOL	17

Index Name	Product Name	Chapter
METHYL TERT-BUTYL ETHER		17
METHYL BUTYL KETONE		17
METHYLBUTYNOL		17
2-Methyl-3-butyn-2-ol	2-METHYL-2-HYDROXY-3-BUTYNE	17
2-Methylbut-3-yn-2-ol	2-METHYL-2-HYDROXY-3-BUTYNE	17
2-Methylbut-3-yn-2-ol	METHYLBUTYNOL	17
2-Methyl-3-butyn-2-ol	METHYLBUTYNOL	17
2-Methylbutyraldehyde	VALERALDEHYDE (ALL ISOMERS)	17
3-Methylbutyraldehyde	VALERALDEHYDE (ALL ISOMERS)	17
METHYL BUTYRATE		17
Methyl 'carbitol' acetate (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL (C1-C6) ETHER ACETATE	17
Methyl 'cellosolve' acetate	ETHYLENE GLYCOL METHYL ETHER ACETATE	17
Methylchloroform	1,1,1-TRICHLOROETHANE	17
Methyl cyanide	ACETONITRILE	17
METHYLCYCLOHEXANE		17
1-Methyl-1,3-cyclopentadiene	METHYLCYCLOPENTADIENE DIMER	17
METHYLCYCLOPENTADIENE DIMER		17
METHYLCYCLOPENTADIENYL MANGANESE TRICARBONYL		17
METHYL DIETHANOLAMINE		17
4-Methyl-1,3-dioxolan-2-one	PROPYLENE CARBONATE	17
Methyl disulphide	DIMETHYL DISULPHIDE	17
Methylenebis(4-isocyanatobenzene)	DIPHENYLMETHANE DIISOCYANATE	17
Methylenebis(4-phenyl isocyanate)	DIPHENYLMETHANE DIISOCYANATE	17
Methylenebis(4-phenylene isocyanate)	DIPHENYLMETHANE DIISOCYANATE	17
Methylenebis(p-phenylene isocyanate)	DIPHENYLMETHANE DIISOCYANATE	17
4,4'-Methylenebis(4-phenyl isocyanate)	DIPHENYLMETHANE DIISOCYANATE	17
Methylene bromide	DIBROMOMETHANE	17
Methylene chloride	DICHLOROMETHANE	17
4,4'-Methylenedi(phenyl isocyanate)	DIPHENYLMETHANE DIISOCYANATE	17
Methylene dichloride	DICHLOROMETHANE	17
4,4'-Methylenediphenyl diisocyanate	DIPHENYLMETHANE DIISOCYANATE	17
Methylenedi-p-phenylene diisocyanate	DIPHENYLMETHANE DIISOCYANATE	17
2-Methylenepropionic acid	METHACRYLIC ACID	17
Methyl ethanoate	METHYL ACETATE	17
1-Methylethyl acetate	ISOPROPYL ACETATE	17
1-Methylethylamine	ISOPROPYLAMINE	17
2-METHYL-6-ETHYL ANILINE		17
Methylethylcarbinol	SEC-BUTYL ALCOHOL	18
Methylethylene glycol	PROPYLENE GLYCOL	18
Methylethylene oxide	PROPYLENE OXIDE	17
METHYL ETHYL KETONE		17
N-(1-Methylethyl)propan-2-amine	DIISOPROPYLAMINE	17
2-METHYL-5-ETHYL PYRIDINE		17
METHYL FORMATE		17

Index Name	Product Name	Chapter
N-METHYLGLUCAMINE SOLUTION (70% OR LESS)		17
N-methyl-D-glucamine solution (70% or less)	N-METHYLGLUCAMINE SOLUTION (70% OR LESS)	17
2-METHYLGLUTARONITRILE WITH 2-ETHYLSUCCINONITRILE (12% OR LESS)		17
Methyl glycol	PROPYLENE GLYCOL	18
5-Methylheptan-3-one	ETHYL AMYL KETONE	17
5-Methyl-3-heptanone	ETHYL AMYL KETONE	17
Methylhexylcarbinol	OCTANOL (ALL ISOMERS)	17
Methyl 2-hydroxybenzoate	METHYL SALICYLATE	17
Methyl o-hydroxybenzoate	METHYL SALICYLATE	17
2-METHYL-2-HYDROXY-3-BUTYNE		17
2-Methyl-2-hydroxy-3-butyne	METHYLBUTYNOL	17
2,2'-(Methylimino)diethanol	METHYL DIETHANOLAMINE	17
N-Methyl-2,2'-iminodiethanol	METHYL DIETHANOLAMINE	17
Methyl isoamyl ketone	METHYL AMYL KETONE	17
Methyl isobutenyl ketone	MESITYL OXIDE	17
Methylisobutylcarbinol	METHYLAMYL ALCOHOL	17
Methylisobutylcarbinol acetate	METHYLAMYL ACETATE	17
METHYL ISOBUTYL KETONE		17
p-Methylisopropyl benzene	P-CYMENE	17
2-Methylactonitrile	ACETONE CYANOHYDRIN	17
methyl mercaptopropionaldehyde	3-(METHYLTHIO)PROPIONALDEHYDE	17
METHYL METHACRYLATE		17
Methyl methanoate	METHYL FORMATE	17
3-METHYL-3-METHOXYBUTANOL		17
Methyl alpha-methylacrylate	METHYL METHACRYLATE	17
7-Methyl-3-methylene-1,6-octadiene	MYRCENE	17
Methyl 2-methylprop-2-enoate	METHYL METHACRYLATE	17
METHYL NAPHTHALENE (MOLTEN)		17
alpha-Methylnaphthalene (molten) (a)	METHYL NAPHTHALENE (MOLTEN)	17
beta-Methylnaphthalene (molten) (a)	METHYL NAPHTHALENE (MOLTEN)	17
(o- and p-) Methylnitrobenzene	O- OR P-NITROTOLUENES	17
8-Methylnonan-1-ol	DECYL ALCOHOL (ALL ISOMERS)	17
Methylolpropane	N-BUTYL ALCOHOL	18
alpha-Methyl-omega-methoxypoly(ethylene oxide)	POLYETHYLENE GLYCOL DIMETHYL ETHER	17
alpha-Methyl-omega-methoxypoly(oxy-1,2-ethanediyl)	POLYETHYLENE GLYCOL DIMETHYL ETHER	17
alpha-Methyl-omega-methoxypoly(oxyethylene)	POLYETHYLENE GLYCOL DIMETHYL ETHER	17
Methyloxirane	PROPYLENE OXIDE	17
2-Methyl-2,4-pentanediol	HEXYLENE GLYCOL	17
2-Methylpentane-2,4-diol	HEXYLENE GLYCOL	17
4-Methylpentanol-2	METHYLAMYL ALCOHOL	17
4-Methylpentan-2-ol	METHYLAMYL ALCOHOL	17
4-Methyl-2-pentanol acetate	METHYLAMYL ACETATE	17
4-Methyl-2-pentanone	METHYL ISOBUTYL KETONE	17
4-Methylpentan-2-one	METHYL ISOBUTYL KETONE	17
2-Methylpentene (a)	HEXENE (ALL ISOMERS)	17

Index Name	Product Name	Chapter
2-Methylpent-1-ene (a)	HEXENE (ALL ISOMERS)	17
2-Methyl-1-pentene (a)	HEXENE (ALL ISOMERS)	17
4-Methyl-1-pentene (a)	HEXENE (ALL ISOMERS)	17
4-Methyl-3-penten-2-one	MESITYL OXIDE	17
4-Methylpent-3-en-2-one	MESITYL OXIDE	17
4-Methyl-2-pentyl acetate	METHYLAMYL ACETATE	17
Methylpentyl acetates	METHYLAMYL ACETATE	17
Methyl tert-pentyl ether	TERT-AMYL METHYL ETHER	17
Methyl pentyl ketone	METHYL AMYL KETONE	17
2-Methyl-m-phenylenediamine (a)	TOLUENEDIAMINE	17
4-Methyl-m-phenylenediamine (a)	TOLUENEDIAMINE	17
Methylphenylene diisocyanate	TOLUENE DIISOCYANATE	17
4-methyl-1,3-phenylene diisocyanate	TOLUENE DIISOCYANATE	17
4-Methyl-m-phenylene diisocyanate	TOLUENE DIISOCYANATE	17
2-Methyl-2-phenylpropane (a)	BUTYLBENZENE (ALL ISOMERS)	17
2-Methylpropanal (a)	BUTYRALDEHYDE (ALL ISOMERS)	17
2-METHYL-1,3-PROPANEDIOL		17
2-Methylpropan-1-ol	ISOBUTYL ALCOHOL	17
2-Methyl-1-propanol	ISOBUTYL ALCOHOL	17
2-Methylpropan-2-ol	TERT-BUTYL ALCOHOL	17
2-Methyl-2-propanol	TERT-BUTYL ALCOHOL	17
2-Methylprop-2-enenitrile	METHACRYLONITRILE	17
2-Methylpropenoic acid	METHACRYLIC ACID	17
alpha-Methylpropenoic acid	METHACRYLIC ACID	17
2-Methylprop-1-enyl methyl ketone	MESITYL OXIDE	17
2-Methylpropyl acrylate (a)	BUTYL ACRYLATE (ALL ISOMERS)	17
2-Methyl-1-propyl alcohol	ISOBUTYL ALCOHOL	17
2-Methyl-2-propyl alcohol	TERT-BUTYL ALCOHOL	17
Methylpropylcarbinol	SEC-AMYL ALCOHOL	17
2-Methylpropyl formate	ISOBUTYL FORMATE	17
METHYL PROPYL KETONE		17
2-METHYLPYRIDINE		17
3-METHYLPYRIDINE		17
4-METHYLPYRIDINE		17
alpha-Methylpyridine	2-METHYLPYRIDINE	17
1-Methylpyrrolidin-2-one	N-METHYL-2-PYRROLIDONE	17
1-Methyl-2-pyrrolidinone	N-METHYL-2-PYRROLIDONE	17
N-Methylpyrrolidinone	N-METHYL-2-PYRROLIDONE	17
1-Methyl-2-pyrrolidone	N-METHYL-2-PYRROLIDONE	17
N-METHYL-2-PYRROLIDONE		17
METHYL SALICYLATE		17
Methyl soyate	SOYBEAN OIL FATTY ACID METHYL ESTER	17
Methylstyrene (all isomers)	VINYLTOLUENE	17
ALPHA-METHYLSTYRENE		17
3-(METHYLTHIO)PROPIONALDEHYDE		17
2-Methyltrimethylene glycol	2-METHYL-1,3-PROPANEDIOL	17

Index Name	Product Name	Chapter
Metolachlor	N-(2-METHOXY-1-METHYL ETHYL)-2-ETHYL-6-METHYL CHLOROACETANILIDE	17
MICROSILICA SLURRY		18
Middle oil	CARBOLIC OIL	17
Milk acid	LACTIC ACID	17
Milk of magnesia	MAGNESIUM HYDROXIDE SLURRY	18
Mineral wax	HYDROCARBON WAX	17
Mixed aliphatic oxygenated hydrocarbons, primary aliphatic alcohols and aliphatic ethers: mol wt: >200 (a)	OXYGENATED ALIPHATIC HYDROCARBON MIXTURE	17
MOLASSES		18
MOLYBDENUM POLYSULPHIDE LONG CHAIN ALKYL DITHIOCARBAMIDE COMPLEX		17
Monochlorobenzene	CHLOROBENZENE	17
Monochlorobenzol	CHLOROBENZENE	17
Monoethanolamine	ETHANOLAMINE	17
Monoethylamine	ETHYLAMINE (*)	17
Monoethylamine solutions, 72% or less	ETHYLAMINE SOLUTIONS (72% OR LESS)	17
Monoisopropanolamine	ISOPROPANOLAMINE	17
Monoisopropylamine	ISOPROPYLAMINE	17
Monomethylamine solutions, 42% or less	METHYLAMINE SOLUTIONS (42% OR LESS)	17
Monopropylamine	N-PROPYLAMINE	17
Monopropylene glycol	PROPYLENE GLYCOL	18
MORPHOLINE		17
MOTOR FUEL ANTI-KNOCK COMPOUND (CONTAINING LEAD ALKYL)		17
Muriatic acid	HYDROCHLORIC ACID (*)	17
MYRCENE		17
Naphtha, coal tar	COAL TAR NAPHTHA SOLVENT	17
NAPHTHALENE (MOLTEN)		17
NAPHTHALENE CRUDE (MOLTEN)		17
NAPHTHALENESULPHONIC ACID-FORMALDEHYDE COPOLYMER, SODIUM SALT SOLUTION		17
Naphtha (petroleum), Light Steam-cracked Aromatics (a)	ALKYLBENZENE MIXTURES (CONTAINING AT LEAST 50% OF TOLUENE)	17
Naphtha safety solvent	WHITE SPIRIT, LOW (15-20%) AROMATIC	17
NEODECANOIC ACID		17
Neodecanoic acid, 2,3-epoxypropyl ester	GLYCIDYL ESTER OF C10 TRIALKYLACETIC ACID	17
Neodecanoic acid, glycidyl ester	GLYCIDYL ESTER OF C10 TRIALKYLACETIC ACID	17
Neodecanoic acid vinyl ester	VINYL NEODECANOATE	17
Neopentane (a)	PENTANE (ALL ISOMERS)	17
Neopentanoic acid	TRIMETHYLACETIC ACID	17
Neopentylene glycol	2,2-DIMETHYLPROPANE-1,3-DIOL (MOLTEN OR SOLUTION)	17
NITRATING ACID (MIXTURE OF SULPHURIC AND NITRIC ACIDS)		17
NITRIC ACID (70% AND OVER)		17
NITRIC ACID (LESS THAN 70%)		17
Nitric acid, fuming (a)	NITRIC ACID (70% AND OVER)	17

Index Name	Product Name	Chapter
Nitric acid, red fuming	NITRIC ACID (70% AND OVER)	17
NITRILOTRIACETIC ACID, TRISODIUM SALT SOLUTION		17
2,2',2"-Nitrilotriethanol	TRIETHANOLAMINE	17
Nitrilo-2,2',2"-triethanol	TRIETHANOLAMINE	17
1,1',1"-Nitrilotripropan-2-ol	TRIISOPROPANOLAMINE	17
1,1',1"-Nitrilotri-2-propanol	TRIISOPROPANOLAMINE	17
NITROBENZENE		17
Nitrobenzol	NITROBENZENE	17
o-Nitrochlorobenzene	O-CHLORONITROBENZENE	17
NITROETHANE		17
NITROETHANE(80%)/ NITROPROPANE(20%)		17
NITROETHANE, 1-NITROPROPANE (EACH 15% OR MORE) MIXTURE		17
ortho-Nitrophenol (molten)	O-NITROPHENOL (MOLTEN)	17
2-Nitrophenol (molten)	O-NITROPHENOL (MOLTEN)	17
O-NITROPHENOL (MOLTEN)		17
1- OR 2-NITROPROPANE		17
NITROPROPANE (60%)/NITROETHANE (40%) MIXTURE		17
2-Nitrotoluene (a)	O- OR P-NITROTOLUENES	17
4-Nitrotoluene (a)	O- OR P-NITROTOLUENES	17
o-Nitrotoluene (a)	O- OR P-NITROTOLUENES	17
p-Nitrotoluene (a)	O- OR P-NITROTOLUENES	17
O- OR P-NITROTOLUENES		17
NONANE (ALL ISOMERS)		17
1-Nonanecarboxylic acid	DECANOIC ACID	17
n-Nonane (a)	NONANE (ALL ISOMERS)	17
NONANOIC ACID (ALL ISOMERS)		17
Nonanols	NONYL ALCOHOL (ALL ISOMERS)	17
NON-EDIBLE INDUSTRIAL GRADE PALM OIL		17
NONENE (ALL ISOMERS)		17
NONYL ALCOHOL (ALL ISOMERS)		17
Nonylcarbinol	DECYL ALCOHOL (ALL ISOMERS)	17
Nonylene (a)	NONENE (ALL ISOMERS)	17
Nonyl hydride (a)	NONANE (ALL ISOMERS)	17
NONYL METHACRYLATE MONOMER		17
NONYLPHENOL		17
NONYLPHENOL POLY(4+)ETHOXYLATE		17
alpha-4-Nonylphenyl-omega-hydroxypoly(oxyethylene) (b)	ALKARYL POLYETHERS (C9-C20)	17
Nopinene	BETA-PINENE	17
Nopinene	BETA-PINENE	17
NOXIOUS LIQUID, NF, (1) N.O.S. (TRADE NAME, CONTAINS) ST1, CAT. X		17
NOXIOUS LIQUID, F, (2) N.O.S. (TRADE NAME, CONTAINS) ST1, CAT. X		17
NOXIOUS LIQUID, NF, (3) N.O.S. (TRADE NAME, CONTAINS) ST2, CAT. X		17

Index Name	Product Name	Chapter
NOXIOUS LIQUID, F, (4) N.O.S. (TRADE NAME, CONTAINS) ST2, CAT. X		17
NOXIOUS LIQUID, NF, (5) N.O.S. (TRADE NAME, CONTAINS) ST2, CAT. Y		17
NOXIOUS LIQUID, F, (6) N.O.S. (TRADE NAME, CONTAINS) ST2, CAT. Y		17
NOXIOUS LIQUID, NF, (7) N.O.S. (TRADE NAME, CONTAINS) ST3, CAT. Y		17
NOXIOUS LIQUID, F, (8) N.O.S. (TRADE NAME, CONTAINS) ST3, CAT. Y		17
NOXIOUS LIQUID, NF, (9) N.O.S. (TRADE NAME, CONTAINS) ST3, CAT. Z		17
NOXIOUS LIQUID, F, (10) N.O.S. (TRADE NAME, CONTAINS) ST3, CAT. Z		17
NOXIOUS LIQUID, (11) N.O.S. (TRADE NAME, CONTAINS) CAT. Z		18
NON NOXIOUS LIQUID, (12) N.O.S. (TRADE NAME, CONTAINS) CAT. OS		18
Octadecan-1-ol	ALCOHOLS (C14-C18), PRIMARY, LINEAR AND ESSENTIALLY LINEAR	17
1-Octadecanol	ALCOHOLS (C14-C18), PRIMARY, LINEAR AND ESSENTIALLY LINEAR	17
OCTAMETHYLCYCLOTETRASIOXANE		17
Octanal (a)	OCTYL ALDEHYDES	17
OCTANE (ALL ISOMERS)		17
1-Octanethiol	N-OCTYL MERCAPTAN	17
OCTANOIC ACID (ALL ISOMERS)		17
OCTANOL (ALL ISOMERS)		17
Octan-1-ol (a)	OCTANOL (ALL ISOMERS)	17
OCTENE (ALL ISOMERS)		17
Octic acid (a)	OCTANOIC ACID (ALL ISOMERS)	17
Octoic acid (a)	OCTANOIC ACID (ALL ISOMERS)	17
Octyl acetate	N-OCTYL ACETATE	17
N-OCTYL ACETATE		17
Octyl acrylate	2-ETHYLHEXYL ACRYLATE	17
Octyl adipate	DI-(2-ETHYLHEXYL) ADIPATE	17
Octyl alcohol (a)	OCTANOL (ALL ISOMERS)	17
OCTYL ALDEHYDES		17
Octylcarbinol	NONYL ALCOHOL (ALL ISOMERS)	17
OCTYL DECYL ADIPATE		17
Octyl decyl phthalate (a)	DIALKYL (C7-C13) PHTHALATES	17
Octylic acid (a)	OCTANOIC ACID (ALL ISOMERS)	17
N-OCTYL MERCAPTAN		17
Octyl nitrate	ALKYL (C7-C9) NITRATES	17
Octyl nitrates (all isomers)	ALKYL (C7-C9) NITRATES	17
Octyl phthalate (a)	DIALKYL (C7-C13) PHTHALATES	17
Oenanthic acid	N-HEPTANOIC ACID	17
Oenanthylic acid	N-HEPTANOIC ACID	17
OFFSHORE CONTAMINATED BULK LIQUID P*		17
OFFSHORE CONTAMINATED BULK LIQUID S*		17

Index Name	Product Name	Chapter
Oil of Mirbane	NITROBENZENE	17
Oil of Myrbane	NITROBENZENE	17
Oil of turpentine	TURPENTINE	17
Oil of vitriol	SULPHURIC ACID	17
Oil of wintergreen	METHYL SALICYLATE	17
Oleamine	OLEYLAMINE	17
OLEFIN-ALKYL ESTER COPOLYMER (MOLECULAR WEIGHT 2000+)		17
OLEFIN MIXTURE (C7-C9) C8 RICH, STABILIZED		17
OLEFIN MIXTURES (C5-C7)		17
OLEFIN MIXTURES (C5-C15)		17
OLEFINS (C13+, ALL ISOMERS)		17
ALPHA-OLEFINS (C6-C18) MIXTURES		17
OLEIC ACID		17
OLEUM		17
OLEYLAMINE		17
OLIVE OIL		17
ORANGE JUICE (CONCENTRATED)		18
ORANGE JUICE (NOT CONCENTRATED)		18
Orthophosphoric acid	PHOSPHORIC ACID	17
Oxal	GLYOXAL SOLUTION (40% OR LESS)	17
Oxalaldehyde	GLYOXAL SOLUTION (40% OR LESS)	17
3-Oxapentane-1,5-diol	DIETHYLENE GLYCOL	17
1,4-Oxazinane	MORPHOLINE	17
2-Oxetanone	BETA-PROPIOLACTONE	17
Oxoacetic acid	GLYOXYLIC ACID SOLUTION (50 % OR LESS)	17
Oxoethanoic acid	GLYOXYLIC ACID SOLUTION (50 % OR LESS)	17
2,2'-Oxybis(1-chloropropane)	2,2'-DICHLOROISOPROPYL ETHER	17
2,2'-Oxybis(ethyleneoxy)diethanol	TETRAETHYLENE GLYCOL	17
2,2'-Oxybispropane	ISOPROPYL ETHER	17
2,2'-Oxydiethanol	DIETHYLENE GLYCOL	17
1,1'-Oxydipropen-2-ol	DIPROPYLENE GLYCOL	17
OXYGENATED ALIPHATIC HYDROCARBON MIXTURE		17
Oxymethylene	FORMALDEHYDE SOLUTIONS (45% OR LESS)	17
PALM ACID OIL		17
PALM FATTY ACID DISTILLATE		17
PALM KERNEL ACID OIL		17
PALM KERNEL FATTY ACID DISTILLATE		17
PALM KERNEL OIL		17
PALM KERNEL OLEIN		17
PALM KERNEL STEARIN		17
PALM MID-FRACTION		17

Index Name	Product Name	Chapter
PALM OIL		17
PALM OIL FATTY ACID METHYL ESTER		17
PALM OLEIN		17
PALM STEARIN		17
Paraffin	HYDROCARBON WAX	17
C9-C11 n-Paraffin	N-ALKANES (C9-C11)	17
Paraffin, food grade	PARAFFIN WAX, HIGHLY-REFINED	17
n-Paraffin (C9-C11)	N-ALKANES (C9-C11)	17
n-Paraffins (C10-C20) (a)	N-ALKANES (C10-C20)	17
Paraffin wax	HYDROCARBON WAX	17
Paraffin wax, cosmetic	PARAFFIN WAX, HIGHLY-REFINED	17
Paraffin wax feedstock	PARAFFIN WAX, SEMI-REFINED	17
PARAFFIN WAX, HIGHLY-REFINED		17
PARAFFIN WAX, SEMI-REFINED		17
Paraffin wax, technical	PARAFFIN WAX, SEMI-REFINED	17
PARALDEHYDE		17
PARALDEHYDE-AMMONIA REACTION PRODUCT		17
Petrolatum	HYDROCARBON WAX	17
Pelargonic acid	NONANOIC ACID (ALL ISOMERS)	17
Pelargonic alcohol	NONYL ALCOHOL (ALL ISOMERS)	17
PENTACHLOROETHANE		17
Pentadecanol (a)	ALCOHOLS (C13+)	17
1-Pentadecene	OLEFINS (C13+, ALL ISOMERS)	17
Pentadec-1-ene (a)	OLEFINS (C13+, ALL ISOMERS)	17
1,3-PENTADIENE		17
Penta-1,3-diene	1,3-PENTADIENE	17
1,3-PENTADIENE (GREATER THAN 50%), CYCLOPENTENE AND ISOMERS, MIXTURES		17
Pentaethylene glycol (a)	POLYETHYLENE GLYCOL	17
PENTAETHYLENEHEXAMINE		17
Pentalin	PENTACHLOROETHANE	17
Pentamethylene	CYCLOPENTANE	17
Pentanal	VALERALDEHYDE (ALL ISOMERS)	17
Pentane (a)	PENTANE (ALL ISOMERS)	17
PENTANE (ALL ISOMERS)		17
Pentanedial solutions, 50% or less	GLUTARALDEHYDE SOLUTIONS (50% OR LESS)	17
n-Pentane (a)	PENTANE (ALL ISOMERS)	17
PENTANOIC ACID		17
N-PENTANOIC ACID (64%)/2-METHYL BUTYRIC ACID (36%) MIXTURE		17
tert-Pentanoic acid	TRIMETHYLACETIC ACID	17
1-Pentanol	N-AMYL ALCOHOL	17
Pentan-1-ol	N-AMYL ALCOHOL	17
2-Pentanol	SEC-AMYL ALCOHOL	17
Pentan-2-ol	SEC-AMYL ALCOHOL	17

Index Name	Product Name	Chapter
3-Pentanol	SEC-AMYL ALCOHOL	17
Pentan-3-ol	SEC-AMYL ALCOHOL	17
1-Pentanol acetate (a)	AMYL ACETATE (ALL ISOMERS)	17
n-Pentanol	N-AMYL ALCOHOL	17
sec-Pentanol	SEC-AMYL ALCOHOL	17
tert-Pentanol	TERT-AMYL ALCOHOL	17
2-Pentanone	METHYL PROPYL KETONE	17
Pentan-2-one	METHYL PROPYL KETONE	17
Pentasodium diethylenetriaminepentaacetate solution	DIETHYLENETRIAMINEPENTAACETIC ACID, PENTASODIUM SALT SOLUTION	17
PENTENE (ALL ISOMERS)		17
Pent-1-ene (a)	PENTENE (ALL ISOMERS)	17
n-Pentene (a)	PENTENE (ALL ISOMERS)	17
Pentenes	PENTENE (ALL ISOMERS)	17
Pentyl acetate (a)	AMYL ACETATE (ALL ISOMERS)	17
sec-Pentyl acetate (a)	AMYL ACETATE (ALL ISOMERS)	17
Pentyl alcohol	N-AMYL ALCOHOL	17
sec-Pentyl alcohol	SEC-AMYL ALCOHOL	17
tert-Pentyl alcohol	TERT-AMYL ALCOHOL	17
Pentyl propanoate	N-PENTYL PROPIONATE	17
N-PENTYL PROPIONATE		17
PERCHLOROETHYLENE		17
Perchloromethane	CARBON TETRACHLORIDE	17
Perhydroazepine	HEXAMETHYLENEIMINE	17
Petrolatum, highly-refined	PARAFFIN WAX, HIGHLY-REFINED	17
Petrolatum, industrial grade	PARAFFIN WAX, SEMI-REFINED	17
Petrolatum, USP-grade	PARAFFIN WAX, HIGHLY-REFINED	17
Petroleum jelly, technical	PARAFFIN WAX, SEMI-REFINED	17
Phene	BENZENE AND MIXTURES HAVING 10% BENZENE OR MORE (I)	17
Phenic acid	PHENOL	17
PHENOL		17
2-Phenoxyethanol	ETHYLENE GLYCOL PHENYL ETHER	17
Phenyl alkane(C10-C21)sulphonate (a)	ALKYL SULPHONIC ACID ESTER OF PHENOL	17
Phenylamine	ANILINE	17
N-Phenylaniline	DIPHENYLAMINE (MOLTEN)	17
N-Phenylbenzenamine	DIPHENYLAMINE (MOLTEN)	17
1-Phenylbutane (a)	BUTYLBENZENE (ALL ISOMERS)	17
2-Phenylbutane (a)	BUTYLBENZENE (ALL ISOMERS)	17
Phenyl carbinol	BENZYL ALCOHOL	17
Phenyl 'cellosolve'	ETHYLENE GLYCOL PHENYL ETHER	17
Phenyl chloride	CHLOROBENZENE	17
1-Phenyldecane (b)	ALKYL(C9+)BENZENES	17
1-Phenyldodecane	ALKYL(C9+)BENZENES	17
Phenylethane	ETHYLBENZENE	17
Phenyl ether	DIPHENYL ETHER	17
Phenylethylene	STYRENE MONOMER	17

Index Name	Product Name	Chapter
1-(Phenylethyl)xylene	1-PHENYL-1-XYLYL ETHANE	17
Phenyl hydride	BENZENE AND MIXTURES HAVING 10% BENZENE OR MORE (I)	17
Phenyl hydroxide	PHENOL	17
Phenylic acid	PHENOL	17
Phenylmethane	TOLUENE	17
Phenylmethanol	BENZYL ALCOHOL	17
Phenylmethyl acetate	BENZYL ACETATE	17
1-Phenylpropane (a)	PROPYLBENZENE (ALL ISOMERS)	17
2-Phenylpropane (a)	PROPYLBENZENE (ALL ISOMERS)	17
2-Phenylpropene	ALPHA-METHYLSTYRENE	17
1-Phenyltetradecane	ALKYL(C9+)BENZENES	17
1-Phenyltridecane	ALKYL(C9+)BENZENES	17
1-Phenylundecane	ALKYL(C9+)BENZENES	17
Phenylxylylethane	1-PHENYL-1-XYLYL ETHANE	17
1-PHENYL-1-XYLYL ETHANE		17
1-Phenyl-1-(2,5-xylyl)ethane (a)	1-PHENYL-1-XYLYL ETHANE	17
1-Phenyl-1-(3,4-xylyl)ethane (a)	1-PHENYL-1-XYLYL ETHANE	17
PHOSPHATE ESTERS, ALKYL (C12-C14) AMINE		17
L-alpha-Phosphatidyl choline	LECITHIN	18
N-(phosphonomethyl)glycine	GLYPHOSATE SOLUTION (NOT CONTAINING SURFACTANT)	17
PHOSPHORIC ACID		17
PHOSPHORUS, YELLOW OR WHITE (*)		17
Phthalandione (molten)	PHTHALIC ANHYDRIDE (MOLTEN)	17
Phthalic acid anhydride (molten)	PHTHALIC ANHYDRIDE (MOLTEN)	17
Phthalic acid, diundecyl ester	DIUNDECYL PHTHALATE	17
PHTHALIC ANHYDRIDE (MOLTEN)		17
2-Picoline	2-METHYLPYRIDINE	17
3-Picoline	3-METHYLPYRIDINE	17
4-Picoline	4-METHYLPYRIDINE	17
alpha-Picoline	2-METHYLPYRIDINE	17
beta-Picoline	3-METHYLPYRIDINE	17
gamma-Picoline	4-METHYLPYRIDINE	17
Pimelic ketone	CYCLOHEXANONE	17
2-Pinene	ALPHA-PINENE	17
2(10)-Pinene	BETA-PINENE	17
ALPHA-PINENE		17
BETA-PINENE		17
PINE OIL		17
PIPERAZINE, 68% SOLUTION		17
2-Piperazin-1-ylethylamine	N-AMINOETHYLPIPERAZINE	17
Piperylene	1,3-PENTADIENE	17
Piperylene concentrates (Mixed)	1,3-PENTADIENE (GREATER THAN 50%), CYCLOPENTENE AND ISOMERS, MIXTURES	17
Pivalic acid	TRIMETHYLACETIC ACID	17
Poly(oxyethylene)	POLYETHER (MOLECULAR WEIGHT 1350+)	17

Index Name	Product Name	Chapter
Poly(oxyethyleneoxyethyleneoxyphthaloyl)	DIETHYLENE GLYCOL PHTHALATE	17
Poly(sodium carboxylatoethylene)	SODIUM POLY(4+)ACRYLATE SOLUTIONS	17
POLYACRYLIC ACID SOLUTION (40% OR LESS)		17
POLYALKYL (C18-C22) ACRYLATE IN XYLENE		17
POLYALKYLALKENAMINESUCCINIMIDE, MOLYBDENUM OXYSULPHIDE		17
POLY(2-8)ALKYLENE GLYCOL MONOALKYL(C1-C6) ETHER		17
POLY(2-8)ALKYLENE GLYCOL MONOALKYL (C1-C6) ETHER ACETATE		17
Poly (2-8) alkylene (C2-C3) glycols / Polyalkylene (C2-C10) glycol monoalkyl (C1-C4) ethers and their borate esters (a)	BRAKE FLUID BASE MIX: POLY(2-8)ALKYLENE (C2-C3) GLYCOLS/POLYALKYLENE (C2-C10) GLYCOLS MONOALKYL (C1-C4) ETHERS AND THEIR BORATE ESTERS	17
POLYALKYL (C10-C20) METHACRYLATE		17
POLYALKYL (C10-C18) METHACRYLATE/ETHYLENE-PROPYLENE COPOLYMER MIXTURE		17
POLYALUMINIUM CHLORIDE SOLUTION		17
POLYBUTENE		17
POLYBUTENYL SUCCINIMIDE		17
POLY(2+)CYCLIC AROMATICS		17
POLYETHER (MOLECULAR WEIGHT 1350+)		17
POLYETHYLENE GLYCOL		17
Poly(4-12)ethylene glycol alkyl(C7-C11)phenyl ether	NONYLPHENOL POLY(4+)ETHOXYLATE	17
POLYETHYLENE GLYCOL DIMETHYL ETHER		17
POLY(ETHYLENE GLYCOL) METHYLBUTENYL ETHER (MW>1000)		17
Polyethylene glycols, mono(p-nonylphenyl) ether (b)	ALKARYL POLYETHERS (C9-C20)	17
Poly(ethylene oxide) (molecular weight 1350+) (a)	POLYETHER (MOLECULAR WEIGHT 1350+)	17
POLYETHYLENE POLYAMINES		17
POLYETHYLENE POLYAMINES (MORE THAN 50% C5 -C20 PARAFFIN OIL)		17
POLYFERRIC SULPHATE SOLUTION		17
Polyglucitol	HYDROGENATED STARCH HYDROLYSATE	18
POLYGLYCERIN, SODIUM SALT SOLUTION (CONTAINING LESS THAN 3% SODIUM HYDROXIDE)		17
Polyglycitol syrup	HYDROGENATED STARCH HYDROLYSATE	18
POLY(IMINOETHYLENE)-GRAFT-N-POLY(ETHYLENEOXY) SOLUTION (90% OR LESS)		17
POLYISOBUTENAMINE IN ALIPHATIC (C10-C14) SOLVENT		17
(POLYISOBUTENE) AMINO PRODUCTS IN ALIPHATIC HYDROCARBONS		17
POLYISOBUTENYL ANHYDRIDE ADDUCT		17
POLY(4+)ISOBUTYLENE (MW>224)		17
POLYISOBUTYLENE (MW≤224)		17
POLYMETHYLENE POLYPHENYL ISOCYANATE		17
POLYOLEFIN (MOLECULAR WEIGHT 300+)		17
POLYOLEFIN AMIDE ALKENEAMINE (C17+)		17

Index Name	Product Name	Chapter
POLYOLEFIN AMIDE ALKENEAMINE BORATE (C28-C250)		17
POLYOLEFIN AMIDE ALKENEAMINE POLYOL		17
POLYOLEFINAMINE (C28-C250)		17
POLYOLEFINAMINE IN ALKYL (C2-C4) BENZENES		17
POLYOLEFINAMINE IN AROMATIC SOLVENT		17
POLYOLEFIN AMINOESTER SALTS (MOLECULAR WEIGHT 2000+)		17
POLYOLEFIN ANHYDRIDE		17
POLYOLEFIN ESTER (C28-C250)		17
POLYOLEFIN PHENOLIC AMINE (C28-C250)		17
POLYOLEFIN PHOSPHOROSULPHIDE, BARIUM DERIVATIVE (C28-C250)		17
Poly(oxyalkylene)alkenyl ether (MW>1000)	POLY(ETHYLENE GLYCOL) METHYLBUTENYL ETHER (MW>1000)	17
Poly(oxy-1,2-ethanediyl), alpha-(3-methyl-3-butenyl)-, omega-hydroxy-	POLY(ETHYLENE GLYCOL) METHYLBUTENYL ETHER (MW>1000)	17
POLY(20)OXYETHYLENE SORBITAN MONOOLEATE		17
Poly(oxypropylene) (molecular weight 1350+) (a)	POLYETHER (MOLECULAR WEIGHT 1350+)	17
poly[(phenyl isocyanate)-alt-formaldehyde] (a)	POLYMETHYLENE POLYPHENYL ISOCYANATE	17
Poly[(phenyl isocyanate)-co-formaldehyde] (a)	POLYMETHYLENE POLYPHENYL ISOCYANATE	17
Poly[propene oxide]	POLYETHER (MOLECULAR WEIGHT 1350+)	17
Polypropylene	POLY(5+)PROPYLENE	17
POLY(5+)PROPYLENE		17
POLYPROPYLENE GLYCOL		17
POLYSILOXANE		17
Potash lye solution	POTASSIUM HYDROXIDE SOLUTION (*)	17
Potassium chloride brine (<26%)	POTASSIUM CHLORIDE SOLUTION (LESS THAN 26%)	18
Potassium chloride drilling brine	POTASSIUM CHLORIDE SOLUTION	17
POTASSIUM CHLORIDE SOLUTION		17
POTASSIUM CHLORIDE SOLUTION (LESS THAN 26%)		18
POTASSIUM FORMATE SOLUTIONS (*)		17
POTASSIUM HYDROXIDE SOLUTION (*)		17
POTASSIUM OLEATE		17
POTASSIUM THIOSULPHATE (50% OR LESS)		17
Propanal	PROPIONALDEHYDE	17
Propan-1-amine	N-PROPYLAMINE	17
2-Propanamine	ISOPROPYLAMINE	17
1,2-Propanediol	PROPYLENE GLYCOL	18
Propane-1,2-diol	PROPYLENE GLYCOL	18
1,2-Propanediol cyclic carbonate	PROPYLENE CARBONATE	17
Propanenitrile	PROPIONITRILE	17
1,2,3-Propanetriol	GLYCERINE	17
Propane-1,2,3-triol	GLYCERINE	17
1,2,3-Propanetriol triacetate	GLYCERYL TRIACETATE	17

Index Name	Product Name	Chapter
Propanoic acid	PROPIONIC ACID	17
Propanoic anhydride	PROPIONIC ANHYDRIDE	17
Propanol	N-PROPYL ALCOHOL	17
1-Propanol	N-PROPYL ALCOHOL	17
Propan-1-ol	N-PROPYL ALCOHOL	17
2-Propanol	ISOPROPYL ALCOHOL	18
Propan-2-ol	ISOPROPYL ALCOHOL	18
N-PROPANOLAMINE		17
3-Propanolide	BETA-PROPIOLACTONE	17
n-Propanol	N-PROPYL ALCOHOL	17
Propanone	ACETONE	18
2-Propanone	ACETONE	18
Propan-2-one	ACETONE	18
Propenamide solution, 50% or less	ACRYLAMIDE SOLUTION (50% OR LESS)	17
2-PROPENE-1-AMINIUM, N,N-DIMETHYL-N-2-PROPENYL-, CHLORIDE, HOMOPOLYMER SOLUTION		17
Propenenitrile	ACRYLONITRILE	17
Propene oxide	PROPYLENE OXIDE	17
Propenoic acid	ACRYLIC ACID	17
2-Propenoic acid, homopolymer solution (40% or less)	POLYACRYLIC ACID SOLUTION (40% OR LESS)	17
1-Propenol-3	ALLYL ALCOHOL	17
2-Propen-1-ol	ALLYL ALCOHOL	17
Prop-2-en-1-ol	ALLYL ALCOHOL	17
Propenyl alcohol	ALLYL ALCOHOL	17
Propiolactone	BETA-PROPIOLACTONE	17
BETA-PROPIOLACTONE		17
PROPIONALDEHYDE		17
PROPIONIC ACID		17
Propionic aldehyde	PROPIONALDEHYDE	17
PROPIONIC ANHYDRIDE		17
PROPIONITRILE		17
beta-Propionolactone	BETA-PROPIOLACTONE	17
Propiononitrile	PROPIONITRILE	17
Propionyl oxide	PROPIONIC ANHYDRIDE	17
1-Propoxypropan-2-ol (a)	PROPYLENE GLYCOL MONOALKYL ETHER	17
Propyl acetate	N-PROPYL ACETATE	17
N-PROPYL ACETATE		17
Propyl acetone	METHYL BUTYL KETONE	17
Propyl alcohol	N-PROPYL ALCOHOL	17
2-Propyl alcohol	ISOPROPYL ALCOHOL	18
N-PROPYL ALCOHOL		17
sec-Propyl alcohol	ISOPROPYL ALCOHOL	18
Propyl aldehyde	PROPIONALDEHYDE	17
Propylamine	N-PROPYLAMINE	17
N-PROPYLAMINE		17

Index Name	Product Name	Chapter
PROPYLBENZENE (ALL ISOMERS)		17
n-Propylbenzene (a)	PROPYLBENZENE (ALL ISOMERS)	17
Propylcarbinol	N-BUTYL ALCOHOL	18
Propylene aldehyde	CROTONALDEHYDE	17
2,2'-[Propylenebis(nitrilomethylene)]diphenol in aromatic solvent	ALKYL (C8-C9) PHENYLAMINE IN AROMATIC SOLVENTS	17
PROPYLENE CARBONATE		17
Propylene chloride	1,2-DICHLOROPROPANE	17
Propylene dichloride	1,2-DICHLOROPROPANE	17
alpha,alpha'- (Propylenedinitrilo)di-o-cresol in aromatic solvent	ALKYL (C8-C9) PHENYLAMINE IN AROMATIC SOLVENTS	17
Propylene epoxide	PROPYLENE OXIDE	17
PROPYLENE GLYCOL		18
1,2-Propylene glycol	PROPYLENE GLYCOL	18
Propylene glycol n-butyl ether (a)	PROPYLENE GLYCOL MONOALKYL ETHER	17
Propylene glycol ethyl ether (a)	PROPYLENE GLYCOL MONOALKYL ETHER	17
Propylene glycol methyl ether (a)	PROPYLENE GLYCOL MONOALKYL ETHER	17
PROPYLENE GLYCOL METHYL ETHER ACETATE		17
PROPYLENE GLYCOL MONOALKYL ETHER		17
Propylene glycol monobutyl ether (a)	PROPYLENE GLYCOL MONOALKYL ETHER	17
Propylene glycol beta-monoethyl ether	PROPYLENE GLYCOL MONOALKYL ETHER	17
Propylene glycol monomethyl ether (a)	PROPYLENE GLYCOL MONOALKYL ETHER	17
PROPYLENE GLYCOL PHENYL ETHER		17
Propylene glycol propyl ether (a)	PROPYLENE GLYCOL MONOALKYL ETHER	17
Propylene glycol trimer	TRIPROPYLENE GLYCOL	17
1,2-Propylene glycol trimer	TRIPROPYLENE GLYCOL	17
PROPYLENE OXIDE		17
PROPYLENE TETRAMER		17
PROPYLENE TRIMER		17
Propylethylene (a)	PENTENE (ALL ISOMERS)	17
Propyl methyl ketone	METHYL PROPYL KETONE	17
N-Propyl-1-propanamine	DI-N-PROPYLAMINE	17
Pseudobutylene glycol	BUTYLENE GLYCOL	17
Pseudocumene	TRIMETHYLBENZENE (ALL ISOMERS)	17
Pseudopinene	BETA-PINENE	17
Psuedopinene	BETA-PINENE	17
Pygas	PYROLYSIS GASOLINE (CONTAINING BENZENE)	17
PYRIDINE		17
Pyroacetic acid	ACETONE	18
Pyroacetic ether	ACETONE	18
PYROLYSIS GASOLINE (CONTAINING BENZENE)		17
Pyrolysis gasoline (steam-cracked naphtha)	BENZENE AND MIXTURES HAVING 10% BENZENE OR MORE (I)	17
Pyrolysis gasoline, containing 10% or more benzene	BENZENE AND MIXTURES HAVING 10% BENZENE OR MORE (I)	17
Pyromucic aldehyde	FURFURAL	17

Index Name	Product Name	Chapter
RAPESEED OIL		17
RAPESEED OIL (LOW ERUCIC ACID CONTAINING LESS THAN 4% FREE FATTY ACIDS)		17
RAPE SEED OIL FATTY ACID METHYL ESTERS		17
Refined, bleached, deodorised grape seed oil (RBD)	GRAPE SEED OIL	17
RESIN OIL, DISTILLED		17
RICE BRAN OIL		17
ROSIN		17
SAFFLOWER OIL		17
Saturated fatty acid (C13 and above) (a)	FATTY ACID (SATURATED C13+)	17
SHEA BUTTER		17
Silicofluoric acid solution (20-30%)	FLUOROSILICIC ACID SOLUTION (20-30%)	17
Slack wax	HYDROCARBON WAX	17
Sludge acid	SULPHURIC ACID, SPENT	17
SME	SOYBEAN OIL FATTY ACID METHYL ESTER	17
Soda ash solution	SODIUM CARBONATE SOLUTION (*)	17
Soda lye solution	SODIUM HYDROXIDE SOLUTION (*)	17
SODIUM ACETATE SOLUTIONS		18
Sodium acid sulphite solution (45% or less)	SODIUM HYDROGEN SULPHITE SOLUTION (45% OR LESS)	17
Sodium alkylbenzene sulphonate solution	ALKYLBENZENE SULPHONIC ACID, SODIUM SALT SOLUTION	17
SODIUM ALKYL (C14-C17) SULPHONATES (60-65% SOLUTION)		17
SODIUM ALUMINOSILICATE SLURRY		17
Sodium aminoacetate solution	GLYCINE, SODIUM SALT SOLUTION	17
SODIUM BENZOATE		17
Sodium 1,3-benzothiazole-2-thiolate solution	MERCAPTOBENZOTHIAZOL, SODIUM SALT SOLUTION	17
Sodium 1,3-benzothiazol-2-yl sulphide solution	MERCAPTOBENZOTHIAZOL, SODIUM SALT SOLUTION	17
SODIUM BICARBONATE SOLUTION (LESS THAN 10%)		18
Sodium bichromate solution (70% or less)	SODIUM DICHROMATE SOLUTION (70% OR LESS)	17
Sodium bisulphide solution (45% or less)	SODIUM HYDROSULPHIDE SOLUTION (45% OR LESS) (*)	17
SODIUM BOROHYDRIDE (15% OR LESS)/SODIUM HYDROXIDE SOLUTION (*)		17
SODIUM BROMIDE SOLUTION (LESS THAN 50%) (*)		17
SODIUM CARBONATE SOLUTION (*)		17
Sodium carboxylate solution	CYCLOHEXANE OXIDATION PRODUCTS, SODIUM SALTS SOLUTION	17
SODIUM CHLORATE SOLUTION (50% OR LESS) (*)		17
Sodium cresylate solution	CRESYLIC ACID, SODIUM SALT SOLUTION	17
SODIUM DICHROMATE SOLUTION (70% OR LESS)		17
Sodium glycinate solution	GLYCINE, SODIUM SALT SOLUTION	17
Sodium hydrate solution	SODIUM HYDROXIDE SOLUTION (*)	17
SODIUM HYDROGEN SULPHIDE (6% OR LESS)/SODIUM CARBONATE (3% OR LESS) SOLUTION		17

Index Name	Product Name	Chapter
Sodium hydrogensulphide solution (45% or less)	SODIUM HYDROSULPHIDE SOLUTION (45% OR LESS) (*)	17
SODIUM HYDROGEN SULPHITE SOLUTION (45% OR LESS)		17
SODIUM HYDROSULPHIDE/AMMONIUM SULPHIDE SOLUTION (*)		17
SODIUM HYDROSULPHIDE SOLUTION (45% OR LESS) (*)		17
SODIUM HYDROXIDE SOLUTION (*)		17
SODIUM HYPOCHLORITE SOLUTION (15% OR LESS)		17
Sodium lignosulphonate	LIGNINSULPHONIC ACID, SODIUM SALT SOLUTION	17
Sodium methanolate	SODIUM METHYLATE 21-30% IN METHYL ALCOHOL	17
Sodium methoxide	SODIUM METHYLATE 21-30% IN METHYL ALCOHOL	17
SODIUM METHYLATE 21-30% IN METHYL ALCOHOL		17
Sodium methylcarbamdithioate	METAM SODIUM SOLUTION	17
Sodium N-methyldithiocarbamate	METAM SODIUM SOLUTION	17
Sodium methyldithiocarbamate solution	METAM SODIUM SOLUTION	17
SODIUM NITRITE SOLUTION		17
SODIUM PETROLEUM SULPHONATE		17
SODIUM POLY(4+)ACRYLATE SOLUTIONS		17
Sodium rhodanate solution (56% or less)	SODIUM THIOCYANATE SOLUTION (56% OR LESS)	17
Sodium rhodanide solution (56% or less)	SODIUM THIOCYANATE SOLUTION (56% OR LESS)	17
Sodium salt of sulphonated naphthalene - formaldehyde condensate	NAPHTHALENESULPHONIC ACID-FORMALDEHYDE COPOLYMER, SODIUM SALT SOLUTION	17
SODIUM SILICATE SOLUTION		17
SODIUM SULPHATE SOLUTIONS		17
SODIUM SULPHIDE SOLUTION (15% OR LESS)		17
SODIUM SULPHITE SOLUTION (25% OR LESS)		17
Sodium sulphocyanate solution (56% or less)	SODIUM THIOCYANATE SOLUTION (56% OR LESS)	17
Sodium sulphocyanide solution (56% or less)	SODIUM THIOCYANATE SOLUTION (56% OR LESS)	17
Sodium tetrahydroborate (15% or less) / sodium hydroxide solution	SODIUM BOROHYDRIDE (15% OR LESS)/SODIUM HYDROXIDE SOLUTION (*)	17
SODIUM THIOCYANATE SOLUTION (56% OR LESS)		17
Sodium tolyl oxides solution	CRESYLIC ACID, SODIUM SALT SOLUTION	17
'D-D Soil fumigant'	DICHLOROPROPENE/DICHLOROPROPANE MIXTURES	17
d-Sorbitol solution	SORBITOL SOLUTION	18
SORBITOL SOLUTION		18
d-Sorbitol solution	SORBITOL SOLUTION	18
SOYABEAN OIL		17
Soya Methyl Ester (SME)	SOYBEAN OIL FATTY ACID METHYL ESTER	17
SOYBEAN OIL FATTY ACID METHYL ESTER		17
Soybean Oil Methyl Ester	SOYBEAN OIL FATTY ACID METHYL ESTER	17
Spirit of turpentine	TURPENTINE	17

Index Name	Product Name	Chapter
Spirits of wine	ETHYL ALCOHOL	18
Stoddard solvent	WHITE SPIRIT, LOW (15-20%) AROMATIC	17
STYRENE MONOMER		17
Styrol	STYRENE MONOMER	17
Suberane	CYCLOHEPTANE	17
Sulfonic acid, alkane(C10-C21) phenyl ester (a)	ALKYL SULPHONIC ACID ESTER OF PHENOL	17
SULPHOHYDROCARBON (C3-C88)		17
SULPHOLANE		17
SULPHONATED POLYACRYLATE SOLUTION		18
SULPHUR (MOLTEN) (*)		17
SULPHURIC ACID		17
Sulphuric acid, fuming	OLEUM	17
SULPHURIC ACID, SPENT		17
Sulphuric chlorohydrin	CHLOROSULPHONIC ACID	17
Sulphuric ether	DIETHYL ETHER (*)	17
SULPHURIZED FAT (C14-C20)		17
SULPHURIZED POLYOLEFINAMIDE ALKENE (C28-C250) AMINE		17
SUNFLOWER SEED OIL		17
Sweet-birch oil	METHYL SALICYLATE	17
sym-Dichloroethane	ETHYLENE DICHLORIDE	17
sym-Dichloroethyl ether	DICHLOROETHYL ETHER	17
sym-Diisopropylacetone	DIISOBUTYL KETONE	17
sym-Dimethylethylene glycol	BUTYLENE GLYCOL	17
sym-Tetrachloroethane	TETRACHLOROETHANE	17
sym-Trioxane	1,3,5-TRIOXANE	17
TALL OIL, CRUDE		17
TALL OIL, DISTILLED		17
TALL OIL FATTY ACID (RESIN ACIDS LESS THAN 20%)		17
TALL OIL PITCH		17
TALL OIL SOAP, CRUDE		17
TALLOW		17
TALLOW FATTY ACID		17
Tar acids (cresols)	CREOLS (ALL ISOMERS)	17
Tar camphor	NAPHTHALENE (MOLTEN)	17
Terephthalic acid, dibutyl ester	DIBUTYL TEREPHTHALATE	17
3,6,9,12-Tetraazatetradecamethylenediamine	PENTAETHYLENEHEXAMINE	17
3,6,9,12-Tetraazatetradecane-1,14-diamine	PENTAETHYLENEHEXAMINE	17
1,3,5,7-Tetraazatricyclo[3.3.1.1 ^{3,7}]decane	HEXAMETHYLENETETRAMINE SOLUTIONS	17
TETRACHLOROETHANE		17
1,1,2,2-Tetrachloroethane	TETRACHLOROETHANE	17
Tetrachloroethylene	PERCHLOROETHYLENE	17
1,1,2,2-tetrachloroethylene	PERCHLOROETHYLENE	17
Tetrachloromethane	CARBON TETRACHLORIDE	17

Index Name	Product Name	Chapter
Tetradecan-1-ol	ALCOHOLS (C14-C18), PRIMARY, LINEAR AND ESSENTIALLY LINEAR	17
1-Tetradecanol	ALCOHOLS (C14-C18), PRIMARY, LINEAR AND ESSENTIALLY LINEAR	17
Tetradecene (a)	OLEFINS (C13+, ALL ISOMERS)	17
Tetradecylbenzene	ALKYL(C9+)BENZENES	17
TETRAETHYLENE GLYCOL		17
TETRAETHYLENE PENTAMINE		17
Tetraethyllead	MOTOR FUEL ANTI-KNOCK COMPOUND (CONTAINING LEAD ALKYL)	17
Tetraethylplumbane	MOTOR FUEL ANTI-KNOCK COMPOUND (CONTAINING LEAD ALKYL)	17
TETRAETHYL SILICATE MONOMER/OLIGOMER (20% IN ETHANOL)		18
3a,4,7,7a-Tetrahydro-3,5-dimethyl-4,7-methano-1H-indene	METHYLCYCLOPENTADIENE DIMER	17
TETRAHYDROFURAN		17
TETRAHYDRONAPHTHALENE		17
1,2,3,4-Tetrahydronaphthalene	TETRAHYDRONAPHTHALENE	17
Tetrahydro-1,4-oxazine	MORPHOLINE	17
2H-Tetrahydro-1,4-oxazine	MORPHOLINE	17
Tetrahydro-2H-1,4-oxazine	MORPHOLINE	17
Tetrahydrothiophene-1-dioxide	SULPHOLANE	17
Tetrahydrothiophene 1,1-dioxide	SULPHOLANE	17
Tetralin	TETRAHYDRONAPHTHALENE	17
TETRAMETHYLBENZENE (ALL ISOMERS)		17
1,2,3,4-Tetramethylbenzene (a)	TETRAMETHYLBENZENE (ALL ISOMERS)	17
1,2,3,5-Tetramethylbenzene (a)	TETRAMETHYLBENZENE (ALL ISOMERS)	17
1,2,4,5-Tetramethylbenzene (a)	TETRAMETHYLBENZENE (ALL ISOMERS)	17
Tetramethylene cyanide	ADIPONITRILE	17
Tetramethylene dicyanide	ADIPONITRILE	17
Tetramethylene glycol (a)	BUTYLENE GLYCOL	17
Tetramethylene oxide	TETRAHYDROFURAN	17
Tetramethylenesulphone	SULPHOLANE	17
Tetramethyllead	MOTOR FUEL ANTI-KNOCK COMPOUND (CONTAINING LEAD ALKYL)	17
Tetrapropylbenzene	ALKYL(C9+)BENZENES	17
Tetrapropylenebenzene	DODECYLBENZENE	17
Tetryl formate	ISOBUTYL FORMATE	17
4-thiapentanal	3-(METHYLTHIO)PROPIONALDEHYDE	17
Thiophan sulphone	SULPHOLANE	17
Thiosulphuric acid, dipotassium salt (50% or less)	POTASSIUM THIOSULPHATE (50% OR LESS)	17
Titanium(IV) oxide slurry	TITANIUM DIOXIDE SLURRY	17
TITANIUM DIOXIDE SLURRY		17
TOLUENE		17
TOLUENEDIAMINE		17
2,4-Toluenediamine (a)	TOLUENEDIAMINE	17
2,6-Toluenediamine (a)	TOLUENEDIAMINE	17
TOLUENE DIISOCYANATE		17

Index Name	Product Name	Chapter
2-Toluidine	O-TOLUIDINE	17
O-TOLUIDINE		17
Toluol	TOLUENE	17
o-Tolylamine	O-TOLUIDINE	17
2,4-Tolylenediamine (a)	TOLUENEDIAMINE	17
2,6-Tolylenediamine (a)	TOLUENEDIAMINE	17
Tolylenediisocyanate	TOLUENE DIISOCYANATE	17
2,4-Tolylene diisocyanate	TOLUENE DIISOCYANATE	17
m-Tolylene diisocyanate	TOLUENE DIISOCYANATE	17
Toxilic anhydride	MALEIC ANHYDRIDE	17
Treacle (a)	MOLASSES	18
Triacetin	GLYOXAL SOLUTION (40% OR LESS)	17
3,6,9-Triazaundecamethylenediamine	TETRAETHYLENE PENTAMINE	17
3,6,9-Triazaundecane-1,11-diamine	TETRAETHYLENE PENTAMINE	17
TRIBUTYL PHOSPHATE		17
1,2,3-TRICHLOROENZENE (MOLTEN)		17
1,2,4-TRICHLOROENZENE		17
1,1,1-TRICHLOROETHANE		17
1,1,2-TRICHLOROETHANE		17
beta-Trichloroethane	1,1,2-TRICHLOROETHANE	17
Trichloroethene	TRICHLOROETHYLENE	17
TRICHLOROETHYLENE		17
Trichloromethane	CHLOROFORM	17
1,2,3-TRICHLOROPROPANE		17
1,1,2-TRICHLORO-1,2,2-TRIFLUOROETHANE		17
TRICRESYL PHOSPHATE (CONTAINING 1% OR MORE ORTHO-ISOMER)		17
TRICRESYL PHOSPHATE (CONTAINING LESS THAN 1% ORTHO-ISOMER)		17
TRIDECANE		17
TRIDECANOIC ACID		17
Tridecanol (a)	ALCOHOLS (C13+)	17
Tridecene (a)	OLEFINS (C13+, ALL ISOMERS)	17
Tridecoic acid	TRIDECANOIC ACID	17
TRIDECYL ACETATE		17
Tridecyl alcohol (a)	ALCOHOLS (C13+)	17
Tridecylbenzene	ALKYL(C9+)BENZENES	17
Tridecylic acid	TRIDECANOIC ACID	17
Tridecylic acid (a)	FATTY ACID (SATURATED C13+)	17
Tri(dimethylphenyl) phosphate (all isomers)	TRIXYLYL PHOSPHATE	17
TRIETHANOLAMINE		17
TRIETHYLAMINE		17
TRIETHYLBENZENE		17
TRIETHYLENE GLYCOL		18
Triethylene glycol butyl ether (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL(C1-C6) ETHER	17

Index Name	Product Name	Chapter
Triethylene glycol ethyl ether (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL(C1-C6) ETHER	17
Triethylene glycol methyl ether (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL(C1-C6) ETHER	17
Triethylene glycol monobutyl ether (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL(C1-C6) ETHER	17
TRIETHYLENETETRAMINE		17
TRIETHYL PHOSPHATE		17
TRIETHYL PHOSPHITE		17
Triformol	1,3,5-TRIOXANE	17
Triglycol	TRIETHYLENE GLYCOL	18
Trihydroxypropane	GLYCERINE	17
Trihydroxytriethylamine	TRIETHANOLAMINE	17
TRISOPROPANOLAMINE		17
TRISOPROPYLATED PHENYL PHOSPHATES		17
TRIMETHYLACETIC ACID		17
TRIMETHYLAMINE SOLUTION (30% OR LESS)		17
TRIMETHYLBENZENE (ALL ISOMERS)		17
1,2,3-Trimethylbenzene (a)	TRIMETHYLBENZENE (ALL ISOMERS)	17
1,2,4-Trimethylbenzene (a)	TRIMETHYLBENZENE (ALL ISOMERS)	17
1,3,5-Trimethylbenzene (a)	TRIMETHYLBENZENE (ALL ISOMERS)	17
2,6,6-Trimethylbicyclo[3.1.1]hept-2-ene	ALPHA-PINENE	17
Trimethylcarbinol	TERT-BUTYL ALCOHOL	17
1,1,3-Trimethyl-3-cyclohexene-5-one	ISOPHORONE	17
3,5,5-Trimethylcyclohex-2-enone	ISOPHORONE	17
3,5,5-Trimethylcyclohex-2-en-one	ISOPHORONE	17
TRIMETHYLOL PROPANE PROPOXYLATED		17
2,2,4-Trimethylpentane (a)	OCTANE (ALL ISOMERS)	17
2,2,4-TRIMETHYL-1,3-PENTANEDIOL DIISOBUTYRATE		17
2,2,4-Trimethylpentane-1,3-diol diisobutyrate	2,2,4-TRIMETHYL-1,3-PENTANEDIOL DIISOBUTYRATE	17
2,2,4-TRIMETHYL-1,3-PENTANEDIOL-1-ISOBUTYRATE		17
2,4,4-Trimethylpentene-1	DIISOBUTYLENE	17
2,4,4-Trimethylpent-1-ene	DIISOBUTYLENE	17
2,4,4-Trimethylpentene-2	DIISOBUTYLENE	17
2,4,4-Trimethylpent-2-ene	DIISOBUTYLENE	17
2,4,6-Trimethyl-1,3,5-trioxane	PARALDEHYDE	17
2,4,6-Trimethyl-s-trioxane	PARALDEHYDE	17
Trioxan	1,3,5-TRIOXANE	17
1,3,5-TRIOXANE		17
5,8,11-Trioxapentadecane	DIETHYLENE GLYCOL DIBUTYL ETHER	17
3,6,9-Trioxaundecane	DIETHYLENE GLYCOL DIETHYL ETHER	17
Trioxymethylene	1,3,5-TRIOXANE	17
Tripropylene	PROPYLENE TRIMER	17
TRIPROPYLENE GLYCOL		17
Tripropylene glycol methyl ether (a)	POLY(2-8)ALKYLENE GLYCOL MONOALKYL(C1-C6) ETHER	17

Index Name	Product Name	Chapter
Tris(dimethylphenyl) phosphate (all isomers)	TRIXYLYL PHOSPHATE	17
Tris(2-hydroxyethyl)amine	TRIETHANOLAMINE	17
2,4-D-tris(2-hydroxy-2-methylethyl)ammonium	2,4-DICHLOROPHENOXYACETIC ACID, TRIISOPROPANOLAMINE SALT SOLUTION	17
Tris(2-hydroxypropyl)amine	TRIISOPROPANOLAMINE	17
Tris(2-hydroxy-1-propyl)amine	TRIISOPROPANOLAMINE	17
Tris(2-hydroxypropyl)ammonium 2,4-dichlorophenoxyacetate solution	2,4-DICHLOROPHENOXYACETIC ACID, TRIISOPROPANOLAMINE SALT SOLUTION	17
Trisodium 2-[carboxylatomethyl(2-hydroxyethyl)amino]ethyliminodi(acetate) solution	N-(HYDROXYETHYL)ETHYLENEDIAMINETRIACETIC ACID, TRISODIUM SALT SOLUTION	17
Trisodium N-(carboxymethyl)-N'-(2-hydroxyethyl)-N,N'-ethylenediglycine solution	N-(HYDROXYETHYL)ETHYLENEDIAMINETRIACETIC ACID, TRISODIUM SALT SOLUTION	17
Trisodium N-(2-hydroxyethyl)ethylenediamine-N,N',N'-triacetate solution	N-(HYDROXYETHYL)ETHYLENEDIAMINETRIACETIC ACID, TRISODIUM SALT SOLUTION	17
Trisodium nitrilotriacetate solution	NITRILOTRIACETIC ACID, TRISODIUM SALT SOLUTION	17
Tritolyl phosphate, containing less than 1% ortho- isomer	TRICRESYL PHOSPHATE (CONTAINING LESS THAN 1% ORTHO-ISOMER)	17
Tritolyl phosphate, containing 1% or more ortho- isomer	TRICRESYL PHOSPHATE (CONTAINING 1% OR MORE ORTHO-ISOMER)	17
Trixylenyl phosphate	TRIXYLYL PHOSPHATE	17
TRIXYLYL PHOSPHATE		17
TUNG OIL		17
TURPENTINE		17
Turpentine oil	TURPENTINE	17
Turps	TURPENTINE	17
Type A Zeolite slurry (a)	SODIUM ALUMINOSILICATE SLURRY	17
1-Undecanecarboxylic acid	LAURIC ACID	17
N-Undecane (a)	N-ALKANES (C10-C20)	17
UNDECANOIC ACID		17
Undecan-1-ol	UNDECYL ALCOHOL	17
1-UNDECENE		17
Undec-1-ene	1-UNDECENE	17
UNDECYL ALCOHOL		17
Undecylbenzene	ALKYL(C9+)BENZENES	17
Undecylic acid	UNDECANOIC ACID	17
n-Undecylic acid	UNDECANOIC ACID	17
uns-Trimethylbenzene (a)	TRIMETHYLBENZENE (ALL ISOMERS)	17
unsym-Trichlorobenzene	1,2,4-TRICHLOROBENZENE	17
UREA/AMMONIUM NITRATE SOLUTION		17
UREA/AMMONIUM PHOSPHATE SOLUTION		17
UREA SOLUTION		17
USED COOKING OIL (M)		17
USED COOKING OIL (TRIGLYCERIDES, C16-C18 AND C18 UNSATURATED)** (M)		17
Valeral	VALERALDEHYDE (ALL ISOMERS)	17
VALERALDEHYDE (ALL ISOMERS)		17

Index Name	Product Name	Chapter
n-Valeraldehyde	VALERALDEHYDE (ALL ISOMERS)	17
Valerianic acid	PENTANOIC ACID	17
Valeric acid	PENTANOIC ACID	17
n-Valeric acid	PENTANOIC ACID	17
Valeric aldehyde	VALERALDEHYDE (ALL ISOMERS)	17
Valerone	DIISOBUTYL KETONE	17
Vaseline (cosmetic)	PARAFFIN WAX, HIGHLY-REFINED	17
VEGETABLE ACID OILS (M)		17
VEGETABLE FATTY ACID DISTILLATES (M)		17
VEGETABLE OIL MIXTURES, CONTAINING LESS THAN 15% FREE FATTY ACID (M)		17
VEGETABLE PROTEIN SOLUTION (HYDROLYSED)		18
Vinegar acid	ACETIC ACID	17
Vinegar naphtha	ETHYL ACETATE	17
VINYL ACETATE		17
Vinylbenzene	STYRENE MONOMER	17
Vinylcarbinol	ALLYL ALCOHOL	17
Vinyl cyanide	ACRYLONITRILE	17
vinyl ethanoate	VINYL ACETATE	17
VINYL ETHYL ETHER		17
Vinylformic acid	ACRYLIC ACID	17
VINYLDENE CHLORIDE		17
VINYL NEODECANOATE		17
VINYLTOLUENE		17
Vinytoluene (all isomers)	VINYLTOLUENE	17
Vinyl trichloride	1,1,2-TRICHLOROETHANE	17
Vitriol brown oil	SULPHURIC ACID	17
WATER		18
Water glass solutions	SODIUM SILICATE SOLUTION	17
White bole	KAOLIN SLURRY	18
White caustic solution	SODIUM HYDROXIDE SOLUTION (*)	17
WHITE SPIRIT, LOW (15-20%) AROMATIC		17
White tar	NAPHTHALENE (MOLTEN)	17
Wine (a)	ALCOHOLIC BEVERAGES, N.O.S.	18
Wintergreen oil	METHYL SALICYLATE	17
Wood alcohol	METHYL ALCOHOL (*)	17
WOOD LIGNIN WITH SODIUM ACETATE/OXALATE		17
Wood naphtha	METHYL ALCOHOL (*)	17
Wood spirit	METHYL ALCOHOL (*)	17
XYLENES		17
XYLENES/ETHYLBENZENE (10% OR MORE) MIXTURE		17
XYLENOL		17
Xylenol (all isomers)	XYLENOL	17
2,3-Xylenol (a)	XYLENOL	17
2,4-Xylenol (a)	XYLENOL	17

Index Name	Product Name	Chapter
2,5-Xylenol (a)	XYLENOL	17
2,6-Xylenol (a)	XYLENOL	17
3,4-Xylenol (a)	XYLENOL	17
3,5-Xylenol (a)	XYLENOL	17
Xylols	XYLENES	17
ZINC ALKARYL DITHIOPHOSPHATE (C7-C16)		17
ZINC ALKENYL CARBOXAMIDE		17
ZINC ALKYL DITHIOPHOSPHATE (C3-C14)		17
Zinc bromide drilling brine	DRILLING BRINES (CONTAINING ZINC CHLORIDE)	17
z-Octadec-9-enamine	OLEYLAMINE	17
(Z)-Octadec-9-enoic acid	OLEIC ACID	17
Z-Octadec-9-enoic acid	OLEIC ACID	17
(Z)-Octadec-9-enylamine	OLEYLAMINE	17

”

7 The complete text of chapter 21 is replaced by the following:

"Chapter 21

Criteria for assigning carriage requirements for products subject to the IBC Code

21.1 Introduction

21.1.1 The following criteria are used for the determination of pollution classification and assignment of appropriate carriage requirements for bulk liquid cargoes being assessed for entry into the IBC Code or lists 1, 3 or 4 of the MEPC.2/Circular.

21.1.2 In developing such criteria, every effort has been made to follow the criteria and cut-off points developed under the Globally Harmonized System (GHS).

21.1.3 Although the criteria are intended to be closely defined in order to establish a uniform approach, it must be emphasized that where human experience or other factors indicate the need for alternative arrangements, these shall always be taken into account. Where deviations from the criteria have been recognized, they shall be properly recorded with justifications.

21.2 Contents

21.2.1 This chapter contains the following:

- .1 minimum safety and pollution criteria for products subject to chapter 17 of the IBC Code;
- .2 criteria used to assign the minimum carriage requirements for products that meet the safety or pollution criteria to make them subject to chapter 17 of the IBC Code;
- .3 criteria used for determining special requirements in chapter 15 of the IBC Code to be included in *column o* of chapter 17 of the IBC Code;
- .4 criteria used for determining special requirements in chapter 16 of the IBC Code to be included in *column o* of chapter 17 of the IBC Code;
- .5 definitions of properties used within this chapter;
- .6 information on the use of the GESAMP Hazard Ratings; and
- .7 information on the application of the SVC/LC₅₀ ratio method.

21.2.2 The information included in parentheses following the classification criteria throughout this chapter refers to the GESAMP Hazard Profile ratings set out in appendix I of MARPOL Annex II under the "Abbreviated legend to the revised GESAMP Hazard Evaluation procedure". The full listing of GESAMP Hazard Profile ratings for evaluated substances are published annually in the GESAMP Composite List as a PPR Circular. It should be noted that ratings in parentheses (based on estimation methods applied by GESAMP) are considered as equivalent to ratings without parentheses for the purpose of assigning carriage requirements.

21.3 Minimum safety and pollution criteria for products subject to chapter 17 of the IBC Code

21.3.1 Products are deemed to be hazardous and subject to chapter 17 of the IBC Code if they meet one or more of the following criteria:

- .1 inhalation LC₅₀/ATE ≤ 20 mg/L/4h (see paragraph 21.7.1.3) (C3 = 1, 2, 3 or 4);
- .2 dermal LD₅₀/ATE ≤ 2000 mg/kg (see paragraph 21.7.1.2) (C2 = 1, 2, 3, or 4);
- .3 oral LD₅₀/ATE ≤ 2000 mg/kg (see paragraph 21.7.1.1) (C1 = 1, 2, 3, or 4);
- .4 toxic to mammals by prolonged exposure (see paragraph 21.7.2) (D3 = C, M, R, N, T, or I);
- .5 cause skin sensitization (see paragraph 21.7.3) (D3 = Ss);
- .6 cause respiratory sensitization (see paragraph 21.7.4) (D3 = Sr);
- .7 corrosive to skin (see paragraph 21.7.5) (D1 = 3, 3A, 3B, or 3C);
- .8 with a Water Reactive Index (WRI) of ≥ 1 (see paragraph 21.7.6);
- .9 require inertion, inhibition, stabilization, temperature control or tank environmental control in order to prevent a hazardous reaction (see definitions in paragraph 21.7.10);
- .10 flashpoint < 23°C; and have an explosive/flammability range (expressed as a percentage by volume in air) of ≥ 20%;
- .11 auto-ignition temperature of ≤ 200°C; and
- .12 classified as pollution category X or Y or meeting the criteria for rules 11 to 13 in table 2 in paragraph 21.4.5.2.

21.4 Criteria used to assign the minimum carriage requirements for products that meet the minimum safety or pollution criteria to make them subject to chapter 17 of the IBC Code

21.4.1 Column a – Product name

21.4.1.1 A standardized chemical name, preferably assigned on the basis of the Chemical Abstracts Service (CAS) or the International Union of Pure and Applied Chemistry (IUPAC) system, shall be used as far as possible. However, where this is unnecessarily complex, then a technically correct and unambiguous alternative name may be used.

21.4.2 Column b – Deleted

21.4.3 Column c – Pollution category

21.4.3.1 *Column c* identifies the pollution category assigned to each product in accordance with MARPOL Annex II, based on table 1 below (see MARPOL Annex II, appendix I).

Table 1 – Guidelines for the categorization of Noxious Liquid Substances

Rule	A1 Bio- accumulation	A2 Bio- degradation	B1 Acute toxicity	B2 Chronic toxicity	D3 Long-term health effects	E2 Effects on marine wildlife and on benthic habitats	Cat
1			≥ 5				X
2	≥ 4		4				
3		NR	4				
4	≥ 4	NR			CMRTNI ¹		
5			4				Y
6			3				
7			2				
8	≥ 4	NR		Not 0			
9				≥ 1			
10						Fp, F or S If not Inorganic	
11					CMRTNI ¹		
12	Any product not meeting the criteria of rules 1 to 11 and 13						Z
13	All products identified as: ≤ 2 in column A1; R in column A2; blank in column D3; not Fp, F or S (if not organic) in column E2; and 0 (zero) in all other columns of the GESAMP Hazard Profile						OS

21.4.4 Column d – Hazards

21.4.4.1 An "S" is assigned to *column d* if any of the safety criteria described in paragraphs 21.3.1.1 to 21.3.1.11 are met.

21.4.4.2 A "P" is assigned to *column d* if the product meets the criteria for assigning Ship Type 1 to 3 as defined by rules 1 to 14 in the table 2.

21.4.5 Column e – Ship Type

21.4.5.1 Assignment of Ship Types is carried out from both a pollution and safety perspective. The basic criteria for assigning Ship Types from a pollution perspective is carried out based on the GESAMP Hazard Profile, shown in table 2. An explanation of the details in the columns is provided in appendix I of MARPOL Annex II.

21.4.5.2 The following criteria are used to assign the Ship Type:

Ship Type 1:

- Inhalation LC₅₀/ATE ≤ 0.5 mg/L/4h (C3 = 4) and SVC/LC₅₀ ≥ 20; and/or
- Dermal LD₅₀/ATE ≤ 50 mg/kg (C2 = 4); and/or
- WRI = 3; and/or
- Auto-ignition temperature ≤ 65°C; and/or
- Explosive range ≥ 50% v/v in air and the flashpoint < 23°C; and/or

¹ Applies if the D3 rating contains any of these letters or any combination thereof.

Rules 1 or 2 of the table 2 shown in 21.4.5.2 (below).

Ship Type 2:

Inhalation LC₅₀/ATE ≤ 0.5 mg/L/4h (C3 = 4) and SVC/LC₅₀ < 20; or
 Inhalation LC₅₀/ATE > 0.5 mg/L/4h – ≤ 2mg/L/4h (C3 = 3) and SVC/LC₅₀ ≥ 2 (see note); and/or
 Dermal LD₅₀/ATE > 50 mg/kg – ≤ 200 mg/kg (C2 = 3); and/or
 WRI = 2; and/or
 Auto-ignition temperature ≤ 200°C; and/or
 Explosive range ≥ 40% v/v in air and the flashpoint < 23°C; and/or
 Any product meeting the criteria of rules 3 to 10 in table 2.

Note: Products with a density >1025 kg/m³ (sinkers) or a water solubility of >50% (dissolvers) that are assigned to Ship Type 2 based on the inhalation toxicity criteria, may be re-assigned to Ship Type 3.

Ship Type 3:

Any of the minimum safety or pollution criteria for bulk liquid cargoes subject to chapter 17 of the IBC Code not meeting the requirements for Ship Types 1 or 2 and not meeting rule 15 of table 2 shown in 21.4.5.2 (below).

Table 2 – Assignment of Ship Types based on the GESAMP Hazard Profile

Rule	A1	A2	B1	B2	D3	E2	Ship Type
1			≥ 5				1
2	≥ 4	NR	4		CMRTNI ²		
3	≥ 4	NR			CMRTNI ²		
4			4				2
5	≥ 4		3				
6		NR	3				
7				≥ 1			
8						Fp	
9					CMRTNI ²	F	
10			≥ 2			S	3
11	≥ 4						
12		NR					
13			≥ 1				
14	All other category Y Substances						NA
15	All other category Z Substances All "Other Substances" (OS)						

21.4.6 Column f – Tank type

21.4.6.1 The tank type is assigned according to the following criteria:

Tank type 1G: Inhalation LC₅₀/ATE ≤ 0.5 mg/L/4h (C3 = 4) and SVC/LC₅₀ ≥ 1000; and/or
 Dermal LD₅₀/ATE ≤ 50 mg/kg (C2 = 4); and/or;

² Applies if the D3 rating contains any of these letters or any combination thereof.

WRI=3; and/or
Auto-ignition temperature $\leq 65^{\circ}\text{C}$; and/or
Explosive range $\geq 40\%$ v/v in air and the flashpoint $< 23^{\circ}\text{C}$.
Based on expert judgement, tank type 1G may be required for specific products (e.g. for molten sulphur, hydrochloric acid)

Tank type 2G: Any of the minimum safety or pollution criteria for bulk liquid cargoes subject to chapter 17 or the IBC Code not meeting the requirements for tank type 1G.

21.4.7 Column g – Tank vents

21.4.7.1 The tank venting arrangements are assigned according to the following criteria:

Controlled: Inhalation $\text{LC}_{50}/\text{ATE} \leq 10 \text{ mg/L/4h}$ (C3 = 2, 3 or 4), unless in accordance with 21.7.12; and/or
Toxic to mammals by prolonged exposure (D3 = C, M, R, T, N, or I); and/or
Respiratory sensitizer (D3 = Sr, see also paragraph 21.7.4); and/or
Special carriage control needed; and/or
Flashpoint $\leq 60^{\circ}\text{C}$; and
Corrosive to skin ($\leq 4\text{h}$ exposure). (D1 = 3A, 3B, or 3C).

Open: Any of the minimum safety or pollution criteria for bulk liquid cargoes subject to chapter 17 or the IBC Code not meeting the requirements for controlled tank vents.

21.4.8 Column h – Tank environmental control

21.4.8.1 The tank environmental control conditions are assigned according to the following criteria:

Inert: Auto-ignition temperature $\leq 200^{\circ}\text{C}$; and/or
Reacts with air to cause a hazard; and/or
Explosive range $\geq 40\%$ and the flashpoint $< 23^{\circ}\text{C}$.
Dry: WRI > 1
Pad: Only applies to specific products identified on a case by case basis.
Vent: Only applies to specific products identified on a case by case basis.
No: Where the above criteria do not apply (inerting requirements may be required under SOLAS).

21.4.9 Column i – Electrical equipment

21.4.9.1 If the flashpoint of the product is $\leq 60^{\circ}\text{C}$ or the product is heated to within 15°C of its flashpoint then the electrical equipment required are assigned according to the following criteria, otherwise "-" is assigned in column i' and i'' :

.1 Column i' – Temperature class:

T1	Auto-ignition temperature $\geq 450^{\circ}\text{C}$
T2	Auto-ignition temperature $\geq 300^{\circ}\text{C}$ but $< 450^{\circ}\text{C}$
T3	Auto-ignition temperature $\geq 200^{\circ}\text{C}$ but $< 300^{\circ}\text{C}$
T4	Auto-ignition temperature $\geq 135^{\circ}\text{C}$ but $< 200^{\circ}\text{C}$
T5	Auto-ignition temperature $\geq 100^{\circ}\text{C}$ but $< 135^{\circ}\text{C}$
T6	Auto-ignition temperature $\geq 85^{\circ}\text{C}$ but $< 100^{\circ}\text{C}$

.2 **Column i'' – Apparatus group:**

Apparatus group	MESG at 20°C (mm)	MIC ratio product/methane
IIA	> 0.90	> 0.80
IIB	> 0.50 to ≤ 0.90	> 0.45 to ≤ 0.80
IIC	≤ 0.50	≤ 0.45

.1 The tests shall be carried out in accordance with the procedures described in IEC 60079-1-1:2002 and IEC 79-3.

.2 For gases and vapours it is sufficient to make only one determination of either the Maximum Experimental Safe Gap (MESG) or the Minimum Igniting Current (MIC) provided that:

for Group IIA: the MESG > 0.90 mm or the MIC ratio > 0.80
for Group IIB: the MESG is > 0.50 mm and ≤ 0.90 mm; or the MIC ratio is > 0.50 and ≤ 0.80
for Group IIC: the MESG is ≤ 0.50 mm or the MIC ratio is ≤ 0.45

.3 It is necessary to determine both the MESG and the MIC ratio when:

.1 The MIC ratio determination only has been made, and the ratio is between 0.80 and 0.90, when an MESG determination will be required;

.2 The MIC ratio determination only has been made, and the ratio is between 0.45 and 0.50, when an MESG determination will be required; or

.3 The MESG only has been found, and is between 0.50 mm and 0.55 mm, when an MIC ratio determination will be required.

.3 **Column i''' Flashpoint:**

> 60°C Yes
≤ 60°C No
Non-flammable NF

21.4.10 Column j – Gauging

21.4.10.1 The gauging equipment is assigned according to the following criteria:

Closed: Inhalation LC₅₀/ATE ≤ 2 mg/L/4h (C3 = 3 or 4), unless in accordance with 21.7.12; and/or
Dermal LD₅₀/ATE ≤ 1000 mg/kg (C2 = 2, 3 or 4); and/or
Toxic to mammals by prolonged exposure (D3 = C, M, R, T, N, or I); and/or
Respiratory sensitizer (D3 = Sr, see also paragraph 21.7.4); and/or
Severely corrosive to skin (≤ 3 min exposure) (D1= 3C).

- Restricted: Inhalation LC₅₀/ATE >2 - ≤10 mg/L/4h (C3 = 2), unless in accordance with 21.7.12; and/or
Special carriage control indicates inerting required; and/or
Highly corrosive to skin (> 3 min - ≤1h exposure) (D1 = 3B); and/or
Flashpoint ≤ 60°C.
- Open: Any of the minimum safety or pollution criteria for bulk liquid cargoes subject to chapter 17 or the IBC Code not meeting the requirements for closed or restricted gauging.

21.4.11 *Column k* – Vapour detection

21.4.11.1 The vapour detection equipment is assigned according to the following criteria:

- Toxic (T): Inhalation LC₅₀/ATE ≤ 10 mg/L/4h (C3 = 2, 3, or 4), unless in accordance with 21.7.12, and/or
Respiratory sensitizer (D3 = Sr, see also paragraph 21.7.4);
and/or
Toxic to mammals by prolonged exposure (D3 = C, M, R, T, N, or I)
- Flammable (F): Flashpoint ≤ 60°C
- No (No): Where the above criteria do not apply

21.4.12 *Column l* – Fire protection equipment

21.4.12.1 The appropriate fire-fighting media are defined as being appropriate according to the following criteria related to the properties of the product:

- | | | |
|----------------------------------|----|--|
| Solubility > 10% (> 100000 mg/L) | A | Alcohol-resistant foam |
| Solubility ≤ 10% (≤ 100000 mg/L) | A | Alcohol-resistant foam; and/or |
| | B | Regular foam |
| WRI = 0 | C | Water spray (generally used as a coolant and can be used with A and/or B providing that the WRI = 0) |
| | D | Dry chemical |
| WRI ≥1 | No | No requirements under this Code. This applies where a product is identified as NF in column i" (see paragraph 21.4.9.1.3). |

Note: all appropriate media shall be listed.

21.4.13 Column m – Deleted

21.4.14 Column n – Emergency equipment

21.4.14.1 The requirement to have personnel emergency equipment on board is identified by "Yes" in *column n* according to the following criteria:

Inhalation $LC_{50}/ATE \leq 2$ mg/L/4h (C3 = 3 or 4); unless in accordance with 21.7.12 and/or
Respiratory sensitizer (D3 = Sr, see also paragraph 21.7.4); and/or
Severely corrosive to skin (≤ 3 min exposure) (D1 = 3C); and/or
WRI = 2

No: indicates that the above criteria do not apply.

21.5 Column o – Criteria for special requirements in chapter 15

21.5.1 The assignment of special requirements in *column o* shall normally follow clear criteria based on the data supplied in the reporting form. Where it is considered appropriate to deviate from such criteria, this shall be clearly documented in such a way that it can easily be retrieved on demand.

21.5.2 The criteria for making reference to the special requirements identified in chapters 15 and 16 are defined below with comments where relevant.

21.5.3 Paragraphs 15.2 to 15.10 and 15.20

21.5.3.1 Paragraphs 15.2 to 15.10 and 15.20 identify specific products by name with special carriage requirements that cannot be easily accommodated in any other way.

21.5.4 Paragraph 15.11 – Acids

21.5.4.1 Paragraph 15.11 applies to all acids unless they:

- .1 are organic acids – when only paragraphs 15.11.2 to 15.11.4 and paragraphs 15.11.6 to 15.11.8 apply; or
- .2 do not evolve hydrogen – when paragraph 15.11.5 need not apply.

21.5.5 Paragraph 15.12 – Toxic products

21.5.5.1 All of paragraph 15.12 is added to *column o* according to the following criteria:

Inhalation $LC_{50}/ATE \leq 2$ mg/L/4h (C3 = 3 or 4), unless in accordance with 21.7.12; and/or
the product is a respiratory sensitizer (D3 = Sr, see also paragraph 21.7.4); and/or
the product is toxic to mammals by prolonged exposure (D3 = C, M, R, T, N, or I).

21.5.5.2 Paragraphs 15.12.3 and 15.12.4 are added to *column o* according to the following criterion:

Inhalation $LC_{50}/ATE > 2 - \leq 10$ mg/L/4h (C3 = 2), unless in accordance with 21.7.12.

21.5.5.3 Paragraph 15.12.3.2 is added to *column o* according to the following criteria:

Dermal $LD_{50}/ATE \leq 1000$ mg/kg (C2 = 2, 3, or 4); and/or
Oral $LD_{50}/ATE \leq 300$ mg/kg (C1 = 2, 3, or 4).

21.5.6 Paragraph 15.13 – Cargoes protected by additives

21.5.6.1 The requirement to assign paragraph 15.13 to *column o* is based on the information related to the product's tendency to polymerize, decompose, oxidize or undergo other chemical changes which may cause a hazard under normal carriage conditions, but which would be prevented by the addition of appropriate additives.

21.5.7 Paragraph 15.14 – Cargoes with a vapour pressure greater than atmospheric at 37.8°C

21.5.7.1 The requirement to assign paragraph 15.14 to *column o* is based on the following criterion:

Boiling point \leq 37.8°C

21.5.8 Paragraph 15.16 – Cargo contamination

21.5.8.1 Paragraph 15.16.1 is deleted.

21.5.8.2 Paragraph 15.16.2 is added to *column o* according to the following criterion:

WRI > 1

21.5.9 Paragraph 15.17 – Increased ventilation requirements

21.5.9.1 Paragraph 15.17 shall be added to *column o* according to the following criteria:

Inhalation LC₅₀/ATE > 0.5 - \leq 2 mg/L/4h (C3 = 3), unless in accordance with 21.7.12;
and/or
Respiratory sensitizer (D3 = Sr, see also paragraph 21.7.4); and/or
Toxic to mammals by prolonged exposure (D3 = C, M, R, T, N, or I); and/or
Highly to severely corrosive to skin (\leq 1h exposure time) (D1 = 3B or 3C).

21.5.10 Paragraph 15.18 – Special cargo pump-room requirements

21.5.10.1 Paragraph 15.18 shall be added to *column o* according to the following criterion:
Inhalation LC₅₀/ATE \leq 0.5 mg/L/4h (C3 = 4), unless in accordance with 21.7.12

21.5.11 Paragraph 15.19 – Overflow control

21.5.11.1 Paragraph 15.19 shall be added to *column o* according to the following criteria:

Inhalation LC₅₀/ATE \leq 2 mg/L/4h (C3 = 3 or 4), unless in accordance with 21.7.12;
and/or
Dermal LD₅₀/ATE \leq 1000 mg/kg (C2 = 2, 3, or 4); and/or
Oral LD₅₀/ATE \leq 300 mg/kg (C1 = 2, 3, or 4); and/or
Respiratory sensitizer (D3 = Sr, see also paragraph 21.7.4); and/or
Severely corrosive to skin (\leq 3 min exposure) (D1 = 3C); and/or
Auto-ignition temperature \leq 200°C; and/or
Explosive range \geq 40% v/v in air and flashpoint < 23°C; and/or
Classified as Ship Type 1 on pollution grounds.

21.5.11.2 Only paragraph 15.19.6 shall apply if the product has any of the following properties:

Inhalation $LC_{50}/ATE > 2 \text{ mg/L/4h} - \leq 10 \text{ mg/L/4h}$ ($C3 = 2$), unless in accordance with 21.7.12; and/or
Dermal $LD_{50}/ATE > 1000 \text{ mg/kg} - \leq 2000 \text{ mg/kg}$ ($C2 = 1$); and/or
Oral $LD_{50}/ATE > 300 \text{ mg/kg} - \leq 2000 \text{ mg/kg}$ ($C1 = 1$); and/or
Skin sensitizer ($D3=Ss$); and/or
Highly corrosive to skin ($> 3 \text{ min} - \leq 1 \text{ h}$ exposure) ($D1 = 3B$); and/or
Flashpoint $\leq 60^{\circ}\text{C}$; and/or
Classified as Ship Type 2 on pollution grounds; and/or
Pollution category X or Y.

21.5.12 Paragraph 15.21 – Temperature sensors

21.5.12.1 Paragraph 15.21 is added to *column o* according to the heat sensitivity of the product. This requirement is related to pumps in cargo pump-rooms only.

21.6 Column o – Criteria for special requirements in chapter 16

21.6.1 Paragraphs 16.1 to 16.2.5 and 16.3 to 16.5

21.6.1.1 These apply to all cargoes and so are not referenced specifically in *column o*.

21.6.2 Paragraph 16.2.6

21.6.2.1 Paragraph 16.2.6 is added to *column o* for products, which meet the following criteria: Pollution Category X or Y and viscosity $\geq 50 \text{ mPa}\cdot\text{s}$ at 20°C .

21.6.3 Paragraph 16.2.9

21.6.3.1 Paragraph 16.2.9 is added to *column o* for products, which meet the following criterion: Melting point $\geq 0^{\circ}\text{C}$.

21.6.4 Paragraph 16.6 – Cargo not to be exposed to excessive heat

21.6.4.1 Paragraphs 16.6.2 to 16.6.4 are added to *column o* for products, which are identified as requiring temperature control during carriage.

21.6.5 Paragraph 16.2.7 – Persistent floaters

Paragraph 16.2.7 is added to *column o* for products which meet the following criteria: Pollution Category Y that are persistent floaters ($E2 = Fp$) with a viscosity greater than or equal to $50 \text{ mPa}\cdot\text{s}$ at 20°C and/or with a melting point greater than or equal to 0°C .

21.7 Definitions

21.7.1 Acute mammalian toxicity

LC_{50} is the concentration in air, LD_{50} is the amount (dose) of test substance, which causes mortality to 50% of a test species. ATE refers to a dose (concentration) range or extrapolated dose (concentration) leading to lethal effects in mammals, equivalent to an LC_{50} or LD_{50} .

21.7.1.1 Acutely toxic if swallowed

Oral toxicity (LD ₅₀ /ATE)		GESAMP Hazard Profile Rating C1
Hazard Level	mg/kg	
High	≤ 5	4
Moderately High	> 5 - ≤ 50	3
Moderate	> 50 - ≤ 300	2
Slight	> 300 - ≤ 2000	1
Negligible	> 2000	0

21.7.1.2 Acutely toxic in contact with skin

Dermal toxicity (LD ₅₀ /ATE)		GESAMP Hazard Profile Rating C2
Hazard Level	mg/kg	
High	≤ 50	4
Moderately high	> 50 - ≤ 200	3
Moderate	> 200 - ≤ 1000	2
Slight	> 1000 - ≤ 2000	1
Negligible	> 2000	0

21.7.1.3 Acutely toxic by inhalation

All inhalation toxicity data are assumed to be for vapours and not mists or sprays, unless otherwise indicated.

Inhalation toxicity (LC ₅₀ /ATE)		GESAMP Hazard Profile Rating C3
Hazard level	mg/L/4h	
High	≤ 0.5	4
Moderately high	> 0.5 - ≤ 2	3
Moderate	> 2 - ≤ 10	2
Slight	> 10 - ≤ 20	1
Negligible	> 20	0

21.7.2 Toxic to mammals by prolonged exposure

21.7.2.1 A product is classified as *toxic to mammals by prolonged exposure* if it meets any of the following criteria: it is known to be, or suspected of being carcinogenic, mutagenic, reprotoxic, neurotoxic, immunotoxic or exposure below the lethal dose is known to cause Specific Target Organ Toxicity.

21.7.2.2 Such effects may be identified from the GESAMP Hazard Profile of the product (D3 = C, M, R, T, N, or I) or other recognized sources of such information.

21.7.3 Skin sensitization

21.7.3.1 A product is classified as a *skin sensitizer*:

- .1 if there is evidence in humans that the substance can induce sensitization by skin contact in a substantial number of persons; or
- .2 where there are positive results from an appropriate test.

21.7.3.2 Such effects are identified in the GESAMP Hazard Profile for the product (D3 = Ss).

21.7.4 Respiratory sensitization

21.7.4.1 A product is classified as a *respiratory sensitizer*:

- .1 if there is evidence in humans that the substance can induce specific respiratory hypersensitivity; and/or
- .2 where there are positive results from an appropriate test; and/or
- .3 where the product does not have a GESAMP Hazard Profile and is identified as a skin sensitizer and there is no evidence to show that it is not a respiratory sensitizer.

21.7.4.2 Such effects are identified in the GESAMP Hazard Profile for the product (D3 = Sr) or other recognized sources of such information, if no profile exists.

21.7.5 Corrosive to skin³

Hazard Level	Exposure time to cause full thickness necrosis of skin	GESAMP Hazard Profile Rating D1
Severely corrosive to skin	≤ 3 min	3C
Highly corrosive to skin	> 3 min - ≤ 1h	3B
Moderately corrosive to skin	> 1h - ≤ 4h	3A

Note: A rating of 3 or (3) in the D1 column of the GESAMP Hazard Profile without any additional letter notation (A, B or C), means that the severity of corrosivity has not been established. For such cases, a rating of 3 or (3) is understood to be equivalent to a rating of 3B for the purpose of assigning carriage requirements.

³ Products that are corrosive to skin are also deemed to be corrosive by inhalation.

21.7.6 Water reactive substances

21.7.6.1 These are classified as follows:

Water Reactive Index (WRI)	Definition
3	Any chemical which is extremely reactive with water and produces large quantities of flammable, toxic or corrosive gas or aerosol
2	Any chemical which, in contact with water, may produce a toxic, flammable or corrosive gas or aerosol
1	Any chemical which, in contact with water, may generate heat or produce a non-toxic, non-flammable or non-corrosive gas
0	Any chemical which, in contact with water, would not undergo a reaction to justify a value of 1, 2 or 3

21.7.7 Air reactive substances

21.7.7.1 Air reactive substances are products that react with air to cause a potentially hazardous situation, e.g. the formation of peroxides that may cause an explosive reaction.

21.7.8 Electrical apparatus – Temperature class

(for products which either have a flashpoint of $\leq 60^{\circ}\text{C}$ or are heated to within 15°C of their flashpoint)

21.7.8.1 The temperature class is defined by the International Electrotechnical Commission (IEC) as:

"The highest temperature attained under practical conditions of operation within the rating of the apparatus (and recognized overloads, if any, associated therewith) by any part of any surface, the exposure of which to an explosive atmosphere may involve a risk."

21.7.8.2 The temperature class of the electrical apparatus is assigned by selecting the Maximum Surface Temperature which is closest to, but less than, the product's auto-ignition temperature (see 21.4.9.1.1).

21.7.9 Electrical apparatus – Apparatus group

(for products with a flashpoint of $\leq 60^{\circ}\text{C}$)

21.7.9.1 This refers to intrinsically safe and associated electrical apparatus for explosive gas atmospheres which the IEC divide into the following groups:

Group I: for mines susceptible to firedamp (not used by IMO); and

Group II: for applications in other industries – further subdivided according to its Maximum Experimental Safe Gap (MESG) and/or the Minimum Igniting Current (MIC) of the gas/vapour into groups IIA, IIB and IIC.

21.7.9.2 This property cannot be determined from other data associated with the product; it has to be either measured or assigned by assimilation with related products in a homologous series.

21.7.10 Special carriage control conditions

21.7.10.1 Special carriage control conditions refer to specific measures that need to be taken in order to prevent a hazardous reaction. They include:

- .1 *Inhibition*: the addition of a compound (usually organic) that retards or stops an undesired chemical reaction such as corrosion, oxidation or polymerization;
- .2 *Stabilization*: the addition of a substance (stabilizer) that tends to keep a compound, mixture or solution from changing its form or chemical nature. Such stabilizers may retard a reaction rate, preserve a chemical equilibrium, act as antioxidants, keep pigments and other components in emulsion form or prevent the particles in colloidal suspension from precipitating;
- .3 *Inertion*: the addition of a gas (usually nitrogen) in the ullage space of a tank that prevents the formation of a flammable cargo/air mixture;
- .4 *Temperature control*: the maintenance of a specific temperature range for the cargo in order to prevent a hazardous reaction or to keep the viscosity low enough to allow the product to be pumped; and
- .5 *Padding and venting*: only applies to specific products identified on a case by case basis.

21.7.11 Flammable cargoes

21.7.11.1 A cargo is defined as flammable according to the following criteria:

IBC Code descriptor	Flashpoint (degrees Centigrade)
Highly flammable	< 23
Flammable	≤ 60 but ≥ 23

21.7.11.2 It should be noted that flashpoints of mixtures and aqueous solutions need to be measured unless all of the components are non-flammable.

21.7.11.3 It should be noted that the carriage of bulk liquid cargoes that have a flashpoint of ≤ 60°C are subject to other SOLAS regulations.

21.7.12 Application of the SVC/LC₅₀ ratio method

21.7.12.1 If the vapour pressure and the molecular weight of a substance are known, an estimate of the maximum vapour concentration in a closed compartment (e.g. a tank) can be calculated. This is called the Saturated Vapour Concentration (SVC).

21.7.12.2 The hazard quotient SVC/LC_{50}^4 is a substance specific value for the velocity of a vapour for achieving a hazardous concentration when emerging from a liquid source (e.g. leak, spillage or tank ventilation), and can be used in the assignment of specific carriage requirements related to inhalation toxicity.

21.7.12.3 If a solid substance is transported in an aqueous solution, the vapour pressure⁵ of this solid rather than that of water may be used in the calculation of the SVC/LC_{50} ratio.

21.7.12.4 Application of the SVC/LC_{50} ratio for assigning Ship Type and Tank type

21.7.12.4.1 For the assignment of Ship Type and tank type, as set out in paragraph 21.4.5 and 21.4.6, the application of the SVC/LC_{50} ratio method is optional. Should this method be used, the vapour pressure at 20°C shall be used when calculating the SVC/LC_{50} ratio.

21.7.12.4.2 The SVC mg/L of a substance should be calculated as follows:

$$SVC(mg/L) = \left(\frac{\text{Vapour pressure @ } 20^{\circ} C (Pa)}{101300 (Pa)} \times 10^6 \right) \times \frac{M_w \left(\frac{g}{mol} \right)}{24(L/mol) \times 1000}$$

where M_w is the molecular weight of the substance.

21.7.12.4.3 The SVC/LC_{50} ratio should be calculated as follows:

$$SVC/LC_{50} = \frac{SVC(mg/L)}{LC_{50}mg/L/4h}$$

21.7.12.5 Application of the SVC/LC_{50} ratio for assigning carriage requirements

21.7.12.5.1 For the carriage requirements listed in 21.7.12.5.5, the application of the SVC/LC_{50} ratio method is optional. If the SVC/LC_{50} ratio method is used in the assignment of these carriage requirements, the vapour pressure at 40°C shall be used when calculating the SVC/LC_{50} ratio. If the carriage temperature is higher than 40°C, then the SVC/LC_{50} ratio should be calculated at that temperature.

21.7.12.5.2 The SVC (mg/l) of a substance should be calculated as follows:

$$SVC(mg/L) = \left(\frac{\text{Vapour pressure @ } 40^{\circ} C (Pa)}{101300(Pa)} \times 10^6 \right) \times \frac{M_w \left(\frac{g}{mol} \right)}{26 (L/mol) \times 1000}$$

where M_w is the molecular weight of the substance.

21.7.12.5.3 The SVC/LC_{50} ratio should be calculated as follows:

$$SVC/LC_{50} = \frac{SVC(mg/L)}{LC_{50}mg/L/4h}$$

⁴ ATE values can be considered as equivalent to LC_{50} values. See paragraph 21.7.1.

⁵ If this data is not available, an estimate may be used.

21.7.12.5.4 The SVC (mg/L) formula described in 21.7.12.5.2 is standardized for calculations at 40°C. When using the vapour pressure at higher temperatures in the calculations, the formula must be amended accordingly.

21.7.12.5.5 For the following carriage requirements, the SVC/LC₅₀ ratio method, calculated at 40°C or higher, may be used as an alternative to the acute inhalation toxicity criteria given in paragraphs 21.4 and 21.5:

.1 **Column g – Tank vents**

Assignment of controlled venting is not required based on the inhalation hazard only, if:

Inhalation LC₅₀/ATE ≤ 10 mg/L/4h (C3 = 2, 3, or 4) and SVC/LC₅₀ < 0.2

.2 **Column j – Gauging**

Closed gauging is not required based on the inhalation hazard only, if:

Inhalation LC₅₀/ATE ≤ 2 mg/L/4h (C3 = 3 or 4) and SVC/LC₅₀ < 0.2 but restricted gauging is required.

Restricted gauging is not required based on the inhalation hazard only, if:

Inhalation LC₅₀/ATE > 2 - ≤ 10 mg/L/4h (C3 = 2) and SVC/LC₅₀ < 0.2

.3 **Column k – Vapour detection**

Assignment of toxic vapour detection is not required based on the inhalation hazard only, if:

Inhalation LC₅₀/ATE ≤ 10 mg/L/4h (C3 = 2, 3, or 4) and SVC/LC₅₀ < 0.2

.4 **Column n – Emergency Equipment**

Inhalation LC₅₀/ATE ≤ 2 mg/L/4h (C3 = 3 or 4) and SVC/LC₅₀ < 0.2

.5 **Column o – Special requirements in chapter 15**

15.12.1 and 15.12.2 are not required based on the inhalation hazard only, if:

Inhalation LC₅₀/ATE ≤ 2 mg/L/4h (C3 = 3 or 4) and SVC/LC₅₀ < 0.2

15.12.3 and 15.12.4 are not required based on the inhalation hazard only, if:

Inhalation LC₅₀/ATE > 2 - ≤ 10 mg/L/4h (C3 = 2) and SVC/LC₅₀ < 0.2

15.17 is not required based on the inhalation hazard only, if:

Inhalation LC₅₀/ATE ≤ 0.5 mg/L/4h (C3 = 4) and SVC/LC₅₀ < 0.2

15.18 is not required based on the inhalation hazard only if:

Inhalation $LC_{50}/ATE \leq 0.5$ mg/L/4h (C3 = 4) and $SVC/LC_{50} < 0.2$

15.19 is not required based on the inhalation hazard only, if:

Inhalation $LC_{50}/ATE \leq 2$ mg/L/4h (C3 = 3 or 4) and $SVC/LC_{50} < 0.2$, but 15.19.6 applies

15.19.6 is not required based on the inhalation hazard only, if:

Inhalation $LC_{50}/ATE > 2 - \leq 10$ mg/L/4h (C3 = 2) and $SVC/LC_{50} < 0.2$ "

ANNEX 8

**RESOLUTION MEPC.319(74)
(adopted on 17 May 2019)**

**AMENDMENTS TO THE CODE FOR THE CONSTRUCTION AND EQUIPMENT OF
SHIPS CARRYING DANGEROUS CHEMICALS IN BULK (BCH CODE)**

(Special, operational and minimum requirements)

THE MARINE ENVIRONMENT PROTECTION COMMITTEE,

RECALLING Article 38(a) of the Convention on the International Maritime Organization concerning the functions of the Marine Environment Protection Committee conferred upon it by international conventions for the prevention and control of marine pollution from ships,

RECALLING ALSO resolution MEPC.20 (22) by which it adopted *The Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk* ("the BCH Code"), and resolution MEPC.16(22) by which the BCH Code has become mandatory under Annex II of the International Convention for the Prevention of Pollution from Ships, 1973, as modified by the Protocol of 1978 relating thereto (MARPOL),

RECALLING FURTHER article 16 of MARPOL and regulation 1.4 of MARPOL Annex II concerning the procedure for amending the BCH Code,

HAVING CONSIDERED, at its seventy-fourth session, proposed amendments to the BCH Code concerning special, operational and minimum requirements,

1 ADOPTS, in accordance with article 16(2)(d) of MARPOL, amendments to the BCH Code, the text of which is set out in the annex to the present resolution;

2 DETERMINES, in accordance with article 16(2)(f)(iii) of MARPOL, that the amendments to the BCH Code shall be deemed to have been accepted on 1 July 2020 unless, prior to that date, not less than one third of the Parties or Parties, the combined merchant fleets of which constitute not less than 50% of the gross tonnage of the world's merchant fleet, have communicated to the Organization their objection to the amendments;

3 INVITES the Parties to note that, in accordance with article 16(2)(g)(ii) of MARPOL, the amendments to the BCH Code shall enter into force on 1 January 2021 upon their acceptance in accordance with paragraph 2 above;

4 INVITES ALSO the Maritime Safety Committee to note this resolution and take action as appropriate;

5 REQUESTS the Secretary-General, for the purposes of article 16(2)(e) of MARPOL, to transmit certified copies of the present resolution and the text of the amendments to the BCH Code contained in the annex, to all Parties to MARPOL;

6 REQUESTS ALSO the Secretary-General to transmit copies of the present resolution and its annex to the Members of the Organization which are not Parties to MARPOL.

ANNEX

AMENDMENTS TO THE CODE FOR THE CONSTRUCTION AND EQUIPMENT OF SHIPS CARRYING DANGEROUS CHEMICALS IN BULK (BCH CODE)

Chapter IV

Special requirements

- 1 A new section 4.24 is inserted after existing section 4.23 as follows:

"4.24 Hydrogen sulphide (H₂S) detection equipment for bulk liquids

Hydrogen sulphide (H₂S) detection equipment shall be provided on board ships carrying bulk liquids prone to H₂S formation. It should be noted that scavengers and biocides, when used, may not be 100% effective in controlling the formation of H₂S. Toxic vapour detection instruments complying with the requirement in 3.11.1 of the Code for testing for H₂S may be used to satisfy this requirement."

Chapter V

Operational requirements

- 2 Paragraph 5.2.7 is replaced by the following:

"5.2.7 Where *column m* in the table of chapter VI of this Code refers to this paragraph, the cargo is subject to the prewash requirements in regulation 13.7.1.4 of Annex II of MARPOL."

Chapter VI

Summary of minimum requirements

IBC/BCH Codes cross-references to the requirements

- 3 The following cross-references are added under section Special requirements (*column o*):

"15.15 4.24
16.2.7 5.2.7"

ANNEX 14

RESOLUTION MEPC.320(74)
(adopted 17 May 2019)

**2019 GUIDELINES FOR CONSISTENT IMPLEMENTATION OF
THE 0.50% SULPHUR LIMIT UNDER MARPOL ANNEX VI**

THE MARINE ENVIRONMENT PROTECTION COMMITTEE,

RECALLING Article 38(a) of the Convention on the International Maritime Organization concerning the functions of the Marine Environment Protection Committee (the Committee) conferred upon it by international conventions for the prevention and control of marine pollution from ships,

RECALLING ALSO that, at its fifty-eighth session, the Committee adopted, by resolution MEPC.176(58), a revised MARPOL Annex VI which significantly strengthens the emission limits for sulphur oxides (SO_x),

RECALLING FURTHER that, at its seventieth session, the Committee adopted, resolution MEPC.280(70), *Effective date of implementation of the fuel oil standard in regulation 14.1.3 of MARPOL Annex VI*, confirming "1 January 2020" as the effective date of implementation for ships to comply with global 0.50% m/m sulphur content of fuel oil requirement,

NOTING ALSO that, at its seventy-third session, the Committee approved circular MEPC.1/Circ.878 on the *Guidance on the development of a ship implementation plan for the consistent implementation of the 0.50% sulphur limit under MARPOL Annex VI*,

HAVING CONSIDERED, at its seventy-fourth session, draft 2019 Guidelines for consistent implementation of the 0.50% sulphur limit under MARPOL Annex VI, prepared by the Sub-Committee on Pollution Prevention and Response, at its sixth session,

- 1 ADOPTS the *2019 Guidelines for consistent implementation of the 0.50% sulphur limit under MARPOL Annex VI*, as set out in the annex to the present resolution;
- 2 REQUESTS Parties to MARPOL Annex VI and other Member Governments to bring these Guidelines to the attention of shipowners, ship operators, fuel oil suppliers and any other interested groups;
- 3 AGREES to keep these Guidelines under review in the light of experience gained with their application.

ANNEX

2019 GUIDELINES FOR CONSISTENT IMPLEMENTATION OF THE 0.50% SULPHUR LIMIT UNDER MARPOL ANNEX VI

1 Introduction

1.1 Objective

1.1.1 The purpose of these Guidelines is to ensure consistent implementation of the 0.50% sulphur limit under MARPOL Annex VI. These Guidelines are intended for use by Administrations, port States, shipowners, shipbuilders and fuel oil suppliers, as appropriate.

1.2 Definitions

1.2.1 For the purpose of these Guidelines, the definitions in MARPOL Annex VI apply.

1.2.2 The following definitions of fuel oils are used, as applicable:

- .1 Distillate marine fuels (DM) are as specified in ISO 8217:2017¹ (e.g. DMA, DMB, DMX, DMZ);
- .2 Residual marine fuels (RM) are as specified in ISO 8217:2017¹ (e.g. RMD 80, RMG 380);
- .3 Ultra-low sulphur fuel oil (ULSFO) are as specified in ISO 8217:2017¹ (e.g. maximum 0.10% S ULSFO-DM, maximum 0.10% S ULSFO-RM);
- .4 Very low sulphur fuel oil (VLSFO) (e.g. maximum 0.50% S VLSFO-DM, maximum 0.50% S VLSFO-RM); and
- .5 High sulphur heavy fuel oil (HSHFO) exceeding 0.50% S.

2 Ship implementation planning for 2020

2.1 MEPC 70 agreed to "1 January 2020" as the effective date of implementation for ships to comply with the 0.50% m/m fuel oil sulphur content limit requirement and adopted resolution MEPC.280(70) on the *Effective date of implementation of the fuel oil standard in regulation 14.1.3 of MARPOL Annex VI*².

2.2 In this context, MEPC 73 agreed that Administrations should encourage ships flying their flag to develop implementation plans, outlining how the ship may prepare in order to comply with the required sulphur content limit of 0.50% by 1 January 2020. The plan should be complemented with a record of actions taken by the ships in order to be compliant by the applicable date.

2.3 MEPC 73, recognizing the need for guidance to support the consistent implementation of the 0.50% sulphur limit under MARPOL Annex VI, approved MEPC.1/Circ.878 on the *Guidance on the development of a ship implementation plan for the consistent implementation of the 0.50% sulphur limit under MARPOL Annex VI*.

¹ The latest edition of the ISO standard is recommended.

² Regulation 14.1.3 of MARPOL Annex VI, was amended by resolution MEPC.305(73).

3 Impact on fuel and machinery systems

3.0.1 The experiences and lessons learned from the transition to the 0.10% m/m SO_x-ECA limit indicated that current ship machinery operations should be sufficiently capable of addressing the concerns regarding combustion of the new 0.50% m/m limit fuel oils.

3.0.2 Currently most of the marine diesel engines and boilers on ships operating outside Emission Control Areas (ECAs) are optimized to operate on heavy fuel oil. From 2020 ships are required to use fuel oils with a sulphur content of 0.50% m/m or lower, unless fitted with an approved equivalent means of compliance.

3.1 *Distillate fuels*

3.1.1 A major challenge with distillate fuels is low viscosity. Low viscosity may cause internal leakages in diesel engines, boilers and pumps. Internal leakages in fuel injection system may result in reduced fuel pressure to the engine, which may have consequences for the engine performance (e.g. starting of the engine). Equipment makers recommendations should be taken into account, and adequate testing, maintenance and possible installation of coolers, etc. may be performed.

3.1.2 Cold Filter Plugging Points (CFPP) and Cloud Points (CP) as well as the Pour Point (PP) for distillate fuels need to be considered in light of the ship's intended operating area and ambient temperatures.

3.1.3 These issues are critical concerns as they can result in the formation and accumulation of wax sediment, which can cause costly and avoidable maintenance. In the worst-case scenario, sediment can cause engine fuel starvation and power loss.

3.1.4 ISO 8217:2017³ limits the cold flow properties of a fuel through setting a limit on the PP. However, given that wax crystals form at temperatures above the PP, fuels that meet the specification in terms of PP can still be challenging to operations in colder operating regions, as the wax particles can rapidly block filters, potentially plugging them completely. For cold weather, additional cold flow properties, CFPP and CP, should be reported by the supplier when the receiving ship has ordered distillate fuel for cold weather operations, a requirement that is specified in ISO 8217:2017³.

3.1.5 Since the residual fuels are usually heated and distillate fuels are not heated, particular attention needs to be given to the cold flow properties of distillates. Cold flow property challenges can be managed by heating the fuel. CIMAC has issued "01 2015 CIMAC Guideline Cold flow properties of marine fuel oils"⁴.

3.1.6 Fuel temperature should be kept approximately 10°C above the PP in order to avoid any risk of solidification, however this may not reduce the risk of filter blocking in case of high CFPP and CP.

3.1.7 It is good practice to review the possibilities of heating arrangements for distillate fuels on board. This is usually very limited, as it is not standard practice to have heating arrangements in distillate storage, settling or service tanks. Transfer arrangements may be adapted to pass through a residual fuel oil heat exchanger should the need arise.

³ The latest edition of the ISO standard is recommended.

⁴ https://www.cimac.com/cms/upload/workinggroups/WG7/CIMAC_WG7_2015_01_Guideline_Cold_Flow_Properties_Marine_Fuel_Oils_final.pdf

3.1.8 Knowing the fuel properties before bunkering will assist in taking the necessary precautions where and when necessary. If the ship is heading towards colder climates and the cold flow properties are inferior, the fuel may be:

- .1 either used before entering cold regions, or
- .2 used with suitable heating arrangement, as mentioned above.

3.1.9 If the approach of applying heat is being followed it should be ensured that the fuel is not overheated resulting in the viscosity dropping below the minimum recommendation of 2 cSt at any point in the fuel system, including the engine inlet. In order to reduce this risk, heating should be limited to max 40°C.

3.2 *Distillate fuel with FAME content*

3.2.1 Increased demand for Distillate fuels may result in more land-based products making their way into the marine supply pool, some of these fuels (e.g. biodiesel) may contain Fatty Acid Methyl Ester (FAME).

3.2.2 There are various technical challenges associated with use of fuel having FAME content, e.g. potential oxidation of biodiesel, its biodegradable nature, etc. with adverse implications, limitations in storage life, etc. It also needs to be tested for stability.

3.2.3 The ISO 8217:2017³ standard includes a maximum FAME content of 7.0% by volume for DFA/DFZ/DFB fuel oil grades since some ports may offer automotive diesel fuel as the only fuel available, which contains FAME and could violate the fuel flashpoint requirements addressed in SOLAS chapter II-2. The maximum 7.0% (v/v) has been chosen as this aligns with the concentrations allowed in some of the countries applying environmental regulations.

3.2.4 Manufacturers of engines and equipment like oily water separators, overboard discharge monitors, filters, coalescers, etc. need to be consulted to confirm the ability of engines and equipment to handle biodiesel blends of up to B7 (i.e. 7.0% v/v).

3.2.5 It is recommended to avoid using such biodiesel blend fuels for lifeboat engines, emergency generators, fire pumps, etc. where it is stored in isolated individual unit fuel tanks and subjected to conditions for accelerated degradation.

3.2.6 CIMAC has provided a Guideline for Shipowners and Operators on Managing Distillate Fuels up to 7.0% v/v FAME (Biodiesel).⁵

3.3 *Residual fuels*

3.3.1 *Stability and compatibility*

3.3.1.1 It is essential to distinguish between "Fuel stability" within a single batch of fuel and "Fuel compatibility" between different fuel batches.

3.3.1.2 Regarding stability: the fuel shall be stable and homogeneous at delivery and it is the responsibility of the fuel oil blenders and suppliers to ensure this.

⁵ https://www.cimac.com/cms/upload/workinggroups/WG7/CIMAC_WG7_Guideline_for_Ship_Owners_and_Operators_on_Managing_Distillate_Fuels_May_2013.pdf

3.3.1.3 A wide range of blends of refined products will be used to make the new 0.50% sulphur fuels, and the stability and compatibility of the blends will be an important concern for shipowners/operators. Unstable fuels can separate on their own and incompatible ones can do so when mixed in a single bunker tank, forming sludge that can block filters and ultimately cause engine failures.

3.3.1.4 It is recommended that ships have a commingling procedure. The procedure should primarily aim to ensure new bunkers are loaded into empty tanks to the extent possible. In the event that a ship finds itself possibly having to commingle a new bunker with bunkers already on board, then it is important that the ship determines the compatibility between the two said bunkers before comingling.

3.3.1.5 The reference test method shall be the total potential sediment test in accordance with ISO 10307-2:2009.

3.3.2 *Catalytic fines (cat fines)*

3.3.2.1 Cat fines are a by-product of refining and consist of small particles of metal that are deliberately introduced as catalysts to "crack" the fuel oil. Unless reduced by purification, cat fines will become embedded in engine parts and cause serious and rapid engine damage. Reference should be made to engine manufacturer's guidance with respect to managing cat fines.

3.4 **Key technical considerations for shipowners and operators**

3.4.1 Ship tank configuration and fuel system – the viscosity of most of these blended residual fuels is such that they cannot be used in distillate fuel-only systems and machinery, as they require heating for cleaning and combustion. A fully segregated fuel system for both distillate fuels and these new fuels is recommended.

3.4.2 Tank cleaning is recommended when using a residual fuel tank for storing these new fuels. This is to prevent sludge that has built up in these tanks from entering the fuel system. Further information on tank cleaning is set out in appendix 3 of MEPC.1/Circ.878 on *Guidance on the development of a ship implementation plan for the consistent implementation of the 0.50% sulphur limit under MARPOL Annex VI*.

3.4.3 Heating requirements – due to the cold flow properties of most of these new fuels, permanent heating of the fuel may be necessary to minimize the risk of wax formation, also in storage. This is especially important in colder regions.

3.4.4 Fuel treatment system – Some of these new fuels may contain cat fines and/or sediments and therefore need onboard cleaning. Separator temperature and settings should be adjusted to the fuels' viscosity and density. Please refer to recommendations from OEM and fuel supplier.

3.4.5 Considering that many of these new fuels have lower viscosities compared to conventional residual fuels, care should be taken to ensure no overheating occurs.

3.5 **ISO Standard for residual fuels**

3.5.1 The bunker market uses ISO 8217:2017⁶ specifications to ensure that the properties of the fuels it delivers conform to a standard that mean they comply with MARPOL Annex VI.

⁶ The latest edition of the ISO standard is recommended.

3.5.2 The existing ISO 8217:2017⁶ specification for marine fuels takes into consideration the diverse nature of marine fuels and incorporates a number of categories of distillate or residual fuels, even though not all categories may be available in every supply location it covers all marine petroleum fuel oils used today as well as the 0.50% Sulphur fuels of 2020. The General requirements, in the ISO 8217:2017⁶ specification for marine fuels and characteristics, included in table 1 and 2 of ISO 8217:2017⁶ identified safety, performance and environmental concerns and further takes into consideration the onboard handling requirements, including storage, cleaning and combustion aspects of all fuel oils used today and the anticipated fuel blends of 2020, irrespective of the sulphur content of the fuel oils.

3.5.3 It is important that any new standards address and do not preclude the use of renewable and alternative non-fossil crude derived products, so long as they comply with the chemical properties specified for these fuel oils.

3.6 *Cylinder lubrication*

3.6.1 The choice of cylinder lubricating oils will often follow the fuel type in use. Therefore, when changing to VLSFO operation from RM operation the choice of appropriate cylinder lubricating oil should be considered in accordance with the recommendations of the engine manufacturer.

4 Verification issues and control mechanism and actions

4.1 *Survey and certification by Administrations*

4.1.1 When undertaking a survey in accordance with regulation 5 of MARPOL Annex VI, the Administration should conduct a survey of a ship to verify that the ship complies with the provisions to implement the 0.50% sulphur limit. In particular, the Administration should check whether the ship carries compliant fuel oils for use, based on the Bunker Delivery Note (BDN) on board, any other document or fuel oil samples as appropriate consistent with the provisions of regulation 18 of MARPOL Annex VI. If carriage of HSHFO for use is identified, the Administration should check whether regulation 3.2, regulation 4 of MARPOL Annex VI are applied to the ship, or if the ship encountered a fuel availability problem and is operating pursuant to regulation 18.2 of MARPOL Annex VI.

4.1.2 When an Administration decides to analyse a fuel oil sample to determine compliance with the sulphur limits in regulation 14.1 or 14.4, the final analysis should be carried out in accordance with ISO 8754:2003 by a laboratory that is accredited for the purpose of conducting the test in accordance with ISO/IEC 17025 or an equivalent standard. The test results should be in accordance with ISO 8754 reporting protocol, meaning a tested value at or above 0.10% sulphur should be reported with no more than two decimal places.

4.1.3 According to regulation 11.4 of MARPOL Annex VI, the Administration shall investigate any report of an alleged violation and thereafter promptly inform the Party which made the report, as well as the Organization, of the action taken. When informing the Organization, the MARPOL Annex VI GISIS module should be used.

4.2 Control measures by port States

4.2.1 Port States should take appropriate measures to ensure compliance with the 0.50% of sulphur limit under MARPOL Annex VI, in line with the regulation 10 of MARPOL Annex VI and the *2019 Guidelines for port State control under MARPOL Annex VI* (resolution MEPC.[...](74)) (2019 PSC Guidelines). Specifically, the port State should conduct initial inspections based on documents and other possible materials, including remote sensing and portable devices. Given "clear grounds" to conduct a more detailed inspection, the port State may conduct sample analysis and other detailed inspections to verify compliance to the regulation, as appropriate.

4.2.2 Regulation 18.2.3 of MARPOL Annex VI requires a Party to take into account all relevant circumstances and the evidence presented to determine the action to take, including not taking control measures. Administrations and port State control authorities may take into account the implementation plan when verifying compliance with the 0.50% sulphur limit requirement.

4.2.3 *Inspections based on documents and other possible targeting measurements*

4.2.3.1 During the port State control and other enforcement activities, the port State should investigate whether a ship carries either compliant fuel oils or HSHFOs for use, based on the documents listed in paragraph 2.1.2 of the 2019 PSC Guidelines additionally records required to demonstrate compliance should also then be viewed. Results from remote sensing could be used to trigger inspections and portable devices could be used during the initial inspections, as appropriate. Remote sensing and portable devices are, however, of indicative nature and should not be regarded as the evidence of non-compliance but may be considered clear grounds for expanding the inspection.

4.2.3.2 Port state should determine if regulations 3.2, 4 or 18.2.3 apply together with retained bunker delivery notes and IAPP Certificate when considering the status of any HSHFO being carried for use on board.

4.2.4 *Fuel oil sample analysis*

4.2.4.1 When the port State identifies clear grounds of suspected non-compliance of a ship based on initial inspections, the port State may require samples of fuel oils to be analysed. The samples to be analysed may be either the representative samples provided with BDN in accordance with regulation 18.8.2, MARPOL delivered samples or samples from designated sampling points in accordance with the *2019 Guidelines for onboard sampling for the verification of the sulphur content of the fuel oil used on board ships* (MEPC.1/Circ.864/Rev.1) (in-use fuel oil samples) or other samples obtained by the port State.

4.2.4.2 Where the MARPOL delivered sample is taken from the ship a receipt should be provided to the ship. The outcome of the analysis undertaken with appendix VI of MARPOL Annex VI should be advised to the ship for its records.

4.2.4.3 In detecting suspected non-compliance, the sample analysis should be conducted in a uniform and reliable manner as described in paragraph 4.1.2. The verification procedure for MARPOL delivered samples should be in accordance with appendix VI⁷ of MARPOL Annex VI. For other samples taken on board the ship, the in-use and onboard sample, the sample should

⁷ Amendments to MARPOL VI, Appendix VI, *Verification procedures for a MARPOL Annex VI fuel oil sample (regulation 18.8.2 or regulation 14.8)*, expected to be adopted in Spring 2020 and set out in annex 13 to document MEPC 74/18/Add.1.

be deemed to meet the requirements provided the test result from the laboratory does not exceed the specification limit $+0.59R$ (where R is the reproducibility of the test method) and no further testing is necessary.

4.2.4.4 Notwithstanding the above process, all possible efforts should be made to avoid a ship being unduly detained or delayed. In particular, sample analysis of fuel oils should not unduly delay the operation, movement or departure of the ship.

4.2.4.5 If a non-compliance is established, consistent with regulation 18.2.3 the port State may prevent the ship from sailing until the ship takes any suitable measures to achieve compliance which may include de-bunkering all non-compliant fuel oil. In addition, the port State should report the information of the ship using or carrying for use non-compliant fuel oil to the Administration of the ship and inform the Party or non-Party under whose jurisdiction a bunker delivery note was issued of cases of delivery of non-compliant fuel oil, giving all relevant information. Upon receiving the information, the Party detecting the deficiency should report the information to the MARPOL Annex VI GISIS module in accordance with paragraph 3.4 of these Guidelines.

4.2.4.6 The Parties (the port and flag States); however, may permit, with the agreement of the destination port authority, a single voyage for bunkering of compliant fuel oil for the ship, in accordance with regulation 18.2.4 of MARPOL Annex VI. The single voyage should be one way and minimum for bunkering, and the ship proceeds directly to the nearest bunkering facility appropriate to the ship. In the case that the parties permit a single voyage of a ship, the port State should confirm that the Administration of the ship has advised the authority at the destination port of the approval for a single voyage including information on the ship granted with the approval and the certified record of analysis of the sample as the evidence. Once confirmation has been provided the port State should permit the ship to sail as agreed.

4.2.4.7 If the port State is made aware that a ship is carrying non-compliant fuel oil, which is not for use through an equivalent method under regulation 4 or a permit under regulation 3.2 of MARPOL Annex VI, the port State should take action to confirm the fuel is not being used. Action to confirm should include but is not limited to the examination of the oil record book and the record of tank soundings. Where necessary the port State may require tank soundings to be undertaken during the inspection. Where it is determined that the fuel has been used the control action in paragraph 4.2.4.5 should be applied.

4.2.5 Other open-sea compliance monitoring tools:

- .1 fuel oil changeover calculator;
- .2 data collection system for fuel oil consumption of ships (resolution MEPC.278(70)); and
- .3 continuous SO_x monitoring.

4.3 Control on fuel oil suppliers

4.3.1 Designated authorities should, if deemed necessary, take a sample and test fuel oils from bunker barges or shore bunker terminals. Sampling of fuel oils in bunker barges or shore bunker terminals can be taken and tested in the same manner that the MARPOL delivered fuel oils are tested by the PSC. All possible efforts should be made to avoid a ship being unduly detained or delayed. If a sample is analysed, sample analysis of fuel oils should not unduly delay the operation, movement or departure of the ship.

4.3.2 If non-compliance, such as issuance of an incorrect BDN or a BDN without measurement of sulphur content, was found, the designated authorities should take appropriate corrective measures against the non-compliant supplier. In such case, the designated authorities should inform the Organization for transmission to the Member States of the non-compliant supplier, in accordance with the regulation 18.9.6 of MARPOL Annex VI and paragraph 4.4 of these Guidelines.

4.4 Information sharing related to non-compliances under MARPOL Annex VI

4.4.1 When a Party finds a non-compliance of a ship or a fuel oil supplier, the information of the non-compliance should be reported to the MARPOL Annex VI GISIS module (regulation 11.4).

4.4.2 Publication of information on non-compliant ships/fuel oil suppliers or a reporting scheme to IMO to be registered on centralized information platforms are proposed as elements of an effective enforcement strategy. Various PSC regimes have successfully used the publishing of information related to substandard ships/fuel suppliers as a deterrent to non-compliance. Port States also need to report detentions of ships to IMO which may affect the future PSC targeting of the ship. The IMO GISIS database already makes available certain information related to non-compliances with the MARPOL Annex VI regulations.

5 Fuel oil non-availability

5.1 Guidance and information sharing on fuel oil non-availability

5.1.1 Regulation 18.2.1 of MARPOL Annex VI provides that in the event compliant fuel oil cannot be obtained, a Party to MARPOL Annex VI can request evidence outlining the attempts made to obtain the compliant fuel oil, including attempts made to local alternative sources. Regulations 18.2.4 and 18.2.5 then require that the ship notifies its Administration and the competent authority of the port of destination on the inability to obtain compliant fuel oil, with the Party to notify IMO of the non-availability. This notification is commonly referred to as a Fuel Oil Non-Availability Report (FONAR).

5.1.2 Guidance on consistent evidence

5.1.3 Regulation 18.2.1.2 of MARPOL Annex VI requires that evidence be provided to support a claim that all efforts were made to obtain compliant fuel oil. In this regard, a Party may develop more detailed guidance for the consistent use and acceptance of these reports, including what evidence is needed to accompany a report to ensure that port States are applying the provisions under regulation 18.2.3, consistently.

5.1.4 Should a ship, despite its best effort to obtain compliant fuel oil, be unable to do so, the master/company must:

- .1 present a record of actions taken to attempt to bunker correct fuel oil and provide evidence of an attempt to purchase compliant fuel oil in accordance with its voyage plan and, if it was not made available where planned, that attempts were made to locate alternative sources for such fuel oil and that despite best efforts to obtain compliant fuel oil, no such fuel oil was made available for purchase; and
- .2 best efforts to procure compliant fuel oil include, but are not limited to, investigating alternate sources of fuel oil prior to commencing the voyage. If, despite best efforts, it was not possible to procure compliant fuel oil, the

master/Company must immediately notify the port State Administration in the port of arrival and the flag Administration (regulation 18.2.4 of MARPOL Annex VI).

5.1.5 In order to minimize disruption to commerce and avoid delays, the master/company should submit a FONAR as soon as it is determined or becomes aware that it will not be able to procure and use compliant fuel oil.

5.1.6 *Investigating non-availability*

5.1.7 A Party should investigate the reports of non-availability. This process is important to ensure a consistent supply of compliant fuel to industry, as well as prevent incentives for ships to use ports where it is known that compliant fuel is not available on an ongoing basis. Critical to this process will be the sharing of information between Member States on reported compliant fuel oil supply issues.

5.1.8 Regulation 18.2.5 of MARPOL Annex VI provides that a Party to MARPOL Annex VI notify the Organization when a ship has presented evidence of the non-availability of compliant fuel oil in a port or at their terminal. For this purpose, MARPOL Annex VI GISIS module provides the platform for Parties to upload such notifications.

5.1.9 Regulation 18.1 of MARPOL Annex VI provides that each Party take all reasonable steps to promote the availability of above compliant fuel oil and inform the Organization through MARPOL Annex VI GISIS module of the availability of compliant fuel oils in its ports and terminals.

5.1.10 Port State control authority may contact the submitter (and/or shipowner or operator), including in the event of an incomplete submission, and request additional information, or to pursue an enforcement action such as a Notice of Violation.

5.2 ***Standard format for reporting fuel oil non-availability***

5.2.1 For ships which are unable to purchase fuel oil meeting the requirements of regulations 14.1 or 14.4 of MARPOL Annex VI, the standard format for reporting fuel oil non-availability is set out in appendix 1 to this document, pursuant to regulation 18.2.4 of MARPOL Annex VI.

6 **Possible safety implications relating to fuel oils meeting the 0.50% m/m sulphur limit**

6.1 MEPC 73 (October 2018) approved MEPC.1/Circ.878 on *Guidance on the development of a ship implementation plan for the consistent implementation of the 0.50% sulphur limit under MARPOL Annex VI* (hereafter the "Ship Implementation Plan Guidance") addresses some safety issues identified with regard to 0.50% maximum sulphur fuel oil, in particular through the section on risk assessment (section 1 of the Ship Implementation Plan Guidance) and additional guidance provided on impact on machinery systems and tank cleaning (appendix 2 and appendix 3 of the Ship Implementation Plan Guidance, respectively).

6.2 Identified potential safety implications include, but are not limited to, the following:

- .1 stability of blended fuel oil;
- .2 compatibility, including new tests and metrics appropriate for future fuels;

- .3 cold flow properties;
- .4 acid number;
- .5 flash point;
- .6 ignition and combustion quality;
- .7 cat fines;
- .8 low viscosity; and
- .9 unusual components.

6.3 Additional technical information and a review, displayed in tabular format, of the possible potential safety implications is set out in appendix 2.

6.4 Reference should also be made to general industry guidance on potential safety and operational issues related to the supply and use of 0.50% maximum sulphur fuels⁸.

⁸ ICS, ASA and ECSA Guidance to shipping companies and crews on preparing for compliance with the 2020 global sulphur limit can be accessed at the following link: <http://www.ics-shipping.org/free-resources/2020-sulphur-compliance>

APPENDIX 1

FUEL OIL NON-AVAILABILITY REPORT (FONAR)

Note:

1 This report is to be sent to the flag Administration and to the competent authorities in the relevant port(s) of destination in accordance with regulation 18.2.4 of MARPOL Annex VI. The report shall be sent as soon as it is determined that the ship/operator will be unable to procure compliant fuel oil and preferably before the ship leaves the port/terminal where compliant fuel cannot be obtained. A copy of the FONAR should be kept on board for inspection for at least 36 months.

2 This report should be used to provide evidence if a ship is unable to obtain fuel oil compliant with the provisions stipulated in regulations 14.1 or 14.4 of MARPOL Annex VI.

3 Before filing a FONAR, the following should be observed by the ship/operator:

3.1 A fuel oil non-availability report is not an exemption. According to regulation 18.2 of MARPOL Annex VI, it is the responsibility of the Party of the destination port, through its competent authority, to scrutinize the information provided and take action, as appropriate.

3.2 In the case of insufficiently supported and/or repeated claims of non-availability, the Party may require additional documentation and substantiation of fuel oil non-availability claims. The ship/operator may also be subject to more extensive inspections or examinations while in port.

3.3 Ships/operators are expected to take into account logistical conditions and/or terminal/port policies when planning bunkering, including but not limited to having to change berth or anchor within a port or terminal in order to obtain compliant fuel.

3.4 Ships/operators are expected to prepare as far as reasonably practicable to be able to operate on compliant fuel oils. This could include, but is not limited to, fuel oils with different viscosity and different sulphur content not exceeding regulatory requirements (requiring different lube oils) as well as requiring heating and/or other treatment on board.

1 Particulars of ship

1.1 Name of ship: _____

1.2 IMO number: _____

1.3 Flag: _____

1.4 (if other relevant registration number is available, enter here): _____

2 Description of ship's voyage plan

2.1 Provide a description of the ship's voyage plan in place at the time of entry into "country X" waters (and ECA, if applicable) (Attach copy of plan if available):

2.2 Details of voyage:

1 – Last port of departure

2 – First port of arrival in "country X":

3 – Date of departure from last port (dd-mm-yyyy):

4 – Date of arrival at first "country X" (dd-mm-yyyy):

5 – Date ship first received notice that it would be transiting in "country X" waters
(and ECA, if applicable) (dd-mm-yyyy):

6 – Ship's location at the time of notice:

7 – Date ship operator expects to enter "country X" waters (and ECA, if applicable)
(dd-mm-yyyy):

8 – Time ship operator expects to enter "country X" waters (and ECA, if applicable)
(hh:mm UTC):

9 – Date ship operator expects to exit "country X" waters (and ECA, if applicable)
(dd-mm-yyyy):

10 – Time ship operator expects to exit "country X" waters (and ECA, if applicable)
(hh:mm UTC):

11 – Projected days ship's main propulsion engines will be in operation within
"country X" waters (and ECA, if applicable):

12 – Sulphur content of fuel oil in use when entering and operating in "country X"
waters (and ECA, if applicable):

3 Evidence of attempts to purchase compliant fuel oil

3.1 Provide a description of actions taken to attempt to achieve compliance prior to entering "country X" waters (and ECA, if applicable), including a description of all attempts that were made to locate alternative sources of compliant fuel oil, and a description of the reason why compliant fuel oil was not available:

3.2 Name and email address of suppliers contacted, address and phone number and date of contact (dd-mm-yyyy):

Please attach copies of communication with suppliers (e.g. emails to and from suppliers)

4 In case of fuel oil supply disruption only

4.1 Name of port at which ship was scheduled to receive compliant fuel oil:

4.2 Name, email address, and phone number of the fuel oil supplier that was scheduled to deliver (and now reporting the non-availability): _____

5 Operation constraints, if applicable

5.1 If non-compliant fuel has been bunkered due to concerns that the quality of the compliant fuel available would cause operational or safety problems on board the ships, the concerns should be thoroughly documented.

5.2 Describe any operational constraints that prevented use of compliant fuel oil available at port:

5.3 Specify steps taken, or to be taken, to resolve these operational constraints that will enable compliant fuel use:

6 Plans to obtain compliant fuel oil

6.1 Describe availability of compliant fuel oil at the first port-of-call in "country X", and plans to obtain it:

6.2 If compliant fuel oil is not available at the first port-of-call in "country X", list the lowest sulphur content of available fuel oil(s) or the lowest sulphur content of available fuel oil at the next port-of-call:

7 Previous Fuel Oil Non-Availability Reports

7.1 If shipowner/operator has submitted a Fuel Oil Non-Availability Report to "country X" in the previous 12 months, list the number of Fuel Oil Non-Availability Reports previously submitted and provide details on the dates and ports visited while using non-compliant fuel oil, as set out below:

Report: _____
Date (dd-mm-yyyy): _____
Port: _____
Type of fuel: _____
Comments: _____

8 Master/Company information

Master name: _____
Local agent in "country X": _____
Ship operator name: _____
Shipowner name: _____
Name and position of official: _____
Email address: _____
Address (street, city, country, postal/zip code): _____
Telephone number: _____

Signature of Master: _____

Print name: _____
Date (DD/MM/YYYY): _____

APPENDIX 2

**TECHNICAL REVIEW OF IDENTIFIED POTENTIAL SAFETY IMPLICATIONS
ASSOCIATED WITH THE USE OF 2020 COMPLIANT FUELS**

Fuel Property	Potential Challenges	Remarks
Stability	The consequences of a ship receiving an unstable fuel, or one that becomes unstable during storage or handling, can be serious. Sludge may build up in the storage tanks, piping systems or centrifuges and filters can become totally blocked by voluminous amounts of sludge.	<p>The challenge for the fuel producer is to blend a fuel which is not only stable but also has a degree of reserve stability such that it will remain stable during periods of storage and treatment at elevated temperatures.</p> <p>More paraffinic blend components are expected for Very Low Sulphur Fuel Oil (VLSFO) compared to existing fuels. Whereas aromatic components have a stabilizing effect on asphaltenes, paraffins do not. Fuel suppliers are responsible for ensuring that the supplied fuel is stable.</p>
Compatibility issues	Challenges are the same as with stability (above).	<p>An incompatible mix may be harmful to ship's operation.</p> <p>VLSFOs are expected to be paraffinic based in some regions and aromatic based in other regions. There is a risk of experiencing incompatibility when mixing an aromatic fuel with a paraffinic fuel. The same risk exists today, but with the wide range of products which may exist post 2020, it is important to segregate fuels as far as possible and to be cautious of how to manage/handle incompatible fuels on board.</p>
Cold flow properties and Pour Point	ISO 8217:2017 limits the cold flow properties of a fuel through setting a limit on the pour point (PP). However, given that wax crystals form at temperatures above the PP, fuels that meet the specification in terms of PP can still be challenging when operating in colder regions. Wax particles can rapidly block filters, potentially plugging them completely. The paraffin's may crystallize and/or deposit in the storage tanks leading to blockages at the filters and reduced fuel flow to the machinery plants. If fuels are held at temperatures below the pour point, wax will begin to	<p>VLSFO products are expected to be more paraffinic compared to existing fuels. As such, it is important to know the cold flow properties of the bunkered fuel in order to ensure proper temperature management on board.</p> <p>It is important to note that for additives to be effective, they have to be applied before crystallization has occurred in the fuel.</p> <p>Reference 1.</p>

Fuel Property	Potential Challenges	Remarks
	<p>precipitate. This wax may cause blocking of filters and can deposit on heat exchangers. In severe cases the wax will build up in storage tank bottoms and on heating coils, which can restrict the coils from heating the fuel (fuel will become unpumpable from the bunker tanks).</p>	
Acid number	<p>The fuel shall be free from strong, inorganic acids.</p> <p>Fuels with high acid number test results arising from acidic compounds cause accelerated damage to marine diesel engines. Such damage is found primarily within the fuel injection equipment.</p>	<p>There is currently no recognized correlation between an acid number test result and the corrosive activity of the fuel.</p> <p>ISO 8217:2017, appendix E covers the topic.</p>
Flashpoint	<p>Flashpoint is considered to be a useful indicator of the fire hazard associated with the storage of marine fuels. Even if fuels are stored at temperatures below the determined flash point, flammable vapours may still develop in the tank headspace.</p>	<p>SOLAS requirement.</p>
Ignition and combustion quality	<p>Fuels with poor ignition & combustion properties can, in extreme cases, result in serious operational problems, engine damage and even total breakdown. Poor combustion performance is normally characterized by an extended combustion period and/or poor rates of pressure increase and low "p max" resulting in incomplete combustion of the fuel. The resulting effects are increased levels of unburned fuel and soot that may be deposited in the combustion chamber, on the exhaust valves and in the turbocharger system, exhaust after treatment devices, waste heat recovery units and other exhaust system components. Extended combustion periods may also result in exposure of the cylinder liner to high temperatures which may disrupt the lubricating oil film, leading to</p>	<p>High and medium-speed engines are more prone to experience operational difficulties due to poor ignition and combustion properties than low speed two stroke types. With four stroke engines, poor ignition can result in excessive exhaust gas system deposits, black smoke, engine knocking and difficulties operating at low load.</p> <p>If the ignition process is delayed for too long a period by virtue of some chemical quality of the fuel, too large a quantity of fuel will be injected into the engine cylinders and will ignite at once, producing a rapid pressure and heat rise and causing associated damage to the piston rings and cylinder liners of the engine.</p> <p>Reference 2.</p>

Fuel Property	Potential Challenges	Remarks
	increased wear rates and scuffing. Unburnt fuel droplets may also carry over impinging on the liner surfaces causing further risk of damage to the liner.	
Cat fines	Cat fines will cause abrasive wear of cylinder liners, piston rings and fuel injection equipment if not reduced sufficiently by the fuel treatment system. High wear in the combustion chamber can result.	Major engine manufacturers recommend that the fuel's cat fines content does not exceed 10 mg/kg (ppm) at engine inlet.
Low viscosity	<p>Low-viscosity fuels (less than 2 cSt at engine inlet) challenge the function of the fuel pump in the following ways:</p> <ul style="list-style-type: none"> .1 breakdown of the oil film, which could result in seizures; .2 insufficient injection pressure, which results in difficulties during start-up and low-load operation; and .3 insufficient fuel index margin, which limits acceleration. 	<p>Low fuel viscosity does not only affect the engine fuel pumps. Most pumps in the external fuel oil system (supply pumps, circulating pumps, transfer pumps and feed pumps for the centrifuge) also need viscosities above 2 cSt to function properly.</p> <p>Viscosity is highly temperature dependent and the crew must take proper care of fuel oil temperature management to avoid viscosity related issues.</p> <p>Reference 3.</p>
Unusual components	<p>The below components and group of components can be linked to the risk of encountering the following problems:</p> <p>Polymers (e.g. polystyrene, polyethylene, polypropylene) Associated with filter blocking</p> <p>Polymethacrylates Associated with fuel pump sticking</p> <p>Phenols Occasionally Associated with filter blocking/fuel oil pump sticking</p> <p>Tall oils Associated with filter blocking</p> <p>Chlorinated hydrocarbons Associated with fuel pump seizures</p>	<p>Only for few components, there exists a clear cause and effect between component and associated operational problems.</p> <p>There is no statistical study performed of which components are typically found in marine fuels and in which concentration.</p> <p>As per ISO 8217:2017, annex B: The marine industry continues to build on its understanding of the impact of specific chemical species and the respective critical concentrations at which detrimental effects are observed on the operational characteristics of marine fuels in use.</p> <p>Only in some of the past cases the origin of the unusual components found in bunkers were revealed and</p>

Fuel Property	Potential Challenges	Remarks
	<p>Estonian shale oil Associated in the past with excessive separator sludging</p> <p>Organic acids Associated with corrosion as well as fuel pump sticking</p>	<p>were due to various reasons such as:</p> <ul style="list-style-type: none"> .1 Russia/Baltic states 1997, cross contamination in storage/piping (polypropylene); .2 Singapore 2001, 4 bunker barges received material from road tankers which, in addition to transporting fuel, also collected/transported waste oil from shipyards and motor shops (esters); .3 Ventspils 2007, Estonian shale oil to convert HSHFOs to LSFOS; and .4 Houston 2010/11, bunker barges that were not cleaned between cargoes (polyacrylates) Reference 4.

References

- 1 CIMAC WG7 Fuels Guideline 01/2015: "Cold flow properties of marine fuel oils"
- 2 CIMAC WG7 Fuels 2011: "Fuel Quality Guide: Ignition and Combustion"
- 3 MAN Service Letter SL2014-593/DOJA
- 4 Bureau Veritas Verifuel, Investigative analysis of marine fuel oils: Pros & Cons

ANNEX 16

**RESOLUTION MEPC.322(74)
(adopted on 17 May 2019)**

**AMENDMENTS TO THE 2018 GUIDELINES ON THE METHOD OF CALCULATION OF
THE ATTAINED ENERGY EFFICIENCY DESIGN INDEX (EEDI) FOR NEW SHIPS
(RESOLUTION MEPC.308(73))**

THE MARINE ENVIRONMENT PROTECTION COMMITTEE,

RECALLING article 38(a) of the Convention on the International Maritime Organization concerning the functions of the Marine Environment Protection Committee (the Committee) conferred upon it by international conventions for the prevention and control of marine pollution from ships,

RECALLING ALSO that, at its sixty-second session, it adopted, by resolution MEPC.203(62), *Amendments to the annex of the Protocol of 1997 to amend the International Convention for the Prevention of Pollution from Ships, 1973, as modified by the Protocol of 1978 relating thereto* (inclusion of regulations on energy efficiency for ships in MARPOL Annex VI),

NOTING that the aforementioned amendments to MARPOL Annex VI entered into force on 1 January 2013,

NOTING ALSO that regulation 20 (Attained Energy Efficiency Design Index (attained EEDI)) of MARPOL Annex VI, as amended, requires that the EEDI shall be calculated taking into account the guidelines developed by the Organization,

NOTING FURTHER the *2012 Guidelines on the method of calculation of the attained Energy Efficiency Design Index (EEDI) for new ships*, adopted at its sixty-third session by resolution MEPC.212(63), and the amendments thereto, adopted at its sixty-fourth session by resolution MEPC.224(64),

NOTING FURTHER that, at its sixty-sixth session, it adopted, by resolution MEPC.245(66), *2014 Guidelines on the method of calculation of the attained Energy Efficiency Design Index (EEDI) for new ships*, and, at its sixty-eighth session, by resolution MEPC.263(68), MEPC.281(70), amendments thereto,

NOTING FURTHER that, at its seventy-three, it adopted, by resolution MEPC.308(73), *2018 Guidelines on the method of calculation of the attained Energy Efficiency Design Index (EEDI) for new ships*,

RECOGNIZING that the amendments to MARPOL Annex VI require relevant guidelines for the smooth and uniform implementation of the regulations,

HAVING CONSIDERED, at its seventy-fourth session, proposed amendments to the *2018 Guidelines on the method of calculation of the attained Energy Efficiency Design Index (EEDI) for new ships*, as amended

1 ADOPTS amendments to the *2018 Guidelines on the method of calculation of the attained Energy Efficiency Design Index (EEDI) for new ships*, as amended, as set out in the annex to the present resolution;

2 INVITES Administrations to take the aforementioned amendments into account when developing and enacting national laws which give force to and implement provisions set forth in regulation 20 of MARPOL Annex VI, as amended;

3 REQUESTS the Parties to MARPOL Annex VI and other Member Governments to bring the amendments to the attention of shipowners, ship operators, shipbuilders, ship designers and any other interested parties;

4 AGREES to keep these Guidelines, as amended, under review, in the light of experience gained with their implementation.

ANNEX

AMENDMENTS TO THE 2018 GUIDELINES ON THE METHOD OF CALCULATION OF THE ATTAINED ENERGY EFFICIENCY DESIGN INDEX (EEDI) FOR NEW SHIPS (RESOLUTION MEPC.308(73))

1 The following text is added after 2.2.18 in the table of "CONTENTS":

"2.2.19 f_m ; Factor for ice-classed ships having IA Super and IA"

2 The EEDI Formula in section 2.1 is replaced with the following:

"2.1 EEDI Formula

The attained new ship Energy Efficiency Design Index (EEDI) is a measure of ships' energy efficiency (g/t · nm) and calculated by the following formula:

$$\frac{\left(\prod_{j=1}^n f_j \right) \left(\sum_{i=1}^{nME} P_{ME(i)} \cdot C_{FME(i)} \cdot SFC_{ME(i)} \right) + (P_{AE} \cdot C_{FAE} \cdot SFC_{AE} *) + \left(\left(\prod_{j=1}^n f_j \cdot \sum_{i=1}^{nPTI} P_{PTI(i)} - \sum_{i=1}^{neff} f_{eff(i)} \cdot P_{AE_{eff}(i)} \right) C_{FAE} \cdot SFC_{AE} \right) - \left(\sum_{i=1}^{neff} f_{eff(i)} \cdot P_{eff(i)} \cdot C_{FME} \cdot SFC_{ME} ** \right)}{f_i \cdot f_c \cdot f_i \cdot Capacity \cdot f_w \cdot V_{ref} \cdot f_m}$$

"

3 A new section 2.2.19 is added after the existing section 2.2.18 as follows:

"2.2.19 f_m ; Factor for ice-classed ships having IA Super and IA

For ice-classed ships having IA Super or IA, the following factor, f_m , should apply:

$$f_m = 1.05$$

For further information on approximate correspondence between ice classes, see HELCOM Recommendation 25/7*."

* HELCOM Recommendation 25/7 may be found at <http://www.helcom.fi>

4 ALBERT EMBANKMENT
LONDON SE1 7SR
Telephone: +44 (0)20 7735 7611 Fax: +44 (0)20 7587 3210

MEPC.1/Circ.864/Rev.1
21 May 2019

**2019 GUIDELINES FOR ON BOARD SAMPLING FOR THE VERIFICATION OF THE
SULPHUR CONTENT OF THE FUEL OIL USED ON BOARD SHIPS**

- 1 The Marine Environment Protection Committee, at its seventy-fourth session (13 to 17 May 2019), approved the *2019 Guidelines for on board sampling for the verification of the sulphur content of the fuel oil used on board ships*.
- 2 Member Governments are invited to bring the annexed Guidelines to the attention of Administrations, industry, relevant shipping organizations, shipping companies and other stakeholders concerned.
- 3 This circular revokes MEPC.1/Circ.864.

ANNEX

2019 GUIDELINES FOR ON BOARD SAMPLING FOR THE VERIFICATION OF THE SULPHUR CONTENT OF THE FUEL OIL USED ON BOARD SHIPS

1 Preface

The objective of these Guidelines is to establish an agreed method for sampling to enable effective control and enforcement of liquid fuel oil being used on board ships under the provisions of MARPOL Annex VI.

2 Sampling location

The in-use¹ representative sample or samples should be obtained from a designated sampling point or points. The number and location of designated fuel oil sampling points should be confirmed by the Administration following consideration of possible fuel oil cross-contamination and service tank arrangements. Fuel oil sampling points to be used should fulfil all of the following conditions:

- .1 be easily and safely accessible;
- .2 take into account different fuel oil grades being used for the fuel oil combustion machinery item;
- .3 be downstream of the in-use fuel oil service tank;
- .4 be as close to the fuel oil combustion machinery as safely feasible taking into account the type of fuel oil, flow-rate, temperature, and pressure behind the selected sampling point;
- .5 be clearly marked for easy identification and described in either the piping diagram or other relevant documents;
- .6 each sampling point should be located in a position shielded from any heated surface or electrical equipment and the shielding device or construction should be sturdy enough to endure leaks, splashes or spray under design pressure of the fuel oil supply line so as to preclude impingement of fuel oil onto such surface or equipment; and
- .7 the sampling arrangement should be provided with suitable drainage to the drain tank or other safe location.

¹ In-use sample means the sample of fuel oil in use on a ship.

3 Sample handling

The fuel oil sample should be taken when a steady flow is established in the fuel oil circulating system. The sampling connection² should be thoroughly flushed through with the fuel oil in use prior to drawing the sample. The sample or samples should be collected in a sampling container or containers and should be representative of the fuel oil being used. The sample bottles should be sealed by the inspector with a unique means of identification installed in the presence of the ship's representative. The ship should be given the option of retaining a sample. The label should include the following information:

- .1 sampling point location where the sample was drawn;
- .2 date and port of sampling;
- .3 name and IMO number of the ship;
- .4 details of seal identification; and
- .5 signatures and names of the inspector and the ship's representative.

² The sampling connection is the valve and associated pipework designated for sample collection which is connected to the fuel oil service system.

4 ALBERT EMBANKMENT
LONDON SE1 7SR
Telephone: +44 (0)20 7735 7611 Fax: +44 (0)20 7587 3210

MEPC.1/Circ.881
21 May 2019

**GUIDANCE FOR PORT STATE CONTROL ON CONTINGENCY MEASURES FOR
ADDRESSING NON-COMPLIANT FUEL OIL**

1 The Marine Environment Protection Committee, at its seventy-fourth session (13 to 17 May 2019), approved the *Guidance for port State control on contingency measures for addressing non-compliant fuel oil*, as set out in the annex.

2 Member Governments are invited to bring the annexed Guidance to the attention of their Administration, industry, relevant shipping and fuel industry organizations, shipping companies and other stakeholders concerned, as appropriate.

ANNEX

GUIDANCE FOR PORT STATE CONTROL ON CONTINGENCY MEASURES FOR ADDRESSING NON-COMPLIANT FUEL OIL

1 In the case of non-compliant fuel oil, communication between the ship and the port State should occur. The ship and the port State should consider the following as possible contingency measures:

- .1 actions predetermined in the Ship implementation plan, if available, for consistent implementation of the 0.50% sulphur limit under MARPOL Annex VI (MEPC.1/Circ.878);
- .2 discharging non-compliant fuel oil to another ship to be carried as cargo or to an appropriate shipboard or land-based facility, if practicable and available;
- .3 managing the non-compliant fuel oil in accordance with a method acceptable to the port State; and
- .4 operational actions, such as modifying sailing or bunkering schedules and/or retention of non-compliant fuel oil on board the ship. The port State and the ship should consider any safety issues and avoid possible undue delays.

2 Having considered all of the options in paragraph 1 above, the non-compliant fuel oil may be discharged to the port or retained on board, as acceptable to the port State. Port State consideration may include environmental, safety, operational and logistical implications of allowing or disallowing the carriage of non-compliant fuel oil. The carriage of non-compliant fuel oil is subject to any conditions of the port State.

3 The port State, the flag State and the ship should work together to agree on the most appropriate solution, taking into account the information provided in the Fuel Oil Non-Availability Report (FONAR),* to address the non-compliant fuel oil.

4 After the non-compliant fuel oil is completely used or discharged, such actions should include the possibility of cleaning and/or flushing through or dilution of remaining residues by using compliant fuel oil with the lowest sulphur content available.

* Appendix 1 of the 2019 Guidelines for consistent implementation of the 0.50% sulphur limit under MARPOL Annex VI (MEPC.320(74)).

4 ALBERT EMBANKMENT
LONDON SE1 7SR
Telephone: +44 (0)20 7735 7611 Fax: +44 (0)20 7587 3210

MEPC.1/Circ.882
16 July 2019

**EARLY APPLICATION OF THE VERIFICATION PROCEDURES FOR A
MARPOL ANNEX VI FUEL OIL SAMPLE
(REGULATION 18.8.2 OR REGULATION 14.8)**

- 1 The Marine Environment Protection Committee, at its seventy-fourth session (13 to 17 May 2019), approved amendments to appendix VI of MARPOL Annex VI on Verification procedures for a MARPOL Annex VI fuel oil sample (regulation 18.8.2 or regulation 14.8), providing an agreed method to determine whether the fuel oil delivered to, in-use or carried for use on board a ship is in accordance with the applicable sulphur limit of regulation 14 of MARPOL Annex VI.
- 2 To ensure a consistent approach to verifying the sulphur limit of the fuel oil delivered to, in-use or carried for use on board a ship until the entry into force of the approved amendments, Member Governments are invited to apply the approved amendments to appendix VI of MARPOL Annex VI related to the verification procedure for a MARPOL Annex VI fuel oil sample (regulation 18.8.2 or regulation 14.8), as contained in the annex to this Circular, in advance of their entry into force.
- 3 Member Governments are invited to bring the annexed Guidance to the attention of Administrations, port State control authorities, industry, fuel oil suppliers, relevant shipping organizations, shipping companies and other stakeholders concerned.
- 4 This circular expires on entry into force of the amendments.

ANNEX

THE APPROVED AMENDMENTS TO THE VERIFICATION PROCEDURES FOR A MARPOL ANNEX VI FUEL OIL SAMPLE (REGULATION 18.8.2 OR REGULATION 14.8)

Regulation 2

Definitions

1 New paragraphs 52, 53, 54, 55 and 56 are added as follows:

"52 *Sulphur content of fuel oil* means the concentration of sulphur in a fuel oil, measured in % m/m as tested in accordance with a standard acceptable to the Organization.¹

53 *Low-flashpoint fuel* means gaseous or liquid fuel oil having a flashpoint lower than otherwise permitted under paragraph 2.1.1 of SOLAS regulation II-2/4.

54 *MARPOL delivered sample* means the sample of fuel oil delivered in accordance with regulation 18.8.1 of MARPOL Annex VI.

55 *In-use sample* means the sample of fuel oil in use on a ship.

56 *On board sample* means the sample of fuel oil intended to be used or carried for use on board that ship."

Regulation 14

Sulphur oxides (SO_x) and particulate matter

2 "In-use and on board fuel oil sampling and testing" and a new paragraph 8 and 9 are added at the end of regulation 14 as follows:

"In-use and on board fuel oil sampling and testing

8 If the competent authority of a Party requires the in-use or on board fuel oil sample to be analysed, it shall be done in accordance with the verification procedure set forth in appendix VI to determine whether the fuel oil being used or carried for use on board meets the requirements in paragraph 1 or paragraph 4 of this regulation. The in-use fuel oil sample shall be drawn taking into account the guidelines developed by the Organization.² The on board fuel oil sample shall be drawn taking into account the guidelines to be developed by the Organization.³

¹ Refer to ISO 8754: 2003 Petroleum products – Determination of sulfur content – Energy-dispersive X-ray fluorescence spectrometry."

² Refer to the *2019 Guidelines for on board sampling for the verification of the sulphur content of the fuel oil used on board ships* (MEPC.1/Circ.864/Rev.1)."

³ Refer to the Guidelines to be developed prior to entry into force of the provision."

9 The sample shall be sealed by the representative of the competent authority with a unique means of identification installed in the presence of the ship's representative. The ship shall be given the option of retaining a duplicate sample."

3 "In-use fuel oil sampling point" and new paragraphs 10, 11, 12 and 13 are added at the end of regulation 14 as follows:

"In-use fuel oil sampling point

10 For each ship subject to regulations 5 and 6 of this Annex, sampling point(s) shall be fitted or designated for the purpose of taking representative samples of the fuel oil being used on board the ship taking into account guidelines developed by the Organization.²

11 For a ship constructed before entry into force of these requirements, the sampling point(s) referred to in paragraph 10 shall be fitted or designated no later than the first renewal survey that occurs 12 months or more after the entry into force of this regulation.

12 The requirements of paragraphs 10 and 11 above are not applicable to a fuel oil service system for a low-flashpoint fuel for combustion purposes for propulsion or operation on board the ship.

13 The competent authority of a Party shall, as appropriate, utilize the sampling point(s) which is fitted or designated for the purpose of taking representative sample(s) of the fuel oil being used on board in order to verify the fuel oil complies with this regulation. Taking fuel oil samples by the competent authority of the Party shall be performed as expeditiously as possible without causing the ship to be unduly delayed."

Regulation 18

Fuel oil availability and quality

4 Paragraph 8.2 is replaced with the following:

"8.2 If a Party requires the representative sample to be analysed, it shall be done in accordance with the verification procedure set forth in appendix VI to determine whether the fuel oil meets the requirements of this Annex."

Appendix VI

Fuel verification procedure for MARPOL Annex VI fuel oil samples (regulation 18.8.2)

5 Appendix VI is replaced with the following:

"Verification procedures for a MARPOL Annex VI fuel oil sample (regulation 18.8.2 or regulation 14.8)

The following relevant verification procedure shall be used to determine whether the fuel oil delivered to, in-use or carried for use on board a ship has met the applicable sulphur limit of regulation 14 of this Annex.

This appendix refers to the following representative MARPOL Annex VI fuel oil samples:

Part 1 – sample of fuel oil delivered⁴ in accordance with regulation 18.8.1, hereafter referred to as the "MARPOL delivered sample" as defined in regulation 2.54.

Part 2 – sample of fuel oil in use,⁵ intended to be used or carried for use on board in accordance with regulation 14.8, hereafter referred to as the "in-use sample" as defined in regulation 2.55 and "on board sample"⁶ as defined in regulation 2.56.

Part 1 – MARPOL delivered fuel oil sample

1 General Requirements

1.1 The representative fuel oil sample, which is required by regulation 18.8.1 (the MARPOL delivered sample) shall be used to verify the sulphur content of the fuel oil delivered to a ship.

1.2 A Party, through its competent authority, shall manage the verification procedure.

1.3 A laboratory undertaking the sulphur testing procedure given in this appendix shall have valid accreditation⁷ in respect of the test method to be used.

2 Verification Procedure Part 1

2.1 The MARPOL delivered sample shall be conveyed by the competent authority to the laboratory.

2.2 The laboratory shall:

- .1 record the details of the seal number and the sample label on the test record;
- .2 record the condition of the seal of the sample as received on the test record; and
- .3 reject any sample where the seal has been broken prior to receipt and record that rejection on the test record.

2.3 If the seal of the sample as received has not been broken, the laboratory shall proceed with the verification procedure and shall:

- .1 unseal the sample;
- .2 ensure that the sample is thoroughly homogenized;

⁴ Samples taken in accordance with the *2009 Guidelines for the sampling of fuel oil for determination of compliance with the revised MARPOL Annex VI* (resolution MEPC.182(59))."

⁵ Samples taken in accordance with the *2019 Guidelines for onboard sampling for the verification of the sulphur content of the fuel oil used on board ships* (MEPC.1/Circ.864/Rev.1)."

⁶ Refer to the Guidelines to be developed by the Organization prior to entry into force of the provision."

⁷ The laboratory is to be accredited to ISO/IEC 17025:2017 or an equivalent standard for the performance of the given sulphur content test ISO 8754:2003."

- .3 draw two subsamples from the sample; and
- .4 reseal the sample and record the new reseal details on the test record.

2.4 The two subsamples shall be tested in succession, in accordance with the specified test method referred to in regulation 2.52 of this Annex. For the purposes of this Part 1 verification procedure, the results of the test analysis shall be referred to as "1A" and "1B":

- .1 results "1A" and "1B" shall be recorded on the test record in accordance with the requirements of the test method; and
- .2 if the results of "1A" and "1B" are within the repeatability (r)⁸ of the test method, the results shall be considered valid; or
- .3 if the results "1A" and "1B" are not within the repeatability (r) of the test method, both results shall be rejected and two new subsamples shall be taken by the laboratory and tested. The sample bottle shall be resealed in accordance with paragraph 2.3.4 after the new subsamples have been taken.
- .4 in the case of two failures to achieve repeatability between "1A" and "1B", the cause of that failure shall be investigated by the laboratory and resolved before further testing of the sample is undertaken. On resolution of that repeatability issue, two new subsamples shall be taken in accordance with paragraph 2.3. The sample shall be resealed in accordance with paragraph 2.3.4 after the new subsamples have been taken.

2.5 If the test results of "1A" and "1B" are valid, an average of these two results shall be calculated. The average value shall be referred to as "X" and shall be recorded on the test record:

- .1 if the result "X" is equal to or less than the applicable limit required by regulation 14, the fuel oil shall be considered to have met the requirement; or
- .2 if the result "X" is greater than the applicable limit required by regulation 14, the fuel oil shall be considered to have not met the requirement.

Table 1: Summary of Part 1 MARPOL delivered fuel oil sample procedure

On the basis of the test method referred to in regulation 2.52 of this Annex		
Applicable limit % m/m: V	Result 2.5.1: $X \leq V$	Result 2.5.2: $X > V$
0.10	Met the requirement	Not met the requirement
0.50		
Result "X" reported to 2 decimal places		

⁸ Repeatability (r) calculation in accordance with ISO 4259:2017-2 and as defined in the test method used."

2.6 The final results obtained from this verification procedure shall be evaluated by the competent authority.

2.7 The laboratory shall provide a copy of the test record to the competent authority managing the verification procedure.

Part 2 – In-use and onboard fuel oil samples

3 General Requirements

3.1 The in-use or onboard fuel oil sample, as appropriate, shall be used to verify the sulphur content of the fuel oil as represented by that sample of fuel oil at the point of sampling.

3.2 A Party, through its competent authority, shall manage the verification procedure.

3.3 A laboratory undertaking the sulphur testing procedure given in this appendix shall have valid accreditation⁹ in respect of the test method to be used.

4 Verification Procedure Part 2

4.1 The in-use or onboard fuel oil sample shall be conveyed by the competent authority to the laboratory.

4.2 The laboratory shall:

- .1 record the details of the seal number and the sample label on the test record;
- .2 record the condition of the seal of the sample as received on the test record; and
- .3 reject any sample where the seal has been broken prior to receipt and record that rejection on the test record.

4.3 If the seal of the sample as received has not been broken, the laboratory shall proceed with the verification procedure and shall:

- .1 unseal the sample;
- .2 ensure that the sample is thoroughly homogenized;
- .3 draw two subsamples from the sample; and
- .4 reseal the sample and record the new reseal details on the test record.

⁹ The laboratory is to be accredited to ISO/IEC 17025:2017 or an equivalent standard for the performance of the given sulphur content test ISO 8754:2003."

4.4 The two subsamples shall be tested in succession, in accordance with the specified test method referred to in regulation 2.52 of this Annex. For the purposes of this Part 2 verification procedure, the results obtained shall be referred to as "2A" and "2B":

- .1 results "2A" and "2B" shall be recorded on the test record in accordance with requirements of the test method; and
- .2 if the results of "2A" and "2B" are within the repeatability (r)¹⁰ of the test method, the results shall be considered valid; or
- .3 if the results of "2A" and "2B" are not within the repeatability (r) of the test method, both results shall be rejected and two new subsamples shall be taken by the laboratory and tested. The sample bottle shall be resealed in accordance with paragraph 4.3.4 after the new subsamples have been taken.
- .4 in the case of two failures to achieve repeatability between "2A" and "2B", the cause of that failure shall be investigated by the laboratory and resolved before further testing of the sample is undertaken. On resolution of that repeatability issue, two new subsamples shall be taken in accordance with paragraph 4.3. The sample shall be resealed in accordance with paragraph 4.3.4 after the new subsamples have been taken.

4.5 If the test results of "2A" and "2B" are valid, an average of these two results shall be calculated. That average value shall be referred to as "Z" and shall be recorded on the test record:

- .1 if "Z" is equal to or less than the applicable limit required by regulation 14, the sulphur content of the fuel oil as represented by the tested sample shall be considered to have met the requirement;
- .2 if "Z" is greater than the applicable limit required by regulation 14 but less than or equal to that applicable limit + 0.59R (where R is the reproducibility¹¹ of the test method), the sulphur content of the fuel oil as represented by the tested sample shall be considered to have met the requirement; or
- .3 if "Z" is greater than the applicable limit required by regulation 14 + 0.59R, the sulphur content of the fuel oil as represented by the tested sample shall be considered to have not met the requirement.

¹⁰ Repeatability (r) calculation in accordance with ISO 4259:2017-2 and as defined in the test method used."

¹¹ Reproducibility (R) calculation in accordance with ISO 4259:2017-2 and as defined in the test method."

Table 2: Summary of in-use or onboard fuel oil sample procedure¹²

On the basis of the test method referred to in regulation 2.52 of this Annex				
Applicable limit %m/m: V	Test margin value: W	Result 4.5.1: $Z \leq V$	Result 4.5.2: $V < Z \leq W$	Result 4.5.3: $Z > W$
0.10	0.11	Met the requirement	Met the requirement	Not met the requirement
0.50	0.53			
Result "Z" reported to 2 decimal places				

4.6 The final results obtained from this verification procedure shall be evaluated by the competent authority.

4.7 The laboratory shall provide a copy of the test record to the competent authority managing the verification procedure."

¹² "Results of testing undertaken by the Company or other entities are outside the MARPOL process and hence should be considered within the approach given by ISO 4259:2017-2 regarding recipient drawn samples."

4 ALBERT EMBANKMENT
LONDON SE1 7SR
Telephone: +44 (0)20 7735 7611 Fax: +44 (0)20 7587 3210

MEPC.1/Circ.883
21 May 2019

**GUIDANCE ON INDICATION OF ONGOING COMPLIANCE IN THE CASE OF THE
FAILURE OF A SINGLE MONITORING INSTRUMENT, AND RECOMMENDED ACTIONS
TO TAKE IF THE EXHAUST GAS CLEANING SYSTEM (EGCS) FAILS TO MEET THE
PROVISIONS OF THE 2015 EGCS GUIDELINES (resolution MEPC.259(68))**

1 The Marine Environment Protection Committee, at its seventy-fourth session (13 to 17 May 2019), approved the *Guidance on indication of ongoing compliance in the case of the failure of a single monitoring instrument, and recommended actions to take if the Exhaust Gas Cleaning System (EGCS) fails to meet the provisions of the 2015 EGCS Guidelines (resolution MEPC.259(68))*.

2 Member Governments are invited to bring the annexed Guidance to the attention of Administrations, port State control authorities, industry, relevant shipping organizations, shipping companies and other stakeholders concerned.

ANNEX

GUIDANCE ON INDICATION OF ONGOING COMPLIANCE IN THE CASE OF THE FAILURE OF A SINGLE MONITORING INSTRUMENT, AND RECOMMENDED ACTIONS TO TAKE IF THE EGCS FAILS TO MEET THE PROVISIONS OF THE 2015 EGCS GUIDELINES (MEPC.259(68))

System malfunction

1 An Exhaust Gas Cleaning System (EGCS) malfunction is any condition that leads to an emission exceedance, with the exception of the short-term temporary emission exceedance cases described in sections 7 and 8, or an interim indication of ongoing compliance in the case of sensor failure described in sections 9 to 11.

2 As soon as possible after evidence of a malfunction (e.g. alarm is triggered), the ship should take action to identify and remedy the malfunction.

3 The ship operator should follow the process to identify and remedy the malfunction in the Exhaust Gas Cleaning System – Technical Manual that is approved at the time the EGCS is certified or in other documentation provided by the EGCS manufacturer.

4 The trouble-shooting process specified by the EGCS manufacturer should describe how to determine, within a reasonable amount of time, if the system itself is not working properly and whether the system fault must be addressed through adjustment and/or repair. The procedure would describe events that can trigger a monitoring alarm or other evidence of a scrubber malfunction (e.g. pump flow rates) and the troubleshooting process to identify and remedy the malfunction. The process should include at a minimum the following:

- .1 a checklist for the operator to use to identify a malfunction; and
- .2 a list of remedial actions that can be taken to resolve the malfunction after it is identified.

5 An EGCS malfunction event should be included in the EGCS Record Book including the date and time the malfunction began and, if relevant, how it was resolved, the actions taken to resolve it and any necessary follow-up actions.

6 A system malfunction that cannot be rectified is regarded as an accidental breakdown. The ship should then change over to compliant fuel oil if the EGCS cannot be put back into a compliant condition within one hour. If the ship does not have compliant fuel oil or sufficient amount of compliant fuel oil on board, a proposed course of action, in order to bunker compliant fuel oil or carry out repair works, should be communicated to relevant authorities including the ship's administration, for their agreement.

Short-term exceedances

7 A short-term temporary emission exceedance is an exceedance of the applicable Emissions Ratio that may occur due to the EGCS dynamic response when there is a sudden change in the exhaust gas flow rate to the EGCS. There may be a short period during which the measured emission values might indicate that the applicable Emissions Ratio limit has been exceeded. This is a common behaviour of monitoring equipment and EGCS dynamic response (due to a sudden change in exhaust gas flow rate). A time lapse between when the sensor takes its reading and when the unit responds may trigger an alarm from the continuous

emission monitoring device even though the EGCS has not malfunctioned. Thus, transitory periods and isolated spikes in the recorded output do not necessarily mean exceedance of emissions and should therefore not be considered as a breach of the requirements.

8 The typical operating conditions that may result in a short-term temporary emission exceedance should be specified by the EGCS manufacturer in the EGCS Technical Manual that is approved at the time the EGCS is certified.

Interim indication of ongoing compliance in the case of sensor failure

9 When running on a fuel oil with a constant sulphur content and at constant washwater engine load ratio, all parameters monitored according to the 2015 EGCS Guidelines (MEPC.259(68)) (i.e. Emission Ratio, washwater pH, etc.) will be in a certain interrelation, all depending on each other. If one of the parameters changes, some other(s) will necessarily also have to change.

10 This interrelation also serves as an indicator of instrumentation malfunction; i.e. if a single sensor signal starts to deviate or even does not display, the effect on the other parameters may indicate whether the change in signal is caused by sensor failure or whether the performance of the EGCS itself has changed. If the other parameters are continuing at the normal levels, it is an indication that there is only an instrumentation malfunction rather than non-compliance with regard to the levels allowed in the exhaust gas and the discharge water.

11 If a malfunction occurs in the instrumentation for the monitoring of Emission Ratio or discharge water (pH, PAH, Turbidity), the ship should keep records of interim indication for demonstrating compliance. The documentation and actions should include (but are not limited to):

- .1 the manual or automatic recording of the data at the time of malfunction may be used to confirm that all other relevant data as recorded for the performance of the EGCS are showing values in line with values prior to the malfunction;
- .2 the ship operator should record the sulphur content of the various grades of fuel oil used in the affected fuel oil combustion units from the time when the malfunction started;
- .3 the ship operator should log the malfunctioning of the monitoring equipment and (for Scheme A) record all parameters that might be suitable to indicate compliant operation. This record could serve as an alternative documentation demonstrating compliance until the malfunction is rectified; and
- .4 the monitoring equipment that has suffered a malfunction should be repaired or replaced as soon as practicable.

Notifications to relevant Authorities

12 Any EGCS malfunction that lasts more than one hour or repetitive malfunctions should be reported to the flag and port State's Administration along with an explanation of the steps the ship operator is taking to address the failure. At their discretion, the flag and port State's Administration could take such information and other relevant circumstances into account to determine the appropriate action to take in the case of an EGCS malfunction, including not taking action.

4 ALBERT EMBANKMENT
LONDON SE1 7SR
Telephone: +44 (0)20 7735 7611 Fax: +44 (0)20 7587 3210

MEPC.1/Circ.886
6 June 2019

**GUIDANCE ON THE IMPLEMENTATION OF PROVISIONAL CATEGORIZATION OF
LIQUID SUBSTANCES IN ACCORDANCE WITH MARPOL ANNEX II AND THE
IBC CODE RELATED TO PARAFFIN-LIKE PRODUCTS**

1 The Marine Environment Protection Committee, at its seventy-fourth session (13 to 17 May 2019), recognizing the need to provide clarification on the implementation of existing products which had been reclassified and published with validity for all countries, without expiry dates, in list 1 of the MEPC.2/Circular and how the revised requirements for such products shall be complied with until the revisions are incorporated in the next amendment to the IBC Code, approved the *Guidance on the implementation of provisional categorization of liquid substances in accordance with MARPOL Annex II and the IBC Code related to paraffin-like products*, which is set out in the annex.

2 Member Governments and international organizations are invited to bring the annexed Guidelines to the attention of Administrations, recognized organizations, port authorities, shipowners, ship operators and other parties concerned.

ANNEX

GUIDANCE ON THE IMPLEMENTATION OF PROVISIONAL CATEGORIZATION OF LIQUID SUBSTANCES IN ACCORDANCE WITH MARPOL ANNEX II AND THE IBC CODE RELATED TO PARAFFIN-LIKE PRODUCTS

1 The Marine Environment Protection Committee (MEPC), at its seventy-first session (3 to 7 July 2017), endorsed the amendments to the names of four paraffin-like products and their minimum carriage requirements, namely "n-Alkanes (C10-C20)", "Paraffin wax, highly-refined", "Paraffin wax, semi-refined", and "Hydrocarbon wax",** as contained in list 1 of the MEPC.2/Circular on *Provisional categorization of liquid substances in accordance with MARPOL Annex II and the IBC Code* as of December 2017 (MEPC.2/Circ.23).

2 The table below shows the pollution categories and hazards that were assigned to the four paraffin-like products.

Product Name	Pollution Category	Hazards
Hydrocarbon Wax	X*	S/P
Paraffin wax, semi-refined	X*	S/P
Paraffin wax, highly-refined	Y	P
n-Alkanes (C10 – C20)	Y	P

* The product has been reclassified as toxic due to its safety hazards, and category X due to its pollution hazards requiring mandatory prewash in compliance with Regulation 13.6 of MARPOL Annex-II.

3 MEPC 71 approved the inclusion of the above four paraffin-like cargoes in MEPC.2/Circ.23, which was issued in December 2017 (MEPC 71/17, paragraphs 9.3). The Committee also approved, in principle, the draft revised chapter 21 of the IBC Code (MEPC 71/17, paragraph 9.5; and PPR 4/21, annex 1), pending finalization of the revision of chapters 17 and 18 of the IBC Code, with a view to entry into force on 1 January 2021.

4 According to paragraph 7 of the Foreword of the IBC Code (2016 edition), annex 1 of the MEPC.2/Circular includes products that are expected to become new entries or amended information in existing entries in the IBC Code. The product information set out in the circular serves as prior notice of the carriage conditions, which will apply to that product when the next set of amendments enter into force.

5 The carriage requirements in the current chapter 17 of the IBC Code (resolution MEPC.166(56)) for "n-Alkanes (C10+)", "Paraffin wax", "Petrolatum", and "Waxes" are therefore applicable for the carriage of these paraffin-like products until the entry into force of the revised chapter 17 of the IBC Code on 1 January 2021.

6 If a shipment is to be carried out in accordance with the four new amended entries, "n-Alkanes (C10-C20)", "Paraffin wax, highly-refined", "Paraffin wax, semi-refined" and "Hydrocarbon wax", prior to entry into force of the revised chapter 17 of the IBC Code, the following should be taken into account:

- .1 the products as listed above in paragraph 1, should be listed in an addendum to the Certificate of Fitness; and

** Corresponding to the following previous product names respectively: n-Alkanes (C10+), Paraffin wax, Petrolatum, and Waxes.

- .2 confirmation should be obtained from the port of discharge that adequate reception facilities are available for receiving any prewash.

7 If the products listed in paragraph 1 above are not listed in an addendum to the Certificate of Fitness, then they cannot be loaded or shipped under the names listed in paragraph 1 and should be shipped in accordance with the existing entries in the current chapter 17 of the IBC Code (resolutions MEPC.250 (66) and MSC.369(93)).

8 If a receiving State intends to apply the amended carriage requirements as per list 1 of the MEPC.2/Circular in advance of the entry into force of the revised chapter 17 of the IBC Code, then it is invited to:

- .1 notify the IMO Secretariat in writing (esph@imo.org) of its intention, for dissemination in an ESPH information document; and
- .2 ensure that adequate reception facilities are available at its port for receiving any prewash required after discharge.

9 If a cargo listed in paragraph 1 is loaded prior to the entry into force date of the amendments to the IBC Code, the product name and associated carriage requirements at the time of loading will apply throughout the voyage.
