Subject

Emergency escape breathing devices (EEBDs) onboard the Panama flag vessels



 No.
 TEC-1150

 Date
 2 May 2018

To whom it may concern

Panama Maritime Authority has partly revised Merchant Marine Circular (MMC) No.142 about the special requirements for EEBDs onboard the Panama flag vessels, and then the latest requirements are as follows.

Emergency escape breathing device

- 1. Number of EEBDs
 - (1) For cargo ships: At least two EEBDs and one spare EEBD in accommodation.
 - (2) For passenger ships carrying not more than 36 passengers: At least two EEBDs per main vertical zone and a total of two spare EEBDs, except those defined in the regulation SOLAS II-2/13.3.4.5.
 - (3) For passenger ships carrying more than 36 passengers: At least four EEBDs per main vertical zone and a total of two spare EEBDs, except those defined in the regulation SOLAS II-2/13.3.4.5.
 - (4) The minimum number of EEBDs required on machinery spaces of category A where crews are normally employed or may be present on a routine basis shall be as follows:
 - (i) One EEBD at the engine control room, if located within the machinery space;
 - (ii) One EEBD at the workshop areas, if there is, however, a direct access to an escape way from the workshop, an EEBD is not required; and
 - (iii) One EEBD on each deck or platform level near the escape ladder constituting the second means of escape from the machinery space (the other means being an enclosed escape trunk or water tight door at the lower level of the space).
 - (5) If the ship has a machinery space with more than one deck, then one EEBD for each deck shall be placed at the same area as in point (4)(iii).
- 2. <u>Additional</u> Spares

Ships with ten or less EEBDs on board shall carry at least one additional spare device <u>more than</u> the one mentioned in item 1. Ships with 11 to 20 EEBDs on board shall carry at least two spare devices. Ships with more than 20 EEBDs on board shall carry spares equal to at least 10% of the total EEBDs but no more than 4 spares will be required.

(To be continued)

NOTES:

- ClassNK Technical Information is provided only for the purpose of supplying current information to its readers.
- ClassNK, its officers, employees and agents or sub-contractors do not warrant the accuracy of the information contained herein and are not liable for any loss, damage or expense sustained whatsoever by any person caused by use of or reliance on this information.
- Back numbers are available on ClassNK Internet Homepage (URL: www.classnk.or.jp).

3. Training

At least one EEBD training device shall be provided for training purpose. All EEBD training units should be clearly marked and placed in addition to EEBDs required for the machinery and accommodation spaces and its spare parts.

4. The above requirements are applied to all Panama flag vessels. ClassNK surveyors are to confirm the compliance at the first periodical Safety Equipment survey on or after 1 May 2018. In case where the arrangement of EEBD needs change, please note that all Fire Control Plans onboard should be corrected accordingly.

This ClassNK Technical Information supersedes the previous ClassNK Technical Information No. TEC-1149 dated 27 April 2018. Revised parts from ClassNK Technical Information No.TEC-1149 are underlined.

For any questions about the above, please contact:

NIPPON KAIJI KYOKAI (ClassNK)

Material and Equipment Department Administration Center Annex, Head OfficeAddress:3-3 Kioi-cho, Chiyoda-ku, Tokyo 102-0094, JapanTel.:+81-3-5226-2020Fax:+81-3-5226-2057

E-mail: eqd@classnk.or.jp

Attachment:

1. Merchant Marine Circular No.142



PANAMA MARITIME AUTHORITY

MERCHANT MARINE CIRCULAR MMC-142

PanCanal Building Albrook, Panama City Republic of Panama Tel: (507) 501-5355 mmc@amp.gob.pa

| То: | Ship-owners/Operators, of Panamanian Flagged Vessels, Class Societies and Recognized Organizations (RO's). | | |
|------------|--|--|--|
| Subject: | Emergency Escape Breathing Devices (EEBD) | | |
| Reference: | a. SOLAS 74, 2000 amendments b. MSC/Circ.1081 – Unified interpretation of the revised SOLAS Chapter II-2 – 13 June 2003. c. IMO MSC.1/Circ.849 – May 1998 | | |

1 Purpose

This Merchant Marine Circular replaces MMC 119.

2 Application

The 2000 amendments to SOLAS 74, Chapter II-2, Reg. 13 require Emergency Escape Breathing Devices (EEBD) which will be used for escape from a compartment that has a hazardous atmosphere. The EEBD have become mandatory under the new amendments for all ships to which the safety equipment certificate is required. The application of EEBDs provisions onboard Panama flag ships shall be as follow:

3 Number of EEBDs

- a. At least two (2) EEBDs in accommodation spaces of cargo ships and one (1) spare EEBD. Applicable to new and existing ships.
- b. At least two (2) EEBDs per main vertical zone, and a total of two (2) spare EEBDs. Applicable to new and existing passenger ships carrying not more than 36 passengers.
- c. At least four (4) EEBDs per main vertical zone , and a total of two (2) spare EEBDs.. Applicable to new and existing passenger ships carrying more than 36 passengers.
- d. For the purpose of this requirement (based on UI MSC/Circ. 1081), the minimum number of EEBDs required on machinery spaces shall be as follows:
 - i. One (1) EEBD at the engine control room if located inside the machinery space;
 - ii. One (1) EEBD at the machine shop or work shop area. If there is, however, a direct

| Prepared by: Lawyer | Revised by: Compliance and En | forcement Deputy Chief | Aproved by: Compliance and Enforcement Chief |
|-------------------------|-------------------------------|------------------------|--|
| Control N°: F-RIN-04-01 | Versión: 06 | Date: August 1, 2016 | Page 1 of 3 |

access to an escape way from the workshop, an EEBD is not required; and

iii. One (1) EEBD located near the escape ladder used a second means of escape from the machinery space.

If the ship has a machinery space with more than one deck, then one (1) EEBD for each deck shall be placed at the same area as in point (.3)

4 Additional Spares

Ships with ten or less EEBDs on board shall carry at least one (1) additional spare device more than the one mentioned in item 3. Ships with 11 to 20 EEBDs on board shall carry at least two spare devices. Ships with more than 20 EEBDs on board shall carry spares equal to at least 10 % of the total EEBDs but no more than 4 spares will be required. Applicable to new and existing ships.

Additional to the above requirements, the EEBD shall have a service duration of at least 10 minutes. Also, the number and location of EEBDs and spares shall be indicated in the fire control plan.

For existing ships, the requirement is to be complied with by the first survey after 1 July 2002. For more reference, the 2000 amendments to SOLAS 74, Chapter II-2, Reg. 1.2.2 clarify the applicable requirements to existing ships.

The detailed technical standards for the EEBD, are separately provided in a mandatory code called "The International Code for the Fire Safety System (FSS Code)" adopted simultaneously.

Note: "New ships" cited above means ships constructed on or after 1 July 2002 and "Existing ships" means ships constructed prior to that date.

Authorized Organizations are instructed to follow the above mentioned guidelines, before issuing the appropriate certificate.

5 Training (as per the IMO MSC.1/Circ.849 – May 1998)

Training in the use of the EEBD should be considered as a part of basic safety training .At least one EEBD training device shall be provided for training purposes at first Safety Equipment survey on or after 1st May 2018.. This device will be in addition to EEBDs required for the machinery and accommodation spaces.

All EEBD training units should be clearly marked and placed in addition to those minimum number required and its spare parts

Personnel should be trained to immediately don an EEBD prior to exiting a space when the atmosphere becomes life threatening. This is necessary due to the possibility of encountering smoke during escape. Such training should be accomplished by scheduling routine escape drills for crew members working in the engineering or machinery spaces.

An EEBD may also be used to escape from a machinery space due to an accidental release of a fixed CO2 system and can be carried by firefighters for the sole purpose of providing the device to personnel in need of emergency assistance.

```
April, 2018
March,2018 – Point 4,Point 5
January, 2018 – Point 3 a), b) and c) amended as well as 3 d) ii); subtitle 4 amended, and point 5 "Training added"
as per IMO MSC.1/Circ.849 – may, 1998.
```

| Prepared by: Lawyer | Revised by: Compliance and En | forcement Deputy Chief | Aproved by: Compliance and Enforcement Chief |
|-------------------------|-------------------------------|------------------------|--|
| Control N°: F-RIN-04-01 | Versión: 06 | Date: August 1, 2016 | Page 2 of 3 |

June, 2013 November 2005 (revised) April 2002

Inquiries concerning the subject of this Circular or any request should be directed to: SEGUMAR-Panama Directorate General of Merchant Marine Panama Maritime Authority

Phone: (507) 501-5348 / 5350 Fax: (507) 501-5363 / 5364 E-mail: <u>rberrocal@segumar.com</u> <u>deputychief@segumar.com</u>



| Prepared by: Lawyer | Revised by: Compliance and En | forcement Deputy Chief | Aproved by: Compliance and Enforcement Chief |
|-------------------------|-------------------------------|------------------------|--|
| Control N°: F-RIN-04-01 | Versión: 06 | Date: August 1, 2016 | Page 3 of 3 |