Mechanical Strength Testing for Side Scuttles

Object of Amendment

Rules for the Survey and Construction of Steel Ships Part L

Reason for Amendment

Chapter 7 of Part L of the Rules for the Survey and Construction of Steel Ships stipulates requirements for side scuttles based on ISO 1751 which specifies requirements for ship's side scuttles.

ISO 1751 stipulates the loading procedure for mechanical strength tests for deadlights in reference to ISO 614, which stipulates procedures for the punch method of the non-destructive strength testing of glass plates. However, ISO 1751 was amended, and the loading procedure for the deadlight according to ISO 614 was deleted, with a separate loading procedure being specified instead.

Accordingly, relevant requirements are amended based on ISO 1751.

Outline of the Amendment

Amends the reference to ISO 614 related to the loading procedure for mechanical strength tests for deadlights and specifies the loading procedure.

Effective Date and application

This amendment applies to tests for which the application is submitted to the Society on or after 1 January 2026.

ID:DH25-05

Amended-Original Requirements Comparison Table (Mechanical Strength Testing for Side Scuttles)

<u> </u>	Amended-Original Requirements Comparison Table (Mechanical Strength Testing for Side Scuttles)		
Amended	Original	Remarks	
RULES FOR THE SURVEY AND	RULES FOR THE SURVEY AND		
CONSTRUCTION OF STEEL SHIPS	CONSTRUCTION OF STEEL SHIPS		
Part L EQUIPMENT	Part L EQUIPMENT		
Chapter 7 SIDE SCUTTLES	Chapter 7 SIDE SCUTTLES		
7.1 Side Scuttles	7.1 Side Scuttles		
 7.1.5 Testing 2 Mechanical strength testing (1) A prototype side scuttle without glass pane and with closed deadlight is to be subjected to a mechanical strength test by the punch method specified in Fig. L7.1 according to the test pressures given in Table L7.8. (2) The punch is to be placed on that side of the deadlight which could be subjected to direct contact with the sea. Where the construction of the deadlight makes it necessary, a plate of 100 mm diameter and 	 7.1.5 Testing 2 Mechanical strength test (1) A prototype side scuttle without glass pane and with closed deadlight is to be subjected to a mechanical strength test by a punch method according to the test pressures given in Table L7.8. For this test, ISO 614 is to be used as a guide. (2) The punch is to be placed on that side of the deadlight which could be subjected to direct contact with the sea. Where the construction of the deadlight makes it necessary, a plate of 100mm diameter and 		
 10 mm thickness may be placed between the punch and the deadlight. (3) When subjected to the pressure given in Table L7.8, the permanent deformation of the deadlight is not to exceed 1 % of the nominal size of the side scuttle. 	 10mm thickness may be placed between the punch and the deadlight. (3) When subjected to the pressure given in Table L7.8, the permanent deformation of the deadlight is not to exceed 1% of the nominal size of the side scuttle. 		

Amended-Original Requirements Comparison Table (Mechanical Strength Testing for Side Scuttles)

Č 1	parison Table (Mechanical Strength Testing for Side Sc	
Amended	Original	Remarks
Table L7.8 Test Pressure for Mechanical Strength Type of Test pressure side scuttle (kPa) Class A 240 Class B 120	Table L7.8 Test Pressure for Mechanical Strength Type of Test pressure (kPa) Class A 240 Class B 120	
Fig. L7.1 Mechanical Strength Test Loading direction		Specify the loading direction with reference to ISO 1751:2012.
100 mm		
EFFECTIVE DATE A	AND APPLICATION	
 The effective date of the amendments is 1 January 2020 Notwithstanding the amendments, the current requirem Society before the effective date. 	6. nents apply to tests for which the application is submitted to the	