Recent Amendments to the IGC Code (MSC.566(109)) and Review of Existing Requirements (Machinery Related)

Object of Amendment

Rules for the Survey and Construction of Steel Ships Part N Guidance for the Survey and Construction of Steel Ships Parts GF and N

Reason for Amendment

The Society has incorporated the International Code for the Construction and Equipment of Ships Carrying Liquefied Gases in Bulk (IGC Code) into Part N of its Rules for the Survey and Construction of Steel Ships.

In recent years, ammonia has been attracting attention as a zero-emission fuel, and currently there are plans worldwide for the newbuilding of ammonia carriers that will use ammonia as fuel for their engines. On the other hand, Chapter 16 of the IGC Code stipulates that the use of cargoes identified as toxic products as fuel is not permitted. Therefore, the possibility of using ammonia as fuel was discussed by the IMO. As a result, an amendment to the IGC Code to permit the use of ammonia as fuel was agreed upon, provided that the same level of safety as natural gas is ensured. This amendment was adopted as MSC.566(109) at the 109th session of the IMO Maritime Safety Committee (MSC109) held in December 2024.

Accordingly, relevant requirements are amended in accordance with MSC.566(109).

In addition, the relevant guidance was reviewed, and the requirements for the burners for dual fuel boilers, which presuppose the use of an oil fuel burner for ignition, are amended to also allow the use of a spark ignition type burner.

Outline of the Amendment

The main contents of this amendment are as follows.

- (1) Amends requirements related to toxic products that cannot be used as fuel.
- (2) Amends requirements related to the burners for dual fuel boilers to include spark ignition types.

Effective Date and Application

- (1) Chapter 16, Part N of the Rules for the Survey and Construction of Steel Ships Effective date of the amendment is 1 July 2026.
- (2) Annex 1, Part GF and Annex 1, Part N of the Guidance for the Survey and Construction of Steel Ships

Effective date of the amendment is 1 January 2026.

ID:DD25-19

Amended	Original Original	Remarks
RULES FOR THE SURVEY AND	RULES FOR THE SURVEY AND	Remarks
CONSTRUCTION OF STEEL SHIPS	CONSTRUCTION OF STEEL SHIPS	
B ANGUING CARRYING LIQUERUED CAGE	B ANGUING CARRANG LIQUERUR CAGRO	
Part N SHIPS CARRYING LIQUEFIED GASES	Part N SHIPS CARRYING LIQUEFIED GASES	
IN BULK	IN BULK	
Chapter 16 USE OF CARGO AS FUEL	Chapter 16 USE OF CARGO AS FUEL	
16.9 Alternative Fuels and Technologies (IGC Code 16.9)	16.9 Alternative Fuels and Technologies (IGC Code 16.9)	
10.5 Atternative rucis and recimologies (roc code 10.5)	10.7 Atternative rucis and reciniologies (roc code 10.7)	
16.9.1 Alternative Fuels and Technologies	16.9.1 Alternative Fuels and Technologies	
1 If acceptable to the Administration, other cargo	1 If acceptable to the Administration, other cargo	
gases may be used as fuel, providing that the same level of	gases may be used as fuel, providing that the same level of	
safety as natural gas in this Part is ensured.	safety as natural gas in this Part is ensured.	
2 The use of cargoes requiring carriage in type 1G	2 The use of cargoes identified as toxic products is not	Outline of the
ships, as identified in column "c" in Table N19.1, is not to be	to be permitted.	Amendment (1)
permitted. If acceptable to the Administration, cargoes		MSC.566(109)
identified as toxic products in column "f" which are required		
to be carried in type 2G/2PG ships in column "c" in Table N19.1 may be used as fuel, provided that the same level of		
safety as natural gas (methane) is ensured in accordance with		
the relevant requirements of this Rules, including those in		
1.1.2, and taking into account the guidelines developed by		
the <i>IMO</i> , after special consideration has been given by the		
Administration.		
The effective date of the amendment is according	to EFFECTIVE DATE AND APPLICATION (A)	

Amended-Original Requirements Comparison Table (Recent Amendments to the IGC Code (MSC.566(109)) and Review of Existing Requirements (Machinery Related))

Amended	Original Original	Remarks
GUIDANCE FOR THE SURVEY AND CONSTRUCTION OF STEEL SHIPS	GUIDANCE FOR THE SURVEY AND CONSTRUCTION OF STEEL SHIPS	
Part GF SHIPS USING LOW-FLASHPOINT FUELS	Part GF SHIPS USING LOW-FLASHPOINT FUELS	
Annex 2 GUIDANCE FOR GAS-FUELLED BOILERS	Annex 2 GUIDANCE FOR GAS-FUELLED BOILERS	
Chapter 2 CONSTRUCTION AND EQUIPMENT OF BOILER	Chapter 2 CONSTRUCTION AND EQUIPMENT OF BOILER	
2.3 Burners	2.3 Burners	
3 Gas fuel burners are to be so arranged that they can be ignited individually only by flames of oil fuel burners unless the boiler and combustion equipment is designed and approved by the Society to light on gas fuel. In such cases, oil fuel burners are to be large enough to instantly ignite the gas fuel at any nozzle of gas fuel burners.	3 Gas fuel burners are to be so arranged that they can be ignited individually only by flames of oil fuel burners. In such cases, oil fuel burners are to be large enough to instantly ignite the gas fuel at any nozzle of gas fuel burners.	Outline of the Amendment (2) Amends in accordance with 10.4.5, Part GF of the Rules so that direct ignition type ones can be used.
	(For reference: 10.4.5, Part GF of the Rules) Gas nozzles and the burner control system are to be configured such that gas fuel can only be ignited by an established oil fuel flame, unless the boiler and combustion equipment is designed and approved by the Society to light on gas fuel.	uscu

Amended	Original Original	Remarks
Chapter 3 CONTROL SYSTEMS AND SAFETY SYSTEMS	Chapter 3 CONTROL SYSTEMS AND SAFETY SYSTEMS	
3.1 Control Systems	3.1 Control Systems	
 3.1.1 Gas Burning Control Systems Control systems for gas fuel burning are to be in accordance with the requirements specified in the following (1) to (5), in addition to the requirements of 18.4.1 and 18.4.2, Part D of the Rules. (1) In cases where pilot burners are used for gas fuel ignition, it is to be so arranged that gas fuel is not supplied to burners until the flames of pilot burners are established and secured. In cases where gas fuel supply is initiated manually, it is to be so arranged that the gas fuel supply is cut off automatically when gas fuel supply valves are opened before flame of pilot burners are established, or that the gas fuel supply valves are locked until the pilot burner flames are established. 	 3.1.1 Gas Burning Control Systems Control systems for gas fuel burning are to be in accordance with the requirements specified in the following (1) to (5), in addition to the requirements of 18.4.1 and 18.4.2, Part D of the Rules. (1) It is to be so arranged that gas fuel is not supplied to burners until the flames of pilot burners used for gas fuel ignition are established and secured. In cases where gas fuel supply is initiated manually, it is to be so arranged that the gas fuel supply is cut off automatically when gas fuel supply valves are opened before flame of pilot burners are established, or that the gas fuel supply valves are locked until the pilot burner flames are established. 	Outline of the Amendment (2) Amends in conjunction with 2.3
(2) Control systems regulating oil/gas supply ratios are to be capable of maintaining combustion over the full range of loads approved for oil/gas burning with consideration given to ensuring sufficient supplies of combustion air.	(2) Control systems regulating oil/gas supply ratios are to be capable of maintaining combustion over the full range of loads approved for oil/gas burning with consideration given to ensuring sufficient supplies of combustion air.	
(3) Combustion air supplies for gas burning or oil/gas burning are to be automatically controlled to ensure safe combustion within the possible combustible range.	(3) Combustion air supplies for gas burning or oil/gas burning are to be automatically controlled to ensure safe combustion within the possible combustible range.	
(4) Combustion chambers of boilers are to be capable of automatic purging with sufficient volumes of air	(4) Combustion chambers of boilers are to be capable of automatic purging with sufficient volumes of air	

	Amended		Original	Remarks
(5) I	both before igniting base burners and after extinction of all burners. Arrangements deemed appropriate by the Society are to be made to enable boilers to be manually purged. In the case of gas fuel supply rate control systems, it is to be so arranged that gas fuel supply rates are ensured not to be reduced less than predetermined minimum supply rates verified in advance by tests.	(5)	both before igniting base burners and after extinction of all burners. Arrangements deemed appropriate by the Society are to be made to enable boilers to be manually purged. In the case of gas fuel supply rate control systems, it is to be so arranged that gas fuel supply rates are ensured not to be reduced less than predetermined minimum supply rates verified in advance by tests.	

Amended-Original Requirements Comparison Table (Recent Amendments to the IGC Code (MSC.566(109)) and Review of Existing Requirements (Machinery Related))

Amended	Original Original	Remarks
GUIDANCE FOR THE SURVEY AND	GUIDANCE FOR THE SURVEY AND	
CONSTRUCTION OF STEEL SHIPS	CONSTRUCTION OF STEEL SHIPS	
Part N SHIPS CARRYING LIQUEFIED	Part N SHIPS CARRYING LIQUEFIED	
GASES IN BULK	GASES IN BULK	
Annex 2 GUIDANCE FOR DUAL FUEL BOILERS	Annex 2 GUIDANCE FOR DUAL FUEL BOILERS	
Chapter 2 CONSTRUCTION AND EQUIPMENT OF DF BOILER	Chapter 2 CONSTRUCTION AND EQUIPMENTS OF DF BOILER	
2.3 Burners	2.3 Burners	
3 Gas fuel burners are to be so arranged that they can be ignited individually only by a flame of an oil fuel burner unless the boiler and combustion equipment is designed and approved by the Society to light on gas fuel. In this case, oil	3 Gas fuel burners are to be so arranged that they can be ignited individually only by a flame of an oil fuel burner. In this case, oil fuel burner is to be large enough to instantly ignite the gas fuel at any nozzle of the gas fuel burners.	Outline of the Amendment (2) Amends in accordance with 16.6.2, Part N of the
fuel burner is to be large enough to instantly ignite the gas fuel at any nozzle of the gas fuel burners.	(For reference: 16.6.2 Part N of the Rules) 4 Gas nozzles and the burner control system are to be configured such that gas fuel can only be ignited by an	Rules so that direct ignition type ones can be used.
	established oil fuel flame, unless the boiler and combustion equipment is designed and approved by recognized organization to light on gas fuel.	

Amended	Original Original	Remarks
Chapter 3 CONTROL SYSTEMS AND	Chapter 3 CONTROL SYSTEMS AND	T COMMIND
SAFETY SYSTEMS	SAFETY SYSTEMS	
SAFETT STSTEMS	SAFETT STSTEMS	
3.1 Control Systems	3.1 Control Systems	
·	·	
3.1.1 Gas Burning Control System	3.1.1 Gas Burning Control System	0.41. 64
Control systems for gas fuel burning are to comply	Control systems for gas fuel burning are to comply	Outline of the Amendment (2)
with the following requirements (1) through (7), in addition	with the following requirements (1) through (7), in addition	Amendment (2)
to the requirements of 18.4.1 and 18.4.2, Part D of the	to the requirements of 18.4.1 and 18.4.2, Part D of the	Amends in conjunction
Rules.	Rules.	with 2.3
(1) In cases where pilot burners are used for gas fuel	(1) It is to be so arranged that the gas fuel is not supplied	
ignition, it is to be so arranged that the gas fuel is not		
supplied to the burners until the flame of a pilot		
burner is established and secured. Where gas fuel		
supply is initiated manually, it is to be so arranged		
that the gas fuel supply is cut off automatically when	automatically when the gas fuel supply valve is	
the gas fuel supply valve is opened before the flame	opened before the flame of a pilot burner is	
of a pilot burner is established, or the gas fuel supply	11.	
valve is locked until the pilot burner flame is established.	until the pilot burner flame is established.	
	(2) The control system regulating the oil/gas supply	
(2) The control system regulating the oil/gas supply ratio is to be capable of maintaining combustion for	ratio is to be capable of maintaining combustion for	
the full range of loads approved for mixed burning	1	
taking into account of sufficient supplies of		
combustion air.	combustion air.	
	(3) Combustion air supplies for gas burning or oil/gas	
(3) Combustion air supplies for gas burning or oil/gas burning are to be controlled to automatically control		
to secure safe combustion within the combustible	to secure safe combustion within the combustible	
range. (4) Combustion chambers of DF boilers are to be	range. (4) Combustion chambers of DF boilers are to be	
capable of automatic purging with a sufficient		
capable of automatic purging with a sufficient	capable of automatic purging with a sufficient	1

Amended-Original Requirements Comparison Table (Recent Amendments to the IGC Code (MSC.566(109)) and Review of Existing Requirements (Machinery Related))

	Amended		Original Original	Remarks
(5)	volume of air before igniting the base burners and after extinction of all burners. Arrangements are to be made to enable the boilers are manually purged and to have the satisfaction of the Society. In the case of a gas fuel supply rate control system, it is to be so arranged that the gas fuel supply rate is secured not to be reduced less than predetermined minimum supply rate which is verified by a test in advance.	(5)	volume of air before igniting the base burners and after extinction of all burners. Arrangements are to be made to enable the boilers are manually purged and to have the satisfaction of the Society. In the case of a gas fuel supply rate control system, it is to be so arranged that the gas fuel supply rate is secured not to be reduced less than predetermined minimum supply rate which is verified by a test in advance.	
	The effective date of the amendment is according to EFFECTIVE DATE AND APPLICATION (B)			
	EFFECTIVE DATE AND APPLICATION (A)			
1.	1. The effective date of the amendments is 1 July 2026.			
EFFECTIVE DATE AND APPLICATION (B)				
1.	1. The effective date of the amendments is 1 January 2026.			