

Subject

Amendments to COLREG (Convention on the International Regulations for Preventing Collisions at Sea, 1972)

ClassNK

Technical Information

No. TEC-0489
Date 15 November 2002

To whom it may concern

Amendments to COLREG (Convention on the International Regulations for Preventing Collisions at Sea, 1972) were adopted by IMO assembly 22nd session as Resolution A. 910 (22), and would be enter into force on 29 November 2003.

For your reference the amendments is attached.

Major points are amendments to Wing-In-Ground (WIG) craft, to sound signals and to masthead lights position of high-speed crafts.

For any questions about the above, please contact:

NIPPON KAIJI KYOKAI (ClassNK)

Material and Equipment Department, Administration Center, Head Office

Address: 4-7 Kioi-cho, Chiyoda-ku, Tokyo 102-8567, Japan

Tel.: +81-3-5226-2020

Fax: +81-3-5226-2057

E-mail: eqd@classnk.or.jp

Attachment:

1. Amendments to the international regulations for preventing collisions at sea, 1972

NOTES:

- ClassNK Technical Information is provided only for the purpose of supplying current information to its readers.
- ClassNK, its officers, employees and agents or sub-contractors do not warrant the accuracy of the information contained herein and are not liable for any loss, damage or expense sustained whatsoever by any person caused by use of or reliance on this information.
- Back numbers are available on ClassNK Internet Homepage (URL: www.classnk.or.jp).

Attachment 1. to
ClassNK Technical Information No. TEC-0489

AMENDMENTS TO THE INTERNATIONAL REGULATIONS FOR
PREVENTING COLLISIONS AT SEA, 1972

Rule 3 General definitions: *[underlined words are added]*

Paragraph (a) is amended to read as follows:

- (a) The word "vessel" includes every description of water craft, including non-displacement craft, WIG craft and seaplanes, used or capable of being used as a means of transportation on water.

A new paragraph (m) is added as follows:

- (m) The term "Wing-In-Ground (WIG) craft" means a multimodal craft which, in its main operational mode, flies in close proximity to the surface by utilizing surface- effect action.

Rule 8 Action to avoid collision: *[underlined words are added]*

Paragraph (a) is amended to read as follows:

- (a) Any action to avoid collision shall be taken in accordance with the Rules of this Part and shall, if the circumstances of the case admit, be positive, made in ample time and with due regard to the observance of good seamanship.

Rule 18 Responsibilities between vessels: *[underlined words are added]*

A new paragraph (f) is added as follows:

- (f) (i) A WIG craft shall, when taking off, landing and in flight near the surface, keep well clear of all other vessels and avoid impeding their navigation;
(ii) A WIG craft operating on the water surface shall comply with the Rules of this Part as a power-driven vessel.

Rule 23 Power-driven vessels underway: *[underlined words are added]*

A new paragraph (c) is added as follows, and the following paragraph renumbered accordingly:

- (c) A WIG craft only when taking off, landing and in flight near the surface shall, in addition to the lights prescribed in paragraph (a) of this Rule, exhibit a high intensity all-round flashing red light.

Rule 31 Seaplanes : *[underlined words are added]*

The paragraph is amended to read as follows:

Where it is impracticable for a seaplane or a WIG craft to exhibit lights and shapes of the characteristics or in the positions prescribed in the Rules of this Part she shall exhibit lights and shapes as closely similar in characteristics and position as is possible.

Rule 33 Equipment for sound signals: *[underlined words are added][crossed out words are deleted]*

Paragraph (a) is amended to read as follows:

(a) A vessel of 12 metres or more in length shall be provided with a whistle ~~and a bell~~, a vessel of 20 metres or more in length shall be provided with a bell in addition to a whistle, and a vessel of 100 metres or more in length shall, in addition, be provided with a gong, the tone and sound of which cannot be confused with that of the bell. The whistle, bell and gong shall comply with the specification in Annex III to these Regulations. The bell or gong or both may be replaced by other equipment having the same respective sound characteristics, provided that manual sounding of the ~~prescribed~~ required signals shall always be possible.

Rule 35 Sound signals in restricted visibility: *[underlined words are added]*

A new paragraph (i) is added as follows, and the following paragraphs renumbered accordingly:

(i) A vessel of 12 metres or more but less than 20 metres in length shall not be obliged to give the bell signals prescribed in paragraphs (g) and (h) of this Rule. However, if she does not she shall make some other efficient sound signal at intervals of not more than 2 minutes.

ANNEX I Positioning and technical details of lights and shapes:

Section 13 is amended to read as follows: *[underlined words are added][crossed out words are deleted]*

13. High-speed craft*

(a) The masthead light of high-speed craft ~~with a length to breadth ratio of less than 3.0~~ may be placed at a height related to the breadth of the craft lower than that prescribed in paragraph 2(a)(i) of this annex, provided that the base angle of the isosceles triangles formed by the sidelights and masthead light, when seen in end elevation, is not less than 27°.

(b) On high-speed craft of 50 metres or more in length, the vertical separation between foremast and mainmast light of 4.5 metres required by paragraph 2(a)(ii) of this annex may be modified provided that such distance shall not be less than the value determined by the following formula:

$$y = \frac{(a + 17\psi)C}{1000} + 2$$

where: y is the height of the mainmast light above the fore mast light in metres;

a is the height of the foremast light above the water surface in service condition in metres;

Ψ is the trim in service condition in degrees;

C is the horizontal separation of masthead lights in metres.

* Refer to the International Code of Safety for High-Speed Craft, 1994 and the International Code of Safety for High-Speed Craft, 2000.

ANNEX III Technical details of sound signal appliances

1. Whistles:

Paragraph (a) is amended to read as follows: *[underlined words are added]*

(a) Frequencies and range of audibility

The fundamental frequency of the signal shall lie within the range 70-700Hz. The range of audibility of the signal from a whistle shall be determined by those frequencies, which may include the fundamental and/or one or more higher frequencies, which lie within the range 180-700Hz (+/-1%) for a vessel of 20 metres or more in length, or 180-2100Hz (+/-1%) for a vessel of less than 20 metres in length and which provide the sound pressure levels specified in paragraph 1(c) below.

Paragraph (c) is amended to read as follows: *[underlined words are added]*

(c) Sound signal intensity and range of audibility

A whistle fitted in a vessel shall provide, in the direction of maximum intensity of the whistle and at a distance of 1 metre from it, a sound pressure level in at least one 1/3rd- octave band within the range of frequencies 180-700Hz (+/- 1%) for a vessel of 20 metres or more in length, or 180-2100Hz (+/-1%) for a vessel of less than 20 metres in length, of not less than the appropriate figure given in the table below.

Length of vessel in metres	1/3rd-octave band level at 1 metre in dB referred to $2 \times 10^{-5} \text{N/m}^2$	Audibility range in nautical miles
200 or more	143	2
75 but less than 200	138	1.5
20 but less than 75	130	1
Less than 20	120^{*1}	0.5
	115^{*2}	
	111^{*3}	

*1 When the measured frequencies lie within the range 180-450Hz

*2 When the measured frequencies lie within the range 450-800Hz

*3 when the measure frequencies lie within the range 800-2100Hz

2. Bell or gong:

Paragraph (b) is amended to read as follows: *[crossed out words are deleted]*

(b) Construction

Bells and gongs shall be made of corrosion-resistant material and designed to give a clear tone. The diameter of the mouth of the bell shall be not less than 300 mm for vessels of 20 metres or more in length. ~~and shall be not less than 200 mm for vessels of 12 metres or more, but of less than 20 metres in length.~~ Where practicable, a power-driven bell striker is recommended to ensure constant force but manual operation shall be possible. The mass of the striker shall be not less than 3 per cent of the mass of the bell.